



DME

MOLD BASES AND PLATES



This book is completely linked both internally and to the EStore-Download For Easy Access

Table of Contents

Introduction

Terms and Conditions of Sale	4
Sales and Ordering Information Mold and Die	5
Steels	8
Mold Base Benefits	9
DME Item Number System	10
Mold Base Terminology	11
Machining of Clamp Slots	12

Mold Base and Plate Services

XPress A&BMoldBases	16-19
Mold BasePLUS	20-23
Special MoldBases&Plates	25
Large Custom Mold Bases and Plates	28
ContourRoughingServices	28

American Standard Mold Bases

Key Features	40
Mold Base Series Selections	41
Standard Steel Types	42-43
Standard Features Overview	44-45
Optional Features Overview	46-47
Quote Request Form	48-49
Special Feature Location Form	50
Standard A-Series Mold Bases	52-137
B-Series Mold Bases	138
Standard and Optional Features	139-172
Locating Rings	146
Sprue Bushings	147
Upper & Lower Assembly Screws	148-149
Clamp Slots	150
Guide Pins and Bushings	151
Return Pins, Stop Pins and Sprue Puller Pins	152-153
Ejector Housing and Cover	154-155
Ejector Assembly Screws	156
Minimum Additional SHCS	157-158
Mold Base Features and Delivery Time	159
Self-Lubricating Bushings	160
Pry Slots	161
Guided Ejection Systems	162-163
Lifting Holes	164
Pockets	165
Support Pillars	166-167
Leader Pin Vents, Spring Pockets and Mold Strap Holes	168
Waterlines	169
3-Plate Extension Bushings	170
Interlocks	171
Insulator Sheets	172

American Standard Mold Bases

X-, AX- and T-Series Mold Bases	173-198
Features	174-175
Stripper Plate Mold Bases	176-184
AX-Series	185
T-Series	186-196
3-Plate Extension Bushings	197
Ball Bushings for Floating Plates	198
Small and Shuttle Mold Bases	199-210
Small and Custom	200-205
Shuttle Mold Bases	206-209
MoldBasics Mold Bases	211-220
Features	212-215
Product Selection Tables	216-219
Polimold Industrial S.A.	220

Cavity Retainer Sets

Cavity Retainer Sets	221-248
--	---------

Mold Plates

Die Blocks & Plates	251-252
Cavity Insert Blocks	253
Standard Mold Plates	254-260
Ejector Plates	261
Ejector Retainers	262
Spacer Blocks/Rails	263-265
Ejector Housings	266-267
Small Mold Base Ejector Plates, Retainers & Housings	268
Large Mold Plates	269-273

Molding Supplies

Mold Cleaner and Mold Saver	275-276
---	---------

Technical Reference

Metric Equivalents and Conversions	278
Steel Hardness Chart	279
Tensile Strength	280
Draft Angles	281
Steel Designations	282
Tables for Determining Metric Tolerances	283-294
American Standard Mold Base Features	295-298

Index

3-Plate Extension Bushings	170, 197	Mold Base 1623A	102-103
A-Series Mold Bases	11, 26-32, 39-137	Mold Base 1626A	104-105
A-Slotted Rail	264	Mold Base 1629A	106-107
AX-Series Mold Bases	11, 41, 175, 185	Mold Base 1635A	108-109
Adapter Plates, Custom Universal	201	Mold Base 1724A	110-111
Adapter Plates, Small Mold Base	200	Mold Base 1729A	112-113
Additional Assembly SHCS, Minimum Recommended	157-158	Mold Base 1818A	114-115
Arburg Locating Rings	146	Mold Base 1820A	116-117
Assembly Screws (SHCS)	148-149, 157-158	Mold Base 1823A	118-119
B-Series Mold Bases	11, 41, 138	Mold Base 1826A	120-121
Ball Bushings	198	Mold Base 1829A	122-123
Bolster Plate	see Support Plate	Mold Base 1835A	124-125
Cavity Insert Blocks	253	Mold Base 1924A	126-127
Cavity Retainer Sets	221-248	Mold Base 1929A	128-129
Clamp Slots	12, 150	Mold Base 1935A	130-131
Column	see Support Pillars	Mold Base 2424A	132-133
Contour Roughing Services	36	Mold Base 2429A	134-135
Core Retainer Plate	see B Plate	Mold Base 2435A	136-137
Custom Large Mold Bases and Plates	28	Mold Base PLUS	20-23
Determining Metric Tolerances	283-294	Mold Base Features – Standard	40-45, 142-143, 295-298
Die Blocks and Plates	251-252	Mold Base Features – Optional	46-47, 144-145
Ejector Assembly Screws	156	MoldBasics Mold Bases	212-220
Ejector Housing and Cover	154-155	Mold Cleaner and Mold Saver	276
Finish Ground Mold Plates	254	Mold Plates	249-274
Floating Plate	see Stripper Plate	Mold Strap Holes	168
Guide Pins and Bushings	151	Parallels	see Spacer Blocks
Guided Ejection Systems	162-163	Pillow	see Support Pillars
Insulator Sheets	172	Pockets	165
Interlocks	171	Pry Slots	161
Leader Pin Vents	168	Quick Delivery Specials	33-35
Lifting Holes	164	Quick Delivery Standards	25-32
Locating Rings	146	Quote Request Form, Mold Base	48-49
Lower Half	see B Plate	Rails	see Spacer Blocks
Machining Services, Clamp Slots	12	Rear Cavity Plate	see B Plate
Metric Equivalents and Conversions	210, 278	Return Pins	152-153
Mold and Die Steel Descriptions	42-43, 248, 282	Risers	see Spacer Blocks
Mold Base 88A	52-53	Rotary Ground Mold Plates	254
Mold Base 812A	54-55	Self-Lubricating Bushings	160
Mold Base 108A	56-57	Shuttle Mold Bases	206-209
Mold Base 1012A	58-59	Small Mold Bases	202-205
Mold Base 1016A	60-61	Spacer Blocks	263-265, 273
Mold Base 1020A	62-63	Spacers	see Spacer Blocks
Mold Base 1112A	64-65	Special Mold Bases & Plates	25
Mold Base 1114A	66-67	Special Feature Location Form	50
Mold Base 1118A	68-69	Spring Pockets	168
Mold Base 1123A	70-71	Sprue Bushings	147
Mold Base 1212A	72-73	Sprue Puller Pins	152-153
Mold Base 1215A	74-75	Steel Designations	8, 42-43, 248, 282
Mold Base 1220A	76-77	Steel Hardness Chart	51, 279
Mold Base 1223A	78-79	Steel Processing Services	274
Mold Base 1315A	80-81	Stop Pins	152-153
Mold Base 1318A	82-83	Stripper Plate	11, 41, 174, 176-184, 198
Mold Base 1321A	84-85	Support Pillars	166-167
Mold Base 1323A	86-87	Support Plate	11
Mold Base 1326A	88-89	T-Series Mold Bases	11, 41, 175, 186-196
Mold Base 1329A	90-91	Tensile Strength	280
Mold Base 1518A	92-93	Upper and Lower Assembly Screws	148-149, 157-158
Mold Base 1524A	94-95	Waterlines	169
Mold Base 1529A	96-97	X-Plate	see Stripper Plate
Mold Base 1616A	98-99	X-Series Stripper Mold Bases	11, 41, 176-184, 198
Mold Base 1620A	100-101	XPress A&B Mold Bases	16-18

Terms and Conditions of Sale

DME COMPANY LLC ("SELLER") TERMS AND CONDITIONS OF SALE

1. **ACCEPTANCE OF TERMS:** Seller's offer is expressly conditioned upon Buyer's acceptance of these Terms and Conditions, and Seller expressly objects to any additional or different terms proposed by Buyer. Any subsequent purchase order issued by Buyer shall constitute Buyer's agreement to these Terms and Conditions. Any contrary terms and conditions contained in any purchase order, facility entry form, or other instrument issued by the Buyer are expressly rejected and shall not apply to this transaction. Unless otherwise specified in the quotation, Seller's quotation shall expire 30 days from its date and may be modified or withdrawn by Seller before receipt of Buyer's conforming purchase order.

2. **PAYMENT TERMS:** Payment is due in accordance with any applicable progress, advance or other agreed upon payment schedule, or, if no such schedule has been agreed to, no later than 30 days from the date of invoice. Buyer shall pay a late payment charge computed at the lower of 1.5% per month on any overdue balance, or the maximum rate permitted by law. No cash discount is provided. If at any time Seller reasonably determines that Buyer's financial condition or payment history does not justify continuation of Seller's performance, Seller shall be entitled to require full or partial payment in advance or otherwise restructure payments, request additional forms of payment security, suspend its performance or terminate the order.

3. DELIVERY

3.1 In the United States, products are sold FCA Incoterms 2020 point of origin; for export sales, terms are FCA Incoterms port of export. Unless otherwise agreed in writing, title and risk of loss shall pass at the time of shipment. Buyer is responsible for all taxes, duties, fees, or other governmental charges related to its purchase of goods, with the sole exception of taxes on Seller's income. Unless otherwise agreed, Buyer shall pay all packing and delivery costs.

3.2 Seller's quoted lead times and targeted delivery dates are good faith estimates and are not binding on Seller. Buyer's acceptance of delivery of Seller's products from the carrier shall constitute a waiver of any claim for delay. If Seller notifies Buyer that the products are ready for shipment and Buyer delays delivery, then Seller may charge Buyer a storage fee equal to 1.5% of the contract price per month for each month of delay. Such storage fees are in addition to any other remedies Seller may have.

3.3 Buyer shall have a reasonable opportunity to inspect any products prior to shipment. Products shall be deemed to be accepted upon the earlier of: (i) inspection at Seller's plant (provided that no reasonable objection is then raised by Buyer), or (ii) if no inspection is requested, then at shipment. If an objection is made during inspection, then Products shall be deemed accepted upon resolution of the objection by Seller.

4. WARRANTY:

4.1 Seller's express product warranty be as stated in DME's order specification documentation and shall run from the date of shipment (the "Warranty Period"). During the Warranty Period, Seller warrants that the products and services sold hereunder will be free from material defects in material, workmanship and title (the "Warranty").

4.2 If, during the Warranty Period, Seller reasonably determines that the products do not meet the Warranty, then Seller shall, at its option, repair or replace the defective product or component thereof, reperform any defective services at Seller's expense, or refund or credit to Buyer its purchase price for the defective products or services.

4.3 The Warranty will be void and will not apply: (i) when Buyer fails to promptly notify Seller of any alleged defect, (ii) when Buyer fails to properly install, maintain, or operate the products, (iii) to any product or parts thereof with a useful life, under normal operating conditions, inherently shorter than 1 month, or (iv) to products which were not made by Seller or any of Seller's affiliates, provided that in such cases Seller shall use reasonable efforts to pass on to Buyer the manufacturer's warranty.

4.4 If Seller provides any parts or services to repair a product that is not under Warranty, then such parts and services will be billed to Buyer at Seller's prevailing rates for time and materials.

4.5 The Warranty set out above is the sole and exclusive warranty provided by Seller for its products and is in lieu of, and Seller expressly disclaims, all other warranties, express or implied, oral, written or statutory. **THERE ARE NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR PURPOSE FOR SELLER'S PRODUCTS.**

5. LIMITATION OF LIABILITIES:

5.1 Seller's total liability to Buyer arising out of or resulting from this Contract or related in any way to Seller's products or parts thereof shall not exceed the contract price for such products.

5.2 Seller shall not be liable for loss of profit or revenues, loss of use of products, interruption of business, downtime costs, increased operating costs, or any special, consequential, incidental indirect or punitive damages, whether incurred by Buyer or Buyer's customers.

5.3 Because the conditions of actual production in each end user's plant vary considerably, Buyer assumes all risk for the results obtained by use of Seller's products in the practice of any process, whether in terms of operating costs, general effectiveness, success or failure, and regardless of any oral or written statements made by Seller related to the use of its products.

6. **SECURITY INTEREST.** Buyer agrees that the Seller shall have and retain a purchase money security interest in the Products securing the payment of all sums becoming due hereunder. Such security interest shall attach, upon completion of manufacture, to the Products and to any parts or accessories attached to the Products and to the proceeds of any sale thereof. Buyer represents that the Products are being acquired for use in its business and that such Products will not, without prior written consent of the Seller, be sold or removed from the Buyer's place of business to which delivery is made. Buyer agrees upon Seller's request to execute any financing statements or other documents required to perfect, continue or renew Seller's security interest in the Products.

7. **CANCELLATION:** Unless otherwise agreed, Buyer may cancel all or any part of the order by written notice received by Seller before the completion of the order. On receipt of such cancellation notice, all work on the order or part thereof canceled will be stopped as promptly as is reasonably possible. Buyer will then be invoiced for and will pay to Seller as liquidated damages a cancellation charge. For completed items, the charge will be equal to their established prices. For items not completed, the charge will be equal to 135% of Seller's full cost as determined by Seller in accordance with Seller's standard accounting practices (which includes burden and overhead), plus a charge for any packing and storage, less a credit for the balance of the material as scrap.

8. **RETURNS:** All returned items require a Return Merchandise Authorization (RMA) number from DME. Returns are subject to a quality inspection to validate whether it can be returned to inventory. Mold bases, plates, special components, made-to-order products and other date-sensitive products are non-returnable items. Items returned to DME without prior authorization (RMA) may be returned to sender. Items returned for stated defect or non-conforming reason require detailed explanation. No products are returnable beyond 30 days after receipt.

9. **CONFIDENTIALITY.** Any nonpublic information, including without limitation, Seller's pricing information and the contents of Seller's quotation or proposal and Buyer's purchase order, exchanged between the parties is deemed confidential ("Confidential Information"). Each party agrees to maintain the other party's Confidential Information in confidence, to not disclose the same to any third parties, and to use it only in connection with this sale. These restrictions shall expire two (2) years after the date of disclosure. This provision does not modify or supersede any separate confidentiality or nondisclosure contract signed by the parties.

10. **FORCE MAJEURE:** Seller shall not be liable for any delay in performance or nonperformance which is due to war, fire, flood, pandemic, acts of God, acts of third parties, acts of governmental authority or any agency or commission thereof, accident, breakdown of products, differences with employees or similar or dissimilar causes beyond Seller's reasonable control, including but not limited to, those interfering with production, supply or transportation of products, raw materials or components or Seller's ability to obtain, on terms Seller deem reasonable, material, labor, products or transportation.

11. **MERGER CLAUSE:** This Contract entirely supersedes any prior oral or written representations, correspondence, proposals, or contracts between the parties regarding the products. This writing constitutes the final and total expression of such contract between the parties, and it is a complete and exclusive statement of the terms of that contract.

12. **ASSIGNMENT:** Neither party may assign this Contract without the written consent of the other party, except that Seller may assign this Contract to a third party that acquires substantially all of Seller's assets and Seller may assign the flow of funds arising out of this Contract.

13. **COMPLIANCE WITH LAWS.** Each party agrees to comply with all applicable laws in the performance of its obligations; Buyer shall not trans-ship, re-export, divert or redirect Products outside of the original country of delivery without Seller's prior written consent.

14. **GOVERNING LAW:** This Contract shall be governed by and construed in accordance with the laws of the State of Michigan, without regard to the Convention for the International Sale of Goods (CISG), which shall not apply.

Sales and Ordering Information

U.S.A.

TERMS AND CONDITIONS OF SALE: See previous page.

PHONE ORDERS – TOLL FREE: 800-626-6653. Our Customer Service Dept. operates Monday through Friday from 8 a.m. to 6 p.m. E.S.T. Calls can be made from anywhere in the continental U.S. and Puerto Rico (Puerto Rico: use “137” prefix instead of “1”). Our Customer Service Representatives will be happy to answer your questions on DME products or services, provide on-the-spot feedback on product availability and shipping details, or take any messages you wish relayed to your local DME sales, manufacturing or technical service representatives.

MAIL ORDERS: If you prefer to order by mail, please address your order to:

DME Company, 29111 Stephenson Highway, Madison Heights, Michigan 48071-2330 FAX 888-808-4363
ATTN: Customer Service Dept.

FAX: You may fax your order to:

DME Customer Service
248-544-5113 • 888-808-4363

CHECKS OR MONEY ORDERS: When paying invoices by check or money order, please make payable to *DME Company*. Include remittance copy of invoice and mail to:

DME Company, PO Box 854867 Minneapolis, MN 55485-4867

WALK-IN ORDERS, PICK-UPS AND RETURNS: If desired, ordered products in stock at your nearest DME Service Center can be picked up rather than shipped. Walk-in orders at Service Center locations can also be processed while you wait. Products being returned for repair or exchange should be processed through Customer Service prior to being returned.

SPECIAL MACHINING SERVICES: Prints for quotation on special machining work can be sent by EDI to dme_cad@dme.net or mailed to the Estimating Department of the DME manufacturing location nearest you. Call our toll-free number if desired to clarify location which serves your area.

Estimating locations are:

DME Company, 29111 Stephenson Highway, Madison Heights, Michigan 48071-2330 FAX 888-808-4363
1117 Fairplains Street, Greenville, MI 48838, Tel. 616-754-4601, FAX: 616-225-3924
3275 Deziel Drive, Windsor, Ont N8W 5A5, Tel. 519-948-5001, FAX: 519-948-4652

Please add “DME Company” and “Attn: Estimating Dept.” to above addresses when mailing prints. To obtain prices and delivery on special mold base orders or to check status of special work in progress please contact Customer Service.

CANADA

TERMS AND CONDITIONS OF SALE: See previous page.

PHONE ORDERS: Contact our Mississauga, Ontario office at 800-387-6600, FAX: 800-461-9965.

MAIL ORDERS: Send to: DME Company Ltd., 6210 Northwest Drive, Mississauga, Ontario L4V 1J6.

CHECK OR MONEY ORDERS: Make payable to *DME Company Ltd.* Include remittance copy of invoice and mail to Mississauga address above.

WALK-IN ORDERS, PICK-UPS, RETURNS, AND SPECIAL MACHINING: Contact our Mississauga office.

Mold Bases: What Every Molder Should Know


Mold Bases

Today's mold-building process is a complex one for the molder, who must grapple with a long list of design details before placing a tooling order. It's understandable that much of the buyer's attention goes to the "heart" of the injection mold, the core and cavity inserts, since they have the most visible influence on the molded part. Yet all sorts of ancillary tooling components, to which the molder might not be inclined to give much thought, can also make or break a mold.

One item that sometimes gets lost in the shuffle is the mold base, even though the wrong one can severely limit a mold's productivity. Rather than an afterthought, mold base selection should be considered critical to the profitability of the entire molding project.

When selecting a mold base for a particular job, first ask a few key questions about the part's design and processing demands: What kind of ejection does it need? Does it have a cam action or some other mold-action device? What are the volume requirements? What type of machine will it run on?

Answer these design and processing questions, and you'll be well on your way to picking the standardized or special-purpose mold base best suited to your application.



A-Series Mold Base Assembly

The most frequently used standard assembly, the "A" Series Mold Base, is available in 43 sizes from 7.875 x 7.875 to 23.75 x 35.5.

Standard Mold Base Styles

For most applications, a standard mold base will fit the bill. The most common of these is the "A-style," which has the flexibility to fit into the widest variety of molding applications.

A-style models have a four-plate design: (from top to bottom) top clamp plate, A-plate, B-plate, support plate, ejector retainer, ejector bar, and ejector housing. Mold makers using an A-style mold base typically machine through pockets in the "A" and "B" plates to accept just about any kind of core and cavity insert.

The B-style mold base represents an economy version of the A-style. The B-style's two-plate design combines the top clamp plate and the "A" plate into one component called the "A-Clamping Plate" or ACP. Likewise, a beefed-up "B" plate eliminates the need for a support plate on the core side of the mold.

Molders can use the less-costly "B" Series when the part design allows the cavity and core to be machined directly into the cavity plates. If the mold will be used with cavity inserts, they must be machined into blind pockets. The compactness of the "B" series mold base also makes it applicable whenever overall mold height must be limited in order to fit the tool in a given molding machine.

"Core and cavity inserts ... have the most visible influence on the molded part yet ... mold base selection should be considered critical to the profitability of the entire molding project."

Special-Purpose Machines

Mold action and ejection requirements will often dictate the use one of three special-purpose mold bases instead of the simpler A- and B-styles.

One of these is the X-style, or stripper-plate, mold base. Sandwiched between the “A” and “B” plates, its stripper (“X”) plate engages the edge of a part and pushes it off the core. Typically, the X-style sees use with round parts like cups, caps, and containers. This style of mold base comes in both five- and six-plate styles- -with the six-plate version including a support plate.

The AX-style mold base is used for parts requiring core detail in the cavity side of the mold. When the mold opens, that core detail is pulled so that the part remains on the ejector side of the mold. The AX-style is essentially an A-style mold base with an “X-1” plate, located between the “A” and “B” plates but attached to the top half of the mold so that it can pull the part off the core detail.

The “T” style, or three-plate, mold base is used when the molder would like to separate the part from the runner in the tool. “T” series mold bases consist of an “A” clamping plate, “X-1” plate, “X-2” plate, “B” plate, and the ejector assembly and housing. Unlike the other mold bases, the “T” series operates with two parting lines. The first parting line, which occurs between the X-1 and X-2 plates, separates the part from the gate prior to opening the main parting line. The main parting line then opens and the X-1 plate is actuated to pull the runner from the sprue-puller pin, thereby freeing the runner and allowing it to be ejected separately from the part being produced.

See page 11 for illustrations of standard mold base types.

Choosing A Steel

Steel selection is an important aspect of specifying the right mold base. Generally there are four standard grades of steel available. See page 8 for mold and die steel descriptions.

Molding Machine Considerations

After you’ve picked the right style and steel for your mold base, it’s time to consider variables related to the molding machine: the locating-ring style, sprue bushing, and clamp slots.

The mold maker must select the type of locating ring that will match the platens of the machine in which the mold will

be running. Locating rings are available in a wide variety of configurations to fit most injection machines, but the most common locating ring has a 3.990 in. outside diameter.

Sprue bushings must also match the machine, so be sure to determine the proper orifice and radius of the sprue bushing so it will match the machine nozzle. The most common type of sprue bushing is made from 6145 steel that has been hardened, ground, and polished for sprue release. In some applications it is desirable to use a high-conductivity copper-alloy sprue bushing.



“High-performance sprue bushings cool the sprue quickly when either the sprue weight is greater than the part weight, or a rigid target is needed for a robotic sprue picker ...”

These “high-performance” sprue bushings can cool the sprue quickly when either the sprue weight is greater than the part weight, or a rigid target is needed for a robotic sprue picker, or when scrap would result from a hot sprue coming in contact with a finished part. High-performance sprue bushings are fully interchangeable with the standard bushings.

A number of different clamp-slot styles are available. Whatever the style, make sure it’s compatible with the thickness of the top clamping plate on your mold base (ACP, “A” plate, or AX plate).

Finally, the molder needs to determine the correct mold base height in relation to the maximum space available in the press. A mold base that won’t run in the appropriate size of press can turn potential profit into loss. In addition, be aware of the maximum stroke required to eject the part for the mold.

Mold and Die Steels

STEEL DESCRIPTIONS

Three Steels for Structural Sections

DME NO. 1 STEEL

No. 1 Steel is a medium carbon (SAE 1030) or equivalent, silicon-killed forging quality steel with approximately 25% greater tensile strength than typical low-carbon warehouse steels. It machines easily, but is not “sticky,” permitting a faster and smoother cut.



DME NO. 2 STEEL

No. 2 Steel is an AISI 4130 or equivalent type steel. It is supplied pre-heat treated to 28-34 HRC (271-321 Bhn). A high strength steel, it is ideal for cavity and core retainer plates, clamping plates and support plates in molds and dies.

DME NO. 7 STEEL

No. 7 Steel is a modified AISI 400 or equivalent series stainless steel for holder block applications. It is supplied pre-heat treated to 32-36 HRC (302-340 Bhn). This stainless steel offers corrosion-resistance and exceptional machinability but cannot be further hardened (see DME No. 6). For humid environments, corrosive plastics, “clean room” or “100% stainless” applications, it is an ideal choice for all structural (non-cavity/core) mold plates.

Three Steels for Cavities and Cores

DME NO. 3 STEEL

No. 3 Steel is a P-20 AISI 4130 (modified) type cavity steel. Exceptionally clean, it is pre-heat treated to 28-34 HRC (271-321 Bhn). It provides high hardness, good machinability and exceptional polishability for both plastics molds and die cast dies.

DME NO. 5 STEEL

No. 5 Steel is a thermal shock resistant, hotwork die steel (AISI-SAE H-13 type) or equivalent. Supplied fully annealed 13-20 HRC (approx. 200 Bhn) for easy machinability, it can be subsequently heat treated to the desired hardness with a minimum of deformation.

Mainly used for die cast dies, it is also suitable for plastics molds with exceptional hardness or polishability requirements.

DME NO. 5 Steel meets or exceeds the acceptance criteria established by the NADCA as detailed in Technical Digest Number 01-80-01D

DME NO. 6 STEEL


No. 6 Steel is T-420 type or equivalent stainless steel. It is supplied fully annealed to 8-23 HRC (179-241 Bhn), making it readily machinable. It can be used for injection, compression or transfer molds where the properties of the plastics materials or excessive condensation require a highly corrosion resistant cavity steel.

OTHER TYPES OF STEEL AVAILABLE ON SPECIAL ORDER. CONTACT DME.

Benefits of Standard Mold Base Assemblies and Components

Seven major benefits of DME Standard Mold Base Assemblies and Components

1. Made of high quality, pre-finished mold and die steels that give you more for your money; more metallurgical consistency; more cleanliness in cavity steels; more reliability.
2. Assemblies, plates and components are pre-engineered to give you the economic and technical benefits of interchangeability.
3. Manufactured with the most advanced, precision equipment – and quality control tested to give you reliable performance.
4. Gives designers more freedom and flexibility – more time to devote to the truly creative aspects of mold, die, and product design.
5. Gives mold and die makers more time to concentrate on cavities and cores – thus increasing productivity as much as 40%.
6. Gives molders more quality parts per hour, more profitability – with production proven construction that outlasts the longest runs.
7. Readily available as you need them. The more popular assemblies are always in stock for same-day service. Our nationwide network of Service Centers means you have the products and the people near you to help you save time, money and inventory costs.




These three features have helped make DME Standard Mold Bases the most frequently specified mold base assemblies in the world:

- 1 CLAMP SLOTS that save platen space and provide maximum cavity area
- 2 TUBULAR DOWELS that provide more room for waterlines
- 3 THREE-PIECE EJECTOR HOUSING with shoulder bolts

DME Standard "A" Series Mold Base with Cavity Inserts

INJECTION MOLDING

Injection molding is recognized as the single most important form of plastics processing. Beginning with just a handful of standardized mold bases and components in 1942, DME now offers thousands of standardized mold base assemblies and a broad variety of mold components to satisfy the consistent need for high-quality injection molds. Primarily used for thermoplastics injection molding, most of our assemblies and components are readily adaptable for the injection molding of thermosets. Future product developments from DME will include standardized components specifically designed for the injection molding of thermoset materials.



DME Item Number System

The item number system employed by DME not only prevents the duplication of item numbers, but helps lessen the chances of error in the writing and production of orders. This is accomplished by incorporating actual dimensional data into the item numbers as indicated below.

MOLD BASES – “A” AND “B” SERIES

The item numbers for Standard Mold Bases in the “A” and “B” Series combine the NOMINAL Size (width and length), the Series (A or B) and the thicknesses of the “A” (or “A”-Clamping) and “B” Plates.

Since all the standard mold plate thicknesses are a combination of a whole number and either $\frac{3}{8}$ or $\frac{7}{8}$, the designation 13 indicates 1 and $\frac{3}{8}$; 17 indicates 1 and $\frac{7}{8}$; 23 indicates 2 and $\frac{3}{8}$, etc.

For Example: 1016A-13-37 is the item number for a $9\frac{7}{8} \times 16$ “A” Series Mold Base with “A” plate $1\frac{3}{8}$ and “B” plate $3\frac{7}{8}$ thick.

MOLD BASES – “X” OR STRIPPER PLATE SERIES

The item numbers for the Stripper Plate Series Mold Base combine the NOMINAL Size (width and length), the letter “X” for Stripper Plate, the numeral 5 or 6 (plate series) and the “AX” plate thickness.

Since the “X” plate thickness is constant at $\frac{7}{8}$ or $1\frac{3}{8}$, and the “BX” plate thickness is constant at $1\frac{3}{8}$, $1\frac{7}{8}$ or $2\frac{3}{8}$, depending on the mold base nominal size and number of plates in the assembly, these thicknesses are not represented in the item number.

For Example: 1818X-5-13 is the item number for a $17\frac{7}{8} \times 18$, 5-plate “X” series Mold Base with a $1\frac{3}{8}$ thick “AX” plate. (In this case, the “X” plate is $1\frac{3}{8}$ thick, and the “BX” plate is $2\frac{3}{8}$ thick).

“AX” AND “T” SERIES MOLD BASES

The item numbers for the “AX” Series Mold Bases combine the NOMINAL Size (width and length), the letters “AX” and the thickness of the “A” and “B” plates. The “X-1” plate thickness is specified when ordering and is omitted from the item number.

For Example: 1212AX-13-37 is the item number for an $11\frac{7}{8} \times 12$ “AX” Series Mold Base with a $1\frac{3}{8}$ thick “A” plate and $3\frac{7}{8}$ thick “B” plate. The “X-1” plate thickness (e.g. $\frac{7}{8}$) is then specified when ordering.

The item numbers for the “T” Series Mold Bases combine the NOMINAL Size (width and length), the letter “T” and the thickness of the “X-2” and “B” plates.

Since the thickness of the “A”-Clamping plate is constant at $1\frac{7}{8}$ or $2\frac{3}{8}$ and the “X-1” plate thickness is constant at $\frac{7}{8}$ or $1\frac{3}{8}$, depending on the nominal size of the mold base, these thicknesses are not represented in the item number.

For Example: 1012T-23-17 is the item number for a $9\frac{7}{8} \times 11\frac{7}{8}$ “T” Series Mold Base with a $2\frac{3}{8}$ thick “X-2” plate and $1\frac{7}{8}$ thick “B” plate. (In this case, the “A”-Clamping plate is $1\frac{7}{8}$ thick and the “X-1” plate is $\frac{7}{8}$ thick).

CAVITY RETAINER SETS

Since Cavity Retainer Sets are made up solely of an “A” and “B” plate, the item numbers combine the NOMINAL Size, and the “A” and “B” plate thicknesses. (The absence of the letter “A”, “B”, “AX”, or “T” distinguish these numbers from the item numbers of Standard Mold Bases).

For Example: 1215-33-47 is an $11\frac{7}{8} \times 15$ Cavity Retainer Set with “A” plate $3\frac{3}{8}$ and “B” plate $4\frac{7}{8}$ thick.

MOLD PLATES

The same principle used for numbering Cavity Retainer Sets is applied to Standard Mold Plates; however, only one plate thickness is required. (Since the item numbers for retainer sets will always indicate two separate plate thicknesses, the distinction between these two items is easily identified).


For Example: 1318-47 is a $13\frac{3}{8} \times 18$ Mold Plate, $4\frac{7}{8}$ thick.

NOTE: While an understanding of this item number system can be very helpful in identifying and referring to the various standard sizes, the DME catalog should be consulted when ordering any standard item.


[CONTACT US](#)

Standard Mold Base Terminology

"A" AND REVERSE "A" SERIES ASSEMBLIES




The most frequently used Standard Assembly, the "A" Series Mold Base is available in 43 sizes from $7\frac{7}{8} \times 7\frac{7}{8}$ to $23\frac{3}{4} \times 35\frac{1}{2}$. See pages 52-137 for complete information.



REVERSE "A" SERIES

Identical to the "A" Series, with leader pins and bushings "reversed." Specify "AX" and "BX" plate thicknesses when ordering (rather than "A" and "B").


"B" SERIES ASSEMBLY




When cavities and cores are to be inserted into blind pockets, or machined directly into the "A" and "B" plates, the "B" Series Assembly is used. The Top Clamping Plate and Support Plate are omitted from the assembly.

"X" SERIES (STRIPPER PLATE) ASSEMBLY

Most frequently used for molds requiring stripper plate ejection, the "X" Series Assembly is available with a Support Plate (6-plate series) or without a Support Plate (5-plate series).




"AX" SERIES ASSEMBLY



The "AX" Series Assembly is used when the mold requires a floating plate to remain with the upper or stationary half of the assembly. It is basically an "A" Series Assembly with a floating plate ("X-1") added.


"T" SERIES ASSEMBLY



The "T" Series Assembly is used for top runner molds that require two floating plates ("X-1" – runner stripper plate, "X-2" – cavity plate) to remain with the upper or stationary half of the assembly.


Machining of Clamp Slots

Clamp Slots facilitate clamping the mold to the platen of the press. DME mold bases offer four slot types (shown below) to ensure the best fit for the requirements of your application.



Type A


Machined when Top Clamping Plate is 0.875 or 1.375



NOTE:
When this plate is 0.875 thick, the slots will be machined through the thickness.


Type B

Machined in plates that are 2.375 or thicker




Type C

Machined only when specified by a customer



Type D

Machined plates that are 1.875 thick



DME Mold Base and Plate Services

The fastest delivery of standard, mold bases, special mold bases, and contour roughed mold plates






Table of Contents




DME XPress A&B Mold Bases..... 16 to 19

*Precision Interchangeable Plates,
Fully Featured, Immediate Shipment*



DME XPress Plus Mold Bases 20 to 23

*Special mold bases with the features you
want delivered with precision and speed*



Special Mold Bases & Plates25

*Special mold bases with the features you
want delivered with precision and speed*



Large Custom Mold Bases & Plates; Contour Roughing Services28

*Precision machined custom mold bases and
plates with lengths up to 90"; rough milling of
your complex part shapes into mold plates*

Online Configurator

DME XPress™ Mold Bases

SUPERIOR STEEL
EASY TO ORDER
FASTER DELIVERY
THOUSANDS OF CONFIGURATIONS



DME XPress Mold Bases

DME XPress A-Series Mold Bases



DME XPress™ A-Series Mold Base

PRECISION INTERCHANGEABLE PLATES, FULLY FEATURED, IMMEDIATE SHIPMENT

The all new DME XPress mold base sets the standard for immediate shipment with **32,400 combinations ready for same or next day shipment**. By starting your project with DME XPress you gain a competitive edge as it provides greater value through improved quality, tighter tolerances, and the fastest delivery. In fact, every steel plate within this mold bases is interchangeable. If you have a plate emergency, a new fully drilled replacement plate is available and ready to ship the same day.

The DME XPress mold base is completely engineered, pre-machined and ready to purchase off the shelf. We've taken these steps to add value to your compressed due dates.

The DME XPress mold base truly redefines value for standard mold bases.


KEY CUSTOMER BENEFITS

- Immediate or Next Day Shipments*
- Interchangeable Plates
- 23 Sizes – 8" x 8" to 19" x 24"
- 9 - A/B Plate thicknesses - 7/8" to 5 7/8"
- 162 A/B Plate Combinations, 4 or 5 rail height
- Design is fully engineered and validated
- Off the shelf
- Replacement plates, ship same day
- Extends time available to design
- Price and features represents much greater value over the purchase of 7 individual RGM plates

Contact - DME

For more information or delivery options contact at:
800-626-6653 (U.S.) • 800-387-6600 (Canada) • 248-398-6000 (Worldwide).

CONTACT US



IT'S ALL IN THERE!

Finished Precision Interchangeable Plates,
Fully Featured, Immediate Shipment

DME XPRESS™ MOLD BASE FEATURES

- 7 Plate "A" Series Design
- No. 3 Premium P20 for A and B Plates
- Stress Relieved and Pre-hardened
- Steel Finish Ground $\pm .001$ "
- Interchangeable Plates
- Center Hole option
- Guided Ejection option
- Return Pins – Inboard (prevents spring breakout)
- Locating Ring
- Sprue Bushing
- Vented Leader Pins
- Type "C" Clamp Slots
- Lift Holes (top clamp plate and support plate)
- Pry bar slots on parting line and ejector plate
- Chamfering on all plate edges
- Stop Disks
- 3-Piece ejector housing with shoulder bolts

XPA MOLDBASE STEEL

DESCRIPTION	STEEL	T	W X L
Top Clamp Plate	#2	± 0.001	± 0.002
AC Plate	#3	± 0.001	± 0.002
A Plate	#3	± 0.001	± 0.002
B Plate	#3	± 0.001	± 0.002
Support Plate	#2	± 0.001	± 0.002
Rails	#1	± 0.001	+0/-0.004
Ejector Retainer Plate	#1	± 0.015	+0/-0.004
Ejector Plate	#1	± 0.015	+0/-0.004
Bottom Clamp Plate	#1	± 0.001	± 0.002

DME XPress A-Series Mold Bases

DME XPress™ A-Series Mold Base

Get XPress 3D CAD data: Go to: dme.net/cad-data/
 3D CAD data available in SolidWorks, Parametric, Creo and Parasolid.

TO ORDER AN XPRESS PLUS MOLD BASE:

Go to the [CONFIGURATOR](#)

Click on DME XPress A or B Series and configure your XPress mold base through the following 6 steps:

- 1 Configure your new mold base by choosing one choice for each selection option.
- 2 Sprue Bushing "O" 3 Sprue Bushing "R" 4 Locating Ring 5 Quantity

Example Part Number for highlighted selections: **XPA1012 -17 -17 -35 -GE -3**

1	XP	A	1012	-17	-17	-35	-GE	-3
---	----	---	------	-----	-----	-----	-----	----

FAMILY	SERIES		BASE	SIZE (W" X L")	AP	THICKNESS	BP	THICKNESS	RAIL	HEIGHT	EJECTION		A/B PLATE MATERIAL	
XP	A	A Series	0808	7.875 x 7.875	7*	0.875"	7	0.875"	25 [†]	2.50"	GE	Guided Ejection	3	P20
XP	B	B Series	0812	7.875 x 11.875	13*	1.375"	13	1.375"		3.00"				
			1008	9.875 x 8	17	1.875"	17	1.875"	35	3.50"	NG	No Guided Ejection		
			1012	9.875 x 11.875	23	2.375"	23	2.375"	40	4.00"				
			1016	9.875 x 16	27	2.875"	27	2.875"	45	4.50"				
			1112	10.875 x 12	33	3.375"	33	3.375"						
			1114	10.875 x 14	37	3.875"	37	3.875"						
			1118	10.875 x 18	47	4.875"	47	4.875"						
			1212	11.875 x 12	57	5.875"	57	5.875"						
			1215	11.875 x 15	7NCH*	7/8"								
			1220	11.875 x 20	13NCH*	1 3/8"								
			1315	13.375 X 15	17NHC	1 7/8"								
			1318	13.375 X 18	23NHC	2 3/8"								
			1321	13.375 X 20.75	27NHC	2 7/8"								
			1518	14.875 x 17.875	33NHC	3 3/8"								
			1524	14.875 x 23.75	37NHC	3 7/8"								
			1616	15.875 x 16	47NHC	4 7/8"								
			1620	15.875 x 20	57NHC	5 7/8"								
			1623	15.875 x 23.5										
			1818	17.875 x 18										
			1820	17.875 x 20										
			1823	17.875 x 23.5										
			1924	19.5 x 23.75										



- A & B-Series plates with no additional letters = Center hole in the TCP, AP, and AC plates.
 - NCH = No center hole in the TCP and the AP plate for the A-series or the AC plate for B-Series
 * 7/8" and 1 3/8" available only in the A-Series
 † = 2.5" Rails only available in base sizes 0808 to 1118

2		3		4	
0 - 7/32"		R - 1/2"		L - 6501	
SPRUE ORIFICE		SPRUE RADIUS		LOCATING RING	DESCRIPTION
0	5/32"	R	1/2"	6501	3.99 ø Standard
	7/32"		3/4"	6521	3.99 ø Standard, Extra Length
	9/32"		Omit	6504	3.99 ø Clamp Type
	11/32"				Omit
	Omit				

5 SELECT A QUANTITY

XPA MOLD BASE STEEL COMPOSITION

- #1 Steel: AISI 1045, 1.1730 or equivalent, stress-relieved, annealed
- #2 Steel: AISI 4130, 4140 or equivalent, stress-relieved, pre-hardened, 28/34 HRC
- #3 Steel: AISI P20, DIN 1.2311, G40CrMnMo7 or equivalent, stress-relieved, pre-hardened, 28/35 HRC

XPA MOLD BASE SUPPORT MATERIAL

- [3D CAD DATA AVAILABLE](#) for download: Solidworks parametric, Creo, & Parasolid drawings
- Product Specifications
- Product Features
- ONE YEAR Manufacturers warranty

* Plates ≥ 5 7/8" thick may require additional time for delivery.



DME XPress B-Series Mold Bases



DME XPress™ B-Series Mold Base

**PRECISION INTERCHANGEABLE PLATES,
FULLY FEATURED, IMMEDIATE SHIPMENT**

The all new DME XPress mold base sets the standard for immediate shipment with **58,000 combinations ready for same or next day shipment.**

THE DME XPRESS ADVANTAGE

Stress Relieved & Pre-Hardened Steel

- Increases your cutting speeds
- Reduces machine center spindle time
- Avoid unnecessary downtime
- Extended tool life
- DME #3 premium P20 steel - "Machined 4 Quality"


Interchangeable plates

- Precision machined
- Repeatable
- Replacement plates ship same day

Off the Shelf

- 58,000 configurations
- Engineered and validated
- Immediate shipment*

Immediate Quotes and Orders - eStore

- Configurable mold base
- Real-time pricing on-line 24/7
- Add to , Order
- Emailed confirmation

Configure, Price, Order < 1 Minute


Contact Milacron - DME

For more information or delivery options contact at:
800-626-6653 (U.S.) • 800-387-6600 (Canada) • 248-398-6000 (Worldwide).

[CONTACT US](#)

* Plates $\geq 5\ 7/8$ " thick may require additional time for delivery.

U.S. 800-626-6653 • Canada 800-387-6600 • sales@dme.net • www.dme.net



IT'S ALL IN THERE!

Finished Precision Interchangeable Plates,
Fully Featured, Immediate Shipment

STANDARD MOLD BASE FEATURES INCLUDE:

- 5 Plate B-Series Design
- 23 Sizes – 8" x 8" to 19" x 24"
- 7 AC/B-Plate thicknesses – 1-7/8" to 5-7/8"
- 126 A/B-Plate combinations
- Rail Heights 2.5" - 4.5"
- #3 Premium P20 steel for AC and B-Plates
- Steel Finish Ground $\pm .001$ "
- Center Hole (optional)
- Guided Ejection - system #3 (optional)
- Return Pins – inboard, position #2 (prevents spring breakout)
- Locating Ring (optional)
- Sprue Bushing (optional)
- Vented Leader Pins
- Clamp Slots
- Pry Bar Slots on parting line and ejector plate
- Chamfering on all plate edges
- Stop Disks
- 3-Piece Ejector Housing with shoulder bolts

XPRESS MOLD BASE STEEL

DESCRIPTION	STEEL	T	W X L
AC-Plate	#3	± 0.001	± 0.002
B-Plate	#3	± 0.001	± 0.002
Rails	#1	± 0.001	+0/-0.004
Ejector Retainer Plate	#1	± 0.015	+0/-0.004
Ejector Plate	#1	± 0.015	+0/-0.004
Bottom Clamp Plate	#1	± 0.001	± 0.002

DME XPress B-Series Mold Bases

DME XPress™ B-Series Mold Base

Get XPress 3D CAD data: Go to: dme.net/cad-data/

3D CAD data available in SolidWorks® Parametric, Creo Parametric, and Parasolid.

TO ORDER AN XPRESS MOLD BASE:


Go to the [CONFIGURATOR](#)

Click on DME XPress B-Series TAB and configure your XPress mold base through the following 5 steps:

- 1 Configure your new mold base by choosing one choice for each selection option.
- 2 Sprue Bushing "O"
- 3 Sprue Bushing "R"
- 4 Locating Ring
- 5 Quantity

Example Part Number for highlighted selections: **XPB1012 -17 -17 -35 -GE -3**

1



XP		B		1012		-17		-17		-35		-GE		-3	
FAMILY	SERIES	BASE	SIZE (W" X L")	AC	THICKNESS	BP	THICKNESS	RAIL	HEIGHT	EJECTION		A/B PLATE MATERIAL			
XP	A	A Series	0808	7.875 x 7.875	7*	0.875"	7	0.875"	25†	2.50"	GE	Guided Ejection	3	P20	
XP	B	B Series	0812	7.875 x 11.875	13*	1.375"	13	1.375"	30	3.00"					
			1008	9.875 x 8	17	1.875"	17	1.875"	35	3.50"	NG	No Guided Ejection			
			1012	9.875 x 11.875	23	2.375"	23	2.375"	40	4.00"					
			1016	9.875 x 16	27	2.875"	27	2.875"	45	4.50"					
			1112	10.875 x 12	33	3.375"	33	3.375"							
			1114	10.875 x 14	37	3.875"	37	3.875"							
			1118	10.875 x 18	47	4.875"	47	4.875"							
			1212	11.875 x 12	57	5.875"	57	5.875"							
			1215	11.875 x 15	7NCH*	0.875"									
			1220	11.875 x 20	13NCH*	1.375"									
			1315	13.375 X 15	17NHC	1.875"									
			1318	13.375 X 18	23NHC	2.375"									
			1321	13.375 X 20.75	27NHC	2.875"									
			1518	14.875 x 17.875	33NHC	3.375"									
			1524	14.875 x 23.75	37NHC	3.875"									
			1616	15.875 x 16	47NHC	4.875"									
			1620	15.875 x 20	57NHC	5.875"									
			1623	15.875 x 23.5											
			1818	17.875 x 18											
			1820	17.875 x 20											
			1823	17.875 x 23.5											
			1924	19.5 x 23.75											

2

0 - 7/32"

SPRUE ORIFICE	
0	5/32"
	7/32"
	9/32"
	11/32"
	Omit

3

R - 1/2"

SPRUE RADIUS	
R	1/2"
	3/4"
	Omit

4

L - 6501

LOCATION RING	DESCRIPTION	
L	6501	3.99 Ø Standard
	6521	3.99 Ø Standard, Extra Length
	6504	3.99 Ø Clamp Type
		Omit

- A & B-Series plates with no additional letters include center hole in the TCP & AP, or AC plates.
 - **NCH** = No center hole in the TCP and AP plate for the A-Series or the AC plate for B-Series
 * 7/8" and 1 3/8" available only in the A-Series
 † = 2.5" Rails only available in base sizes 0808 to 1118

- 5** SELECT A QUANTITY
- 6** ADD TO ORDER

XPRESS MOLD BASE STEEL COMPOSITION

- #1 Steel:** AISI 1045, 1.1730 or equivalent, stress-relieved, annealed
- #2 Steel:** AISI 4130, 4140 or equivalent, stress-relieved, pre-hardened, 28-34 HRC
- #3 Steel:** AISI P20, DIN 1.2311, G40CrMnMo7 or equivalent, stress-relieved, pre-hardened, 28-35 HRC

XPRESS MOLD BASE SUPPORT MATERIAL

- [3D CAD DATA AVAILABLE](#) for download: Solidworks® Parametric, Creo, & Parasolid drawings
- Product Specifications
- Product Features
- ONE YEAR Manufacturers warranty

store.milacron.com

U.S. 800-626-6653 • Canada 800-387-6600 • sales@dme.net • www.dme.net


DME XPress B-Series Mold Bases

DME XPress A-Series Stainless Steel

DME XPress™ Stainless Steel

A-Series Mold Bases

**INTERCHANGEABLE PLATES, FULLY FEATURED,
IMMEDIATE SHIPMENT**



SUPERIOR STEEL

- Stress relieved, pre-hardened DME #7 (420S) steel
- Enables faster cutting speeds for reduced spindle time
- Extended tool insert life
- Avoid costly manufacturing downtime

EASY TO ORDER

- Configurable mold base
 - Real-time pricing on-line 24/7
 - Add to Order
 - Emailed confirmation
- All in under 1 Minute*

FASTER DELIVERY

- Tight deadline... no problem...
- Off the shelf availability
- Ships same or next day*
- Start cutting immediately

eSTORE 24/7 at www.store.dme.net or call DME Customer Care at 800-626-6653

Configure your mold base using steps 1-4 below. Example Part Number for highlighted selections: **XPA1012 -17 -17 -30 -GE -7**

1	XP	A	1012	-17	-17	-30	-GE	-7					
	FAMILY	SERIES	BASE	SIZE (W" X L")	AP	THICKNESS	BP	THICKNESS	RAIL	HEIGHT	EJECTION	MATERIAL ALL PLATES	
	XP	A	A Series	0808	7.875 x 7.875	13	1.375"	13	1.375"	30	3.00"	GE	7
				0812	7.875 x 11.875	17	1.875"	17	1.875"	40	4.00"	Guided Ejection	420 SS
				1012	9.875 x 11.875	23	2.375"	23	2.375"				
				1016	9.875 x 16	27*	2.875"	27	2.875"				
				1118	10.875 x 18								
				1215	11.875 x 15								
				1318	13.375 X 18								

* 2-7/8 AP thickness (-27) only available in the 1318 base size

XPRESS MOLD BASE STEEL

DESCRIPTION	STEEL	T	W X L
Top Clamp Plate	#7	±0.001	±0.002
A-Plate	#7	±0.001	±0.002
B-Plate	#7	±0.001	±0.002
Support Plate	#7	±0.001	±0.002
Rails	#7	±0.001	+0/-0.004
Ejector Retainer Plate	#7	±0.015	+0/-0.004
Ejector Plate	#7	±0.015	+0/-0.004
Bottom Clamp Plate	#7	±0.001	±0.002

2	3	4
0 - 7/32"	R - 1/2"	L - 6501
SPRUE ORIFICE	SPRUE RADIUS	LOCATING RING
0	R	L
5/32"	1/2"	6501
7/32"	3/4"	6521
9/32"	Omit	6504
11/32"		
Omit		
		Omit

may be extended due to inventory level.

Get XPress 3D CAD data: Go to: www.dme.net/cad-data/
3D CAD data available in SolidWorks® Parametric, Creo Parametric and Parasolid.

DME XPress PLUS Stainless Steel

With a value, quality, and lead time that is so compelling the DME XPress Mold Base enables even the most efficient shop to save time and money by purchasing instead of making – *increasing productivity as much as 40%*.

Now take it to the next level...

DME XPress PLUS offers the XPress mold base features, **plus** additional services to meet your needs and a 50% faster lead time than the industry standard.

TO ORDER AN XPRESS PLUS MOLD BASE:

Go to the [CONFIGURATOR](#)
[ESTORE](#)

- 1 CONFIGURE YOUR NEW MOLD BASE STACK-UP
- 2 SPRUE BUSHING "O" 3 SPRUE BUSHING "R" 4 LOCATING RING 5 SELECT A QUANTITY
- 6 ADD XPRESS PLUS SERVICES

- Support Pillars
- Secondary Leader Pins – Manifold Alignment
- Reversed Leader Pins – Manifold Alignment
- Additional Stop Disks – (drill/tapped holes)
- Additional Assembly Screws
- Additional Return Pins
- Additional Pry bar Slots
- Waterlines – including Counterbores & Taps
- Ejector Pin Holes
- Spring Holes (std. dia. only) Return Pin Loc.
- Rectangular Insert Pockets – Blind/Through (minimum 0.375" corner radius)
- Rough or Finished Pockets
- Lock Pockets
- Slide Pockets
- Rough Bore – Blind/Through
- Side & Parting Line Interlocks
- Knock Out Holes
- Stripper Bolt Holes
- Safety Strap Holes
- Additional Lift Holes
- Pipe Clearance Slots
- Shot Counter Pocketing

7 SEND CAD FILES TO DME

Drawing Formats: Electronic drawing/models from you:

- Download DME XPress 3D CAD data in: Solidworks™ Parasolids, Creo Parasolids and Step
- Return to DME dme_cad@dme.net Modified 3D model with additional features required
- 2D-drawings with tolerances

DME is able to work paperless only from 3D-models, 2D-Data is required for tolerance info.

CONTACT US

For more information or delivery options contact at:
800-626-6653 (U.S.) • 800-387-6600 (Canada) • 248-398-6000 (Worldwide).



DME XPress A-Series Stainless Steel

DME XPress PLUS Mold Bases



Premium, Interchangeable Plate Mold Base "PLUS" Additional Services

DME XPRESS™ PLUS MOLD BASE

The DME XPress is an A or B-Series mold base, available in 23 sizes, which can be configured into 58,000 standard mold bases. Please see the XPress [CONFIGURATOR](#)

With a value, quality, and lead time that is so compelling the DME XPress Mold Base enables even the most efficient shop to save time and money by purchasing instead of making – *increasing productivity as much as 40%.*

Now take it to the next level...

DME XPress PLUS offers the XPress mold base features, *plus* additional services to meet your needs and a 50% faster lead time than the industry standard.

THE DME XPRESS ADVANTAGE

Stress Relieved & Pre-Hardened Steel

- Increases your cutting speeds
- Reduces machine center spindle time
- Avoid unnecessary downtime
- Extended tool life
- DME #3 premium P20 steel - "Machined 4 Quality"

Interchangeable plates

- Precision machined
- Repeatable
- Replacement plates ship same day

Off the Shelf

- 58,000 configurations
- Engineered and validated
- Immediate shipment*
- Plates $\geq 5\ 7/8$ " thick may require additional time for delivery.

For more information or delivery options contact at:
800-626-6653 (U.S.) • 800-387-6600 (Canada) • 248-398-6000 (Worldwide).

[CONTACT US](#)



ADDITIONAL XPRESS PLUS SERVICES

- Support Pillars
- Secondary and/or Reversed Leader Pins
- Additional Stop Disks, Assembly Screws, Return Pins
- Knock Out Holes
- Waterlines Horizontal & Vertical
- Ejector Pin and Spring Holes
- Rectangular Pockets - Rough or Finished
- Lock and Slide Pockets
- Rough Bore – Blind/Through
- Side & Parting Line Interlocks
- Stripper Bolt, Safety Strap and Lift Holes
- Pipe Clearance Slots
- Shot Counter Pocketing

XPRESS MOLD BASE STEEL COMPOSITION

#1 Steel: AISI 1045, 1.1730 or equivalent, stress-relieved, annealed

#2 Steel: AISI 4130, 4140 or equivalent, stress-relieved, pre-hardened, 28-34 HRC

#3 Steel: AISI P20, DIN 1.2311, G40CrMnMo7 or equivalent, stress-relieved, pre-hardened, 28-35 HRC

XPRESS MOLD BASE STEEL

DESCRIPTION	STEEL	T	W X L
Top Clamp Plate	#2	±0.001	±0.002
AC-Plate	#3	±0.001	±0.002
A-Plate	#3	±0.001	±0.002
B-Plate	#3	±0.001	±0.002
Support Plate	#2	±0.001	±0.002
Rails	#1	±0.001	+0/-0.004
Ejector Retainer Plate	#1	±0.015	+0/-0.004
Ejector Plate	#1	±0.015	+0/-0.004
Bottom Clamp Plate	#1	±0.001	±0.002

DME XPress PLUS Mold Bases

Get XPress 3D CAD data: Go to: dme.net/cad-data/
 3D CAD data available in SolidWorks® Parametric, Creo Parametric and Parasolid.

TO ORDER AN XPRESS PLUS MOLD BASE:

Go to the [CONFIGURATOR](#)

Click on DME XPress A or B-Series tab and configure your XPress mold base through the following 6 steps:

Configure your mold base using steps 1-7 below. Example Part Number for highlighted selections: **XPA1012 -17 -17 -35 -GE -3**

1 XP A 1012 -17 -17 -35 -GE -3


FAMILY	SERIES	
XP	A	A Series
XP	B	B Series

BASE	SIZE (W" X L")
0808	7.875 x 7.875
0812	7.875 x 11.875
1008	9.875 x 8
1012	9.875 x 11.875
1016	9.875 x 16
1112	10.875 x 12
1114	10.875 x 14
1118	10.875 x 18
1212	11.875 x 12
1215	11.875 x 15
1220	11.875 x 20
1315	13.375 X 15
1318	13.375 X 18
1321	13.375 X 20.75
1518	14.875 x 17.875
1524	14.875 x 23.75
1616	15.875 x 16
1620	15.875 x 20
1623	15.875 x 23.5
1818	17.875 x 18
1820	17.875 x 20
1823	17.875 x 23.5
1924	19.5 x 23.75

AP	THICKNESS	BP	THICKNESS
7*	0.875"	7	0.875"
13*	1.375"	13	1.375"
17	1.875"	17	1.875"
23	2.375"	23	2.375"
27	2.875"	27	2.875"
33	3.375"	33	3.375"
37	3.875"	37	3.875"
47	4.875"	47	4.875"
57	5.875"	57	5.875"
7NCH*	0.875"		
13NCH*	1.375"		
17NHC	1.875"		
23NHC	2.375"		
27NHC	2.875"		
33NHC	3.375"		
37NHC	3.875"		
47NHC	4.875"		
57NHC	5.875"		

RAIL	HEIGHT
25†	2.50"
30	3.00"
35	3.50"
40	4.00"
45	4.50"

EJECTION		A/B PLATE MATERIAL
GE	Guided Ejection	3 P20
NG	No Guided Ejection	



2

0 - 7/32"

SPRUE ORIFICE

0	5/32"
	7/32"
	9/32"
	11/32"
	Omit

3

R - 1/2"

SPRUE RADIUS

R	1/2"
	3/4"
	Omit

4

L - 6501

LOCATION RING	DESCRIPTION
L 6501	3.99 Ø Standard
6521	3.99 Ø Standard, Extra Length
6504	3.99 Ø Clamp Type
	Omit

5 SELECT A QUANTITY

6 ADD XPRESS PLUS SERVICES

7 SEND CAD FILES TO DME

CUSTOMER SUPPORT MATERIAL

Drawing Formats: Electronic drawing/models from you:

- Download DME XPress 3D CAD data in: Solidworks™ Parasolids, Creo Parasolids and Step
- Return to DME dme_cad@dme.net Modified 3D model with additional features required
- 2D-drawings with tolerances

DME is able to work paperless only from 3D-models, 2D-Data is required for tolerance info.

- Support Pillars
- Secondary Leader Pins – Manifold Alignment
- Reversed Leader Pins – Manifold Alignment
- Additional Stop Disks – (drill/tapped holes)
- Additional Assembly Screws
- Additional Return Pins
- Additional Pry bar Slots
- Waterlines – including Counterbores & Taps
- Ejector Pin Holes
- Spring Holes (std. dia. only) Return Pin Loc.
- Rectangular Insert Pockets – Blind/Through (max pocket depth 3" / minimum 0.375" corner radius)
- Rough or Finished Pockets
- Lock Pockets
- Slide Pockets
- Rough Bore – Blind/Through
- Side & Parting Line Interlocks
- Knock Out Holes
- Stripper Bolt holes
- Safety Strap Holes
- Additional Lift Holes
- Pipe Clearance Slots
- Shot Counter Pocketing



Get the Edge with DME Mold Components

DME innovation has been vital to the development of mold technologies ever since standardized DME mold base offerings were created in the 1940s to enable moldmakers to focus their creativity on value-added core and cavity work. New DME mold components continue to be developed to complement your Edge mold base, or any DME mold base, for that matter.

Here are just a few of the mold components that will give your DME mold base the edge:

Pins, sleeves and blades

A comprehensive line of pins, sleeves and blades – in Inch, DIN and JIS standards – all of which undergo rigorous DME quality assurance testing, are available at competitive prices with fast delivery. From straight, shoulder or keyed ejector pins to nitrided ejector sleeves and close-tolerance ejector blades to core pins, return pins and sprue puller pins, DME products match your application needs.

Sprue bushings and locating rings


A wide range of DME hardened, ground and polished sprue bushings and more than a dozen locating ring options are available for maximum production performance.

Mold interlocks

For precise alignment of mold halves, mold plates or individual cavities or cores, DME mold interlocks are a perfect fit for all of your applications. From the innovative IN2 interlocks that offer interchangeable inserts to a variety of side, top, round and rectangular interlocks, DME products eliminate your mold alignment concerns.


Thousands of other mold components to complement your mold base selection

DME market-leading mold technologies are available around the globe, with many choices within hundreds of product lines. Our proven knowledge and expertise has made DME the preferred supplier to many of the world's leading companies. Check out the [DME Mold Components Catalog](#) for the products that match your application needs.




DME Special Mold Bases & Plates

**DOZENS OF MOLD BASE FEATURES
TO CHOOSE FROM IN A PROGRAM
THAT DELIVERS WITH SPEED,
QUALITY AND AFFORDABILITY**



Special Mold Bases & Plates

Quick Delivery Special Features



DME Standard Mold Bases Included in the QDS Program

- A-Series Mold Bases
- B-Series Mold Bases
- X-Series Mold Bases
- AX-Series Mold Bases
- T-Series Mold Bases
- Cavity Retainer Sets

Steel Types and Plate Thicknesses Included

- DME #1, #2 and #3 steel from 7/8" thick to 57/8" thick
- DME #7 steel from 7/8" thick to 27/8" thick

No Charge Features

Available on all DME Mold Bases and Cavity Retainer Sets

- 1-piece or 3-piece housing (standard DME rails)
- Ejector housing covers
- Relocate or omit return pins
- Relocate or omit assembly screws (top and/or bottom)
- Relocate or omit assembly screws in ejector set
- Relocate or omit leader pins and bushings
- Relocate or omit center holes
- Relocate or omit stop pins in ejector bar
- Sprue puller pin of your choice
- Machining for all DME sprue bushings and most clamp slots
- Machining for most locating rings

All ship dates are calculated from receipt of final customer information.

Quick Delivery Special Features

SHIPPING OPTIONS

5

5-DAY
SHIPPING

Special Mold Bases Shipping in FIVE Working Days

Includes all DME Standard Mold Bases #1, #2 and #3 steel (7/8" to 57/8" thick) and #7 steel (7/8" to 27/8" thick); and all "no charge" items, plus:

- Machine for and install guided ejection – 2 or 4 places
- Machine for and install support pillars
- Machine for and install additional stop pins
- Machine press knock-out in bottom clamp plate (tap in ejector bar, if required)
- Machine pry bar slots
- Machine leader pin vent slots in rails
- Machine for spring holes
- Drill and tap lifting holes
- Drill and tap safety strap holes (location $\pm 1/32"$)
- Machine for and install extra assembly screws in top and/or bottom
- Machine for and install extra assembly screws in ejector assembly
- Machine for and install added return pins
- Rough mill/bore cavity and core pocket; blind or through (NOTE: 1/2" minimum radius required)

7

7-DAY
SHIPPING

Special Mold Bases Shipping in SEVEN Working Days

Includes all features specified above in five working days, plus:

- Machine for DME three-piece extension bushings
- Drill and tap horizontal water lines
- Drill water pipe clearance holes
- Drill vertical water lines (excluding o-ring machining)
- Machine for DME angle pin inserts
- Finish mill/bore cavity and core pocket; blind or through (NOTE: 1/2" minimum radius required)

11

11-DAY
SHIPPING

Special Mold Bases Shipping in ELEVEN Working Days

Includes all features specified above in seven working days, plus:

- Machine for DME parting line interlocks
- Provide special thickness plates (maximum plate thickness of 57/8" in DME #1, #2 and #3 steels, and 27/8" in DME #7 steel)
- Provide special plate lengths and widths within DME standard size offerings
- Angle pin machining and clearance (maximum 4)
- Ejector pin machining – maximum of 25 pins (3/16" minimum diameter ejector pin; 27/8" maximum plate thickness)
- Side interlock machining

Large Custom Mold Bases and Plates / Contour Roughing Services

Large Custom Mold Bases and Plates

Precision Machined Mold Bases and Plates with Lengths to 90"

- Plate lengths up to 90" (2300mm)
- Plate widths up to 60" (1500mm)
- Plate thicknesses up to 39" (1000mm)
- Plate weights up to 6,600 pounds (3000kg) after machining – 8600 lbs. (3900kg) before machining
- Proven medical/packaging market specialization; also specialize in automotive, caps & closures, housewares and PET preform applications

[CONTACT US](#)

[SERVICES](#)



Contour Roughing Services - At Your Request


Key Advantages of Contour Roughing

Moldmakers can use this service to extend their in-house capacity, reduce lead time and focus on other high-value machining

Consistent machining allowance throughout the surface of the cavity block provides even finishing without areas of heavy stock

DME Contour Roughing Services from Milacron can provide customers with the CAM program to continue the work where we left off, saving time and programming expense

Contour roughing can be bundled with the option to stress-relieve cavity blocks and a custom mold base



At the request of moldmakers, DME contour roughing services are available to rough mill complex part shapes into mold plates, even for milling that requires large and deep cavities.

The Contour Roughing Service begins with complex core and cavity CAD files from customers

Industry-leading CAM software enables the programming of contour roughing tool paths, leaving consistent machining allowance throughout the surface of the cavity block

3D cavity roughing tool paths to generate a rough milled surface, allowing machining stock for finishing by the customer

For more details on the Contour Roughing Service, contact your DME representative today.


DME American Standard Mold Bases

Mold Bases with optional
feature-based selections
and rapid delivery



SHUTTLE MOLD BASES

INTERCHANGEABLE
WEAR SURFACES




A-SERIES

X-SERIES

T-SERIES

X-SERIES



DME


Table of Contents



[A-Series Mold Bases.....39 to 137](#)


Available in 43 sizes from 7.875 x 7.875 to 23.75 x 35.5, the DME A-Series Mold Base is the most frequently used standard assembly

[B-Series Mold Bases.....138](#)



[Mold Base Standard & Optional Features 139 to 172](#)

From clamp slots and guided ejection to pockets and waterlines, DME mold base features are available where you want them



[X, AX, T-Series 173 to 198](#)

When you need a floating plate or two or stripper plate ejection, DME mold base assemblies to get the job done



[Small & Shuttle Mold Bases..... 199 to 210](#)

Lower your mold costs with Small Mold Base Adapter Plates and Shuttle Mold Bases



[MoldBasics.....211 to 220](#)

Economical mold bases stocked for immediate delivery

ONLINE
CONFIGURATOR



DME A-Series Mold Bases

**OVER 75 TRILLION POSSIBLE
MOLD BASE CONFIGURATIONS**



A-Series Mold Bases

Table of Contents

<u>88A.....</u>	<u>52-53</u>	<u>1318A.....</u>	<u>82-83</u>	<u>1729A.....</u>	<u>112-113</u>
<u>812A.....</u>	<u>54-55</u>	<u>1321A.....</u>	<u>84-85</u>	<u>1818A.....</u>	<u>114-115</u>
<u>108A.....</u>	<u>56-57</u>	<u>1323A.....</u>	<u>86-87</u>	<u>1820A.....</u>	<u>116-117</u>
<u>1012A.....</u>	<u>58-59</u>	<u>1326A.....</u>	<u>88-89</u>	<u>1823A.....</u>	<u>118-119</u>
<u>1016A.....</u>	<u>60-61</u>	<u>1329A.....</u>	<u>90-91</u>	<u>1826A.....</u>	<u>120-121</u>
<u>1020A.....</u>	<u>62-63</u>	<u>1518A.....</u>	<u>92-93</u>	<u>1829A.....</u>	<u>122-123</u>
<u>1112A.....</u>	<u>64-65</u>	<u>1524A.....</u>	<u>94-95</u>	<u>1835A.....</u>	<u>124-125</u>
<u>1114A.....</u>	<u>66-67</u>	<u>1529A.....</u>	<u>96-97</u>	<u>1924A.....</u>	<u>126-127</u>
<u>1118A.....</u>	<u>68-69</u>	<u>1616A.....</u>	<u>98-99</u>	<u>1929A.....</u>	<u>128-129</u>
<u>1123A.....</u>	<u>70-71</u>	<u>1620A.....</u>	<u>100-101</u>	<u>1935A.....</u>	<u>130-131</u>
<u>1212A.....</u>	<u>72-73</u>	<u>1623A.....</u>	<u>102-103</u>	<u>2424A.....</u>	<u>132-133</u>
<u>1215A.....</u>	<u>74-75</u>	<u>1626A.....</u>	<u>104-105</u>	<u>2429A.....</u>	<u>134-135</u>
<u>1220A.....</u>	<u>76-77</u>	<u>1629A.....</u>	<u>106-107</u>	<u>2435A.....</u>	<u>136-137</u>
<u>1223A.....</u>	<u>78-79</u>	<u>1635A.....</u>	<u>108-109</u>	<i>B-Series Mold Bases</i>	<u>138</u>
<u>1315A.....</u>	<u>80-81</u>	<u>1724A.....</u>	<u>110-111</u>		

Mold Base Key Features

Nobody delivers like the DME American Standard Mold Base. With an infinite number of possible configurations. Some key features and options include:

How to use this catalog

The following pages detail the choices available. If you have questions contact us and one of our knowledgeable representatives will assist you.

Key



Features supplied as standard unless otherwise specified

Delivery



Features available in 5 working days



Features available in 7 working days



Features available in 11 working days

43 Nominal Sizes

9 Plate Thicknesses

4 Steel Types

Guided Ejection

Pry Slots

Lifting Holes

Leader Pin Vents

Ejector Housing Cover

Feature Positions

Feature Omissions


3-Piece or Welded Housing Type

Clamp Slot Type


Mixed Steel

Sprue Puller Pin Diameter

Stop Pin Location




American Mold Base Standard Series Selections




A-SERIES

The most frequently used Standard Assembly, the "A" Series Mold Base is available in 43 sizes from 7.875 x 7.875 to 23.75 x 35.5.




B-SERIES

When cavities and cores are to be inserted into blind pockets, or machined directly into the "A" and "B" plates, the "B" Series Assembly is used. The Top Clamping Plate and Support Plate are omitted from the assembly.




AX-SERIES

The "AX" Series Assembly is used when the mold requires a floating plate to remain with the upper or stationary half of the assembly. It is basically an "A" Series Assembly with a floating plate ("X-1") added.



T-SERIES

The "T" Series Assembly is used for top runner molds that require two floating plates ("X-1" – runner stripper plate, "X-2" – cavity plate) to remain with the upper or stationary half of the assembly.



X-SERIES (5 Plate)

Most frequently used for molds requiring stripper plate ejection, the "X" Series Assembly is available with a Support Plate (6-plate series) or without a Support Plate (5-plate series).

X-SERIES(6 Plate)

NOTE: Location and diameter of standard components are identical for all mold base series.

DME American Standard Steel Types

Synonymous with mold making are the DME American Standard Steel Types. Our experience in selecting mold steel ensures the cleanliness, durability and machinability appropriate to your application.

Steels for Structural and Holder Block Applications

DME #1 Steel is a medium carbon quality steel with greater tensile strength than typical plain carbon warehouse steels. It machines easily, but is not "sticky", permitting a faster and smoother cut. International comparisons: DIN 1.1178 (CK 30) and 1.1730 (C 45 W); JIS S 30 CM, S50C, S55C; ISO 683-1 C30E4.

DME #2 Steel is a medium alloy steel specified for durability in structural applications. It is supplied pre-heat treated to 28-34 HRC (271-321 Bhn). A high strength steel, it is ideal for cavity and core retainer plates, clamping plates and support plates in molds. International comparisons: DIN 1.2312 (40CrMnMoS 8 6), 1.7218 (25CrMo4) and 1.2331 (41CrMoS4); JIS SCM 430; ISO 683-2 Type 1.

DME #7 Steel is a modified AISI 400 series stainless steel for holder block applications. It is supplied pre-heat treated to 32-36 HRC (302-340 Bhn). This stainless steel offers corrosion-resistance and exceptional machinability but cannot be further hardened (see DME #6). For humid environments, corrosive plastics, "clean room" or "100% stainless" applications, it is an ideal choice for all structural mold plates. International comparisons: none.

Steels for Cavity & Core Applications

DME #3 Steel is a P-20 AISI 4130 type cavity steel. Exceptionally clean, it is pre-heat treated to 28-34 HRC (271-321 Bhn). It provides good machinability, the ability to heat treat to higher hardness, and exceptional polishability. International comparisons: DIN 1.2311 G40CrMnMo7; JIS none; ISO none.


DME #5 Steel is an AISI/SAE H-13 type thermal shock resistant, hotwork die steel. Supplied fully annealed (approximately 200 Bhn; 13-20 HRC) for easy machinability, it can be subsequently heat treated to the desired hardness with a minimum of deformation. Mainly used for die cast dies, it is also suitable for plastic molds with exceptional hardness or polishability requirements. DME #5 Steel meets or exceeds the acceptance criteria established by the NADCA as detailed in Technical Digest Number 01-80-01D. International comparisons: DIN 1.2344 (X40CrMoV5-1); JIS SKD 61; ISO 4955 H13.

DME #6 Steel is a modified AISI 420 type stainless steel. It is supplied fully annealed to 179-241 Bhn (8-23 HRC), making it readily machinable. Unlike DME #7 steel, DME #6 steel is a cavity-grade material that can be subsequently heat treated to the desired hardness and has excellent polishability. International comparisons: DIN 1.4028 (X30Cr13); JIS SUS 420 J 2; ISO none.



Typical Steel Types Configurations




"A" Series Mold Bases are available in over 40 standard sizes, 7-7/8 x 7-7/8 to 23-3/4 x 35-1/2. Each size offers a wide variety of standard cavity plate thickness combinations, plus your choice of DME No. 1, No. 2, No. 3 or No. 7 steel.



Steel Selections: Available in 43 Nominal Sizes

MOLD PLATE	STEEL TYPES					
	#1	#2	#3	#7	#5	#6
TOP CLAMP PLATE	⚡	⚡	⚡	⚡		
AC PLATE	⚡	⚡	⚡	⚡		
A PLATE	⚡	⚡	⚡	⚡*		
B PLATE	⚡	⚡	⚡	⚡*		
AX, BX PLATES	⚡	⚡	⚡	⚡		
XP, X-1 AND X-2 PLATES	⚡	⚡	⚡	⚡		
SUPPORT PLATE	⚡	⚡	⚡	⚡		
EJECTOR RETAINER PLATE	⚡			⚡		
EJECTOR BAR PLATE	⚡			⚡		
EJECTOR HOUSING ASSEMBLY	WELDED	⚡				
	THREE PIECE	⚡		⚡		

DME mold base assemblies are regularly comprised of mixed steel types to deliver plates configured to your application requirements. You can select steel types for each plate, as available from the table at left, in any combination for your mold base.

-  = Ships in 5 days or less
-  = Contact DME for quote. DME Customer Service can quote up to 5.875 thickness plates on all plates.
-  = Not available


*Up to 2.375 thickness
NOTE: AC plates are not recommended.

The American Standard Mold Base is available in 43 nominal sizes to match the mold space requirements for your application.

As the creator of the American mold base standard, we have the largest selection of mold base sizes and most are available in less than five business days.

NOTE: Drilled complete replacement plates available with quick delivery.

CONTACT US



NOTE: Approximate mold base weight can be estimated with the following formula:
 WEIGHT = WIDTH x LENGTH x HEIGHT x .283 x 90%


NOMINAL SIZE	WIDTH (IN)	LENGTH (IN)	WEIGHT RANGE (LBS)	
			MIN	MAX
88	7.875	7.875	116	305
812	7.875	11.875	175	460
108	9.875	8.000	156	393
1012	9.875	11.875	235	592
1016	9.875	16.000	316	798
1020	9.875	20.000	395	997
1112	10.875	12.000	261	659
1114	10.875	14.000	305	769
1118	10.875	18.000	392	988
1123	10.875	23.500	511	1290
1212	11.875	12.000	285	719
1215	11.875	15.000	379	899
1220	11.875	20.000	505	1199
1223	11.875	23.500	594	1409
1315	13.375	15.000	427	1038
1318	13.375	18.000	512	1246
1321	13.375	20.750	590	1436
1323	13.375	23.500	669	1627
1326	13.375	26.000	740	1800
1329	13.375	29.500	839	2042
1518	14.875	17.875	599	1410
1524	14.875	23.750	796	1873
1529	14.875	29.500	989	2327
1616	15.875	16.000	573	1347
1620	15.875	20.000	716	1683
1623	15.875	23.500	841	1978
1626	15.875	26.000	930	2189
1629	15.875	29.500	1056	2483
1635	15.875	35.500	1270	2988
1724	16.500	23.750	883	2078
1729	16.500	29.500	1097	2581
1818	17.875	18.000	725	1706
1820	17.875	20.000	806	1896
1823	17.875	23.500	947	2227
1826	17.875	26.000	1048	2464
1829	17.875	29.500	1189	2796
1835	17.875	35.500	1430	3365
1924	19.500	23.750	1044	2456
1929	19.500	29.500	1297	3050
1935	19.500	35.500	1648	3758
2424	23.750	23.750	1343	3062
2429	23.750	29.500	1668	3804
2435	23.750	35.500	2008	4578

American Mold Base Standard Features



Locating Rings

The Locating Ring aligns the mold base to the stationary platen side of the press and positions the sprue bushing correctly.



Clamp Slots

Clamp Slots facilitate clamping the mold to the platen of the press. DME mold bases offer four slot types to ensure the best fit for the requirements of your application.



Sprue Bushings

The Sprue Bushing provides a seat at the spherical radius for the nozzle of the press. This provides a path for the material from the nozzle to the runner system.




Leader Pins, Vents and Bushings

Leader Pins and Bushings align both halves of the mold at the parting line. Leader Pin Vents, which allow trapped air to escape from the mold, are designed into all 15-inch-and-wider series molds. When desired, they can be specified on smaller molds.



Upper and Lower Assembly Screws

Assembly screws are used to hold the plates of the upper and lower halves of the mold together. For simplicity, the upper and lower assembly screws are generally placed in similar positions.




American Mold Base Standard Features



Ejector Housing and Cover


A diverse selection of housing types fit all application demands. A one-piece welded housing is available for customers requiring maximum rigidity and robust durability. For maximum flexibility of configuration options, a three-piece housing is also available.

For additional operator safety, DME mold bases include an ejector housing cover, except when a longer length ejector bar is selected. The housing cover is fastened on both sides with 5/16-18 button-head cap screws.



Ejector Assembly Screws

Ejector assembly screws are used to hold the plate of the ejector assembly together. Recommended position will be provided but you can specify any different position.



Return Pins, Stop Pins and Sprue Puller Pins

Return Pins are used to ensure correct return of the ejector assembly to the home position. DME return pins are precision-ground from superior quality hotwork die steel. Stop Pins arrest travel – preventing excessive wear and possible housing damage. The Sprue Puller Pin removes material from the Sprue Bushing at the end of the molding cycle.



Self-Lubricating Bushings

Saves design and moldmaking costs for lubrication and fittings. Reduces wear and galling. Lowers maintenance and repair costs. Eliminates contamination... ideal for "clean room" environments.



American Mold Base Optional Features

Guided Ejection Systems

Guided Ejection Systems hold the ejector assembly in alignment and support the weight of the ejector assembly throughout the molding cycle – greatly reducing wear on ejection components and preventing cocking of the ejector assembly.





Pockets and Spring Pockets

Per customer specifications, DME finishes any type of cavity and core pockets. See the DME Mold Components catalog for spring free lengths and hole dimensions.



Pry Slots

DME mold bases feature Pry Slots, installed in any plate specified, on the parting and/or non-parting line side. This provides handling ease when opening and/or disassembling a mold.



Lifting Holes

Lifting Holes can be used to install hoist rings for ease of handling. DME mold bases can be configured only with Lifting Holes which are appropriate for the specific mold base size. Refer to DME Mold Components catalog for a comprehensive selection of Hoist Rings.




Mold Strap Holes

Machined holes will be for mounting mold straps. Please provide desired positions and quantity (minimum 2).



American Mold Base Optional Features



Support Pillars




Support Pillars should be used liberally since they greatly increase the capacity of the mold to support the projected area of the cavities, runner and sprue. By providing additional support, they prevent deflection of the mold.



Interlocks





Provides positive alignment between adjacent plates when mold has one or multiple parting line openings. This provides close alignment for interlock cavities and cores in stripper plate type molds.



Waterlines




Waterlines and plugs are provided per customer specifications for optimal cooling efficiency.



3-Plate Extension Bushings



These 3-plate extension bushings can save material, reduce cycle time and help prevent runner hang-ups in 3-plate molds.



Insulator Sheets

These sheets have excellent non-deformation characteristics and a compressive strength which is higher than asbestos and mica materials. Compression molded for high impact strength, they are supplied micro-finished top and bottom, parallel within $\pm.002$.

DME American Standard Mold Base Quote Request Form or Go To THE ONLINE CONFIGURATOR



DME COMPANY
29111 Stephenson Highway
Madison Heights, MI 48071-2383

USA: Tel: 800-626-6653
Fax: 888-808-4363

Canada: Tel: 800-387-6600
Fax: 800-461-9965

dme_cad@dme.net

[ONLINE FORM](#)

NOMINAL SIZE		
88	7.875	7.875
812	7.875	11.875
108	9.875	8.000
1012	9.875	11.875
1016	9.875	16.000
1020	9.875	20.000
1112	10.875	12.000
1114	10.875	14.000
1118	10.875	18.000
1123	10.875	23.500
1212	11.875	12.000
1215	11.875	15.000
1220	11.875	20.000
1223	11.875	23.500
1315	13.375	15.000
1318	13.375	18.000
1321	13.375	20.750
1323	13.375	23.500
1326	13.375	26.000
1329	13.375	29.500
1518	14.875	17.875
1524	14.875	23.750
1529	14.875	29.500
1616	15.875	16.000
1620	15.875	20.000
1623	15.875	23.500
1626	15.875	26.000
1629	15.875	29.500
1635	15.875	35.500
1724	16.500	23.750
1729	16.500	29.500
1818	17.875	18.000
1820	17.875	20.000
1823	17.875	23.500
1826	17.875	26.000
1829	17.875	29.500
1835	17.875	35.500
1924	19.500	23.750
1929	19.500	29.500
1935	19.500	35.500
2424	23.750	23.750
2429	23.750	29.500
2435	23.750	35.500

Company Name: _____

Address: _____

City: _____ State: _____ Zip: _____

Email: _____

Account No.: _____ Date: _____

Contact: _____

Telephone: _____ Fax: _____

Cust. Proj. No.: _____ P.O. No.: _____

Page
1 of 2

Order **Quote Only**

NOTE: For feature selections left blank, the DME Standard recommendation will be provided.

_____ **Series (A, AX, B, X or T)**

Mold Base Item No.: _____

Retainer Set Item No.: _____

Type of Steel: DME No. _____

Top Clamp Plate: 7/8 1-3/8 _____

"C" Riser Height: Standard _____

- Welded/Standard
- 3-Piece "BCP" Thickness _____

"E" Ejector Bar Length: Standard _____

Locating Ring: Item No.: _____

Sprue Bushing: Standard _____

"O" Orifice: _____
"R" Radius: _____

Clamp Slot Machining: Standard _____

- Type A Type B Type C Type D
- Omit Upper Slot Machining
- Machine Entire Length
- (4) Sides (Entire Width & Length)
- Omit Lower Clamp Slot Machining

NOTE: Three-piece housing supplied.

"L" Leader Pin Length: Standard _____

- Clearance in Housing:
Accommodate Length _____
Thru Housing _____
Ship w/Block of Wood _____

Leader Pin Bushings: Standard _____

Specify Diameter: _____

- Steel (STD) Self-Lubricating Bronze

Return Pin: Standard _____

Sprue Puller Pin: Standard _____

Omit the Following Holes:

- Locating Ring
- Sprue Bushing
- Sprue Puller Pin
- Upper Assembly Screws
- Leader Pins
- Leader Pin Bushings
- Return Pins
- Stop Pins
- Lower Assembly Screws
- Ejector Assembly Screws
- Omit all center holes**

Omit the Following Parts:

- Locating Ring
- Sprue Bushing
- Sprue Puller Pin
- Upper Assembly Screws
- Leader Pins
- Leader Pin Bushings
- Return Pins
- Stop Pins
- Lower Assembly Screws
- Ejector Assembly Screws
- Omit all center hole parts**

Relocate the Following Features:

- Center Holes
- Upper Assembly Screws
- Return Pins:
 - Position (DME Standard)
 - Position 2 (inboard for spring pockets)
 - Custom Position

NOTE: Provide sketch or dimensions for custom positions (see p. 48).

- Stop Pins
- Lower Assembly Screws
- Ejector Assembly Screws
- Leader Pins and Bushings

Additional Comments/Notes: _____

DME American Standard Mold Base Quote Request Or Go To THE ONLINE CONFIGURATOR

Page 2 of 2

Company Name: _____ Date: _____

Additional Features – Ships in 5 Working Days

Guided Ejection:

- Quantity: _____ Pin Dia.: _____ System 1 System 2
- Recommended Position Custom Position: GEx _____ GEy _____
- Bronze Bushing Self-Lubricating Bushing _____

Pry Slots: (4 places each plate)

- (NOTE: P = Parting Line NP = Non Parting Line)
- TCP: P _____ NP _____
- A Plate: P _____ NP _____
- B Plate: P _____ NP _____
- Support Plate: P _____ NP _____
- Housing: P _____ NP _____
- _____ P _____ NP _____

Lift Holes: (Prints required if not on center)

- TCP: Quantity _____ Dia. _____
- A Plate: Quantity _____ Dia. _____
- B Plate: Quantity _____ Dia. _____
- Support Plate: Quantity _____ Dia. _____
- Housing: _____
- _____: Quantity _____ Dia. _____
- On center _____

Leader Pin Vents:

(NOTE: Designed in all 15" and wider mold bases. When desired, can be specified on smaller molds.)

- Rough Rectangular Pockets:** (Prints required) Length _____ Width _____
- Through Blind (specify depth): _____ Corner Radius (.50 min/1.00 max): _____

(NOTE: Rough Pocket tolerance -.062 per side)

- Knock-out Holes:** (Prints required if not on center) Drill Quantity _____ Tap Quantity _____
- Mold Strap Holes:** (Prints required) Quantity _____
- Spring Pockets:** (Prints required) Quantity _____ Number of Plates _____
- Support Pillars:** (Prints required) Quantity _____ Diameter _____ Style _____

Additional Components: (Prints required)

- Lower Assembly Screws: Quantity _____
- Upper Assembly Screws: Quantity _____
- Ejector Assembly Screws: Quantity _____
- Return Pins: Quantity _____
- Stop Pins: Quantity _____

Comments: _____

Additional Features – Ships in 7 Working Days (includes features listed in 5 working days)

Extension Bushing (T-Series):

Extension Bushing Item Number: _____ Stripper Bushing: TEB-0001

- Finished Rectangular Pockets:** (Prints required) Length _____ Width _____
- Through Blind (specify depth): _____ Corner Radius (.50 min/1.00 max): _____

(NOTE: Finished pocket tolerance +/- .001)

Waterlines: (Prints required)

Diameter: _____

Number of Plates with Waterlines: _____

Total Length of Waterlines (in inches) in Each Plate: _____

Number of Sides: _____

Comments: _____

Additional Features – Ships in 11 Working Days (includes features listed in 7 working days)

Special Plate Thickness:

Plate to be altered: _____ Thickness: _____

Parting Line Interlocks (see Mold Components catalog; Print required):

Quantity: _____


Part Numbers: _____

Comments: _____


For additional work, contact Customer Service at 800-626-6653 or email drawing files to dme_cad@dme.net



Special Feature Location Form or Go To THE ONLINE CONFIGURATOR



END VIEW



Steel Hardness Chart

CROSS-REFERENCE BETWEEN DIFFERENT HARDNESS MEASUREMENTS					
BRINELL HARDNESS BHN*	VICKERS HARDNESS HV	ROCKWELL HARDNESS HRA	ROCKWELL HARDNESS HRB	ROCKWELL HARDNESS HRC	SHORE HARDNESS HS
10mm BALL, 3000kgf LOAD	136° DIAMOND PYRAMID, 10kgf LOAD	BRALE PENETRATOR, 60kgf LOAD	1/16 INCH BALL, 100kgf LOAD	BRALE PENETRATOR, 150kgf LOAD	
86	90		48		
95	100		56.2		
105	110		62.3		
114	120		66.7		
124	130		71.2		20
133	140		75		21
143	150		78.7		22
152	160		81.7	(0)	24
162	170		85	(3)	25
171	180		87.1	(6)	26
181	190		89.5	(8.5)	28
190	200		91.5	(11)	29
200	210		93.4	(13.4)	30
209	220		95	(15.7)	32
219	230		96.7	(18)	33
228	240	60.7	98.1	20.3	34
238	250	61.6	99.5	22.2	36
247	260	62.4	(101)	24	37
256	270	63.1	(102)	25.6	38
265	280	63.8	(103.5)	27.1	40
275	290	64.5	(104.5)	28.5	41
284	300	65.2	(105.5)	29.8	42
303	320	66.4	(107)	32.2	45
322	340	67.6	(108)	34.4	47
341	360	68.7	(109)	36.6	50
360	380	69.8	(110)	38.8	52
379	400	70.8		40.8	55
397	420	71.8		42.7	57
415	440	72.8		44.5	59
433	460	73.6		46.1	62
452	480	74.5		47.7	64
471	500	75.3		49.1	66
488	520	76.1		50.5	67
507	540	76.7		51.7	69
525	560	77.4		53	71
545	580	78		54.1	72
564	600	78.6		55.2	74
582	620	79.2		56.3	75
601	640	79.8		57.3	77
620	660	80.3		58.3	79
638	680	80.8		59.2	80
656	700	81.3		60.1	81
670	720	81.8		61	83
684	740	82.2		61.8	84
698	760	82.6		62.5	86
710	780	83		63.3	87
722	800	83.4		64	88
745	840	84.1		65.3	91
767	880	84.7		66.4	93

*A 10mm steel ball is used for 450 BHN and below. A 10mm carbide ball is used above 450 BHN.


Also known as Firth Diamond Hardness Number.

Values in parentheses are not contained in the normal definition range for hardness checking, but are often used in comparable measure.


7 7/8 x 7 7/8 A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections



Steel Configurations available in:



For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page [42](#).

7 7/8 x 7 7/8 A-Series Mold Bases

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
.875 (7/8)	0.875	2.500	7.375	88A-7-7	111
	1.375	2.500	7.875	88A-7-13	120
	1.875	2.500	8.375	88A-7-17	129
	2.375	2.500	8.875	88A-7-23	138
	2.875	3.000	9.875	88A-7-27	149
	3.375	3.500	10.875	88A-7-33	161
	3.875	3.500	11.375	88A-7-37	170
	4.875	4.500	13.375	88A-7-47	193
5.875	4.500	14.375	88A-7-57	211	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
2.375 (2-3/8)	0.875	2.500	8.875	88A-23-7	138
	1.375	2.500	9.375	88A-23-13	147
	1.875	2.500	9.875	88A-23-17	155
	2.375	3.000	10.875	88A-23-23	167
	2.875	3.500	11.875	88A-23-27	179
	3.375	4.000	12.875	88A-23-33	190
	3.875	4.000	13.375	88A-23-37	199
	4.875	4.500	14.875	88A-23-47	219
5.875	4.500	15.875	88A-23-57	237	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
3.875 (3-7/8)	0.875	3.000	10.875	88A-37-7	167
	1.375	3.500	11.875	88A-37-13	179
	1.875	3.500	12.375	88A-37-17	187
	2.375	4.000	13.375	88A-37-23	199
	2.875	4.000	13.875	88A-37-27	208
	3.375	4.000	14.375	88A-37-33	217
	3.875	4.500	15.375	88A-37-37	228
	4.875	4.500	16.375	88A-37-47	246
5.875	4.500	17.375	88A-37-57	263	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
1.375 (1-3/8)	0.875	2.500	7.875	88A-13-7	120
	1.375	2.500	8.375	88A-13-13	129
	1.875	2.500	8.875	88A-13-17	138
	2.375	3.000	9.875	88A-13-23	149
	2.875	3.000	10.375	88A-13-27	158
	3.375	3.500	11.375	88A-13-33	170
	3.875	4.000	12.375	88A-13-37	181
	4.875	4.500	13.875	88A-13-47	202
5.875	4.500	14.875	88A-13-57	219	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
2.875 (2-7/8)	0.875	3.000	9.875	88A-27-7	149
	1.375	3.000	10.375	88A-27-13	158
	1.875	3.500	11.375	88A-27-17	170
	2.375	3.500	11.875	88A-27-23	179
	2.875	4.000	12.875	88A-27-27	190
	3.375	4.000	13.375	88A-27-33	199
	3.875	4.000	13.875	88A-27-37	208
	4.875	4.500	15.375	88A-27-47	228
5.875	4.500	16.375	88A-27-57	246	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
4.875 (4-7/8)	0.875	3.500	12.375	88A-47-7	187
	1.375	3.500	12.875	88A-47-13	196
	1.875	4.000	13.875	88A-47-17	208
	2.375	4.000	14.375	88A-47-23	217
	2.875	4.000	14.875	88A-47-27	225
	3.375	4.500	15.875	88A-47-33	237
	3.875	4.500	16.375	88A-47-37	246
	4.875	4.500	17.375	88A-47-47	263
5.875	4.500	18.375	88A-47-57	281	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
1.875 (1-7/8)	0.875	2.500	8.375	88A-17-7	129
	1.375	2.500	8.875	88A-17-13	138
	1.875	2.500	9.375	88A-17-17	147
	2.375	3.000	10.375	88A-17-23	158
	2.875	3.500	11.375	88A-17-27	170
	3.375	3.500	11.875	88A-17-33	179
	3.875	4.000	12.875	88A-17-37	190
	4.875	4.500	14.375	88A-17-47	211
5.875	4.500	15.375	88A-17-57	228	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
3.375 (3-3/8)	0.875	3.000	10.375	88A-33-7	158
	1.375	3.500	11.375	88A-33-13	170
	1.875	3.500	11.875	88A-33-17	182
	2.375	4.000	12.875	88A-33-23	190
	2.875	4.000	13.375	88A-33-27	199
	3.375	4.000	13.875	88A-33-33	208
	3.875	4.500	14.875	88A-33-37	219
	4.875	4.500	15.875	88A-33-47	237
5.875	4.500	16.875	88A-33-57	255	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
5.875 (5-7/8)	0.875	3.500	13.375	88A-57-7	205
	1.375	3.500	13.875	88A-57-13	214
	1.875	4.000	14.875	88A-57-17	225
	2.375	4.000	15.375	88A-57-23	234
	2.875	4.000	15.875	88A-57-27	243
	3.375	4.500	16.875	88A-57-33	255
	3.875	4.500	17.375	88A-57-37	263
	4.875	4.500	18.375	88A-57-47	281
5.875	4.500	19.375	88A-57-57	298	

Other plate thickness, riser height and ejector bar length options available

CP TOP CLAMP PLATE THICKNESS	SU SUPPORT PLATE THICKNESS	BCP BOTTOM CLAMP PLATE THICKNESS	PLATE THICKNESS NO.
0.875	0.875	0.875	7
1.375	1.375	1.375	13
1.875	1.875	1.875	17
2.375	2.375	2.375	23
2.875	2.875	2.875	27
3.375	3.375	3.375	33
3.875	3.875	3.875	37
4.875	4.875	4.875	47
5.875	5.875	5.875	57

See Items 7 & 8 below.


C RISER		
C RISER HEIGHT	RISER HEIGHT NO.	S MAX. STROKE OF EJECTOR BAR
2.500	25	0.813
3.000	30	1.313
3.500	35	1.813
4.000	40	2.313
4.500	45	2.813
5.000	50	3.313
5.500	55	3.813
6.000	60	4.313

See Item 8 below.

EB EJECTOR BAR	
E LENGTH NOM.	EJECTOR BAR LENGTH NO.
7.85	8
11.85	12
15.97	16
19.97	20

See Item 6 below.

Ejector Housing Covers provided on both ends of mold when Ejector Bar Length E is nominal length of mold base. Customer to fabricate ejector housing covers for extended ejector bars.



WHEN ORDERING, PLEASE SPECIFY:


- Quantity
- Assembly Item Number (For "B" Series, replace "A" with "B")
- Steel: #1, #2, #3 or #7 (for other steels, please specify)
- Locating ring item number:
Item No. 6501 (D = 3.990 Diameter of Locating Ring) standard
Item No. 6504 (D = 3.990 Diameter of Locating Ring) clamp type (For other rings see DME Mold Components Catalog)
- Type of sprue bushing, series letters: (i.e., U, UV, UR, *B, etc.)
O = Small dia. of sprue bushing orifice: .156, .218 or .281
R = Spherical radius of sprue bushing: .500 or .750
(For sprue bushings see [DME Mold Components Catalog](#))

- Ejector Bar Length E (Ejector Bar Length at nominal length of mold base is highlighted in yellow. All other lengths provide an extended ejector bar)
- Other CP Top Clamp Plate or SU Support Plate thicknesses as needed (Recommended thicknesses are highlighted in yellow)
- Other C Riser heights as needed. Also, other BCP Bottom Clamp Plate thicknesses as needed. Riser height C and BCP Bottom Clamp Plate thicknesses which are highlighted in yellow are available in #1 Steel in a one-piece Welded Housing. Also, all Riser heights C and all BCP Bottom Clamp Plate thicknesses are available in #1 or #7 Steel in a Three-Piece Housing (for other steels, please specify)
- Other features as needed (i.e. Guided Ejection, Lifting Holes, Pry Bar Slots, as well as Leader Pin, Return Pin, or Assembly Screw Relocations, etc.)
- Method of shipment
(For inch decimal to fractional conversion table, [see page 278.](#))

7 7/8 x 11 7/8 A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 7 7/8 x 11 7/8 A-Series Mold Bases

Mold Base Selections



For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Steel Configurations available in:



Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

7/8 x 11/8 A-Series Mold Bases

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
.875 (7/8)	0.875	2.500	7.375	812A-7-7	174
	1.375	3.000	8.375	812A-7-13	191
	1.875	3.000	8.875	812A-7-17	205
	2.375	3.500	9.875	812A-7-23	222
	2.875	3.500	10.375	812A-7-27	235
	3.375	4.000	11.375	812A-7-33	253
	3.875	4.000	11.875	812A-7-37	266
	4.875	4.500	13.375	812A-7-47	297
5.875	4.500	14.375	812A-7-57	323	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
2.375 (2-3/8)	0.875	3.000	9.375	812A-23-7	218
	1.375	3.000	9.875	812A-23-13	231
	1.875	3.500	10.875	812A-23-17	249
	2.375	3.500	11.375	812A-23-23	262
	2.875	4.000	12.375	812A-23-27	279
	3.375	4.000	12.875	812A-23-33	293
	3.875	4.000	13.375	812A-23-37	306
	4.875	4.500	14.875	812A-23-47	336
5.875	4.500	15.875	812A-23-57	363	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
3.875 (3-7/8)	0.875	3.000	10.875	812A-37-7	258
	1.375	3.500	11.875	812A-37-13	275
	1.875	3.500	12.375	812A-37-17	288
	2.375	4.000	13.375	812A-37-23	306
	2.875	4.000	13.875	812A-37-27	319
	3.375	4.000	14.375	812A-37-33	332
	3.875	4.500	15.375	812A-37-37	350
	4.875	4.500	16.375	812A-37-47	376
5.875	4.500	17.375	812A-37-57	403	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
1.375 (1-3/8)	0.875	2.500	7.875	812A-13-7	187
	1.375	3.000	8.875	812A-13-13	205
	1.875	3.000	9.375	812A-13-17	218
	2.375	3.500	10.375	812A-13-23	235
	2.875	3.500	10.875	812A-13-27	249
	3.375	4.000	11.875	812A-13-33	266
	3.875	4.000	12.375	812A-13-37	279
	4.875	4.500	13.875	812A-13-47	310
5.875	4.500	14.875	812A-13-57	336	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
2.875 (2-7/8)	0.875	3.000	9.875	812A-27-7	231
	1.375	3.000	10.375	812A-27-13	244
	1.875	3.500	11.375	812A-27-17	262
	2.375	3.500	11.875	812A-27-23	275
	2.875	4.000	12.875	812A-27-27	293
	3.375	4.000	13.375	812A-27-33	306
	3.875	4.000	13.875	812A-27-37	319
	4.875	4.500	15.375	812A-27-47	350
5.875	4.500	16.375	812A-27-57	376	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
4.875 (4-7/8)	0.875	3.500	12.375	812A-47-7	288
	1.375	3.500	12.875	812A-47-13	302
	1.875	4.000	13.875	812A-47-17	319
	2.375	4.000	14.375	812A-47-23	332
	2.875	4.000	14.875	812A-47-27	346
	3.375	4.500	15.875	812A-47-33	363
	3.875	4.500	16.375	812A-47-37	376
	4.875	4.500	17.375	812A-47-47	403
5.875	4.500	18.375	812A-47-57	429	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
1.875 (1-7/8)	0.875	2.500	8.375	812A-17-7	200
	1.375	3.000	9.375	812A-17-13	218
	1.875	3.500	10.375	812A-17-17	235
	2.375	3.500	10.875	812A-17-23	249
	2.875	4.000	11.875	812A-17-27	266
	3.375	4.000	12.375	812A-17-33	279
	3.875	4.000	12.875	812A-17-37	293
	4.875	4.500	14.375	812A-17-47	323
5.875	4.500	15.375	812A-17-57	350	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
3.375 (3-3/8)	0.875	3.000	10.375	812A-33-7	244
	1.375	3.500	11.375	812A-33-13	262
	1.875	3.500	11.875	812A-33-17	275
	2.375	4.000	12.875	812A-33-23	293
	2.875	4.000	13.375	812A-33-27	306
	3.375	4.000	13.875	812A-33-33	319
	3.875	4.500	14.875	812A-33-37	336
	4.875	4.500	15.875	812A-33-47	363
5.875	4.500	16.875	812A-33-57	389	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
5.875 (5-7/8)	0.875	3.500	13.375	812A-57-7	315
	1.375	3.500	13.875	812A-57-13	328
	1.875	4.000	14.875	812A-57-17	346
	2.375	4.000	15.375	812A-57-23	359
	2.875	4.000	15.875	812A-57-27	372
	3.375	4.500	16.875	812A-57-33	389
	3.875	4.500	17.375	812A-57-37	403
	4.875	4.500	18.375	812A-57-47	429
5.875	4.500	19.375	812A-57-57	456	

Other plate thickness, riser height and ejector bar length options available

CP TOP CLAMP PLATE THICKNESS	SU SUPPORT PLATE THICKNESS	BCP BOTTOM CLAMP PLATE THICKNESS	PLATE THICKNESS NO.
0.875	0.875	0.875	7
1.375	1.375	1.375	13
1.875	1.875	1.875	17
2.375	2.375	2.375	23
2.875	2.875	2.875	27
3.375	3.375	3.375	33
3.875	3.875	3.875	37
4.875	4.875	4.875	47
5.875	5.875	5.875	57

See Items 7 & 8 below.


C RISER		
C RISER HEIGHT	RISER HEIGHT NO.	S MAX. STROKE OF EJECTOR BAR
2.500	25	0.813
3.000	30	1.313
3.500	35	1.813
4.000	40	2.313
4.500	45	2.813
5.000	50	3.313
5.500	55	3.813
6.000	60	4.313

See Item 8 below.

EB EJECTOR BAR	
E LENGTH NOM.	EJECTOR BAR LENGTH NO.
11.85	12
15.97	16
19.97	20

See Item 6 below.

Ejector Housing Covers provided on both ends of mold when Ejector Bar Length E is nominal length of mold base. Customer to fabricate ejector housing covers for extended ejector bars.




WHEN ORDERING, PLEASE SPECIFY:

- Quantity
- Assembly Item Number (For "B" Series, replace "A" with "B")
- Steel: #1, #2, #3 or #7 (for other steels, please specify)
- Locating ring item number:
Item No. 6501 (D = 3.990 Diameter of Locating Ring) standard
Item No. 6504 (D = 3.990 Diameter of Locating Ring) clamp type (For other rings see DME Mold Components Catalog)
- Type of sprue bushing, series letters: (i.e., U, UV, UR, *B, etc.)
O = Small dia. of sprue bushing orifice: .156, .218 or .281
R = Spherical radius of sprue bushing: .500 or .750
(For sprue bushings see [DME Mold Components Catalog](#))
- Ejector Bar Length E (Ejector Bar Length at nominal length of mold base is highlighted in yellow. All other lengths provide an extended ejector bar)
- Other CP Top Clamp Plate or SU Support Plate thicknesses as needed (Recommended thicknesses are highlighted in yellow)
- Other C Riser heights as needed. Also, other BCP Bottom Clamp Plate thicknesses as needed. Riser height C and BCP Bottom Clamp Plate thicknesses which are highlighted in yellow are available in #1 Steel in a one-piece Welded Housing. Also, all Riser heights C and all BCP Bottom Clamp Plate thicknesses are available in #1 or #7 Steel in a Three-Piece Housing (for other steels, please specify)
- Other features as needed (i.e. Guided Ejection, Lifting Holes, Pry Bar Slots, as well as Leader Pin, Return Pin, or Assembly Screw Relocations, etc.)
- Method of shipment
(For inch decimal to fractional conversion table, [see page 278](#).)

9 7/8 x 8" A-Series Mold Bases

A-SERIES MOLD BASES



See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections

A-Series Assembly

B-Series Assembly







Steel Configurations available in:

No. 1 Steel Assembly

No. 2 Steel Assembly

No. 3 Steel Assembly

No. 7 Steel Assembly




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see [page 42](#).

9 7/8 x 11 7/8 A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 9 7/8 x 11 7/8 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

9 7/8 x 16" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




Mold Base Selections

A-Series Assembly




B-Series Assembly




Steel Configurations available in:


No. 1 Steel Assembly




No. 2 Steel Assembly



No. 3 Steel Assembly



No. 7 Steel Assembly




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


9 7/8 x 20" A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




All dimensions are "Nominal" unless a tolerance is specified.



Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page [42](#).

10⁷/₈ x 12" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 10⁷/₈ x 12 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page [42](#).

10⁷/₈ x 14" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 10⁷/₈ x 14 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


10⁷/₈ x 18" A-Series Mold Bases

A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




All dimensions are "Nominal" unless a tolerance is specified.




To reinforce Support Plate, use Support Pillars.

Mold Base Selections



Steel Configurations available in:



For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page [42](#).

10⁷/₈ x 18" A-Series Mold Bases

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
.875 (7/8)	0.875	2.500	7.875	1118A-7-7	393
	1.375	3.000	8.875	1118A-7-13	429
	1.875	3.000	9.375	1118A-7-17	457
	2.375	3.500	10.375	1118A-7-23	493
	2.875	3.500	10.875	1118A-7-27	521
	3.375	4.000	11.875	1118A-7-33	557
	3.875	4.000	12.375	1118A-7-37	585
	4.875	4.500	13.875	1118A-7-47	649
5.875	4.500	14.875	1118A-7-57	705	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
2.375 (2-3/8)	0.875	3.000	9.875	1118A-23-7	485
	1.375	3.000	10.375	1118A-23-13	513
	1.875	3.500	11.375	1118A-23-17	549
	2.375	3.500	11.875	1118A-23-23	576
	2.875	4.000	12.875	1118A-23-27	613
	3.375	4.000	13.375	1118A-23-33	641
	3.875	4.000	13.875	1118A-23-37	668
	4.875	4.500	15.375	1118A-23-47	732
5.875	4.500	16.375	1118A-23-57	788	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
3.875 (3-7/8)	0.875	3.000	11.375	1118A-37-7	568
	1.375	3.500	12.375	1118A-37-13	604
	1.875	3.500	12.875	1118A-37-17	632
	2.375	4.000	13.875	1118A-37-23	668
	2.875	4.000	14.375	1118A-37-27	696
	3.375	4.000	14.875	1118A-37-33	724
	3.875	4.500	15.875	1118A-37-37	760
	4.875	4.500	16.875	1118A-37-47	816
5.875	4.500	17.875	1118A-37-57	871	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
1.375 (1-3/8)	0.875	2.500	8.375	1118A-13-7	421
	1.375	3.000	9.375	1118A-13-13	457
	1.875	3.000	9.875	1118A-13-17	485
	2.375	3.500	10.875	1118A-13-23	521
	2.875	3.500	11.375	1118A-13-27	549
	3.375	4.000	12.375	1118A-13-33	585
	3.875	4.000	12.875	1118A-13-37	613
	4.875	4.500	14.375	1118A-13-47	677
5.875	4.500	15.375	1118A-13-57	732	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
2.875 (2-7/8)	0.875	3.000	10.375	1118A-27-7	512
	1.375	3.000	10.875	1118A-27-13	540
	1.875	3.500	11.875	1118A-27-17	576
	2.375	3.500	12.375	1118A-27-23	604
	2.875	4.000	13.375	1118A-27-27	641
	3.375	4.000	13.875	1118A-27-33	668
	3.875	4.000	14.375	1118A-27-37	696
	4.875	4.500	15.875	1118A-27-47	760
5.875	4.500	16.875	1118A-27-57	816	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
4.875 (4-7/8)	0.875	3.500	12.875	1118A-47-7	632
	1.375	3.500	13.375	1118A-47-13	660
	1.875	4.000	14.375	1118A-47-17	696
	2.375	4.000	14.875	1118A-47-23	724
	2.875	4.000	15.375	1118A-47-27	751
	3.375	4.500	16.375	1118A-47-33	788
	3.875	4.500	16.875	1118A-47-37	816
	4.875	4.500	17.875	1118A-47-47	871
5.875	4.500	18.875	1118A-47-57	926	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
1.875 (1-7/8)	0.875	2.500	8.875	1118A-17-7	448
	1.375	3.000	9.875	1118A-17-13	485
	1.875	3.500	10.875	1118A-17-17	521
	2.375	3.500	11.375	1118A-17-23	549
	2.875	4.000	12.375	1118A-17-27	585
	3.375	4.000	12.875	1118A-17-33	613
	3.875	4.000	13.375	1118A-17-37	641
	4.875	4.500	14.875	1118A-17-47	705
5.875	4.500	15.875	1118A-17-57	760	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
3.375 (3-3/8)	0.875	3.000	10.875	1118A-33-7	540
	1.375	3.500	11.875	1118A-33-13	576
	1.875	3.500	12.375	1118A-33-17	604
	2.375	4.000	13.375	1118A-33-23	641
	2.875	4.000	13.875	1118A-33-27	668
	3.375	4.000	14.375	1118A-33-33	696
	3.875	4.500	15.375	1118A-33-37	732
	4.875	4.500	16.375	1118A-33-47	788
5.875	4.500	17.375	1118A-33-57	843	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
5.875 (5-7/8)	0.875	3.500	13.875	1118A-57-7	687
	1.375	3.500	14.375	1118A-57-13	715
	1.875	4.000	15.375	1118A-57-17	751
	2.375	4.000	15.875	1118A-57-23	779
	2.875	4.000	16.375	1118A-57-27	807
	3.375	4.500	17.375	1118A-57-33	843
	3.875	4.500	17.875	1118A-57-37	871
	4.875	4.500	18.875	1118A-57-47	926
5.875	4.500	19.875	1118A-57-57	982	

Other plate thickness, riser height and ejector bar length options available

CP TOP CLAMP PLATE THICKNESS	SU SUPPORT PLATE THICKNESS	BCP BOTTOM CLAMP PLATE THICKNESS	PLATE THICKNESS NO.
0.875	0.875	0.875	7
1.375	1.375	1.375	13
1.875	1.875	1.875	17
2.375	2.375	2.375	23
2.875	2.875	2.875	27
3.375	3.375	3.375	33
3.875	3.875	3.875	37
4.875	4.875	4.875	47
5.875	5.875	5.875	57

See Items 7 & 8 below.


C RISER		
C RISER HEIGHT	RISER HEIGHT NO.	S MAX. STROKE OF EJECTOR BAR
2.500	25	0.813
3.000	30	1.313
3.500	35	1.813
4.000	40	2.313
4.500	45	2.813
5.000	50	3.313
5.500	55	3.813
6.000	60	4.313

See Item 8 below.

EB EJECTOR BAR	
E LENGTH NOM.	EJECTOR BAR LENGTH NO.
17.97	18
23.47	23
29.47	29

See Item 6 below.

Ejector Housing Covers provided on both ends of mold when Ejector Bar Length E is nominal length of mold base. Customer to fabricate ejector housing covers for extended ejector bars.



WHEN ORDERING, PLEASE SPECIFY:


- Quantity
- Assembly Item Number (For "B" Series, replace "A" with "B")
- Steel: #1, #2, #3 or #7 (for other steels, please specify)
- Locating ring item number:
Item No. 6501 (D = 3.990 Diameter of Locating Ring) standard
Item No. 6504 (D = 3.990 Diameter of Locating Ring) clamp type
(For other rings see DME Mold Components Catalog)
- Type of sprue bushing, series letters: (i.e., B, etc.)
O = Small dia. of sprue bushing orifice: .156, .218, .281 or .343 R
S = Spherical radius of sprue bushing: .500 or .750
(For sprue bushings see [DME Mold Components Catalog](#))

- Ejector Bar Length E (Ejector Bar Length at nominal length of mold base is highlighted in yellow. All other lengths provide an extended ejector bar)
- Other CP Top Clamp Plate or SU Support Plate thicknesses as needed (Recommended thicknesses are highlighted in yellow)
- Other C Riser heights as needed. Also, other BCP Bottom Clamp Plate thicknesses as needed. Riser height C and BCP Bottom Clamp Plate thicknesses which are highlighted in yellow are available in #1 Steel in a one-piece Welded Housing. Also, all Riser heights C and all BCP Bottom Clamp Plate thicknesses are available in #1 or #7 Steel in a Three-Piece Housing (for other steels, please specify)
- Other features as needed (i.e. Guided Ejection, Lifting Holes, Pry Bar Slots, as well as Leader Pin, Return Pin, or Assembly Screw Relocations, etc.)
- Method of shipment
(For inch decimal to fractional conversion table, [see page 278.](#))

10⁷/₈ x 23¹/₂ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 10⁷/₈ x 23¹/₂ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:



For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, [see page 42](#).

10⁷/₈ x 23¹/₂ A-Series Mold Bases

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
1.375 (1-3/8)	1.375	3.000	9.375	1123A-13-13	596
	1.875	3.000	9.875	1123A-13-17	633
	2.375	3.500	10.875	1123A-13-23	680
	2.875	3.500	11.375	1123A-13-27	716
	3.375	4.000	12.375	1123A-13-33	764
	3.875	4.000	12.875	1123A-13-37	800
	4.875	4.500	14.375	1123A-13-47	883
5.875	4.500	15.375	1123A-13-57	956	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
2.875 (2-7/8)	1.375	3.000	10.875	1123A-27-13	705
	1.875	3.500	11.875	1123A-27-17	752
	2.375	3.500	12.375	1123A-27-23	789
	2.875	4.000	13.375	1123A-27-27	836
	3.375	4.000	13.875	1123A-27-33	872
	3.875	4.000	14.375	1123A-27-37	908
	4.875	4.500	15.875	1123A-27-47	992
5.875	4.500	16.875	1123A-27-57	1063	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
4.875 (4-7/8)	1.375	3.500	13.375	1123A-47-13	861
	1.875	4.000	14.375	1123A-47-17	908
	2.375	4.000	14.875	1123A-47-23	945
	2.875	4.000	15.375	1123A-47-27	981
	3.375	4.500	16.375	1123A-47-33	1028
	3.875	4.500	16.875	1123A-47-37	1064
	4.875	4.500	17.875	1123A-47-47	1137
5.875	4.500	18.875	1123A-47-57	1209	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
1.875 (1-7/8)	1.375	3.000	9.875	1123A-17-13	633
	1.875	3.500	10.875	1123A-17-17	680
	2.375	3.500	11.375	1123A-17-23	716
	2.875	4.000	12.375	1123A-17-27	764
	3.375	4.000	12.875	1123A-17-33	800
	3.875	4.000	13.375	1123A-17-37	836
	4.875	4.500	14.875	1123A-17-47	920
5.875	4.500	15.875	1123A-17-57	992	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
3.375 (3-3/8)	1.375	3.500	11.875	1123A-33-13	752
	1.875	3.500	12.375	1123A-33-17	789
	2.375	4.000	13.375	1123A-33-23	836
	2.875	4.000	13.875	1123A-33-27	872
	3.375	4.000	14.375	1123A-33-33	908
	3.875	4.500	15.375	1123A-33-37	956
	4.875	4.500	16.375	1123A-33-47	1028
5.875	4.500	17.375	1123A-33-57	1101	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
5.875 (5-7/8)	1.375	3.500	14.375	1123A-57-13	933
	1.875	4.000	15.375	1123A-57-17	981
	2.375	4.000	15.875	1123A-57-23	1017
	2.875	4.000	16.375	1123A-57-27	1053
	3.375	4.500	17.375	1123A-57-33	1101
	3.875	4.500	17.875	1123A-57-37	1137
	4.875	4.500	18.875	1123A-57-47	1209
5.875	4.500	19.875	1123A-57-57	1282	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
2.375 (2-3/8)	1.375	3.000	10.375	1123A-23-13	669
	1.875	3.500	11.375	1123A-23-17	716
	2.375	3.500	11.875	1123A-23-23	752
	2.875	4.000	12.875	1123A-23-27	800
	3.375	4.000	13.375	1123A-23-33	836
	3.875	4.000	13.875	1123A-23-37	872
	4.875	4.500	15.375	1123A-23-47	956
5.875	4.500	16.375	1123A-23-57	1028	

A	B	C	H	ASSEMBLY ITEM NO.	NET WT.
3.875 (3-7/8)	1.375	3.500	12.375	1123A-37-13	789
	1.875	3.500	12.875	1123A-37-17	825
	2.375	4.000	13.875	1123A-37-23	872
	2.875	4.000	14.375	1123A-37-27	908
	3.375	4.000	14.875	1123A-37-33	945
	3.875	4.500	15.875	1123A-37-37	992
	4.875	4.500	16.875	1123A-37-47	1064
5.875	4.500	17.875	1123A-37-57	1137	

Other plate thickness, riser height and ejector bar length options available

CP TOP CLAMP PLATE THICKNESS	SU SUPPORT PLATE THICKNESS	BCP BOTTOM CLAMP PLATE THICKNESS	PLATE THICKNESS NO.
0.875	0.875	0.875	7
1.375	1.375	1.375	13
1.875	1.875	1.875	17
2.375	2.375	2.375	23
2.875	2.875	2.875	27
3.375	3.375	3.375	33
3.875	3.875	3.875	37
4.875	4.875	4.875	47
5.875	5.875	5.875	57

See Items 7 & 8 below.


C RISER		
C RISER HEIGHT	RISER HEIGHT NO.	S MAX. STROKE OF EJECTOR BAR
3.000	30	1.313
3.500	35	1.813
4.000	40	2.313
4.500	45	2.813
5.000	50	3.313
5.500	55	3.813
6.000	60	4.313

See Item 8 below.

EB EJECTOR BAR	
E LENGTH NOM.	EJECTOR BAR LENGTH NO.
23.47	23
29.47	29

See Item 6 below.

Ejector Housing Covers provided on both ends of mold when Ejector Bar Length E is nominal length of mold base. Customer to fabricate ejector housing covers for extended ejector bars.



WHEN ORDERING, PLEASE SPECIFY:


- Quantity
- Assembly Item Number (For "B" Series, replace "A" with "B")
- Steel: #1, #2, #3 or #7 (for other steels, please specify)
- Locating ring item number:
Item No. 6501 (D = 3.990 Diameter of Locating Ring) standard
Item No. 6504 (D = 3.990 Diameter of Locating Ring) clamp type (For other rings see DME Mold Components Catalog)
- Type of sprue bushing, series letters: (i.e., B, etc.)
O = Small dia. of sprue bushing orifice: .156, .218, .281 or .343 R = Spherical radius of sprue bushing: .500 or .750
(For sprue bushings see [DME Mold Components Catalog](#))

- Ejector Bar Length E (Ejector Bar Length at nominal length of mold base is highlighted in yellow. All other lengths provide an extended ejector bar)
- Other CP Top Clamp Plate or SU Support Plate thicknesses as needed (Recommended thicknesses are highlighted in yellow)
- Other C Riser heights as needed. Also, other BCP Bottom Clamp Plate thicknesses as needed. Riser height C and BCP Bottom Clamp Plate thicknesses which are highlighted in yellow are available in #1 Steel in a one-piece Welded Housing. Also, all Riser heights C and all BCP Bottom Clamp Plate thicknesses are available in #1 or #7 Steel in a Three-Piece Housing (for other steels, please specify)
- Other features as needed (i.e. Guided Ejection, Lifting Holes, Pry Bar Slots, as well as Leader Pin, Return Pin, or Assembly Screw Relocations, etc.)
- Method of shipment (For inch decimal to fractional conversion table, [see page 278.](#))

11⁷/₈ x 12" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




Mold Base Selections

A-Series Assembly




B-Series Assembly




Steel Configurations available in:


No. 1 Steel Assembly




No. 2 Steel Assembly



No. 3 Steel Assembly



No. 7 Steel Assembly




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

11⁷/₈ x 15" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 11⁷/₈ x 15 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page [42](#).

11⁷/₈ x 20" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 11⁷/₈ x 20 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:



For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

1 1/8 x 20" A-Series Mold Bases

Table with 6 columns: A, B, C, H, ASSEMBLY ITEM NO., NET WT. Rows include values for .875 (7/8) riser height.

Table with 6 columns: A, B, C, H, ASSEMBLY ITEM NO., NET WT. Rows include values for 2.375 (2-3/8) riser height.

Table with 6 columns: A, B, C, H, ASSEMBLY ITEM NO., NET WT. Rows include values for 3.875 (3-7/8) riser height.

Table with 6 columns: A, B, C, H, ASSEMBLY ITEM NO., NET WT. Rows include values for 1.375 (1-3/8) riser height.

Table with 6 columns: A, B, C, H, ASSEMBLY ITEM NO., NET WT. Rows include values for 2.875 (2-7/8) riser height.

Table with 6 columns: A, B, C, H, ASSEMBLY ITEM NO., NET WT. Rows include values for 4.875 (4-7/8) riser height.

Table with 6 columns: A, B, C, H, ASSEMBLY ITEM NO., NET WT. Rows include values for 1.875 (1-7/8) riser height.

Table with 6 columns: A, B, C, H, ASSEMBLY ITEM NO., NET WT. Rows include values for 3.375 (3-3/8) riser height.

Table with 6 columns: A, B, C, H, ASSEMBLY ITEM NO., NET WT. Rows include values for 5.875 (5-7/8) riser height.


Other plate thickness, riser height and ejector bar length options available

Table with 4 columns: CP TOP CLAMP PLATE THICKNESS, SU SUPPORT PLATE THICKNESS, BCP BOTTOM CLAMP PLATE THICKNESS, PLATE THICKNESS NO. Rows show various thickness options.

See Items 7 & 8 below.

Table with 6 columns: C RISER C RISER HEIGHT, C RISER HEIGHT NO., S MAX. STROKE OF EJECTOR BAR, EB EJECTOR BAR E LENGTH NOM., EB EJECTOR BAR LENGTH NO. Rows show riser and ejector bar options.

See Item 8 below.



See Item 6 below.

Ejector Housing Covers provided on both ends of mold when Ejector Bar Length E is nominal length of mold base. Customer to fabricate ejector housing covers for extended ejector bars.

WHEN ORDERING, PLEASE SPECIFY:


- 1. Quantity
2. Assembly Item Number (For "B" Series, replace "A" with "B")
3. Steel: #1, #2, #3 or #7 (for other steels, please specify)
4. Locating ring item number: Item No. 6501 (D = 3.990 Diameter of Locating Ring) standard Item No. 6504 (D = 3.990 Diameter of Locating Ring) clamp type (For other rings see DME Mold Components Catalog)
5. Type of sprue bushing, series letters: (i.e., B, etc.) O = Small dia. of sprue bushing orifice: .156, .218, .281 or .343 R = Spherical radius of sprue bushing: .500 or .750 (For sprue bushings see DME Mold Components Catalog)

- 6. Ejector Bar Length E (Ejector Bar Length at nominal length of mold base is highlighted in yellow. All other lengths provide an extended ejector bar)
7. Other CP Top Clamp Plate or SU Support Plate thicknesses as needed (Recommended thicknesses are highlighted in yellow)
8. Other C Riser heights as needed. Also, other BCP Bottom Clamp Plate thicknesses as needed. Riser height C and BCP Bottom Clamp Plate thicknesses which are highlighted in yellow are available in #1 Steel in a one-piece Welded Housing. Also, all Riser heights C and all BCP Bottom Clamp Plate thicknesses are available in #1 or #7 Steel in a Three-Piece Housing (for other steels, please specify)
9. Other features as needed (i.e. Guided Ejection, Lifting Holes, Pry Bar Slots, as well as Leader Pin, Return Pin, or Assembly Screw Relocations, etc.)
10. Method of shipment (For inch decimal to fractional conversion table, see page 278.)


11⁷/₈ x 23¹/₂ A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




All dimensions are "Nominal" unless a tolerance is specified.



Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

13³/₈ x 15" A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 13³/₈ x 15 A-Series Mold Bases

Mold Base Selections

A-Series Assembly




B-Series Assembly




Steel Configurations available in:


No. 1 Steel Assembly




No. 2 Steel Assembly



No. 3 Steel Assembly



No. 7 Steel Assembly




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

13³/₈ x 18" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 13³/₈ x 18 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

13³/₈ x 20³/₄ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 13³/₈ x 20³/₄ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


13³/₈ x 23¹/₂ A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

13³/₈ x 26" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 13³/₈ x 26 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


13³/₈ x 29¹/₂ A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

14⁷/₈ x 17⁷/₈ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




Mold Base Selections

A-Series Assembly




B-Series Assembly




Steel Configurations available in:


No. 1 Steel Assembly




No. 2 Steel Assembly



No. 3 Steel Assembly



No. 7 Steel Assembly




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

14⁷/₈ x 23³/₄ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 14⁷/₈ x 23³/₄ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

14⁷/₈ x 29¹/₂ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 14⁷/₈ x 29¹/₂ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

15⁷/₈ x 16" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 15⁷/₈ x 16 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

15⁷/₈ x 20" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 15⁷/₈ x 20 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

15⁷/₈ x 23¹/₂ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 15⁷/₈ x 23¹/₂ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


15⁷/₈ x 26" A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

15⁷/₈ x 29¹/₂ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 15⁷/₈ x 29¹/₂ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

15⁷/₈ x 35¹/₂ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 15⁷/₈ x 35¹/₂ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


16¹/₂ x 23³/₄ A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


16 1/2 x 29 1/2 A-Series Mold Bases

A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




All dimensions are "Nominal" unless a tolerance is specified.




To reinforce Support Plate, use Support Pillars.

A-Series Mold Bases | 16 1/2 x 29 1/2 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

17⁷/₈ x 18" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 17⁷/₈ x 18 A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


17⁷/₈ x 20" A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

17⁷/₈ x 23¹/₂ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 17⁷/₈ x 23¹/₂ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

17⁷/₈ x 26" A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




Mold Base Selections

A-Series Assembly




B-Series Assembly




Steel Configurations available in:


No. 1 Steel Assembly




No. 2 Steel Assembly



No. 3 Steel Assembly



No. 7 Steel Assembly




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.



17⁷/₈ x 29¹/₂ A-Series Mold Bases

A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




All dimensions are "Nominal" unless a tolerance is specified.




To reinforce Support Plate, use Support Pillars.

A-Series Mold Bases | 17⁷/₈ x 29¹/₂ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198. Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


17⁷/₈ x 35¹/₂ A-Series Mold Bases

A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




All dimensions are "Nominal" unless a tolerance is specified.




To reinforce Support Plate, use Support Pillars.

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.



19¹/₂ x 23³/₄ A-Series Mold Bases

A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




All dimensions are "Nominal" unless a tolerance is specified.




To reinforce Support Plate, use Support Pillars.

A-Series Mold Bases | 19¹/₂ x 23³/₄ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198. Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


19 1/2 x 29 1/2 A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

19¹/₂ x 35¹/₂ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




A-Series Mold Bases | 19¹/₂ x 35¹/₂ A-Series Mold Bases

Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#). Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

23³/₄ x 23³/₄ A-Series Mold Bases


A-SERIES MOLD BASES

See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.




Mold Base Selections

A-Series Assembly




B-Series Assembly




Steel Configurations available in:


No. 1 Steel Assembly




No. 2 Steel Assembly



No. 3 Steel Assembly



No. 7 Steel Assembly




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


23³/₄ x 29¹/₂ A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections



Steel Configurations available in:




For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages 173-198.

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.


23³/₄ x 35¹/₂ A-Series Mold Bases

A-SERIES MOLD BASES


See opposite page for general dimensions, ejector stroke data, locating rings, sprue bushings, ejector bar lengths and other ordering information.



Mold Base Selections



Steel Configurations available in:



For X-Series Stripper Plate, AX-Series and T-Series Mold Bases, see pages [173-198](#).

Other steel combinations also available. (Ejector Plates and Housings are No. 1 Steel, unless otherwise specified.) For additional steel information, see page 42.

Available in 43 Nominal Sizes

The DME "B" Series Mold Base offers economy of design without sacrificing the high-quality steel and workmanship of the "A" Series. The two mold bases are identical except for the "B" Series "two-plate" design. A thicker "A" plate acts as both Top Clamping Plate and upper Cavity Plate. Similarly, a thicker "B" plate eliminates the need for a Support Plate on the "B" side of the mold. The "B" Series is sometimes specified for single-cavity plastics molds or die-cast dies where the cavity and core are machined directly into the Cavity Plates; or where overall mold height is critical. As a two-plate design, cavity inserts have to be installed into "blind" pockets.

Instructions for ordering:

"B" Series Mold Bases are available in the same variety of steels, sizes and plate combinations as the "A" Series. Since the clamp slots are located in the "A" plate, the recommended minimum "A" plate thickness for a "B" Series Mold Base is 1.875. If an "A" plate less than 1.875 is desired, exact clamp slot and center hold specifications must be provided.

Unless otherwise specified, the size and location of return pins and screws will be identical to those of the corresponding size "A" Series Mold Base. In addition, unless otherwise specified, the riser height will be supplied to conform with the standard "C" dimension listed for the corresponding size "A" Series Mold Base.

To create assembly item number:

Use item number prefix shown in chart at right, followed by A and B plate thickness codes.


Example: 10.875 x 14 B-Series with 2.375 A-Plate and 2.875 B-Plate = 1114B-23-27

PLATE THICKNESS CODES	
THICKNESS	CODE
.875*	7
1.375*	13
1.875	17
2.375	23
2.875	27
3.375	33
3.875	37
4.875	47
5.875	57

*Not recommended for "A" Plate. See instructions for ordering on this page.

STANDARD SIZE	ITEM NO. PREFIX	
	W	L
7.875	7.875	88B
	11.875	812B
9.875	8.000	108B
	11.875	1012B
	16.000	1016B
	20.000	1020B
	12.000	1112B
10.875	14.000	1114B
	18.000	1118B
	23.500	1123B
11.875	12.000	1212B
	15.000	1215B
	20.000	1220B
	23.500	1223B
13.375	15.000	1315B
	18.000	1318B
	20.750	1321B
	23.500	1323B
	26.000	1326B
14.875	17.875	1518B
	23.750	1524B
	29.500	1529B

STANDARD SIZE	ITEM NO. PREFIX	
	W	L
15.875	16.000	1616B
	20.000	1620B
	23.500	1623B
	26.000	1626B
	29.500	1629B
16.500	35.500	1635B
	23.750	1724B
	29.500	1729B
17.875	18.000	1818B
	20.000	1820B
	23.500	1823B
	26.000	1826B
	29.500	1829B
19.500	35.500	1835B
	23.750	1924B
	29.500	1929B
23.750	35.500	1935B
	23.750	2424B
	29.500	2429B
	35.500	2435B

**WHEN ORDERING, PLEASE SPECIFY:**

- Quantity
- Assembly Item Number (as created above)
- Steel: #1, #2, #3 or #7 (for other steels, please specify)
- Locating ring item number:
Item No. 6501 (D = 3.990 Diameter of Locating Ring) standard
Item No. 6504 (D = 3.990 Diameter of Locating Ring) clamp type
(For other rings see DME Mold Components Catalog)
- Type of sprue bushing, series letters: (i.e., B, etc.)
O = Small dia. of sprue bushing orifice: .156, .218, .281 or .343
R = Spherical radius of sprue bushing: .500 or .750
(For sprue bushings see [DME Mold Components Catalog](#))
- Ejector Bar Length E (Ejector Bar Length at nominal length of mold base is highlighted in yellow. All other lengths provide an extended ejector bar)
- Other C Riser heights as needed. Also, other BCP Bottom Clamp Plate thicknesses as needed. Riser height C and BCP Bottom Clamp Plate thicknesses which are highlighted in yellow are available in #1 Steel in a one-piece Welded Housing. Also, all Riser heights C and all BCP Bottom Clamp Plate thicknesses are available in #1 or #7 Steel in a three-piece Housing (for other steels, please specify)
- Other features as needed (i.e. Guided Ejection, Lifting Holes, Pry Bar Slots, as well as Leader Pin, Return Pin, or Assembly Screw Relocations, etc.)
- Method of shipment
(For inch decimal to fractional conversion table, [see page 278.](#))

Standard & Optional Mold Base Features

**CONFIGURE YOUR MOLD
BASE TO YOUR EXACT NEEDS**



Standard & Optional Mold Base Features

Table of Contents

<i>Feature Overview</i>	140-145
<i>Locating Rings</i>	146
<i>Sprue Bushings</i>	147
<i>Upper & Lower Assembly Screws</i>	148-149
<i>Clamp Slots</i>	150
<i>Leader Pins & Bushings</i>	151
<i>Return Pins, Stop Pins & Sprue Puller Pins</i>	152-153
<i>Ejector Assembly Screws</i>	156
<i>Ejector Housing & Cover</i>	154-155
<i>Recommended Additional SHCS</i>	157-158
<i>American Mold Base Features</i>	159

<i>Self-Lubricating Bushings</i>	160
<i>Pry Slots</i>	161
<i>Guided Ejection Systems</i>	162-163
<i>Lifting Hole Location</i>	164
<i>Pockets</i>	165
<i>Support Pillars</i>	166-167
<i>Leader Pin Vents, Spring Pockets & Mold Straps</i>	168
<i>Waterlines</i>	169
<i>Three-Plate Extension Bushing</i>	170
<i>Interlocks</i>	171
<i>Insulator Sheets</i>	172



Unlimited Mold Base Selections

With **DME mold bases**, the only limit to your mold base is your imagination. Need guided ejection? Want vented leader pins? Prefer a three-piece ejector housing? DME Custom Mold Bases are available in an infinite number of possible configurations – one of them is perfect for your specific application.

All this and more, and at a competitive price. And, because it's from DME, you know it'll be done right the first time, on time – *every* time.

A whole new way of ordering


You can choose from an extensive menu of options to configure exactly the mold base you need. What some companies would call "a special" is no problem with DME mold bases.

Widest range of features and sizes available

DME Custom Mold Bases aren't just a limited range of common sizes – no one offers more in the industry. More sizes. More high-quality steel types. More plate thicknesses. More value-added features.



[VISIT OUR CONFIGURATOR](#)



Made to order

What you want – not just what’s in stock. That’s the philosophy of the DME mold base offer. Our leading-edge manufacturing and workflow technologies enable us to build your custom-configured mold base with unparalleled speed. Most configurations can be shipped in only a few days.

Buy only the features you need

The DME mold base offer is driven by a simple premise: Your mold base is made up of only the specific features you want. No paying for “extras” that you didn’t need. You can even specify the steel type – at the plate level – to enable customization to meet your objectives.

Why DME mold Bases?

We understand the challenges you face. We know that anything that gives you an edge in today’s competitive marketplace can enable a business advantage. That’s why we work to get you a mold base that’s configured exactly the way you need it, as quickly as possible, without price premiums.

[VISIT OUR CONFIGURATOR](#)

American Mold Base Standard Features


Standard & Optional Mold Base Features | American Mold Base Standard Features



Locating Rings



The Locating Ring aligns the mold base to the stationary platen side of the press and positions the sprue bushing correctly.



Clamp Slots



Clamp Slots facilitate clamping the mold to the platen of the press. DME mold bases offer four slot types to ensure the best fit for the requirements of your application.



Sprue Bushings




The Sprue Bushing provides a seat at the spherical radius for the nozzle of the press. This provides a path for the material from the nozzle to the runner system.



Leader Pins, Vents and Bushings




Leader Pins and Bushings align both halves of the mold at the parting line. Leader Pin Vents, which allow trapped air to escape from the mold, are designed into all 15-inch-and-wider series molds. When desired, they can be specified on smaller molds.



Upper and Lower Assembly Screws



Assembly screws are used to hold the plates of the upper and lower halves of the mold together. For simplicity, the upper and lower assembly screws are generally placed in similar positions.




American Mold Base Standard Features



Ejector Housing and Cover


DME housing types fit all application demands. A one-piece welded housing is available for customers requiring maximum rigidity and robust durability. For maximum flexibility of configuration options, a three-piece housing is also available.

For additional operator safety, DME mold bases include an ejector housing cover, except when a longer length ejector bar is selected. The cover is fastened on both sides with 5/16-18 button-head cap screws.



Ejector Assembly Screws

Ejector assembly screws are used to hold the plate of the ejector assembly together. Recommended position will be provided but you can specify any different position.



Return Pins, stop Pins and Sprue Puller Pins

Return Pins are used to ensure correct return of the ejector assembly to the home position. DME return pins are precision-ground from superior quality hotwork die steel. Stop Pins arrest travel – preventing excessive wear and possible housing damage. The Sprue Puller Pin removes material from the Sprue Bushing at the end of the molding cycle.



Self-lubricating Bushings

Saves design and moldmaking costs for lubrication and fittings. Reduces wear and galling. Lowers maintenance and repair costs. Eliminates contamination... ideal for "clean room" environments.




American Mold Base Optional Features

Standard & Optional Mold Base Features | American Mold Base Optional Features



Guided Ejection Systems hold the ejector assembly in alignment and support the weight of the ejector assembly throughout the molding cycle – greatly reducing wear on ejection components and preventing cocking of the ejector assembly.

Guided Ejection Systems






Per customer specifications, DME finishes any type of cavity and core pockets. See the DME Mold Components catalog for spring free lengths and hole dimensions.

Pockets and Spring Pockets



DME mold bases feature Pry Slots, installed in any plate specified, on the parting and/or non-parting line side. This provides handling ease when opening and/or disassembling a mold.

Pry Slots



Lifting Holes can be used to install hoist rings for ease of handling. DME mold bases can be configured only with Lifting Holes which are appropriate for the specific mold base size. Refer to DME Mold Components catalog for a comprehensive selection of Hoist Rings.

Lifting Holes




Machined holes will be for mounting mold straps. Please provide desired positions and quantity (minimum 2).

Mold Strap Holes



American Mold Base Optional Features



Support Pillars




Support pillars should be used liberally since they greatly increase the capacity of the mold to support the projected area of the cavities, runner and sprue. By providing additional support, they prevent deflection of the mold.



Interlocks





Provides positive alignment between adjacent plates when mold has one or multiple parting line openings. This provides close alignment for interlock cavities and cores in stripper plate type molds.



Waterlines




Waterlines and plugs are provided per customer specifications for optimal cooling efficiency.



3-Plate Extension Bushings



These 3-plate extension bushings can save material, reduce cycle time and help prevent runner hang-ups in 3-plate molds.



Insulator Sheets Standard or Pre-machined

These sheets have excellent non-deformation characteristics and a compressive strength which is higher than asbestos and mica materials. Compression molded for high impact strength, they are supplied micro-finished top and bottom, parallel within $\pm.002$.

Available in Standard or Pre-machined

Locating Rings



Features supplied as standard unless otherwise specified.

Locating Rings

The Locating Ring aligns the mold base to the stationary platen side of the press and positions the sprue bushing correctly.

FOR QUOTING OR ORDERING, SPECIFY:

Locating Rings

Standard 6501 D = 3.990

Other _____
(refer to table below and DME Mold Components catalog)

Position/Omission:



Position on center Center

or relocate to

X _____ Y _____

- Omit locating ring machining
 Omit locating ring
 Rotate tapped holes

CONTACT US



Locating ring #6501 shown; refer to DME Mold Components catalog for dimensions of other locating rings.

Locating Ring Options

ITEM NUMBER	Ø D	DESCRIPTION
6500	2.615	
6501	3.990	STANDARD SERIES
6501LN	3.990	LN SERIES
6502	4.990	
6503	2.000	
6504	3.990	CLAMP TYPE
6505LN	5.990	LN SERIES
6510	7.995	
6511	2.990	
6520	3.990	EXTENSION NOZZLE TYPE
6521	3.990	STANDARD SERIES
6522	3.990	EXTENSION NOZZLE TYPE
6524	3.990	CLAMP TYPE
6534**	1.574	TOP AND BOTTOM RING
6535	3.541	
6536	4.331	TOP RING
6537	4.331	BOTTOM RING
6541*	3.990	STANDARD SERIES
6544*	3.990	CLAMP TYPE

* For use with high-temperature insulator sheets.


** For use with 3.5 x 3.75 Arburg Mold Bases.

See DME Mold Components catalog for dimensions of other locating rings.


Sprue Bushings

Sprue Bushings

The Sprue Bushing provides a seat at the spherical radius for the nozzle of the press. This provides a path for the material from the nozzle to the runner system.



*For 88 & 812 mold base diameter is .750 and R equals 1/8



Features supplied as standard unless otherwise specified.

FOR QUOTING OR ORDERING, SPECIFY:

Sprue Bushing Series

Standard "B" or "U" (for 88 and 812 mold bases) Series or select any standard DME sprue bushings including DME high-performance sprue bushings.

O (Orifice) _____

R (Radius) _____

NOTE: Refer to DME Mold Components catalog for more information on our complete line of sprue bushings.

Position/Omission:

Position on center Center

or relocate to

X _____ Y _____

Omit sprue bushing hole

Omit sprue bushing part

CONTACT US

Upper and Lower Assembly Screws

CONTACT US



Features supplied as standard unless otherwise specified.

FOR QUOTING OR ORDERING, SPECIFY:

Upper Assembly Screws

Recommended position from table (see opposite page) provided standard. If a different position is required, specify below.

Position: STD Specify

- UASx1 _____
- UASx2 _____
- UASx3 _____
- UASx4 _____
- UASx5 _____
- UASx6 _____
- UASx7 _____
- UASx8 _____
- UASx9 _____
- UASx10 _____
- UASx11 _____
- UASx12 _____
- UASy _____
- Omit hole _____
- Omit part _____

- Omit upper assembly holes
- Omit upper assembly screws

Lower Assembly Screws


Recommended position from table (see opposite page) provided standard. If a different position is required, specify below.

Position: STD Specify

- LASx1 _____
- LASx2 _____
- LASx3 _____
- LASx4 _____
- LASx5 _____
- LASx6 _____
- LASx7 _____
- LASx8 _____
- LASx9 _____
- LASx10 _____
- LASx11 _____
- LASx12 _____
- LASy _____
- Omit Hole _____
- Omit Part _____

- Omit lower assembly holes
- Omit lower assembly screws

Assembly screws are used to hold the plates of the upper and lower halves of the mold together. For simplicity, the upper and lower assembly screws are generally placed in similar positions.



Upper and Lower Assembly Screw Positions

BASE SIZE	SCREW SIZE	UASy LASy	UASx1 LASx1	UASx2 LASx2	UASx3 LASx3	UASx4 LASx4	UASx5 LASx5	UASx6 LASx6	UASx7 LASx7	UASx8 LASx8	UASx9 LASx9	UASx10 LASx10	UASx11 LASx11	UASx12 LASx12
88	1/2-13	3.125	1.375	—	—	—	—	1.375	1.375	—	—	—	—	1.375
812	1/2-13	3.125	2.250	—	—	—	—	2.250	2.250	—	—	—	—	2.250
108	1/2-13	4.000	1.875	—	—	—	—	1.875	1.875	—	—	—	—	1.875
1012	1/2-13	4.000	3.250	—	—	—	—	3.250	3.250	—	—	—	—	3.250
1016	1/2-13	4.000	5.000	—	—	—	—	5.000	5.000	—	—	—	—	5.000
1020	1/2-13	4.000	6.500	—	—	1.000	—	6.500	6.500	—	1.000	—	—	6.500
1112	1/2-13	4.469	3.188	—	—	—	—	3.188	3.188	—	—	—	—	3.188
1114	1/2-13	4.469	3.188	—	—	—	—	3.188	3.188	—	—	—	—	3.188
1118	1/2-13	4.469	5.875	—	—	1.000	—	5.875	5.875	—	1.000	—	—	5.875
1123	1/2-13	4.469	8.625	—	3.188	3.188	—	8.625	8.625	—	3.188	3.188	—	8.625
1212	1/2-13	4.969	2.812	—	—	—	—	2.812	2.812	—	—	—	—	2.812
1215	1/2-13	4.969	4.500	—	—	1.000	—	4.500	4.500	—	1.000	—	—	4.500
1220	1/2-13	4.969	6.625	—	—	1.000	—	6.625	6.625	—	1.000	—	—	6.625
1223	1/2-13	4.969	8.625	—	2.812	2.812	—	8.625	8.625	—	2.812	2.812	—	8.625
1315	1/2-13	5.719	4.500	—	—	1.000	—	4.500	4.500	—	1.000	—	—	4.500
1318	1/2-13	5.719	5.438	—	—	1.000	—	5.438	5.438	—	1.000	—	—	5.438
1321	1/2-13	5.719	6.750	—	—	1.000	—	6.750	6.750	—	1.000	—	—	6.750
1323	1/2-13	5.719	8.125	—	2.750	2.750	—	8.125	8.125	—	2.750	2.750	—	8.125
1326	1/2-13	5.719	9.375	—	3.250	3.250	—	9.375	9.375	—	3.250	3.250	—	9.375
1329	1/2-13	5.719	11.125	—	3.250	3.250	—	11.125	11.125	—	3.250	3.250	—	11.125
1518	1/2-13	6.469	5.438	—	—	1.000	—	5.438	5.438	—	1.000	—	—	5.438
1524	1/2-13	6.469	7.750	—	2.750	2.750	—	7.750	7.750	—	2.750	2.750	—	7.750
1529	1/2-13	6.469	10.625	—	3.688	3.688	—	10.625	10.625	—	3.688	3.688	—	10.625
1616	1/2-13	6.969	4.250	—	—	1.000	—	4.250	4.250	—	1.000	—	—	4.250
1620	1/2-13	6.969	6.250	—	—	1.000	—	6.250	6.250	—	1.000	—	—	6.250
1623	1/2-13	6.969	8.000	—	2.750	2.750	—	8.000	8.000	—	2.750	2.750	—	8.000
1626	1/2-13	6.969	9.250	—	3.125	3.125	—	9.250	9.250	—	3.125	3.125	—	9.250
1629	1/2-13	6.969	11.000	—	3.688	3.688	—	11.000	11.000	—	3.688	3.688	—	11.000
1635	1/2-13	6.969	14.000	8.500	2.875	2.875	8.500	14.000	14.000	8.500	2.875	2.875	8.500	14.000
1724	1/2-13	7.281	7.750	—	2.750	2.750	—	7.750	7.750	—	2.750	2.750	—	7.750
1729	1/2-13	7.281	10.625	—	3.688	3.688	—	10.625	10.625	—	3.688	3.688	—	10.625
1818	1/2-13	7.969	5.438	—	—	1.000	—	5.438	5.438	—	1.000	—	—	5.438
1820	1/2-13	7.969	6.438	—	—	1.000	—	6.438	6.438	—	1.000	—	—	6.438
1823	1/2-13	7.969	8.125	—	2.750	2.750	—	8.125	8.125	—	2.750	2.750	—	8.125
1826	1/2-13	7.969	9.375	—	3.125	3.125	—	9.375	9.375	—	3.125	3.125	—	9.375
1829	1/2-13	7.969	11.125	—	3.688	3.688	—	11.125	11.125	—	3.688	3.688	—	11.125
1835	1/2-13	7.969	14.125	8.500	2.875	2.875	8.500	14.125	14.125	8.500	2.875	2.875	8.500	14.125
1924	1/2-13	8.781	7.750	—	2.750	2.750	—	7.750	7.750	—	2.750	2.750	—	7.750
1929	1/2-13	8.781	11.125	—	3.688	3.688	—	11.125	11.125	—	3.688	3.688	—	11.125
1935	1/2-13	8.781	14.125	8.500	2.875	2.875	8.500	14.125	14.125	8.500	2.875	2.875	8.500	14.125
2424	5/8-11	10.844	7.750	—	2.750	2.750	—	7.750	7.750	—	2.750	2.750	—	7.750
2429	5/8-11	10.844	10.625	—	3.688	3.688	—	10.625	10.625	—	3.688	3.688	—	10.625
2435	5/8-11	10.844	13.625	8.500	2.750	2.750	8.500	13.625	13.625	8.500	2.750	2.750	8.500	13.625

Clamp Slots



Features supplied as standard unless otherwise specified.

FOR QUOTING OR ORDERING, SPECIFY:

Clamp Slot Type


- Type A** - Machined when Top Clamping Plate is 0.875 or 1.375
- Type B** - Machined in plates that are 2.375 or thicker
- Type C** - Machined only when specified by a customer and top clamp plate is 1.375
- Type D** - Machined plates that are 1.875 thick

Other options include:

- Omit upper clamp slot
- Omit lower clamp slot (3-piece housing supplied)
- Machine entire length
- Machine all four sides


CONTACT US

Clamp Slots facilitate clamping the mold to the platen of the press. DME American Standard Mold Bases offer four slot types (shown below) to ensure the best fit for the requirements of your application.



Type A


Machined when Top Clamping Plate is 0.875 or 1.375



NOTE: When this plate is 0.875 thick, the slots will be machined through the thickness.


Type B

Machined in plates that are 2.375 or thicker




Type C

Machined only when specified by a customer



Type D

Machined plates that are 1.875 thick



Guide Pins and Bushings

Guide Pins & Bushings

Guide Pins and Bushings align both halves of the mold at the parting line.

[CONTACT US](#)




Features supplied as standard unless otherwise specified.



Guide Pin Positions

SIZE	DIA	LPxos	LPx	LPy
88	0.750	3.000	3.125	3.125
812	0.750	5.000	5.125	3.125
108	0.750	2.938	3.125	4.062
1012	0.875	4.875	5.062	4.062
1016	0.875	6.938	7.125	4.062
1020	0.875	8.938	9.125	4.062
1112	0.875	4.938	5.125	4.562
1114	0.875	5.938	6.125	4.562
1118	0.875	7.938	8.125	4.562
1123	0.875	10.688	10.875	4.562
1212	1.000	4.625	4.812	5.000
1215	1.000	6.125	6.312	5.000
1220	1.000	8.625	8.812	5.000
1223	1.000	10.375	10.562	5.000
1315	1.000	6.125	6.312	5.688
1318	1.000	7.375	7.562	5.688
1321	1.000	8.750	8.938	5.688
1323	1.000	10.125	10.312	5.688
1326	1.000	11.375	11.562	5.688
1329	1.000	13.125	13.312	5.688
1518	1.250	7.375	7.562	6.062
1524	1.250	10.250	10.438	6.062
1529	1.250	13.125	13.312	6.062
1616	1.250	6.375	6.562	6.562
1620	1.250	8.375	8.562	6.562
1623	1.250	10.125	10.312	6.562
1626	1.250	11.375	11.562	6.562
1629	1.250	13.125	13.312	6.562
1635	1.250	16.125	16.312	6.562
1724	1.250	10.250	10.438	6.812
1729	1.250	13.125	13.312	6.812
1818	1.250	7.375	7.562	7.562
1820	1.250	8.375	8.562	7.562
1823	1.250	10.125	10.312	7.562
1826	1.250	11.375	11.562	7.562
1829	1.250	13.125	13.312	7.562
1835	1.250	16.125	16.312	7.562
1924	1.250	10.250	10.438	8.312
1929	1.250	13.125	13.312	8.312
1935	1.250	16.125	16.312	8.312
2424	1.500	10.062	10.250	10.250
2429	1.500	12.938	13.125	10.250
2435	1.500	15.938	16.125	10.250



FOR QUOTING OR ORDERING, SPECIFY:

Guide Pins

Diameter: STD Specify

Recommended diameter from table provided standard. If a different diameter is required, specify below.

Diameter Options:

- 0.750 2.000
- 0.875 2.500
- 1.000 3.000
- 1.500

Length: STD Specify

Recommended pin length for A-Series mold base (A Plate Thickness + B Plate Thickness + 1/2) provided standard. If a different pin length is required, specify below.

Specify Pin Length: _____

Position: STD Specify

Recommended position from table provided standard (bushing location will correspond). If a different position is required, specify below.

- LPxos1 _____ LPy1 _____
- LPx2 _____ LPy2 _____
- LPx3 _____ LPy3 _____
- LPx4 _____ LPy4 _____

Guide Pin Bushings

Type/Omission:

- Steel
- Bronze
- Self-Lubricating
- Omit Machining for Leader Pin and Bushings
- Omit Guide Pin and Bushing

Return Pins, Stop Pins and Sprue Puller Pins

CONTACT US



Features supplied as standard unless otherwise specified.

FOR QUOTING OR ORDERING, SPECIFY:

Return Pins

Position: STD Specify
 Recommended position from table provided standard. If a different position is required, specify below.

Position 1

Standard outboard position for maximum space.

Position 2

Inboard position to allow for spring pockets.

Position/Omission:

- RPxos1 _____ RPy1 _____
- RPx2 _____ RPy2 _____
- RPx3 _____ RPy3 _____
- RPx4 _____ RPy4 _____

- Omit machining for return pins
- Omit return pins

Length: STD Specify _____
Diameter: STD Specify _____

Sprue Puller Pins

Diameter: STD Specify
 Recommended diameter provided standard (.375 diameter, except 88 and 812 are .250 diameter). If a different diameter is required, specify below.

- .250
- .3125
- .375

Length: STD Specify _____

Position/Omission:

Position on center Center

or relocate to

X _____ Y _____




- Omit machining for sprue puller pin
- Omit sprue puller pin

Return Pins, Stop Pins & Sprue Puller

Return Pins are used to ensure correct return of the ejector assembly to the home position. DME return pins are precision-ground from superior quality hotwork die steel.

Stop Pins arrest travel – preventing excessive wear and possible housing damage.

The Sprue Puller Pin removes material from the Sprue Bushing at the end of the molding cycle. It's positioned directly below the Sprue Bushing and is retained between the ejector bar and ejector retainer.



Return Pins, Stop Pins and Sprue Puller Pins

Mold Base Return Pin and Stop Pin Positions

BASE SIZE	RP DIAMETER (RECOMMENDED)	RP-y SP-y	POSITION 1		POSITION 2		SP-x1 SP-x6	SP-x2 SP-x7	SP-x3 SP-x8	SP-x4 SP-x9	SP-x5 SP-x10
			RP-xos	RP-x	RP-xos	RP-x					
88	0.500	1.500	3.250	3.375	3.188	3.312	3.375				3.375
812	0.500	1.500	5.250	5.375	5.188	5.312	5.375		On Center		5.375
108	0.625	2.250	3.250	3.375	3.125	3.250	3.375				3.375
1012	0.625	2.250	5.188	5.312	5.063	5.188	5.312		On Center		5.312
1016	0.625	2.250	7.250	7.375	7.125	7.250	7.375	2.500		2.500	7.375
1020	0.625	2.250	9.250	9.375	9.125	9.250	9.375	3.125		3.125	9.375
1112	0.625	2.812	5.250	5.375	5.125	5.250	5.375		On Center		5.375
1114	0.625	2.812	6.250	6.375	6.125	6.250	6.375		On Center		6.375
1118	0.625	2.812	8.250	8.375	8.125	8.250	8.375		On Center		8.375
1123	0.625	2.812	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
1212	0.750	3.188	5.250	5.375	5.000	5.125	5.375		On Center		5.375
1215	0.750	3.188	6.750	6.875	6.500	6.625	6.875	2.250		2.250	6.875
1220	0.750	3.188	9.250	9.375	9.000	9.125	9.375	3.094		3.094	9.375
1223	0.750	3.188	11.000	11.125	10.750	10.875	11.125	3.750		3.750	11.125
1315	0.750	3.812	6.750	6.875	6.500	6.625	6.875	2.250		2.250	6.875
1318	0.750	3.812	8.250	8.375	8.000	8.125	8.375	2.750		2.750	8.375
1321	0.750	3.812	9.500	9.625	9.375	9.500	9.625	4.000		4.000	9.625
1323	0.750	3.812	10.875	11.000	10.750	10.875	11.000	4.000		4.000	11.000
1326	0.750	3.812	12.125	12.250	12.000	12.125	12.250	4.000		4.000	12.250
1329	0.750	3.812	13.875	14.000	13.750	13.875	14.000	5.000		5.000	14.000
1518	0.750	3.875	8.125	8.250	7.938	8.062	8.250	2.750		2.750	8.250
1524	0.750	3.875	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
1529	0.750	3.875	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1616	0.750	4.375	7.125	7.250	7.000	7.125	7.250	2.375		2.375	7.250
1620	0.750	4.375	9.125	9.250	9.000	9.125	9.250	3.062		3.062	9.250
1623	0.750	4.375	10.875	11.000	10.750	10.875	11.000	4.000		4.000	11.000
1626	0.750	4.375	12.125	12.250	12.000	12.125	12.250	4.000		4.000	12.250
1629	0.750	4.375	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1635	0.750	4.375	16.875	17.000	16.750	16.875	17.000	8.500	On Center	8.500	17.000
1724	0.750	4.625	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
1729	0.750	4.625	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1818	0.750	5.375	8.125	8.250	8.000	8.125	8.250	2.750		2.750	8.250
1820	0.750	5.375	9.125	9.250	9.000	9.125	9.250	3.062		3.062	9.250
1823	0.750	5.375	10.875	11.000	10.750	10.875	11.000	4.000		4.000	11.000
1826	0.750	5.375	12.125	12.250	12.000	12.125	12.250	4.000		4.000	12.250
1829	0.750	5.375	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1835	0.750	5.375	16.875	17.000	16.750	16.875	17.000	8.500	On Center	8.500	17.000
1924	0.750	6.125	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
1929	0.750	6.125	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1935	0.750	6.125	16.875	17.000	16.750	16.875	17.000	8.500	On Center	8.500	17.000
2424	0.750	7.750	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
2429	0.750	7.750	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
2435	0.750	7.750	16.875	17.000	16.750	16.875	17.000	8.500	On Center	8.500	17.000

Ejector Housing and Cover



Features supplied as standard unless otherwise specified.

FOR QUOTING OR ORDERING, SPECIFY:

Ejector Housing Type

Welded Housing

Available in #1 steel

3-Piece Housing

DME #1 steel

DME #7 steel

Riser Height:

- 2.500 4.500
 3.000 5.000*
 3.500 5.500*
 4.000 6.000*
 Other _____

*Available in 3-Piece only

Bottom Clamp Plate

Thickness for

3-Piece Housing

- 0.875 3.375
 1.375 3.875
 1.875 4.875
 2.375 5.875
 2.875
 Other _____

CONTACT US

Ejector Housing & Cover

Ejector Housing Cover


For additional operator safety, DME Standard Mold Bases include an ejector housing cover, except when a longer length ejector bar is selected. The cover is fastened on both sides with 5/16-18 button-head cap screws.

Ejector Housing


A wide selection of housing types are certain to fit all application demands. A one-piece welded housing is available for customers requiring maximum rigidity and robust durability. For maximum flexibility of configuration options, a three-piece housing is also available.



Ejector Housing and Cover



Recommended Dimensions for Drilling and Tapping



Ejector Housing & Cover

Ejector Housing Cover Item Numbers

HOUSING WIDTH CODE	RISER HEIGHT CODE							
	25	30	35	40	45	50	55	60
08	EHCS0825	EHCS0830	EHCS0835	EHCS0840	EHCS0845	EHCS0850	EHCS0855	EHCS0860
10	EHCS1025	EHCS1030	EHCS1035	EHCS1040	EHCS1045	EHCS1050	EHCS1055	EHCS1060
11	EHCS1125	EHCS1130	EHCS1135	EHCS1140	EHCS1145	EHCS1150	EHCS1155	EHCS1160
12	EHCS1225	EHCS1230	EHCS1235	EHCS1240	EHCS1245	EHCS1250	EHCS1255	EHCS1260
13	EHCS1325	EHCS1330	EHCS1335	EHCS1340	EHCS1345	EHCS1350	EHCS1355	EHCS1360
15	EHCS1525	EHCS1530	EHCS1535	EHCS1540	EHCS1545	EHCS1550	EHCS1555	EHCS1560
16	EHCS1625	EHCS1630	EHCS1635	EHCS1640	EHCS1645	EHCS1650	EHCS1655	EHCS1660
17	EHCS1725	EHCS1730	EHCS1735	EHCS1740	EHCS1745	EHCS1750	EHCS1755	EHCS1760
18	EHCS1825	EHCS1830	EHCS1835	EHCS1840	EHCS1845	EHCS1850	EHCS1855	EHCS1860
19	EHCS1925	EHCS1930	EHCS1935	EHCS1940	EHCS1945	EHCS1950	EHCS1955	EHCS1960
24	EHCS2425	EHCS2430	EHCS2435	EHCS2440	EHCS2445	EHCS2450	EHCS2455	EHCS2460

NOTE: EHC item numbers are assembled from the prefix EHCS plus the width code and thickness code.
Example: EHCS0825 would be the cover for an 88 or 812 with a riser of 2.5".

Ejector Assembly Screws

Assembly Screws

Ejector Assembly Screws are used to hold the plates of the ejector assembly together (including the ejector bar and retainer).



Features supplied as standard unless otherwise specified.

FOR QUOTING OR ORDERING, SPECIFY:

Ejector Assembly Screws

Position: STD Specify

Recommended position from table provided standard. If a different position is required, specify below.


EASx _____

EASy _____

Omit upper assembly holes

Omit upper assembly screws

CONTACT US



Ejector Assembly Screw Positions

BASE SIZE	SCREW SIZE	EASx	EASy	BASE SIZE	SCREW SIZE	EASx	EASy
88	5/16-18	3.375	2.250	1518	3/8-16	8.312	5.000
812	5/16-18	5.375	2.250	1524	3/8-16	11.250	5.000
108	5/16-18	3.375	3.062	1529	3/8-16	14.125	5.000
1012	5/16-18	5.312	3.062	1616	3/8-16	7.375	5.438
1016	5/16-18	7.375	3.062	1620	3/8-16	9.375	5.438
1020	5/16-18	9.375	3.062	1623	3/8-16	11.125	5.438
1112	5/16-18	4.562	3.312	1626	3/8-16	12.375	5.438
1114	5/16-18	5.562	3.312	1629	3/8-16	14.125	5.438
1118	5/16-18	7.562	3.312	1635	3/8-16	17.125	5.438
1123	5/16-18	10.312	3.312	1724	3/8-16	11.250	5.750
1212	5/16-18	4.500	3.812	1729	3/8-16	14.125	5.750
1215	5/16-18	6.000	3.812	1818	3/8-16	8.375	6.438
1220	5/16-18	8.500	3.812	1820	3/8-16	9.375	6.438
1223	5/16-18	10.250	3.812	1823	3/8-16	11.125	6.438
*1315	3/8-16	5.812	4.250	1826	3/8-16	12.375	6.438
*1318	3/8-16	7.312	4.250	1829	3/8-16	14.125	6.438
1321	3/8-16	8.688	4.250	1835	3/8-16	17.125	6.438
1323	3/8-16	10.062	4.250	1924	1/2-13	11.250	7.250
1326	3/8-16	11.312	4.250	1929	1/2-13	14.125	7.250
1329	3/8-16	13.062	4.250	1935	1/2-13	17.125	7.250
				2424	1/2-13	11.250	8.875
				2429	1/2-13	14.125	8.875
				2435	1/2-13	17.125	8.875

*New X dimension effective 10/02.

American Mold Base Features and Delivery Time

SHIPPING OPTIONS



Special Mold Bases Shipping in Five Working Days

includes all DME Standard Mold Bases #1, #2 and #3 steel (7/8" to 57/8" thick) and #7 steel (7/8" to 27/8" thick); and all "no charge" items, plus:

- Machine for and install guided ejection – 2 or 4 places
- Machine for and install support pillars
- Machine for and install additional stop pins
- Machine press knock-out in bottom clamp plate (tap in ejector bar, if required)
- Machine pry bar slots
- Machine leader pin vent slots in rails
- Machine for spring holes
- Drill and tap lifting holes
- Drill and tap mold strap holes (location $\pm 1/32"$)
- Machine for and install extra assembly screws in top and/or bottom
- Machine for and install extra assembly screws in ejector assembly
- Machine for and install added return pins
- Rough mill/bore cavity and core pocket; blind or through (NOTE: 1/2" minimum radius required)



Special Mold Bases Shipping in Seven Working Days

includes all features specified in five working days, plus:

- Machine for DME three-piece extension bushings
- Drill and tap horizontal water lines
- Drill water pipe clearance holes
- Drill vertical water lines (excluding o-ring machining)
- Machine for DME angle pin inserts
- Finish mill/bore cavity and core pocket; blind or through (NOTE: 1/2" minimum radius required)



Special Mold Bases Shipping in Eleven Working Days

includes all features specified in seven working days, plus:

- Machine for DME parting line interlocks
- Provide special thickness plates (maximum plate thickness of 57/8" in DME #1, #2 and #3 steels, and 27/8" in DME #7 steel)
- Provide special plate lengths and widths within DME standard size offerings
- Angle pin machining and clearance (maximum 4)
- Ejector pin machining – maximum of 25 pins (3/16" minimum diameter ejector pin; 27/8" maximum plate thickness)
- Side interlock machining

CONTACT US

Self-Lubricating Bushings

Self-Lubricating Bushings

DME Self-Lubricating Bushings save time and money in the design, construction and operation of injection molds. Their built-in lubrication capability also makes them a good choice for fast cycling, high-production molds.





FOR QUOTING OR ORDERING, SPECIFY:

Self-Lubricating Bushings

Item Number: _____

Quantity: _____

CONTACT US



General Dimensions

NOMINAL I.D.	Ø E ^{+0.005} _{-0.000}	H ^{+0.000} _{-0.030}	K
3/4	1.1255	1.302	3/16
7/8	1.2505	1.427	
1"	1.3755	1.552	
1 1/4	1.6255	1.802	
1 1/2	2.0005	2.177	
2"	2.5005	2.677	
2 1/2	3.2505	3.427	1/2
3"	3.7505	3.990	

Self-Lubricating Straight Bushings

NOMINAL I.D.	Ø D ^{+0.005} _{-0.000}	L ^{+0.00} _{-0.06} LENGTH	H ^{+0.005} _{-0.000}	ITEM NUMBER
3/4	.7505	7/8	1.1255	GBS-06-07
		1 3/8	1.1255	GBS-06-13
7/8	.8755	1 3/8	1.2505	GBS-07-13
1"	1.0005	1 3/8	1.3755	GBS-08-13
1 1/4	1.2505	1 3/8	1.6255	GBS-10-13
		1 7/8	1.6255	GBS-10-17
1 1/2	1.5005	1 3/8	2.0005	GBS-12-13
		1 7/8	2.0005	GBS-12-17
2"	2.0005	3 7/8	2.5005	GBS-16-37
2 1/2	2.5005	4 7/8	3.2505	GBS-20-47
3"	3.0005	4 7/8	3.7505	GBS-24-47


Pry Slots

Mold base features Pry Slots, installed in any plate specified, on the parting and/or non-parting line side. This provides handling ease when opening and/or disassembling a mold.



Pry Slot Options

BASE SIZE	SLOT LENGTH Z
88-1123	.56 x 45°
1212-1315	.88 x 45°
1318-2435	1.00 x 45°




FOR QUOTING OR ORDERING, SPECIFY:

Pry Slot options:

- q Clamp Plate – parting line
- q A Plate – non-parting line
- q A Plate – parting line
- q B Plate – parting line
- q B Plate – non-parting line
- q Support Plate – parting line
- q Support Plate – non-parting line
- q Housing – parting line

CONTACT US



Guided Ejection Systems

CONTACT US



FOR QUOTING OR ORDERING, SPECIFY:

Guided Ejection System Type

- System 1
 System 2

Quantity (2 or 4): _____

Guided Ejection Bushing Type

- Bronze-Plated Steel Bushings
 Self-Lubricating Bushings

Guided Ejection

Position:

- STD Specify

Recommended position from table provided standard (see opposite page). If a different position is required, specify below.

GEx _____

GEy _____

Diameter:

- STD Specify

Recommended diameter from table provided standard. If a different diameter is required, it will require a positioning change; specify below.

Available diameters:


- 0.750
 0.875
 1.000
 1.250

Guided Ejector Pins

Guided Ejection Systems hold the ejector assembly in alignment and support the weight of the ejector assembly throughout the molding cycle – greatly reducing wear on ejection components and preventing cocking of the ejector assembly.


SYSTEM 1

When pins are installed in the support plate, the ejector housing can be removed from the mold without removing ejector plates. This permits easy access to service the ejector system.





SYSTEM 2


Pins installed in the ejector housing permit fast installation. When the ejector housing is removed from the mold base, the complete ejector assembly is removed.



Guided Ejection Systems



**"B" HALF OF MOLD
FOR 88, 812 & 108 MOLD BASE
SIZE ONLY**



**"B" HALF OF MOLD
FOR 1012 – 2435 BASES**

Guided Ejection Positions

PIN DIAMETER (RECOMMENDED)	BASE SIZE	GE _x	GE _y
0.750	88	3.000	Center
	812	5.000	Center
	108	3.062	Center
	1012	5.000	1.000
	1016	7.062	1.000
	1020	9.062	1.000
	1112	5.062	1.625
	1114	6.062	1.625
	1118	8.062	1.625
0.875	1123	10.812	1.625
	212	5.000	1.750
	1215	6.500	1.750
	1220	9.000	1.750
	1223	10.750	1.750
	1315	6.500	2.375
	1318	8.000	2.375
	1321	9.375	2.375
	1323	10.750	2.375
	1326	12.000	2.375
	1329	13.750	2.375

PIN DIAMETER (RECOMMENDED)	BASE SIZE	GE _x	GE _y
1.000	1518	7.875	2.375
	1524	10.812	2.375
	1529	13.688	2.375
	1616	6.938	2.875
	1620	8.938	2.875
	1623	10.688	2.875
	1626	11.938	2.875
	1629	13.688	2.875
	1635	16.688	2.875
	1724	10.812	3.125
	1729	13.688	3.125
	1818	7.938	3.875
	1820	8.938	3.875
	1823	10.688	3.875
	1826	11.938	3.875
	1829	13.688	3.875
	1835	16.688	3.875
	1.250	1924	10.812
1929		13.688	4.625
1935		16.688	4.625
2424		10.688	6.125
2429	13.562	6.125	
2435	16.562	6.125	

Standard & Optional Mold Base Features | Guided Ejection Systems

CONTACT US

Lifting Holes



FOR QUOTING OR ORDERING, SPECIFY:

Lifting Holes

Lifting holes can be selected up to three per plate edge. They are available in top clamp plate, A-plate, B-plate, support plate, and bottom clamp plate.

Note that for safety reasons, only the recommended hole diameters (or larger) shown in the table are offered.

Diameter _____

Quantity in each plate _____

Plates with lift holes _____

(Prints required if not on center)

CONTACT US



Lifting Holes can be used to install hoist rings for ease of handling. Mold base can be configured only with Lifting Holes which are appropriate for the specific mold base size. Refer to the DME Mold Components catalog for a comprehensive selection of hoist rings.

Lifting Hole Diameters

BASE SIZE	PLATE THICKNESS	
	0.875	1.375
88-1118	1/2-13 UNC	1/2-13 UNC
1123-1524	5/8-11 UNC	5/8-11 UNC
1529-1829	5/8-11 UNC	3/4-10 UNC
1835-2429	5/8-11 UNC	1"-8 UNC
2435	N/A	1"-8 UNC

Lifting Holes

THREAD SIZE	S	T MAX.
1/2-13	1.00	1.38
5/8-11	1.25	1.75
3/4-10	1.50	2.00
1"-8	2.00	2.62



Pockets

Per customer specifications, any type of cavity and core pockets will be finished. See DME Mold Components catalog for spring free lengths and hole dimensions.



Quick delivery on any type of cavity or core pockets



FOR QUOTING OR ORDERING, SPECIFY:

Rectangular Pockets

- Rough rectangular pockets: 5 days
- Finished rectangular pockets: 7 days

Length _____

Width _____

- Through
- Blind _____
(specify depth)

Corner Radius _____
(.50 min/1.00 max)

NOTE: Rough pocket tolerance
-.062 per side; finished
pocket tolerance $\pm .001$

[CONTACT US](#)

Support Pillars

Support Pillars

Support Pillars greatly increase the capacity of the mold to support the projected area of the cavities, runner and sprue. By providing additional support, they prevent deflection of the mold. Support Pillars are universally adaptable for cap screw, threaded locating pin, or socket set screw application.



FOR QUOTING OR ORDERING, SPECIFY:

Support Pillars

Quantity: _____

Diameter: _____

Style:

- Cap screw
- Threaded locating pin
- Socket set screw

CONTACT US

Cap Screw Application

Threaded Locating Pin Application

Socket Set Screw Application

No support pillars

One row of support pillars increases the permissible cavity area 4 times

Two rows of support pillars increase the permissible cavity area 9 times

Ø D	E	F	H (APPROX)	J SOCKET SET SCREW
1", 1 1/4", 1 1/2", 2"	5/8	3/8-16	1/2	ITEM NO. SSS-38114
3", 4"	1 1/4	5/8-11	3/8	ITEM NO. SSS-582


NOTE: Order SHCS separately.

Support Pillars



Support Pillars

$\emptyset D$ ^{+0.00} _{-.060}	H ^{+0.01} _{-.000} HEIGHT	ITEM NUMBER
1"	2.500	6090
	3.000	6091
	3.500	6092
	4.000	6093
	4.500	6094
1 1/4"	2.500	6130
	3.000	6131
	3.500	6132
	4.000	6133
	4.500	6134
	5.000	6135
1 1/2"	2.500	6140
	3.000	6141
	3.500	6142
	4.000	6143
	4.500	6144
	5.000	6145
2"	2.500	6150
	3.000	6151
	3.500	6152
	4.000	6153
	4.500	6154
	5.000	6155
3"	6.000	6235
	8.000	6236
	10.000	6238
4"	5.000	6245
	6.000	6246
	8.000	6248



Support pillars are universally adaptable for cap screw, threaded locating pin, or socket set screw applications.

Order pillars from chart at left and required "fasteners" as listed below.

Cap Screw (S.H.C.S.) Applications

3/8-16 or 5/8-11 socket head cap screws can be ordered in length required, see DME Mold Components Catalog.

Threaded Locating Pin Applications

Locating pins unavailable for 3" and 4" diameter pillars.

$\emptyset D$ PILLAR	ITEM NUMBER
1" TO 2"	TLP-38

Socket Set Screw Applications

Order pins and screws in package lots only.

$\emptyset D$ PILLAR	ITEM NUMBER	QTY PER PACKAGE
1" TO 2"	SSS-38114	10
3" AND 4"	SSS-582	5

Leader Pin Vents, Spring Pockets & Mold Strap Holes




FOR QUOTING OR ORDERING, SPECIFY:

Leader Pin Vents

Leader Pin Vents (0.50 wide x 0.12 deep) can be machined in the housing under the bushing location.

Leader Pin Vents, which allow trapped air to escape from the mold, are designed into all 15-inch-and-wider series molds. When desired, they can be specified on smaller molds.




Spring Pockets

Quantity: _____

Plate(s) with pockets: _____

Per customer specifications, any type of cavity and core pockets can be finished. See DME Mold Components catalog for spring free lengths and hole dimensions.



Mold Strap Holes

Provide desired positions and quantity (minimum 2).

Quantity: _____

Positions: _____


Machined holes will be for mounting mold straps. Please provide desired positions and quantity (minimum 2).



CONTACT US

Waterlines

DME will provide waterlines and plugs per customer specifications.



Jiffy-Tite® Plugs (JP)

Male Plug Mounting Information

ITEM NUMBER	NPT	HEX SIZE	A	B	C	H
JP-250	1/16	7/16	11/16	11/16	1"	5/8
JP-251	1/8	7/16	11/16	11/16	1"	5/8
JP-252-(SV)	1/4	9/16	27/32	15/16	13/16	7/8
JP-253-(SV)	3/8	11/16	1.000	15/16	11/4	29/32
JP-351	1/8	9/16	1.000	15/16	11/4	7/8
JP-352-(SV)	1/4	9/16	1.000	13/32	17/16	11/32
JP-353-(SV)	3/8	11/16	1.000	11/8	17/16	11/16
JP-354-(SV)	1/2	7/8	13/16	11/4	19/16	13/16
JP-553	3/8	7/8	11/4	13/16	15/8	11/8
JP-554	1/2	7/8	11/4	11/2	113/16	17/16
JP-556	3/4	11/8	11/2	19/16	17/8	11/2

FOR QUOTING OR ORDERING, SPECIFY:

Waterlines

Diameter: _____

Specify plates with waterlines:

Total length (in inches) of waterlines in each plate:

[CONTACT US](#)

3-Plate Extension Bushings

3-Plate Extension Bushings

Three-Plate Extension Bushings can save material, reduce cycle time and help prevent runner hang-ups in 3-plate molds.




FOR QUOTING OR ORDERING, SPECIFY:

Extension Bushings

Item Number: _____



Quantity: _____

CONTACT US



NOTES:

1. Stripper plate bushing TEB-0001 is used with all small and large extension nozzle bushings.
2. Appropriate S.H.C.S. are included with all bushings (TEB-0001 thru TEB-0009).
3. Select small or large bushing based on "A" clamping plate (A.C.P.) thickness, X-1 stripper plate thickness, machine nozzle spherical radius and machine nozzle clearance requirements.



ITEM NUMBER	R SPH. RAD	Ø A	Ø B	Ø C	E	F	G	H	J	K	L
TEB-0002	1/2	4.490	2.375	3.120	.375	2.265	1.377	1.875	2.640	#10-24 x 7/8 LONG (2) INCLUDED	1.781
TEB-0003	3/4							1.812			
TEB-0004	1/2							2.375	3.140		
TEB-0005	3/4	5.490	3.250	3.932	.750	2.765	1.877	2.375	3.140	5/16-18 x 7/8 LONG (2) INCLUDED	2.312
TEB-0006	1/2							2.312			
TEB-0007	3/4							2.875	3.640		
TEB-0008	1/2							2.812			
TEB-0009	3/4										

Interlocks

Interlocks

DME Interlocks are precision tolerated and precision manufactured to provide off-the-shelf interchangeability and accurate alignment of mold halves.



FOR QUOTING OR ORDERING, SPECIFY:


Interlocks

Quantity: _____

Item Number: _____

NOTE: See DME Mold Components catalog for additional interlock options.

CONTACT US



ITEM NUMBER	A NOMINAL	B	C	D NOMINAL	E	F*	G	H	J	K	L	M
PLM-0001	1.5000	.870	1.18	.5000	.870	1/4-20 X 3/4	.281	.281	.437	.281	.620	.19
PLF-0001												
PLM-0002	2.0000	.870	1.18	.6800	.870	1/4-20 X 3/4	.375	.375	.437	.375	.620	.19
PLF-0002												
PLM-0003	3.0000	1.360	1.910	1.0000	1.370	3/8-16 X 1	.688	.375	.688	.375	.745	.19
PLF-0003												
PLM-0004	4.0000	1.870	2.640	1.3750	1.870	3/8-16 X 1	.875	.625	.875	.625	.745	.50
PLF-0004												
PLM-0005	5.0000	1.870	2.640	1.7500	1.870	1/2-13 X 1 1/4	.875	.750	.875	.750	1.120	.50
PLF-0005												


*(2) F size SHCS included with each interlock.

Insulator Sheets

Insulator Sheets

DME High Temperature Insulator Sheets are used on molds and dies between the top clamping plate and the stationary platen, and between the bottom of the ejector housing and the movable platen.

- Asbestos-free material
- High compression strength
- Machinable with high-speed cutting tools



ENERGY SAVINGS

1/4 THICK = 27,508 BTU/HR

1/2 THICK = 31,004 BTU/HR

General Data

COMPRESSIVE STRENGTH	(ASTM D-229)	49,400 PSI AT 75°F 27,200 PSI AT 300°F 18,000 PSI AT 400°F 17,100 PSI AT 500°F 15,000 PSI AT 550°F
MODULUS OF ELASTICITY IN COMPRESSION	(ASTM D-229)	1.8 x 10 ⁶ PSI AT 75°F 2.9 x 10 ⁶ PSI AT 425°F
WATER ABSORPTION	(ASTM D-229)	0.2%
THERMAL CONDUCTIVITY (K FACTOR), (BTU/HR/FT ² /IN/°F)	(ASTM C-177)	1.9 AT 75°F 2.1 AT 425°F
FLAME RESISTANCE	(UL SUBJECT 94)	94V-0
EXPANSION ACROSS THICKNESS EXPANSION ACROSS SURFACE		6.43 x 10 ⁻⁵ IN/IN/°F 1.24 x 10 ⁻⁵ IN/IN/°F
MAXIMUM RECOMMENDED SERVICE TEMPERATURE		550°F

High Temperature Insulator Sheets

THICKNESS	LENGTH	WIDTH	ITEM NUMBER	NET WEIGHT
1/4	36"	18"	HTIS-1836-2	12
		24"	HTIS-2436-2	16
		36"	HTIS-3636-2	24
1/4	96"	48"	HTIS-4896-2	105
1/2	36"	18"	HTIS-1836-4	24
		24"	HTIS-2436-4	32
		36"	HTIS-3636-4	48

NOTE: Special sizes available on special order: Max. length = 96",
Max thickness = 1", Max. width = 48", Min. thickness = 1/8"
Installation: Use 1/4"-20 flat head screws. Drill and tap base to suit.

[CONTACT US](#)

DME X-, AX- and T-Series Mold Bases

A wide selection of DME Standard Stripper Plate, AX and T-Series Mold Bases Available in dozens of standard sizes.



X-, AX- and T-Series Mold Bases


table of contents

<u>Stripper Plate Series Mold Bases.....</u>	<u>174</u>	<u>9-7/8 T-Series Mold Bases</u>	<u>187</u>
<u>AX- and T-Series Mold Bases.....</u>	<u>175</u>	<u>10-7/8 T-Series Mold Bases.....</u>	<u>188</u>
<u>7-7/8 and 9-7/8 Stripper Plate Mold Bases</u>	<u>176</u>	<u>11-7/8 T-Series Mold Bases.....</u>	<u>189</u>
<u>10-7/8 Stripper Plate Mold Bases.....</u>	<u>177</u>	<u>13-3/8 T-Series Mold Bases</u>	<u>190</u>
<u>11-7/8 Stripper Plate Mold Bases</u>	<u>178</u>	<u>14-7/8 T-Series Mold Bases</u>	<u>191</u>
<u>13-3/8 Stripper Plate Mold Bases.....</u>	<u>179</u>	<u>15-7/8 T-Series Mold Bases</u>	<u>192</u>
<u>14-7/8 Stripper Plate Mold Bases.....</u>	<u>180</u>	<u>16-1/2 T-Series Mold Bases</u>	<u>193</u>
<u>15-7/8 and 16-1/2 Stripper Plate Mold Bases</u>	<u>181</u>	<u>17-7/8 T-Series Mold Bases.....</u>	<u>194</u>
<u>17-7/8 Stripper Plate Mold Bases.....</u>	<u>182</u>	<u>19-1/2 T-Series Mold Bases</u>	<u>195</u>
<u>19-1/2 and 23-3/4 Stripper Plate Mold Bases</u>	<u>183</u>	<u>23-3/4 T-Series Mold Bases</u>	<u>196</u>
<u>Multiple Stripper Plate Mold Bases.....</u>	<u>184</u>	<u>3-Plate Extension Bushing</u>	<u>197</u>
<u>AX-Series Mold Bases.....</u>	<u>185</u>	<u>Ball Bushings for Floating Plates</u>	<u>198</u>
<u>7-7/8 T-Series 3-Plate Mold Base</u>	<u>186</u>		


Stripper Plate Series Mold Base Features

DME Standard Stripper ("X" Series) Mold Bases are available with either the 5- or 6-plate construction. The location of the return pins, leader pins, screws and dowels are identical to the Standard "A" Series Mold Bases. Specifications are listed for every DME Standard size from 7.875 × 7.875 to 23.75 × 35.5.

5 Plate Series



6 Plate Series




AX- and T-Series Mold Base Features

“AX” Series Mold Bases

A DME Standard “AX” Series Mold Base is basically an “A” Series type mold base with a floating plate (“X-1” plate) added between the cavity plates. This type assembly is used when it is desirable to have the floating plate remain with the upper half of the assembly.


“AX” Series



“T” Series Mold Bases

DME Standard “T” Series Mold Bases are available in 42 standard sizes, from 7.875 × 7.875 to 23.75 × 35.5. They are used for top runner molds that require two floating plates (“X-1” – runner stripper plate, “X-2” – cavity plate) to remain with the upper or stationary half of the assembly.

“T” Series



7⁷/₈" and 9⁷/₈" Stripper Plate Mold Bases

NO. 1 & NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"AX", "X", and "BX" plates are No. 3 Steel. Top clamping and support plates are No. 2 Steel.

NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.



W	L	TCP	AX	C	5 PLATE		6 PLATE	
					ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
7.875	7.875	0.875	0.875	2.5	88X-5-7	111	88X-6-7	136
			1.375	2.5	88X-5-13	120	88X-6-13	145
			1.875	2.5	88X-5-17	129	88X-6-17	154
			2.375	2.5	88X-5-23	138	88X-6-23	163
	11.875	0.875	0.875	2.5	812X-5-7	174	812X-6-7	211
			1.375	3	812X-5-13	187	812X-6-13	224
			1.875	3.5	812X-5-17	200	812X-6-17	237
			2.375	3.5	812X-5-23	214	812X-6-23	251
	8	0.875	0.875	2.5	108X-5-7	158	108X-6-7	189
			1.375	3	108X-5-13	173	108X-6-13	204
			1.875	3.5	108X-5-17	187	108X-6-17	218
			2.375	3.5	108X-5-23	198	108X-6-23	229
2.875			4	108X-5-27	213	108X-6-27	244	
3.375			4.5	108X-5-33	227	108X-6-33	258	
9.875	11.875	0.875	0.875	2.5	1012X-5-7	235	1012X-6-7	281
			1.375	3	1012X-5-13	256	1012X-6-13	302
			1.875	3.5	1012X-5-17	277	1012X-6-17	323
			2.375	3.5	1012X-5-23	294	1012X-6-23	340
			2.875	4	1012X-5-27	316	1012X-6-27	362
			3.375	4.5	1012X-5-33	337	1012X-6-33	383
	16	0.875	0.875	2.5	1016X-5-7	316	1016X-6-7	378
			1.375	3	1016X-5-13	345	1016X-6-13	407
			1.875	3.5	1016X-5-17	374	1016X-6-17	436
			2.375	3.5	1016X-5-23	396	1016X-6-23	458
			2.875	4	1016X-5-27	425	1016X-6-27	487
			3.375	4.5	1016X-5-33	454	1016X-6-33	516
20	0.875	0.875	2.5	1020X-5-7	395	1020X-6-7	472	
		1.375	3	1020X-5-13	431	1020X-6-13	508	
		1.875	3.5	1020X-5-17	467	1020X-6-17	544	
		2.375	3.5	1020X-5-23	495	1020X-6-23	572	
		2.875	4	1020X-5-27	531	1020X-6-27	608	
		3.375	4.5	1020X-5-33	567	1020X-6-33	644	

NOTE: Mold bases listed above may be ordered with "X", "AX", and "BX" plate thicknesses other than those shown in chart. Prices on request.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3, or No. 7 Steel
- Locating Ring Item Number
- E, O and R Dimensions
- Method of Shipment
- 1.375 Top Clamping Plate if desired

Refer to corresponding size "A" Series Mold Base for detail dimensions



CONTACT US

107/8" Stripper Plate Mold Bases

NO. 1 & NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"AX", "X", and "BX" plates are No. 3 Steel. Top clamping and support plates are No. 2 Steel.



NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.

W	L	TCP	AX	C	5 PLATE BX = 1.875 X = 0.875		6 PLATE BX = 1.375 X = 0.875	
					ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
10.875	12	0.875	0.875	2.5	1112X-5-7	262	1112X-6-7	313
			1.375	3	1112X-5-13	286	1112X-6-13	337
			1.875	3.5	1112X-5-17	310	1112X-6-17	361
			2.375	3.5	1112X-5-23	329	1112X-6-23	380
			2.875	4	1112X-5-27	353	1112X-6-27	404
			3.375	4.5	1112X-5-33	377	1112X-6-33	428
	14	0.875	0.875	2.5	1114X-5-7	306	1114X-6-7	366
			1.375	3	1114X-5-13	334	1114X-6-13	394
			1.875	3.5	1114X-5-17	362	1114X-6-17	422
			2.375	3.5	1114X-5-23	384	1114X-6-23	444
			2.875	4	1114X-5-27	412	1114X-6-27	472
			3.375	4.5	1114X-5-33	440	1114X-6-33	500
	18	0.875	0.875	2.5	1118X-5-7	393	1118X-6-7	470
			1.375	3	1118X-5-13	429	1118X-6-13	506
			1.875	3.5	1118X-5-17	466	1118X-6-17	543
			2.375	3.5	1118X-5-23	493	1118X-6-23	570
			2.875	4	1118X-5-27	530	1118X-6-27	607
			3.375	4.5	1118X-5-33	566	1118X-6-33	643
	23.5	0.875	0.875	2.5	1123X-5-7	513	1123X-6-7	613
			1.375	3	1123X-5-13	560	1123X-6-13	660
			1.875	3.5	1123X-5-17	608	1123X-6-17	708
			2.375	3.5	1123X-5-23	644	1123X-6-23	744
			2.875	4	1123X-5-27	691	1123X-6-27	791
			3.375	4.5	1123X-5-33	739	1123X-6-33	839

NOTE: Mold bases listed above may be ordered with "X", "AX", and "BX" plate thicknesses other than those shown in chart. Prices on request.

Refer to corresponding size "A" Series Mold Base for detail dimensions



WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3, or No. 7 Steel
- Locating Ring Item Number
- E, O and R Dimensions
- Method of Shipment
- 1.375 Top Clamping Plate if desired

CONTACT US

1 1/8" Stripper Plate Mold Bases

NO. 1 & NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"AX", "X", and "BX" plates are No. 3 Steel.

Top clamping and support plates are No. 2 Steel.

NO. 7 STEEL ASSEMBLIES



Any or all plates available as requested.

X-, AX- and T-Series Mold Bases | 1 1/8" Stripper Plate Mold Bases

W	L	AX	C	5 PLATE		6 PLATE	
				ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
11.875	12	1.375	3	1212X-5-13	315	1212X-6-13	371
		1.875	3.5	1212X-5-17	341	1212X-6-17	397
		2.375	3.5	1212X-5-23	361	1212X-6-23	417
		2.875	4	1212X-5-27	387	1212X-6-27	443
		3.375	4	1212X-5-33	407	1212X-6-33	463
		3.875	4.5	1212X-5-37	433	1212X-6-37	489
	15	1.375	3	1215X-5-13	393	1215X-6-13	463
		1.875	3.5	1215X-5-17	426	1215X-6-17	496
		2.375	3.5	1215X-5-23	451	1215X-6-23	521
		2.875	4	1215X-5-27	483	1215X-6-27	553
		3.375	4	1215X-5-33	509	1215X-6-33	579
		3.875	4.5	1215X-5-37	541	1215X-6-37	611
	20	1.375	3	1220X-5-13	525	1220X-6-13	618
		1.875	3.5	1220X-5-17	568	1220X-6-17	661
		2.375	3.5	1220X-5-23	601	1220X-6-23	694
		2.875	4	1220X-5-27	645	1220X-6-27	738
		3.375	4	1220X-5-33	678	1220X-6-33	771
		3.875	4.5	1220X-5-37	721	1220X-6-37	814
	23.5	1.375	3	1223X-5-13	616	1223X-6-13	725
		1.875	3.5	1223X-5-17	667	1223X-6-17	776
		2.375	3.5	1223X-5-23	706	1223X-6-23	815
		2.875	4	1223X-5-27	757	1223X-6-27	866
		3.375	4	1223X-5-33	797	1223X-6-33	906
		3.875	4.5	1223X-5-37	848	1223X-6-37	957

NOTE: Mold bases listed above may be ordered with "X", "AX", and "BX" plate thicknesses other than those shown in chart. Prices on request.

Refer to corresponding size "A" Series Mold Base for detail dimensions.



WHEN ORDERING, PLEASE SPECIFY:

- 1. Quantity & Item Number
- 2. No. 1, No. 2, No. 3, or No. 7 Steel
- 3. Locating Ring Item Number
- 4. E, O and R Dimensions
- 5. Method of Shipment
- 6. 1.375 Top Clamping Plate if desired

CONTACT US

13³/₈" Stripper Plate Mold Bases

NO. 1 & NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"AX", "X", and "BX" plates are No. 3 Steel.

Top clamping and support plates are No. 2 Steel.



NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.

W	L	AX	C	5 PLATE		6 PLATE	
				ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
13.375	15	1.375	3	1315X-5-13	477	1315X-6-13	556
		1.875	3.5	1315X-5-17	513	1315X-6-17	592
		2.375	3.5	1315X-5-23	542	1315X-6-23	621
		2.875	4	1315X-5-27	578	1315X-6-27	657
		3.375	4	1315X-5-33	607	1315X-6-33	686
		3.875	4.5	1315X-5-37	643	1315X-6-37	722
	18	1.375	3	1318X-5-13	572	1318X-6-13	666
		1.875	3.5	1318X-5-17	616	1318X-6-17	710
		2.375	3.5	1318X-5-23	650	1318X-6-23	744
		2.875	4	1318X-5-27	694	1318X-6-27	788
		3.375	4	1318X-5-33	728	1318X-6-33	822
		3.875	4.5	1318X-5-37	771	1318X-6-37	865
	20.75	1.375	3	1321X-5-13	660	1321X-6-13	769
		1.875	3.5	1321X-5-17	710	1321X-6-17	819
		2.375	3.5	1321X-5-23	749	1321X-6-23	858
		2.875	4	1321X-5-27	800	1321X-6-27	909
		3.375	4	1321X-5-33	839	1321X-6-33	948
		3.875	4.5	1321X-5-37	889	1321X-6-37	998
	23.5	1.375	3	1323X-5-13	747	1323X-6-13	870
		1.875	3.5	1323X-5-17	804	1323X-6-17	927
		2.375	3.5	1323X-5-23	849	1323X-6-23	972
		2.875	4	1323X-5-27	906	1323X-6-27	1029
		3.375	4	1323X-5-33	950	1323X-6-33	1073
		3.875	4.5	1323X-5-37	1007	1323X-6-37	1130
	26	1.375	3	1326X-5-13	826	1326X-6-13	962
		1.875	3.5	1326X-5-17	889	1326X-6-17	1025
		2.375	3.5	1326X-5-23	939	1326X-6-23	1075
		2.875	4	1326X-5-27	1002	1326X-6-27	1138
		3.375	4	1326X-5-33	1051	1326X-6-33	1187
		3.875	4.5	1326X-5-37	1114	1326X-6-37	1250
29.5	1.375	3	1329X-5-13	938	1329X-6-13	1092	
	1.875	3.5	1329X-5-17	1009	1329X-6-17	1163	
	2.375	3.5	1329X-5-23	1065	1329X-6-23	1219	
	2.875	4	1329X-5-27	1137	1329X-6-27	1291	
	3.375	4	1329X-5-33	1192	1329X-6-33	1346	
	3.875	4.5	1329X-5-37	1264	1329X-6-37	1418	

NOTE: Mold bases listed above may be ordered with "X", "AX", and "BX" plate thicknesses other than those shown in chart. Prices on request.

Refer to corresponding size "A" Series Mold Base for detail dimensions.



WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3, or No. 7 Steel
- Locating Ring Item Number
- E, O and R Dimensions
- Method of Shipment

[CONTACT US](#)

147/8" Stripper Plate Mold Bases

NO. 1 & NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"AX", "X", and "BX" plates are No. 3 Steel.

Top clamping and support plates are No. 2 Steel.

NO. 7 STEEL ASSEMBLIES


Any or all plates available as requested.

W	L	AX	C	5 PLATE		6 PLATE	
				ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
14.875	17.875	1.375	3	1518X-5-13	668	1518X-6-13	772
		1.875	3.5	1518X-5-17	715	1518X-6-17	819
		2.375	3.5	1518X-5-23	752	1518X-6-23	856
		2.875	4	1518X-5-27	800	1518X-6-27	904
		3.375	4	1518X-5-33	837	1518X-6-33	941
		3.875	4.5	1518X-5-37	885	1518X-6-37	989
	23.75	1.375	3	1524X-5-13	887	1524X-6-13	1025
		1.875	3.5	1524X-5-17	950	1524X-6-17	1088
		2.375	3.5	1524X-5-23	1000	1524X-6-23	1138
		2.875	4	1524X-5-27	1063	1524X-6-27	1201
		3.375	4	1524X-5-33	1112	1524X-6-33	1250
		3.875	4.5	1524X-5-37	1175	1524X-6-37	1313
	29.5	1.375	3	1529X-5-13	1102	1529X-6-13	1273
		1.875	3.5	1529X-5-17	1180	1529X-6-17	1351
		2.375	3.5	1529X-5-23	1242	1529X-6-23	1413
		2.875	4	1529X-5-27	1320	1529X-6-27	1491
		3.375	4	1529X-5-33	1382	1529X-6-33	1553
		3.875	4.5	1529X-5-37	1460	1529X-6-37	1631


NOTE: Mold bases listed above may be ordered with "X", "AX", and "BX" plate thicknesses other than those shown in chart. Prices on request.

Refer to corresponding size "A" Series Mold Base for detail dimensions.

5 PLATE SERIES



6 PLATE SERIES



WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3, or No. 7 Steel
- Locating Ring Item Number
- E, O and R Dimensions
- Method of Shipment

CONTACT US

17⁷/₈" Stripper Plate Mold Bases

NO. 1 & NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"AX", "X", and "BX" plates are No. 3 Steel.

Top clamping and support plates are No. 2 Steel.

NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.

W	L	AX	C	5 PLATE		6 PLATE	
				ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
17.875	18	1.375	3	1818X-5-13	850	1818X-6-13	976
		1.875	3.5	1818X-5-17	905	1818X-6-17	1031
		2.375	3.5	1818X-5-23	951	1818X-6-23	1077
		2.875	4	1818X-5-27	1006	1818X-6-27	1132
		3.375	4	1818X-5-33	1051	1818X-6-33	1177
		3.875	4.5	1818X-5-37	1107	1818X-6-37	1233
	20	1.375	3	1820X-5-13	944	1820X-6-13	1084
		1.875	3.5	1820X-5-17	1006	1820X-6-17	1146
		2.375	3.5	1820X-5-23	1056	1820X-6-23	1196
		2.875	4	1820X-5-27	1118	1820X-6-27	1258
		3.375	4	1820X-5-33	1168	1820X-6-33	1308
		3.875	4.5	1820X-5-37	1230	1820X-6-37	1370
	23.5	1.375	3	1823X-5-13	1109	1823X-6-13	1273
		1.875	3.5	1823X-5-17	1182	1823X-6-17	1346
		2.375	3.5	1823X-5-23	1241	1823X-6-23	1405
		2.875	4	1823X-5-27	1313	1823X-6-27	1477
		3.375	4	1823X-5-33	1372	1823X-6-33	1536
		3.875	4.5	1823X-5-37	1445	1823X-6-37	1609
	26	1.375	3	1826X-5-13	1227	1826X-6-13	1409
		1.875	3.5	1826X-5-17	1307	1826X-6-17	1489
		2.375	3.5	1826X-5-23	1373	1826X-6-23	1555
		2.875	4	1826X-5-27	1453	1826X-6-27	1635
		3.375	4	1826X-5-33	1518	1826X-6-33	1700
		3.875	4.5	1826X-5-37	1598	1826X-6-37	1780
	29.5	1.375	3	1829X-5-13	1392	1829X-6-13	1598
		1.875	3.5	1829X-5-17	1483	1829X-6-17	1689
		2.375	3.5	1829X-5-23	1558	1829X-6-23	1764
		2.875	4	1829X-5-27	1648	1829X-6-27	1854
		3.375	4	1829X-5-33	1723	1829X-6-33	1929
		3.875	4.5	1829X-5-37	1813	1829X-6-37	2019
	35.5	1.375	3	1835X-5-13	1676	1835X-6-13	1924
		1.875	3.5	1835X-5-17	1785	1835X-6-17	2033
		2.375	3.5	1835X-5-23	1874	1835X-6-23	2122
		2.875	4	1835X-5-27	1983	1835X-6-27	2231
		3.375	4	1835X-5-33	2073	1835X-6-33	2321
		3.875	4.5	1835X-5-37	2182	1835X-6-37	2430

NOTE: Mold bases listed above may be ordered with "X", "AX", and "BX" plate thicknesses other than those shown in chart. Prices on request.


WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3, or No. 7 Steel
- Locating Ring Item Number
- E, O and R Dimensions
- Method of Shipment


[CONTACT US](#)

Refer to corresponding size "A" Series Mold Base for detail dimensions.

5 PLATE SERIES



6 PLATE SERIES



19¹/₂" and 23³/₄" Stripper Plate Mold Bases

NO. 1 & NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"AX", "X", and "BX" plates are No. 3 Steel.

Top clamping and support plates are No. 2 Steel.

NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.

W	L	AX	C	5 PLATE		6 PLATE	
				ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
19.5	23.75	1.375	3	1924X-5-13	1221	1924X-6-13	1402
		1.875	3.5	1924X-5-17	1300	1924X-6-17	1481
		2.375	3.5	1924X-5-23	1365	1924X-6-23	1546
		2.875	4	1924X-5-27	1443	1924X-6-27	1624
		3.375	4	1924X-5-33	1509	1924X-6-33	1690
	3.875	4.5	1924X-5-37	1587	1924X-6-37	1768	
	29.5	1.375	3	1929X-5-13	1516	1929X-6-13	1741
		1.875	3.5	1929X-5-17	1614	1929X-6-17	1839
		2.375	3.5	1929X-5-23	1695	1929X-6-23	1920
		2.875	4	1929X-5-27	1793	1929X-6-27	2018
		3.375	4	1929X-5-33	1874	1929X-6-33	2099
	3.875	4.5	1929X-5-37	1971	1929X-6-37	2196	
	35.5	1.375	3	1935X-5-13	1825	1935X-6-13	2095
		1.875	3.5	1935X-5-17	1942	1935X-6-17	2212
		2.375	3.5	1935X-5-23	2040	1935X-6-23	2310
2.875		4	1935X-5-27	2157	1935X-6-27	2427	
3.375		4	1935X-5-33	2255	1935X-6-33	2525	
3.875	4.5	1935X-5-37	2372	1935X-6-37	2642		
23.75	23.75	1.375	3	2424X-5-13	1562	2424X-6-13	1782
		1.875	3.5	2424X-5-17	1655	2424X-6-17	1875
		2.375	3.5	2424X-5-23	1734	2424X-6-23	1954
		2.875	4	2424X-5-27	1827	2424X-6-27	2047
		3.375	4	2424X-5-33	1907	2424X-6-33	2127
	3.875	4.5	2424X-5-37	2000	2424X-6-37	2220	
	29.5	1.375	3	2429X-5-13	1940	2429X-6-13	2213
		1.875	3.5	2429X-5-17	2055	2429X-6-17	2328
		2.375	3.5	2429X-5-23	2154	2429X-6-23	2427
		2.875	4	2429X-5-27	2269	2429X-6-27	2542
		3.375	4	2429X-5-33	2368	2429X-6-33	2641
	3.875	4.5	2429X-5-37	2483	2429X-6-37	2756	
	35.5	1.375	3	2435X-5-13	2334	2435X-6-13	2663
		1.875	3.5	2435X-5-17	2473	2435X-6-17	2802
		2.375	3.5	2435X-5-23	2592	2435X-6-23	2921
2.875		4	2435X-5-27	2730	2435X-6-27	3059	
3.375		4	2435X-5-33	2850	2435X-6-33	3179	
3.875	4.5	2435X-5-37	2988	2435X-6-37	3317		



NOTE: Mold bases listed above may be ordered with "X", "AX", and "BX" plate thicknesses other than those shown in chart. Prices on request.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3, or No. 7 Steel
- Locating Ring Item Number
- E, O and R Dimensions
- Method of Shipment

[CONTACT US](#)

Refer to corresponding size "A" Series Mold Base for detail dimensions.




Multiple Stripper Plate Mold Bases


Multiple Stripper Plate Mold Bases

Multiple Stripper Plate Mold Bases consist of a 5 or 6 plate "X" Series Mold Base with one or more floating plates added to the assembly. The assembly "without the support plate" has the same construction as the 5 Plate "X" Series. When this type of assembly is required please refer to the plate designations listed below. Prices quoted on request.

WITHOUT SUPPORT PLATE




WITH SUPPORT PLATE




VARIATIONS IN EJECTOR ASSEMBLY

DOUBLE EJECTION



Double ejection is sometimes required when using multiple stripper plate mold assemblies. Prices quoted on request.

GUIDED EJECTION



When an exceptionally long stroke is required, or when ejector pin diameters are extremely small a guided ejector assembly can give additional rigidity.

[CONTACT US](#)

AX-Series Mold Bases

AX-Series

NO. 1 OR NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"A", "X-1", and "B" plates are No. 3 Steel.


Top clamping and support plates are No. 2 Steel.

NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.



"AX" Series Assembly



MOLD BASE SIZE WIDTH (W)	TOP CLAMPING PLATE THICKNESS
7.875 to 11.875	0.875
13.375 to 23.75	1.375

"X-1" PLATE THICKNESSES AVAILABLE:

0.875, 1.375, 1.875, 2.375, 2.875, 3.375, 4.875, 5.875

A DME Standard "AX" Series Mold Base is basically an "A" series type mold base with a floating plate ("X-1" plate) added between the "A" and "B" Plates. This type assembly is used where it is desirable to have the floating plate remain with the upper half of the assembly.

INSTRUCTIONS FOR ORDERING:

When ordering "AX" Series Mold Bases, refer to the corresponding size "A" Series Mold Base for detailed dimensions.

To create a Item number, add an "X" after the "A" in Item number of corresponding size A-Series mold base, and follow with thickness of the (1) A-Plate, (2) X-1 Plate and (3) B-Plate.

Example: 1012AX-13-17-23

STANDARD MOLD BASE SIZE		ITEM NUMBER PREFIX
W	L	
7.875	7.875	88AX
	11.875	812AX
9.875	8	108AX
	11.875	1012AX
	16	1016AX
	20	1020AX
10.875	12	1112AX
	14	1114AX
	18	1118AX
	23.5	1123AX
11.875	12	1212AX
	15	1215AX
	20	1220AX
	23.5	1223AX
13.375	15	1315AX
	18	1318AX
	20.75	1321AX
	23.5	1323AX
	26	1326AX
14.875	29.5	1329AX
	17.875	1518AX
	23.75	1524AX
	29.5	1529AX

STANDARD MOLD BASE SIZE		ITEM NUMBER PREFIX
W	L	
15.875	16	1616AX
	20	1620AX
	23.5	1623AX
	26	1626AX
	29.5	1629AX
16.5	35.5	1635AX
	23.75	1724AX
	29.5	1729AX
17.875	18	1818AX
	20	1820AX
	23.5	1823AX
	26	1826AX
	29.5	1829AX
19.5	35.5	1835AX
	23.75	1924AX
	29.5	1929AX
23.75	35.5	1935AX
	23.75	2424AX
	29.5	2429AX
	35.5	2435AX

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3, or No. 7 Steel
- X-1 Plate Thickness
- Locating Ring Item Number
- E, O and R Dimensions
- Method of Shipment
- 1.375 Top Clamping Plate if desired



[CONTACT US](#)

7⁷/₈" T-Series (3-Plate) Mold Bases

T-Series

A typical 3-plate top runner mold operates as follows: The mold opens first at Parting Line 1 (spring loaded). The runner and cavity sprues are pulled from the cavities in the "X-2" Plate and held against the "X-1" Plate by undercut puller pins.

As the mold continues to open ("X-2" Plate moving forward), stripper bolts SB-1 pull the "X-1" Plate forward (at the end of the "X-2" Plate movement). The "X-1" Plate travel is determined by stripper bolts SB-2. The travel of the "X-1" Plate (breaking at Parting Line 2) strips the entire runner system from the puller pins, breaks the main sprue (held to a minimum length), and allows the runner to drop free. Mold opening at Parting Line 3 then takes place for piece-part ejection.



For detailed dimensions, see corresponding size "A" Series Mold Base

X-2	X-1 = 0.875			7.875 x 7.875	
	B	C	H	ITEM NUMBER	NET WT.
1.375	0.875	2.5	9.75	88T-13-7	153
	1.375	2.5	10.25	88T-13-13	162
	1.875	2.5	10.75	88T-13-17	171
1.875	0.875	2.5	10.25	88T-17-7	162
	1.375	2.5	10.75	88T-17-13	171
	1.875	2.5	11.25	88T-17-17	180
2.375	1.375	2.5	11.25	88T-23-13	180
	1.875	2.5	11.75	88T-23-17	188
	2.375	3	12.75	88T-23-23	200
2.875	1.375	3	12.25	88T-27-13	191
	1.875	3.5	13.25	88T-27-17	203
	2.375	3.5	13.75	88T-27-23	212
3.375	1.875	3.5	13.75	88T-33-17	212
	2.375	4	14.75	88T-33-23	223
	2.875	4	15.25	88T-33-27	232
3.875	1.875	3.5	14.25	88T-37-17	220
	2.375	4	15.25	88T-37-23	232
	2.875	4	15.75	88T-37-27	241
4.875	2.375	4	16.25	88T-47-23	250
	2.875	4	16.75	88T-47-27	258
	3.375	4.5	17.75	88T-47-33	270

X-2	X-1 = 0.875			7.875 x 11.875	
	B	C	H	ITEM NUMBER	NET WT.
1.375	0.875	2.5	9.75	812T-13-7	237
	1.375	3	10.75	812T-13-13	254
	1.875	3	11.25	812T-13-17	268
1.875	0.875	2.5	10.25	812T-17-7	250
	1.375	3	11.25	812T-17-13	268
	1.875	3.5	12.25	812T-17-17	285
2.375	1.375	3	11.75	812T-23-13	281
	1.875	3.5	12.75	812T-23-17	298
	2.375	3.5	13.25	812T-23-23	312
2.875	1.375	3	12.25	812T-27-13	294
	1.875	3.5	13.25	812T-27-17	312
	2.375	3.5	13.75	812T-27-23	325
3.375	1.875	3.5	13.75	812T-33-17	325
	2.375	4	14.75	812T-33-23	342
	2.875	4	15.25	812T-33-27	355
3.875	1.875	3.5	14.25	812T-37-17	338
	2.375	4	15.25	812T-37-23	355
	2.875	4	15.75	812T-37-27	369
4.875	2.375	4	16.25	812T-47-23	382
	2.875	4	16.75	812T-47-27	395
	3.375	4.5	17.75	812T-47-33	413

NOTE: Stripper bolts, puller pins and spring shown are not included. When gating directly into the cavity from a top runner, the 3-plate "T" Series assembly may be used. It incorporates an additional runner stripper plate ("X-1") to facilitate automatic removal of the runner from the mold.

The "X-1" and "X-2" Plates have standard shoulder bushings and ride on standard leader pins. (When heavy "X-2" Plates are required, moldmaker may want to specify larger diameter leader pins and have them relocated. Contact customer service for a quotation to your specifications). The "X-1" Plate is supplied without a center hole. A standard sprue bushing long enough to extend through the "X-1" Plate is provided to allow the moldmaker to finish the sprue bushing hole as desired, or to install a recessed bushing to give the shortest main sprue length for minimum stripper plate movement.

Detailed dimensions for the "T" Series are identical to corresponding size "A" Series Mold Bases. Center sprue puller pin and pin holes as well as the socket head cap screws in the "A" — Clamping Plate are omitted since they are not required.

16 1/2" T-Series Mold Bases

T-Series

NO. 1 OR NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"X-1", "X-2" and "B" Plates are No. 3 Steel.

"A" - Clamping and Support Plates are No. 2 Steel.


NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.



X-1 = 1.375				16.5 x 23.75	
X-2	B	C	H	ITEM NUMBER	NET WT.
1.875	1.375	3	12.75	1724T-17-13	1300
	1.875	3.5	13.75	1724T-17-17	1369
	2.375	3.5	14.25	1724T-17-23	1424
2.375	1.375	3.5	13.75	1724T-23-13	1369
	1.875	3.5	14.25	1724T-23-17	1424
	2.375	3.5	14.75	1724T-23-23	1480
2.875	1.375	3.5	14.25	1724T-27-13	1424
	1.875	3.5	14.75	1724T-27-17	1480
	2.375	3.5	15.25	1724T-27-23	1535
3.375	1.875	4	15.75	1724T-33-17	1548
	2.375	4	16.25	1724T-33-23	1603
	2.875	4.5	17.25	1724T-33-27	1671
3.875	1.875	4	16.25	1724T-37-17	1603
	2.375	4.5	17.25	1724T-37-23	1671
	2.875	4.5	17.75	1724T-37-27	1727
4.875	2.375	4.5	18.25	1724T-47-23	1782
	2.875	4.5	18.75	1724T-47-27	1838
	3.375	4.5	19.25	1724T-47-33	1893
5.875	2.875	4.5	19.75	1724T-57-27	1949
	3.875	4.5	20.75	1724T-57-37	2060
	4.875	4.5	21.75	1724T-57-47	2171

X-1 = 1.375				16.5 x 29.5	
X-2	B	C	H	ITEM NUMBER	NET WT.
1.875	1.375	3	12.75	1729T-17-13	1615
	1.875	3.5	13.75	1729T-17-17	1700
	2.375	3.5	14.25	1729T-17-23	1769
2.375	1.375	3.5	13.75	1729T-23-13	1700
	1.875	3.5	14.25	1729T-23-17	1769
	2.375	3.5	14.75	1729T-23-23	1838
2.875	1.375	3.5	14.25	1729T-27-13	1769
	1.875	3.5	14.75	1729T-27-17	1838
	2.375	3.5	15.25	1729T-27-23	1907
3.375	1.875	4	15.75	1729T-33-17	1922
	2.375	4	16.25	1729T-33-23	1991
	2.875	4.5	17.25	1729T-33-27	2076
3.875	1.875	4	16.25	1729T-37-17	1991
	2.375	4.5	17.25	1729T-37-23	2076
	2.875	4.5	17.75	1729T-37-27	2145
4.875	2.375	4.5	18.25	1729T-47-23	2214
	2.875	4.5	18.75	1729T-47-27	2283
	3.375	4.5	19.25	1729T-47-33	2352
5.875	2.875	4.5	19.75	1729T-57-27	2421
	3.875	4.5	20.75	1729T-57-37	2559
	4.875	4.5	21.75	1729T-57-47	2696



For detailed dimensions, see corresponding size "A" Series Mold Bases.

NOTE: For 3-Plate Extension Bushings, see page 197.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3, or No. 7 Steel
- Locating Ring Item Number
- E, O and R Dimensions
- L Dimension (Leader Pin Length)
- Method of Shipment

CONTACT US

19 1/2" T-Series Mold Bases

T-Series

NO. 1 OR NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.



NO. 3 STEEL ASSEMBLIES

"X-1", "X-2" and "B" Plates are No. 3 Steel.

"A" - Clamping and Support Plates are No. 2 Steel.

NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.



For detailed dimensions, see corresponding size "A" Series Mold Bases.

X-1 = 1.375				19.5 × 23.75		X-1 = 1.375				19.5 × 29.5		X-1 = 1.375				19.5 × 35.5	
X-2	B	C	H	ITEM NUMBER	NET WT.	X-2	B	C	H	ITEM NUMBER	NET WT.	X-2	B	C	H	ITEM NUMBER	NET WT.
1.875	1.375	3	12.75	1924T-17-13	1533	1.875	1.375	3	12.75	1929T-17-13	1903	1.875	1.375	3	12.75	1935T-17-13	2291
	1.875	3	13.25	1924T-17-17	1598		1.875	3	13.25	1929T-17-17	1985		1.875	3	13.25	1935T-17-17	2389
	2.375	3.5	14.25	1924T-17-23	1676		2.375	3.5	14.25	1929T-17-23	2082		2.375	3.5	14.25	1935T-17-23	2506
2.375	1.375	3.5	13.75	1924T-23-13	1611	2.375	1.375	3.5	13.75	1929T-23-13	2001	2.375	1.375	3.5	13.75	1935T-23-13	2408
	1.875	3.5	14.25	1924T-23-17	1676		1.875	3.5	14.25	1929T-23-17	2082		1.875	3.5	14.25	1935T-23-17	2506
	2.375	3.5	14.75	1924T-23-23	1742		2.375	3.5	14.75	1929T-23-23	2164		2.375	3.5	14.75	1935T-23-23	2604
2.875	1.375	3.5	14.25	1924T-27-13	1676	2.875	1.375	3.5	14.25	1929T-27-13	2082	2.875	1.375	3.5	14.25	1935T-27-13	2506
	1.875	3.5	14.75	1924T-27-17	1742		1.875	3.5	14.75	1929T-27-17	2164		1.875	3.5	14.75	1935T-27-17	2604
	2.375	3.5	15.25	1924T-27-23	1808		2.375	3.5	15.25	1929T-27-23	2245		2.375	3.5	15.25	1935T-27-23	2702
3.375	1.875	4	15.75	1924T-33-17	1820	3.375	1.875	4	15.75	1929T-33-17	2261	3.375	1.875	4	15.75	1935T-33-17	2721
	2.375	4	16.25	1924T-33-23	1886		2.375	4	16.25	1929T-33-23	2342		2.375	4	16.25	1935T-33-23	2819
	2.875	4.5	17.25	1924T-33-27	1964		2.875	4.5	17.25	1929T-33-27	2439		2.875	4.5	17.25	1935T-33-27	2936
3.875	1.875	4	16.25	1924T-37-17	1886	3.875	1.875	4	16.25	1929T-37-17	2342	3.875	1.875	4	16.25	1935T-37-17	2819
	2.375	4.5	17.25	1924T-37-23	1964		2.375	4.5	17.25	1929T-37-23	2439		2.375	4.5	17.25	1935T-37-23	2936
	2.875	4.5	17.75	1924T-37-27	2030		2.875	4.5	17.75	1929T-37-27	2521		2.875	4.5	17.75	1935T-37-27	3034
4.875	2.375	4.5	18.25	1924T-47-23	2095	4.875	2.375	4.5	18.25	1929T-47-23	2602	4.875	2.375	4.5	18.25	1935T-47-23	3132
	2.875	4.5	18.75	1924T-47-27	2161		2.875	4.5	18.75	1929T-47-27	2684		2.875	4.5	18.75	1935T-47-27	3230
	3.375	4.5	19.25	1924T-47-33	2226		3.375	4.5	19.25	1929T-47-33	2765		3.375	4.5	19.25	1935T-47-33	3328
5.875	2.875	4.5	19.75	1924T-57-27	2292	5.875	2.875	4.5	19.75	1929T-57-27	2847	5.875	2.875	4.5	19.75	1935T-57-27	3426
	3.875	4.5	20.75	1924T-57-37	2423		3.875	4.5	20.75	1929T-57-37	3010		3.875	4.5	20.75	1935T-57-37	3622
	4.875	4.5	21.75	1924T-57-47	2554		4.875	4.5	21.75	1929T-57-47	3173		4.875	4.5	21.75	1935T-57-47	3818

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3, or No. 7 Steel
- Locating Ring Item Number
- E, O and R Dimensions
- L Dimension (Leader Pin Length)
- Method of Shipment

CONTACT US

NOTE: For 3-Plate Extension Bushings, see page 197.

23³/₄" T-Series Mold Bases

T-Series

NO. 1 OR NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.


NO. 3 STEEL ASSEMBLIES

"X-1", "X-2" and "B" Plates are No. 3 Steel.

"A" - Clamping and Support Plates are No. 2 Steel


NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.



For detailed dimensions, see corresponding size "A" Series Mold Bases.

NOTE: Clamp slots for 23.75" wide bases will be type B, not type D as shown in photo.



X-1 = 1.375				23.75 × 23.75	
X-2	B	C	H	ITEM NUMBER	NET WT.
1.875	1.375	3	13.75	2424T-17-13	2021
	1.875	3	14.25	2424T-17-17	2101
	2.375	3.5	15.25	2424T-17-23	2194
2.375	1.375	3.5	14.75	2424T-23-13	2114
	1.875	3.5	15.25	2424T-23-17	2194
	2.375	3.5	15.75	2424T-23-23	2274
2.875	1.375	3.5	15.25	2424T-27-13	2194
	1.875	3.5	15.75	2424T-27-17	2274
	2.375	3.5	16.25	2424T-27-23	2353
3.375	1.875	4	16.75	2424T-33-17	2366
	2.375	4	17.25	2424T-33-23	2446
	2.875	4.5	18.25	2424T-33-27	2538
3.875	1.875	4	17.25	2424T-37-17	2446
	2.375	4.5	18.25	2424T-37-23	2538
	2.875	4.5	18.75	2424T-37-27	2618
4.875	2.375	4.5	19.25	2424T-47-23	2698
	2.875	4.5	19.75	2424T-47-27	2778
	3.375	4.5	20.25	2424T-47-33	2858
5.875	2.875	4.5	20.75	2424T-57-27	2938
	3.875	4.5	21.75	2424T-57-37	3098
	4.875	4.5	22.75	2424T-57-47	3258

X-1 = 1.375				23.75 × 29.5	
X-2	B	C	H	ITEM NUMBER	NET WT.
1.875	1.375	3	13.75	2429T-17-13	2510
	1.875	3	14.25	2429T-17-17	2610
	2.375	3.5	15.25	2429T-17-23	2725
2.375	1.375	3.5	14.75	2429T-23-13	2625
	1.875	3.5	15.25	2429T-23-17	2725
	2.375	3.5	15.75	2429T-23-23	2824
2.875	1.375	3.5	15.25	2429T-27-13	2725
	1.875	3.5	15.75	2429T-27-17	2824
	2.375	3.5	16.25	2429T-27-23	2923
3.375	1.875	4	16.75	2429T-33-17	2939
	2.375	4	17.25	2429T-33-23	3038
	2.875	4.5	18.25	2429T-33-27	3153
3.875	1.875	4	17.25	2429T-37-17	3038
	2.375	4.5	18.25	2429T-37-23	3153
	2.875	4.5	18.75	2429T-37-27	3252
4.875	2.375	4.5	19.25	2429T-47-23	3351
	2.875	4.5	19.75	2429T-47-27	3451
	3.375	4.5	20.25	2429T-47-33	3550
5.875	2.875	4.5	20.75	2429T-57-27	3649
	3.875	4.5	21.75	2429T-57-37	3848
	4.875	4.5	22.75	2429T-57-47	4046

X-1 = 1.375				23.75 × 35.5	
X-2	B	C	H	ITEM NUMBER	NET WT.
1.875	1.375	3	13.75	2435T-17-13	3021
	1.875	3	14.25	2435T-17-17	3140
	2.375	3.5	15.25	2435T-17-23	3279
2.375	1.375	3.5	14.75	2435T-23-13	3159
	1.875	3.5	15.25	2435T-23-17	3279
	2.375	3.5	15.75	2435T-23-23	3398
2.875	1.375	3.5	15.25	2435T-27-13	3279
	1.875	3.5	15.75	2435T-27-17	3398
	2.375	3.5	16.25	2435T-27-23	3518
3.375	1.875	4	16.75	2435T-33-17	3536
	2.375	4	17.25	2435T-33-23	3656
	2.875	4.5	18.25	2435T-33-27	3794
3.875	1.875	4	17.25	2435T-37-17	3656
	2.375	4.5	18.25	2435T-37-23	3794
	2.875	4.5	18.75	2435T-37-27	3914
4.875	2.375	4.5	19.25	2435T-47-23	4033
	2.875	4.5	19.75	2435T-47-27	4152
	3.375	4.5	20.25	2435T-47-33	4272
5.875	2.875	4.5	20.75	2435T-57-27	4391
	3.875	4.5	21.75	2435T-57-37	4630
	4.875	4.5	22.75	2435T-57-47	4869

WHEN ORDERING, PLEASE SPECIFY:

1. Quantity & Item Number
2. No. 1, No. 2, No. 3, or No. 7 Steel
3. Locating Ring Item Number
4. E, O and R Dimensions
5. L Dimension (Leader Pin Length)
6. Method of Shipment

CONTACT US

NOTE: For 3-Plate Extension Bushings, see page 197.

3-Plate Extension Bushings

3-Plate Extension Bushing


Three-plate extension bushings can save material, reduce cycle time and help prevent runner hang-ups in 3-plate molds.



Runner Stripper Plate Bushing
TEB-0001

NOTES:

1. Stripper plate bushing TEB-0001 is used with all small and large extension nozzle bushings.
2. Appropriate S.H.C.S. are included with all bushings (TEB-0001 thru TEB-0009).
3. Select small or large bushing based on "A" clamping plate (A.C.P.) thickness, X-1 stripper plate thickness, machine nozzle spherical radius and machine nozzle clearance requirements.




ITEM NUMBER	R SPH. RAD	Ø A	Ø B	Ø C	E	F	G	H	J	K	L
TEB-0002	1/2	4.490	2.375	3.120	.375	2.265	1.377	1.875	2.640	#10-24 x 7/8 LONG (2) INCLUDED	1.781
TEB-0003	3/4							1.812			
TEB-0004	1/2							2.375			
TEB-0005	3/4	5.490	3.250	3.932	.750	2.765	1.877	2.312	3.140	5/16-18 x 7/8 LONG (2) INCLUDED	2.312
TEB-0006	1/2							2.375			
TEB-0007	3/4							2.312			
TEB-0008	1/2	5.490	3.250	3.932	.750	3.265	2.377	2.875	3.640	5/16-18 x 7/8 LONG (2) INCLUDED	2.312
TEB-0009	3/4							2.812			

CONTACT US

Ball Bushings for Floating Plates*

Ball Bushings are a highly effective means of reducing frictional drag in floating plates within a mold. Multiple-opening molds, with heavy floating (X) plates, are the most frequent application for either Lineal type or Pre-Loaded type Ball Bushings.



General Dimensions for DME Pre-Loaded Type Ball Bushings*

NOMINAL SIZE	3/4	1"	1 1/4	1 1/2	1 3/4	2"
A (PIN DIA.)	.753	1.003	1.253	1.503	1.753	2.003
B (BUSHING DIA.)	1.387	1.717	2.107	2.437	2.747	3.162
C (BUSHING LENGTH)	1 3/4 TO 6"	2" TO 7"	2 1/2 TO 9"	3" TO 12"	3" TO 13"	3" TO 14"
D (1/4 INCREMENT RETAINER LENGTH)	1 1/2" TO 2"	1 1/2 TO 2 1/4	2" TO 3"	2 1/2 TO 3 1/2	2 3/4 TO 4"	3 1/4 TO 4 1/4
M (PIN LENGTH)	3" TO 6"	3 3/4 TO 9"	4 1/2 TO 12"	4 1/2 TO 14"	5" TO 17"	5 1/2 TO 18"

General Dimensions for Thomson Lineal Type Ball Bushings

BUSHING IT	A-122026	A-162536	A-203242	A-243848	A-324864
A (PIN DIA.)	.750	1.000	1.250	1.500	2.000
B (BUSHING DIA.)	1.250	1.5625	2.000	2.375	3.000
C (BUSHING LENGTH)	1.625	2.250	2.625	3.000	4.000
RETAINER RING ITEM NUMBER	W-750	W-1000	W-1250	W-1500	W-2000
D	1.062	1.625	1.875	2.250	3.000
E	1.620	2.040	2.500	2.910	3.600
COUNTERBORE DIA. (FOR RETAINER RING)	1.69	2.10	2.55	3.01	3.69

NOTES:
 Specifications shown are for DME precision grade.
 Due to the larger O.D. of the bushing counterbore required, ball bushings cannot be installed in standard leader pin locations in the mold base assembly.

NOTES:
 Specifications shown are for Thomson precision series A.
 Two rings are required for each bushing.
 Due to the larger O.D. of the bushing counterbore required, ball bushings usually cannot be installed in standard leader pin locations in the mold base assembly.




* THESE ARE SPECIAL ORDER ITEMS ONLY.

[CONTACT US](#)

DME Small and Shuttle Mold Bases

**High-quality, Economical
Mold Base Assemblies
for Prototype or
Production Runs**




Small and Shuttle Mold Bases

table of contents

<i>Small Mold Base Adapter Plates</i>	200
<i>Custom Adapter Plates</i>	201
<i>56U3 Mold Bases</i>	202
<i>58U2 Mold Bases</i>	203
<i>58U3 Mold Bases</i>	204
<i>68J Mold Base</i>	205
<i>68SH Shuttle Mold Base</i>	206-207
<i>810SH Shuttle Mold Base</i>	208-209
<i>Metric Equivalents & Conversions</i>	210

Small Mold Base Adapter Plates



DME No. 2 Steel

With DME Small Mold Base Adapter Plates You Can...

Lower your mold costs

Only one set of low cost Adapter Plates is required for each injection molding machine. The Adapter Plates can become a permanent part of your press platen...or can easily be removed to allow installation of larger mold bases. The Adapter Plates can also be moved to another press to meet your production requirements. DME Small Mold Bases provide the highest quality, most economical mold base assemblies for either short runs or production runs. Cavity and support plates are made from DME No. 3 cavity steel.

Change mold bases in minutes


With the DME exclusive Adapter Plate System, standard 5"x 6" U and 5"x 8" U Series Mold Bases can be easily changed in 10 minutes or less. Costly machine downtime is reduced to a minimum.

Increase your profits


The DME Adapter Plate System provides economic manufacturing for greater profitability. The unique system lends itself to minimum cavity, high-speed cycle operations. Fast interchangeability of mold bases makes short runs just as profitable as long runs... no costly fill-ins!

DME Adapter Plates are:


- ① Pre-drilled and tapped to match platen holes
- ② Pre-machined with clearance holes for knockout rods
- ③ Pre-drilled and tapped to match mounting holes on DME 5"x 6" U series mold bases... with precision dowels for fast, accurate alignment. (One dowel is off-set to prevent improper installation.)
- ④ Completely machined to accommodate your choice of sprue bushing and locating ring.



Custom Designed Standard Universal Adapter Plates – AP-5658-SET



DME No. 2 Steel



Item Number: AP-5658-SET*

***Consists of:**

ITEM	LENGTH	WIDTH	THICKNESS	NET WT.
(1) 5658S-AP-2 (SPRUE SIDE)	9.875	7.875	.875	20
(1) 5658E-AP-2 (EJECTOR SIDE)	9.875	7.875	.875	20

NOTE: Sprue bushings are supplied with DME Small mold bases. Plates MAY be ordered separately.

5" x 6" U 3-Plate Mold Bases – 56U3

These 3-plate assemblies are designed for use with DME Universal Adapter Plates.

Ejector stroke data



C = (height of riser) = 1.625

S = (max. stroke of ejector bar) = .750



WHEN ORDERING PLEASE SPECIFY:

- Quantity & Item Number
- Type of Sprue Bushing ("U", "UV" or "UR" Series) see DME Sprue Bushings
- O & R Dimensions
 O = .15625, .21875 or .28125
 R = .500 or .750 ("U" Series)
 500 ("UV" Series Standard)
 or .750 ("UV" Series Special)
 No spherical radius on "UR" Series
- Method of Shipment



3-Plate Assembly

A	B	ITEM NUMBER	H	OVERALL ASSEMBLY HEIGHT INCLUDING ADAPTER PLATES	NET WT.
7/8	7/8	56U3-7-7	4 5/8	6 3/8	37
7/8	1 3/8	56U3-7-13	5 1/8	6 7/8	41
7/8	1 7/8	56U3-7-17	5 5/8	7 3/8	46
1 3/8	7/8	56U3-13-7	5 1/8	6 7/8	41
1 3/8	1 3/8	56U3-13-13	5 5/8	7 3/8	46


A	B	ITEM NUMBER	H	OVERALL ASSEMBLY HEIGHT INCLUDING ADAPTER PLATES	NET WT.
1 3/8	1 7/8	56U3-13-17	6 1/8	7 7/8	37
1 7/8	7/8	56U3-17-7	5 5/8	7 3/8	46
1 7/8	1 3/8	56U3-17-13	6 1/8	7 7/8	50
1 3/8	1 7/8	56U3-17-17	6 5/8	8 3/8	54

5" x 8" U 2-Plate Mold Bases – 58U2

These 2 & 3 Plate Assemblies are designed for use with DME Universal Adapter Plates


General Dimensions

O = Small Dia. of Sprue Bushing
 Orifice .15625, .21875 or .28125
R = Spherical Radius of
 Sprue Bushing .500 or .750
 (see item 3 to the right)



WHEN ORDERING PLEASE SPECIFY:

- Quantity & Item Number
- Type of Sprue Bushing ("U", "UV" or "UR" Series) see DME Sprue Bushings
- O & R Dimensions
 O = .15625, .21875 or .28125
 R = .500 or .750 ("U" Series)
 500 ("UV" Series Standard) or .750 ("UV" Series Special)
 No spherical radius on "UR" Series
- Method of Shipment



2-Plate Assembly

A	ITEM NUMBER	H	OVERALL ASSEMBLY HEIGHT INCLUDING ADAPTER PLATES	NET WT.
7/8	58U2-7	3 3/4	5 1/2	37
1 3/8	58U2-13	4 1/4	6	43
1 7/8	58U2-17	4 3/4	6 1/2	49

All 2 & 3-Plate assemblies listed are supplied complete with mounting and locating holes to match DME Universal Adapter Plates, and Standard Sprue Bushing specified. Cavity plates are made from DME No. 3 Steel.


NOTE: For 58U Plates and housings, see Mold Plates section.

5" x 8" U 3-Plate Mold Bases – 58U3


Ejector stroke data

C = (height of riser) = 1.625

S = (max. stroke of ejector bar) = .750



These 3-plate assemblies are designed for use with DME adapter plates.



3-Plate Assembly

A	B	ITEM NUMBER	H	OVERALL ASSEMBLY HEIGHT INCLUDING ADAPTER PLATES	NET WT.
7/8	7/8	58U3-7-7	4 5/8	6 3/8	47
7/8	1 3/8	58U3-7-13	5 1/8	6 7/8	53
7/8	1 7/8	58U3-7-17	5 5/8	7 3/8	58
1 3/8	7/8	58U3-13-7	5 1/8	6 7/8	53
1 3/8	1 3/8	58U3-13-13	5 5/8	7 3/8	58



A	B	ITEM NUMBER	H	OVERALL ASSEMBLY HEIGHT INCLUDING ADAPTER PLATES	NET WT.
1 3/8	1 7/8	58U3-13-17	6 1/8	7 7/8	64
1 7/8	7/8	58U3-17-7	5 5/8	7 3/8	58
1 7/8	1 3/8	58U3-17-13	6 1/8	7 7/8	64
1 3/8	1 7/8	58U3-17-17	6 5/8	8 3/8	70

5 7/8" x 8" J Mold Bases – 68J

Ejector stroke data

C = (height of riser) = 1 5/8

S = (max stroke of ejector bar) = 7/8



ITEM NUMBER	A	B	C	NET WT.
68J-13-13	1 3/8	1 3/8	1 5/8	84

WHEN ORDERING, PLEASE SPECIFY:

1. Quantity
2. Item Number
3. Method of Shipment




CONTACT US

6" x 8" SH Shuttle Mold Bases – 68SH

Engineered and designed for various models of Autojectors, Moslo and Newbury vertical injection presses with shuttle tables.


EJECTOR STROKE DATA

C = (Height of Riser) = 1.25
 S = (Max. Stroke of Ejector Bar) = 0.5




Small and Shuttle Mold Bases | 6" x 8" SH Shuttle Mold Bases

6" x 8" SH Shuttle Mold Bases – 68SH



Shuttle Mold Bases listed below are supplied complete with one upper and two lower sub-assemblies. Upper and lower sub-assemblies are pre-drilled to match platen holes of presses listed in chart. The one piece ejector housings include set screws to securely hold the ejector plates in place during installation or removal.

All plates and housings are made from DME No. 3 Steel (see page 8), except for the ejector and ejector retainer plates.



SERIES	TOP PLATE	A	B	BH	SH	H	S	FITS PRESS*	ITEM NUMBER	NET WT.
2 PLATE	–	2.875	–	3.5	–	6.375	0.5	**AJ-M-N	68SH2-0-27-22-0	124
3 PLATE	1	1.875	–	3.5	–	6.375	0.5	**AJ-M-N	68SH3-10-17-22-0	124
	–	2.875	1.375	–	2.125			**AJ-M-N	68SH3-0-27-13-7	124
4 PLATE	–	1.875	0.875	0.875	–	6.25	0.5	N	68SH4-17-7-7-13	123
	–	1.875	0.875	1.375	–			N	68SH4-17-7-13-7	123
	–	1.375	1.375	0.875	–			N	68SH4-13-13-7-13	123
	–	1.375	1.375	1.375	–	2.125	N	68SH4-13-13-13-7	123	
	1	1.875	0.875	–	2.625	6.375	0.5	**AJ-M-N	68SH4-10-17-7-13	124
	1	1.875	1.375	–	2.125			**AJ-M-N	68SH4-10-17-13-7	124
	1	2	1.375	–	2.125			AJ-N	68SH4-10-20-13-7	126


*AJ = Autojectors

M = Moslo

N = Newbury


NOTE: For 68SH Components, see DME's Mold Components catalog.

**NOTE: Autojector applications with 6.375 H dimension require a 0.125" thick spacer for upper half (check with molder; machine may be equipped with required spacer).



SECTION Z-Z REF.

2-PLATE SERIES – 1 PLATE UPPER HALF
1 PLATE LOWER HALF



ALTERNATIVE UPPER HALF MOUNTING HOLES PROVIDED ONLY WHEN AUTOJECTORS APPLICATION IS SPECIFIED (SEE ITEM 3 BELOW).

WHEN ORDERING, PLEASE SPECIFY:

- Quantity
- Item Number
- Mounting Hole Requirement: Standard or Autojectors
- Method of Shipment

CONTACT US




8" x 9 7/8" SH Shuttle Mold Bases – 810SH

Engineered and designed for various models of Autojectors, Moslo, Newbury, Reed, and Van Dorn vertical injection presses with shuttle tables.

EJECTOR STROKE DATA

C	1.25	1.875
S	0.5	1"


C = Height of Riser.
S = Max. Stroke of Ejector Bar.




Small and Shuttle Mold Bases | 8" x 9 7/8" SH Shuttle Mold Bases

8" x 9⁷/₈" SH Shuttle Mold Bases – 810SH


2-PLATE SERIES



4-PLATE SERIES




Shuttle Mold Bases listed below are supplied complete with one upper and two lower sub-assemblies. Upper and lower sub-assemblies are pre-drilled to match platen holes of presses listed in chart. Solid rails (spacer blocks) extend beyond support or cavity plate for ease of installation in press.



SERIES	TOP PLATE	A	B	SUPP. PLATE	C	H	S	FITS PRESS*	ITEM NUMBER	NET WT.
2 PLATE	—	3.375	3.875	—	1.25	8.5	0.5	** AJ-M-N RD-V	810SH2-0-33-37-0	298
	1	2.375	3.875	—	1.25		0.5		810SH3-10-23-37-0	298
3 PLATE	—	3.375	1.375	1.875	1.875	8.5	1	** AJ-M-N RD-V	810SH3-0-33-13-17	286
	—	3.375	1.875	1.375					810SH3-0-33-17-13	286
	—	3.375	2.375	0.875					810SH3-0-33-23-7	286
	—	3.375	2.375	0.875					810SH3-0-33-23-7	286
4 PLATE	2.375	0.875	0.875	2.375	1.875	8.375	1	N-RD-V	810SH4-23-7-7-23	284
	2.375	0.875	1.375	1.875				N-RD-V	810SH4-23-7-13-17	284
	1.875	1.375	1.375	1.875				N-RD-V	810SH4-17-13-13-17	284
	1.875	1.375	1.875	1.375				N-RD-V	810SH4-17-13-17-13	284
	1.875	1.375	2.375	0.875				N-RD-V	810SH4-17-13-23-7	284
	1.375	1.875	1.875	1.375				N-RD-V	810SH4-13-17-17-13	284
	1	2.375	1.375	1.875		8.5	1	** AJ-M N-RD-V	810SH4-10-23-13-17	286
	1	2.375	1.875	1.375					810SH4-10-23-17-13	286
	1	2.375	1.875	1.375					810SH4-10-23-17-13	286
	1	2.375	2.375	0.875					810SH4-10-23-23-7	286

*AJ = Autojectors M = Moslo N = Newbury RD = Reed V = Van Dorn

** NOTE: All Autojector applications require a 0.5" thick spacer for upper half (check with molder; machine may be equipped with required spacer).



SECTION Z-Z REF.
2-PLATE SERIES – 1 PLATE UPPER HALF
1 PLATE LOWER HALF

AVAILABLE IN:

- DME No. 1 or No. 3 Steel

NO. 3 STEEL ASSEMBLY

- "A" and "B" Plate - No. 3 Steel
- Top & Support Plates - No. 2 Steel

WHEN ORDERING, PLEASE SPECIFY:

1. Quantity & Item Number
2. No. 1 or No. 3 Steel
3. Method of Shipment

[CONTACT US](#)

Metric Equivalents and Conversions

Equivalents: Inch, fraction, decimal, millimeter

INCHES	MILLIMETERS	INCHES	MILLIMETERS
1	25.4	34	863.6
2	50.8	35	889.0
3	76.2	36	914.4
4	101.6	37	939.8
5	127.0	38	965.2
6	152.4	39	990.6
7	177.8	40	1016.0
8	203.2	41	1041.4
9	228.6	42	1066.8
10	254.0	43	1092.2
11	279.4	44	1117.6
12	304.8	45	1143.0
13	330.2	46	1168.4
14	355.6	47	1193.8
15	381.0	48	1219.2
16	406.4	49	1244.6
17	431.8	50	1270.0
18	457.2	51	1295.4
19	482.6	52	1320.8
20	508.0	53	1346.2
21	533.4	54	1371.6
22	558.8	55	1397.0
23	584.2	56	1422.4
24	609.6	57	1447.8
25	635.0	58	1473.2
26	660.4	59	1498.6
27	685.8	60	1524.0
28	711.2	61	1549.4
29	736.6	62	1574.8
30	762.0	63	1600.2
31	787.4	64	1625.6
32	812.8	65	1651.0
33	838.2	66	1676.4

INCHES		MILLIMETERS		INCHES		MILLIMETERS	
1/64	0.015625	0.396875	33/64	0.515625	13.096875		
1/32	0.031250	0.793750	17/32	0.531250	13.493750		
3/64	0.046875	1.190625	35/64	0.546875	13.890625		
1/16	0.062500	1.587500	9/16	0.562500	14.287500		
5/64	0.078125	1.984375	37/64	0.578125	14.684375		
3/32	0.093750	2.381250	19/32	0.593750	15.081250		
7/64	0.109375	2.778125	39/64	0.609375	15.478125		
1/8	0.125000	3.175000	5/8	0.625000	15.875000		
9/64	0.140625	3.571875	41/64	0.640625	16.271875		
5/32	0.156250	3.968750	21/32	0.656250	16.668750		
11/64	0.171875	4.365625	43/64	0.671875	17.065625		
3/16	0.187500	4.762500	11/16	0.687500	17.462500		
13/64	0.203125	5.159375	45/64	0.703125	17.859375		
7/32	0.218750	5.556250	23/32	0.718750	18.256250		
15/64	0.234375	5.953125	47/64	0.734375	18.653125		
1/4	0.250000	6.350000	3/4	0.750000	19.050000		
17/64	0.265625	6.746875	49/64	0.765625	19.446875		
9/32	0.281250	7.143750	25/32	0.781250	19.843750		
19/64	0.296875	7.540625	51/64	0.796875	20.240625		
5/16	0.312500	7.937500	13/16	0.812500	20.637500		
21/64	0.328125	8.334375	53/64	0.828125	21.034375		
11/32	0.343750	8.731250	27/32	0.843750	21.431250		
23/64	0.359375	9.128125	55/64	0.859375	21.828125		
3/8	0.375000	9.525000	7/8	0.875000	22.225000		
25/64	0.390625	9.921875	57/64	0.890625	22.621875		
13/32	0.406250	10.318750	29/32	0.906250	23.018750		
27/64	0.421875	10.715625	59/64	0.921875	23.415625		
7/16	0.437500	11.112500	15/16	0.937500	23.812500		
29/64	0.453125	11.509375	61/64	0.953125	24.209375		
15/32	0.468750	11.906250	31/32	0.968750	24.606250		
31/64	0.484375	12.303125	63/64	0.984375	25.003125		
1/2	0.500000	12.700000	1	1.000000	25.400000		


Small and Shuttle Mold Bases | Metric Equivalents and Conversions

Equivalents: Decimal, millimeter

INCHES	MILLIMETERS	INCHES	MILLIMETERS	INCHES	MILLIMETERS
0.001	0.0254	0.01	0.254	0.1	2.54
0.002	0.0508	0.02	0.508	0.2	5.08
0.003	0.0762	0.03	0.762	0.3	7.62
0.004	0.1016	0.04	1.016	0.4	10.16
0.005	0.1270	0.05	1.270	0.5	12.70
0.006	0.1524	0.06	1.524	0.6	15.24
0.007	0.1778	0.07	1.778	0.7	17.78
0.008	0.2032	0.08	2.032	0.8	20.32
0.009	0.2286	0.09	2.286	0.9	22.86

Measurement conversions

MULTIPLY BY	FROM	TO	MULTIPLY BY
0.03937	inch	millimeter	25.4
0.0016	inch ²	millimeter ²	645.16
0.061	inch ³	centimeter ³	16.3871
0.2642	gallon (U.S.)	liter	3.7854
0.03527	oz. (avdp.)	gram	28.3495
2.2044	pound	kilogram	0.4536
62.43	lbs/ft ³	g/cm ³	0.0160
0.145	psi	kPa	6.8948
14.2247	psi	kg/cm ²	0.0703
1.8°C + 32	°F	°C	(°F-32)/1.8



[DME MoldBasics™ Mold Bases](#)

**ECONOMICAL MOLD BASES
STOCKED FOR
IMMEDIATE DELIVERY**



MoldBasics™ Mold Bases



Features and Applications

Low Cost

Simple Construction

Broad Range of Sizes


Immediate Availability

DME new MoldBasics® mold bases are ideal for a variety of applications, including prototype molding and short-runs. Any project that requires a mold base with fewer standard features and a dramatically lower cost is perfect for the MoldBasics series. With MoldBasics, you'll have the flexibility to perform more value-added work and reduce the mold base cost significantly.

You can count on the MoldBasics series to deliver reliable, trouble-free performance. And our knowledgeable customer service representatives can help you select the mold base that's just right for your application.

The MoldBasics series mold bases ship the day your order is received – to help you meet critical deadlines. Like all DME products, your satisfaction is guaranteed with all MoldBasics series mold bases.


Features



Features

The DME MoldBasics series is available in-stock in a range of popular sizes. This stocking program ensures rapid delivery.

To simplify ordering, this brochure provides key MoldBasics dimensions in nominal sizes from 7.875" x 7.875" up to 15.875" x 23.500". The drawings below provide specific definition of the variables referenced in the product dimension tables. Standard features of the MoldBasics series are also illustrated below.



* For all 9.875 x 8.000 mold bases, dimension is 3/4"
 ** For all 7.875 x 7.875 and 7.875 x 11.875 mold bases, dimension is 1/2"

Mold Base Product Line

DME MoldBasics mold bases are available in a wide range of sizes. To meet the needs of a variety of applications, all sizes are available in both #1 and #2 steel.

No.1 Steel

DME MoldBasics #1 steel is a medium-carbon (AISI 1045), silicon-killed forging quality steel with approximately 25% greater tensile strength than typical low-carbon warehouse steels. It machines easily, but isn't "sticky," permitting a faster and smoother cut.

No.2 Steel

DME MoldBasics #2 steel is an AISI 4140-type steel. It is supplied pre-heat-treated to 28-34 Rc (269-321 Bhn). A high-strength steel, it is ideal for cavity and core retainer plates, clamping plates, and support plates in molds and dies.

Thickness of

A Plate	07	13	17	23	27
B Plate	07	13	17	23	27
0808	◆	◆	◆	◆	
0812	◆	◆	◆	◆	
1008	◆	◆	◆	◆	
1012	◆	◆	◆	◆	
1016	◆	◆	◆	◆	
1020		◆	◆	◆	
1112		◆	◆	◆	
1114		◆	◆	◆	
1118		◆	◆	◆	
1212		◆	◆	◆	◆
1215		◆	◆	◆	◆
1220		◆	◆	◆	◆
1315		◆	◆	◆	◆
1318		◆	◆	◆	◆
1321			◆	◆	◆
1323			◆	◆	◆
1518			◆	◆	◆
1524			◆	◆	◆
1616				◆	◆
1620				◆	◆
1623				◆	◆




Item Numbering

	MBA	9999	- 99	- 99	- 9						
Prefix	MBA — “MB” for MoldBasics, “A” for A Series										
Nominal Size	Four numbers for nominal size. No space after prefix. Note that single-digit nominal sizes begin with a zero (e.g. “0808” for 8" x 8")										
"A" Plate Thickness	Two numbers for plate thickness. Note that single-digit thicknesses begin with a zero (e.g. “07” for 7/8")										
"B" Plate Thickness	Two numbers for plate thickness. Note that single-digit thicknesses begin with a zero (e.g. “07” for 7/8")										
Steel Type	“1” for DME MoldBasics #1 Steel, “2” for DME MoldBasics #2 Steel										
Examples	<table border="0"> <tr> <td>MBA1008-07-07-2</td> <td>9.875" x 8.000" mold base with 0.875" A plate and 0.875" B plate of #2 steel.</td> </tr> <tr> <td>MBA0808-17-17-1</td> <td>7.875" x 7.875" mold base with 1.875" A plate and 1.875" B plate of #1 steel.</td> </tr> <tr> <td>MBA1623-27-27-2</td> <td>15.875" x 23.500" mold base with 2.875" A plate and 2.875" B plate of #2 steel.</td> </tr> </table>					MBA1008-07-07-2	9.875" x 8.000" mold base with 0.875" A plate and 0.875" B plate of #2 steel.	MBA0808-17-17-1	7.875" x 7.875" mold base with 1.875" A plate and 1.875" B plate of #1 steel.	MBA1623-27-27-2	15.875" x 23.500" mold base with 2.875" A plate and 2.875" B plate of #2 steel.
MBA1008-07-07-2	9.875" x 8.000" mold base with 0.875" A plate and 0.875" B plate of #2 steel.										
MBA0808-17-17-1	7.875" x 7.875" mold base with 1.875" A plate and 1.875" B plate of #1 steel.										
MBA1623-27-27-2	15.875" x 23.500" mold base with 2.875" A plate and 2.875" B plate of #2 steel.										


MoldBasicsTM

Product Selection Tables

Mold Basics



Variables

Below is a list of the variables for the MoldBasics series mold bases and their definitions

- W** = Width
- L** = Length
- CP** = Top clamp plate thickness
- A** = A plate thickness
- B** = B plate thickness
- SU** = Support plate thickness
- C** = Height of the riser
- S** = Maximum stroke of the ejector bar
- H** = Mold base height
- EB** = Ejector bar thickness
- ER** = Ejector retainer thickness
- P** = Housing riser thickness
- RPx** = Return pin location on the X axis (3 places)
- RPy** = Return pin location on the Y axis (4 places)
- RPoS** = Return pin offset on the X axis (1 place)
- RPg** = Return pin diameter
- LPg** = Leader pin diameter

7.875 x 7.875

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA0808-07-07	7.875	7.875	0.875	0.875	2.500	0.813	7.375	111
MBA0808-13-13	7.875	7.875	1.375	1.375	2.500	0.813	8.375	129
MBA0808-17-17	7.875	7.875	1.875	1.875	2.500	0.813	9.375	147
MBA0808-23-23	7.875	7.875	2.375	2.375	3.000	1.313	10.875	167

ALL ITEMS	W	7.875	EB	1.000	P	1.250	TCP	0.875	RPx	3.313	RPg	0.500
	L	7.875	ER	0.500	SU	1.375	RPoS	3.188	RPy	1.500	LPg	0.750

7.875 x 11.875

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA0812-07-07	7.875	11.875	0.875	0.875	2.500	0.813	7.875	174
MBA0812-13-13	7.875	11.875	1.375	1.375	3.000	1.313	8.875	205
MBA0812-17-17	7.875	11.875	1.875	1.875	3.500	1.813	10.375	235
MBA0812-23-23	7.875	11.875	2.375	2.375	3.500	1.813	11.375	262

ALL ITEMS	W	7.875	EB	1.000	P	1.250	TCP	0.875	RPx	5.313	RPg	0.500
	L	11.875	ER	0.500	SU	1.375	RPoS	5.188	RPy	1.500	LPg	0.750

9.875 x 8.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1008-07-07	9.875	8.000	0.875	0.875	2.500	0.813	7.875	158
MBA1008-13-13	9.875	8.000	1.375	1.375	2.500	0.813	8.875	181
MBA1008-17-17	9.875	8.000	1.875	1.875	3.500	1.813	10.875	209
MBA1008-23-23	9.875	8.000	2.375	2.375	3.500	1.813	11.875	232

ALL ITEMS	W	9.875	EB	1.000	P	1.438	TCP	0.875	RPx	3.250	RPg	0.625
	L	8.000	ER	0.500	SU	1.875	RPoS	3.125	RPy	2.250	LPg	0.750

9.875 x 11.875

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1012-07-07	9.875	11.875	0.875	0.875	2.500	0.813	7.875	235
MBA1012-13-13	9.875	11.875	1.375	1.375	3.000	1.313	9.375	273
MBA1012-17-17	9.875	11.875	1.875	1.875	3.500	1.813	10.875	311
MBA1012-23-23	9.875	11.875	2.375	2.375	3.500	1.813	11.875	344

ALL ITEMS	W	9.875	EB	1.000	P	1.438	TCP	0.875	RPx	5.188	RPg	0.625
	L	11.875	ER	0.500	SU	1.875	RPoS	5.063	RPy	2.250	LPg	0.875


9.875 x 16.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1016-07-07	9.875	16.000	0.875	0.875	2.500	0.813	7.875	316
MBA1016-13-13	9.875	16.000	1.375	1.375	3.000	1.313	9.375	367
MBA1016-17-17	9.875	16.000	1.875	1.875	3.500	1.813	10.875	418
MBA1016-23-23	9.875	16.000	2.375	2.375	3.500	1.813	11.875	463

ALL ITEMS	W	9.875	EB	1.000	P	1.438	TCP	0.875	RPx	7.250	RPg	0.625
	L	16.000	ER	0.500	SU	1.875	RPoS	7.125	RPy	2.250	LPg	0.875

Product Selection Tables

Mold Basics



9.875 x 20.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1020-13-13	9.875	20.000	1.375	1.375	3.000	1.313	9.375	459
MBA1020-17-17	9.875	20.000	1.875	1.875	3.500	1.813	10.875	523
MBA1020-23-23	9.875	20.000	2.375	2.375	3.500	1.813	11.875	579

ALL ITEMS	W	9.875	EB	1.000	P	1.438	TCP	0.875	RPx	9.250	RPg	0.625
	L	20.000	ER	0.500	SU	1.875	RPos	9.125	RPy	2.250	LPg	0.875

10.875 x 12.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1112-13-13	10.875	12.000	1.375	1.375	3.000	1.313	9.375	305
MBA1112-17-17	10.875	12.000	1.875	1.875	3.500	1.813	10.875	347
MBA1112-23-23	10.875	12.000	2.375	2.375	3.500	1.813	11.875	384

ALL ITEMS	W	10.875	EB	1.000	P	1.688	TCP	0.875	RPx	5.250	RPg	0.625
	L	12.000	ER	0.500	SU	1.875	RPos	5.125	RPy	2.813	LPg	0.875

10.875 x 14.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1114-13-13	10.875	14.000	1.375	1.375	3.000	1.313	9.375	355
MBA1114-17-17	10.875	14.000	1.875	1.875	3.500	1.813	10.875	405
MBA1114-23-23	10.875	14.000	2.375	2.375	3.500	1.813	11.875	448

ALL ITEMS	W	10.875	EB	1.000	P	1.688	TCP	0.875	RPx	6.250	RPg	0.625
	L	14.000	ER	0.500	SU	1.875	RPos	6.125	RPy	2.813	LPg	0.875

10.875 x 18.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1118-13-13	10.875	18.000	1.375	1.375	3.000	1.313	9.375	457
MBA1118-17-17	10.875	18.000	1.875	1.875	3.500	1.813	10.875	521
MBA1118-23-23	10.875	18.000	2.375	2.375	3.500	1.813	11.875	576

ALL ITEMS	W	10.875	EB	1.000	P	1.688	TCP	0.875	RPx	8.250	RPg	0.625
	L	18.000	ER	0.500	SU	1.875	RPos	8.125	RPy	2.813	LPg	0.875


11.875 x 12.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1212-13-13	11.875	12.000	1.375	1.375	3.000	1.188	9.375	335
MBA1212-17-17	11.875	12.000	1.875	1.875	3.000	1.188	10.375	375
MBA1212-23-23	11.875	12.000	2.375	2.375	3.500	1.688	11.875	422
MBA1212-27-27	11.875	12.000	2.875	2.875	4.000	2.188	13.375	468

ALL ITEMS	W	11.875	EB	1.125	P	1.688	TCP	0.875	RPx	5.125	RPg	0.750
	L	12.000	ER	0.500	SU	1.875	RPos	5.000	RPy	3.188	LPg	1.000

Product Selection Tables

Mold Basics



Variables

Below is a list of the variables for the MoldBasics series mold bases and their definitions

- W** = Width
- L** = Length
- CP** = Top clamp plate thickness
- A** = A plate thickness
- B** = B plate thickness
- SU** = Support plate thickness
- C** = Height of the riser
- S** = Maximum stroke of the ejector bar
- H** = Mold base height
- EB** = Ejector bar thickness
- ER** = Ejector retainer thickness
- P** = Housing riser thickness
- RPx** = Return pin location on the X axis (3 places)
- RPy** = Return pin location on the Y axis (4 places)
- RPoS** = Return pin offset on the X axis (1 place)
- RPg** = Return pin diameter
- LPg** = Leader pin diameter

11.875 x 15.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1215-13-13	11.875	15.000	1.375	1.375	3.000	1.188	9.375	419
MBA1215-17-17	11.875	15.000	1.875	1.875	3.000	1.188	10.375	469
MBA1215-23-23	11.875	15.000	2.375	2.375	3.500	1.688	11.875	527
MBA1215-27-27	11.875	15.000	2.875	2.875	4.000	2.188	13.375	584

ALL ITEMS	W	11.875	EB	1.125	P	1.688	TCP	0.875	RPx	6.625	RPg	0.750
	L	15.000	ER	0.500	SU	1.875	RPOs	6.500	RPy	3.188	LPg	1.000

11.875 x 20.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1220-13-13	11.875	20.000	1.375	1.375	3.000	1.188	9.375	558
MBA1220-17-17	11.875	20.000	1.875	1.875	3.000	1.188	10.375	625
MBA1220-23-23	11.875	20.000	2.375	2.375	3.500	1.688	11.875	702
MBA1220-27-27	11.875	20.000	2.875	2.875	4.000	2.188	13.375	779

ALL ITEMS	W	11.875	EB	1.125	P	1.688	TCP	0.875	RPx	9.125	RPg	0.750
	L	20.000	ER	0.500	SU	1.875	RPOs	9.000	RPy	3.188	LPg	1.000

13.375 x 15.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1315-13-13	13.375	15.000	1.375	1.375	3.000	1.063	9.875	505
MBA1315-17-17	13.375	15.000	1.875	1.875	3.000	1.063	10.875	562
MBA1315-23-23	13.375	15.000	2.375	2.375	3.500	1.563	12.375	627
MBA1315-27-27	13.375	15.000	2.875	2.875	4.000	2.063	13.875	692

ALL ITEMS	W	13.375	EB	1.125	P	1.875	TCP	1.375	RPx	6.625	RPg	0.750
	L	15.000	ER	0.625	SU	1.875	RPOs	6.500	RPy	3.813	LPg	1.000

13.375 x 18.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1318-13-13	13.375	18.000	1.375	1.375	3.000	1.063	9.875	606
MBA1318-17-17	13.375	18.000	1.875	1.875	3.000	1.063	10.875	675
MBA1318-23-23	13.375	18.000	2.375	2.375	3.500	1.563	12.375	752
MBA1318-27-27	13.375	18.000	2.875	2.875	4.000	2.063	13.875	830

ALL ITEMS	W	13.375	EB	1.125	P	1.875	TCP	1.375	RPx	8.125	RPg	0.750
	L	18.000	ER	0.625	SU	1.875	RPOs	8.000	RPy	3.813	LPg	1.000


13.375 x 20.750

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1321-17-17	13.375	20.750	1.875	1.875	3.000	1.063	10.875	777
MBA1321-23-23	13.375	20.750	2.375	2.375	3.500	1.563	12.375	867
MBA1321-27-27	13.375	20.750	2.875	2.875	4.000	2.063	13.875	957

ALL ITEMS	W	13.375	EB	1.125	P	1.875	TCP	1.375	RPx	9.500	RPg	0.750
	L	20.750	ER	0.625	SU	1.875	RPOs	9.375	RPy	3.813	LPg	1.000

Product Selection Tables

Mold Basics



13.375 x 23.500

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1323-17-17	13.375	23.500	1.875	1.875	3.000	1.063	10.875	881
MBA1323-23-23	13.375	23.500	2.375	2.375	3.500	1.563	12.375	982
MBA1323-27-27	13.375	23.500	2.875	2.875	4.000	2.063	13.875	1084

ALL ITEMS	W	L	EB	ER	P	SU	TCP	RPx	RPy	RPg	LPg
	13.375	23.500	1.125	0.625	1.875	1.875	1.375	10.875	3.813	0.750	1.000

14.875 x 17.875

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1518-17-17	14.875	17.875	1.875	1.875	3.500	1.563	11.875	790
MBA1518-23-23	14.875	17.875	2.375	2.375	3.500	1.563	12.875	865
MBA1518-27-27	14.875	17.875	2.875	2.875	4.000	2.063	14.375	950

ALL ITEMS	W	L	EB	ER	P	SU	TCP	RPx	RPy	RPg	LPg
	14.875	17.875	1.125	0.625	1.875	2.375	1.375	8.063	3.875	0.750	1.250

14.875 x 23.750

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1524-17-17	14.875	23.750	1.875	1.875	3.500	1.563	11.875	1050
MBA1524-23-23	14.875	23.750	2.375	2.375	3.500	1.563	12.875	1150
MBA1524-27-27	14.875	23.750	2.875	2.875	4.000	2.063	14.375	1262

ALL ITEMS	W	L	EB	ER	P	SU	TCP	RPx	RPy	RPg	LPg
	14.875	23.750	1.125	0.625	1.875	2.375	1.375	11.000	3.875	0.750	1.250

15.875 x 16.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1616-23-23	15.875	16.000	2.375	2.375	3.500	1.563	12.875	825
MBA1616-27-27	15.875	16.000	2.875	2.875	4.000	2.063	14.375	906

ALL ITEMS	W	L	EB	ER	P	SU	TCP	RPx	RPy	RPg	LPg
	15.875	16.000	1.125	0.625	1.875	2.375	1.375	7.125	4.375	0.750	1.250

15.875 x 20.000

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1620-23-23	15.875	20.000	2.375	2.375	3.500	1.563	12.875	1031
MBA1620-27-27	15.875	20.000	2.875	2.875	4.000	2.063	14.375	1132

ALL ITEMS	W	L	EB	ER	P	SU	TCP	RPx	RPy	RPg	LPg
	15.875	20.000	1.125	0.625	1.875	2.375	1.375	9.125	4.375	0.750	1.250

15.875 x 23.500

ITEM NUMBER	W	L	A	B	C	S	H	WEIGHT (LBS)
MBA1623-23-23	15.875	23.500	2.375	2.375	3.500	1.563	12.875	1212
MBA1623-27-27	15.875	23.500	2.875	2.875	4.000	2.063	14.375	1330


ALL ITEMS	W	L	EB	ER	P	SU	TCP	RPx	RPy	RPg	LPg
	15.875	23.500	1.125	0.625	1.875	2.375	1.375	10.875	4.375	0.750	1.250

Value-Added MoldBasics






Stocked for immediate shipment, the DME line of MoldBasics mold bases is ideal for prototyp molding and short runs. Available in-stock in a range of popular sizes, MoldBasics has few standard features and a much lower cost.

MoldBasics mold bases ship the day your order is received to help meet your critical deadlines. Like all DME products, MoldBasics mold bases are delivered with your satisfaction guaranteed.



DME Cavity Retainer Sets

Cavity Retainer Sets
That Match Your
Application
Requirements



TWO-PLATE
THREE-PLATE

CAVITY
RETAINER
SETS

Steel Information

Two and Three-Plate Cavity Retainer Sets offer accurate alignment and complete interchangeability

DME Standard Cavity Retainer Sets are available in 49 standard sizes from 6" × 10⁷/₈" to 23³/₄" × 35¹/₂". Each size is offered in various cavity plate thickness combinations in your choice of DME No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 available up to 2⁷/₈" thick standard). DME's precision-built interchangeable construction makes possible the wide variety of two-plate combinations as well as the three-plate construction.



DME No. 1 Steel

DME No. 1 Steel is a medium carbon (SAE 1030), silicon-killed forging quality steel with approximately 25% greater tensile strength than typical low-carbon warehouse steels. It machines easily, but is not "sticky," permitting a faster and smoother cut.

DME No. 2 Steel

DME No. 2 Steel is an AISI 4130 type steel. It is supplied pre-heat treated to 271-321 Bhn (28-34 HRC). A high strength steel, it is ideal for cavity and core retainer plates, clamping plates and support plates in molds and dies.

DME No. 3 Steel

DME No. 3 Steel is a P-20 AISI 4130 (modified) type cavity steel. Exceptionally clean, it is pre-heat treated to 271-321 Bhn (28-34 HRC). It provides high hardness, good machinability and exceptional polishability.

DME No. 7 Steel

No. 7 Steel is a modified AISI 400 series stainless steel for holder block applications. It is supplied pre-hardened to 32-36 HRC (302-340 Bhn). This stainless steel offers corrosion resistance and exceptional machinability but cannot be further hardened (see DME No. 6). For humid environments, corrosive plastics, "clean room" or "100% stainless" applications, it is an ideal choice for all structural (non-cavity/core) mold plates.

CONTACT US

Three-Plate Cavity Retainer Sets

Cavity Retainer Sets – 6" x 10^{7/8}

THREE-PLATE CAVITY RETAINER SETS

When "Three-plate" Cavity Sets are ordered the following information should be specified:

Width and length of Cavity Set, thicknesses of "A", "X-1" and "B" plates, length of leader pins and type of steel required.


To determine the price:

Take the price of the same size Standard Cavity Retainer Set having identical "A" and "B" Plate Thicknesses... PLUS...

½ the price of a Cavity Set with "A" and "B" plates each the same thickness as the "X-1" Plate.

For quotations on assemblies with more than one floating plate, contact DME.

CONTACT US




CAVITY RETAINER SETS— 6" x 10^{7/8}

A	B	6" (W) x 10 ^{7/8} (L)	
		ITEM NUMBER	NET WT.
7/8	7/8	611-7-7	33
	1 3/8	611-7-13	42
	1 7/8	611-7-17	51
	2 3/8	611-7-23	61
	2 7/8	611-7-27	70
1 3/8	3 3/8	611-7-33	79
	7/8	611-13-7	42
	1 3/8	611-13-13	51
	1 7/8	611-13-17	61
	2 3/8	611-13-23	70
1 7/8	2 7/8	611-13-27	79
	3 3/8	611-13-33	88
	7/8	611-17-7	51
	1 3/8	611-17-13	61
	1 7/8	611-17-17	70
1 7/8	2 3/8	611-17-23	79
	2 7/8	611-17-27	88
	3 3/8	611-17-33	98



This 6" x 10^{7/8} Cavity Set is designed for use in the Stokes Model 800 Compression Press.



WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel
(No. 7 Steel available standard only for plates up to and including 2^{7/8} thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

SPECIAL ORDER SIZES: Please contact DME.

CONTACT US

Cavity Retainer Sets

$8\frac{15}{16}$ or $9" \times 11\frac{7}{8}$, $9\frac{7}{8} \times 7\frac{7}{8}$


CAVITY RETAINER SETS



A	B	$8\frac{15}{16}$ OR $9" \times 11\frac{7}{8}$		
		ITEM NUMBER $8\frac{15}{16}$	ITEM NUMBER $9"$	NET WT.
$7\frac{7}{8}$	$\frac{7}{8}$	912-7-7V	912-7-7M	53
	$1\frac{1}{8}$	912-7-13V	912-7-13M	69
	$1\frac{7}{8}$	912-7-17V	912-7-17M	84
	$2\frac{3}{8}$	912-7-23V	912-7-23M	99
	$2\frac{7}{8}$	—	912-7-27M	114
	$3\frac{3}{8}$	—	912-7-33M	129
$1\frac{3}{8}$	$\frac{7}{8}$	912-13-7V	912-13-7M	69
	$1\frac{1}{8}$	912-13-13V	912-13-13M	84
	$1\frac{7}{8}$	912-1317V	912-13-17M	99
	$2\frac{3}{8}$	—	912-13-23M	114
	$2\frac{7}{8}$	—	912-13-27M	129
	$3\frac{3}{8}$	—	912-13-33M	144
$1\frac{7}{8}$	$\frac{7}{8}$	912-17-7V	912-17-7M	84
	$1\frac{1}{8}$	912-17-13V	912-17-13M	99
	$1\frac{7}{8}$	—	912-17-17M	114
	$2\frac{3}{8}$	—	912-17-23M	129
	$2\frac{7}{8}$	—	912-17-27M	144
	$3\frac{3}{8}$	—	912-17-33M	159

A	B	$9" \times 11\frac{7}{8}$	
		ITEM NUMBER	NET WT.
$2\frac{3}{8}$	$\frac{7}{8}$	912-23-7M	99
	$1\frac{1}{8}$	912-23-13M	114
	$1\frac{7}{8}$	912-23-17M	129
	$2\frac{3}{8}$	912-23-23M	144
	$2\frac{7}{8}$	912-23-27M	159
	$3\frac{3}{8}$	912-23-33M	175
$2\frac{7}{8}$	$\frac{7}{8}$	912-27-7M	114
	$1\frac{1}{8}$	912-27-13M	129
	$1\frac{7}{8}$	912-27-17M	144
	$2\frac{3}{8}$	912-27-23M	159
	$2\frac{7}{8}$	912-27-27M	175
	$3\frac{3}{8}$	912-27-33M	190
$3\frac{3}{8}$	$\frac{7}{8}$	912-33-7M	129
	$1\frac{1}{8}$	912-33-13M	144
	$1\frac{7}{8}$	912-33-17M	159
	$2\frac{3}{8}$	912-33-23M	175
	$2\frac{7}{8}$	912-33-27M	190
	$3\frac{3}{8}$	912-33-33M	205


$8\frac{15}{16}$ or $9" \times 11\frac{7}{8}$



These $8\frac{15}{16}$ or $9" \times 11\frac{7}{8}$ cavity retainer sets are designed for use with 912V and 912M Mold Bases.

A	B	$9\frac{7}{8} \times 7\frac{7}{8}$	
		ITEM NUMBER	NET WT.
$7\frac{7}{8}$	$\frac{7}{8}$	108R-7-7	39
	$1\frac{1}{8}$	108R-7-13	50
	$1\frac{7}{8}$	108R-7-17	61
	$2\frac{3}{8}$	108R-7-23	72
$1\frac{3}{8}$	$\frac{7}{8}$	108R-13-7	50
	$1\frac{1}{8}$	108R-13-13	61
	$1\frac{7}{8}$	108R-13-17	72
$1\frac{7}{8}$	$\frac{7}{8}$	108R-17-7	61
	$1\frac{1}{8}$	108R-17-13	72

$9\frac{7}{8} \times 7\frac{7}{8}$



These $9\frac{7}{8} \times 7\frac{7}{8}$ cavity retainer sets are designed for use with 108R Mold bases.

Thickness of each plate is finish ground $\pm .001"$. Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel
(No. 7 Steel available standard only for plates up to and including $2\frac{7}{8}$ thick)
- L Dimension (Guide Pin Length)
- Method of Shipment



SPECIAL ORDER SIZES: Please contact DME.

[CONTACT US](#)

Cavity Retainer Sets

7 7/8 x 7 7/8 and 7 7/8 x 11 7/8

Cavity Retainer Sets



A	B	ITEM NUMBER	NET WT.
7/8	7/8	88-7-7	31
	1 1/8	88-7-13	40
	1 3/8	88-7-17	49
	2 1/8	88-7-23	58
	2 3/8	88-7-27	66
	3 1/8	88-7-33	75
	3 3/8	88-7-37	84
	4 1/8	88-7-47	102
	5 1/8	88-7-57	119
1 3/8	7/8	88-13-7	40
	1 1/8	88-13-13	49
	1 3/8	88-13-17	58
	2 1/8	88-13-23	66
	2 3/8	88-13-27	75
	3 1/8	88-13-33	84
	3 3/8	88-13-37	93
	4 1/8	88-13-47	110
	5 1/8	88-13-57	128
1 7/8	7/8	88-17-7	49
	1 1/8	88-17-13	58
	1 3/8	88-17-17	66
	2 1/8	88-17-23	75
	2 3/8	88-17-27	84
	3 1/8	88-17-33	93
	3 3/8	88-17-37	102
	4 1/8	88-17-47	119
	5 1/8	88-17-57	137
2 3/8	7/8	88-23-7	58
	1 1/8	88-23-13	66
	1 3/8	88-23-17	75
	2 1/8	88-23-23	84
	2 3/8	88-23-27	93
	3 1/8	88-23-33	102
	3 3/8	88-23-37	110
	4 1/8	88-23-47	128
	5 1/8	88-23-57	145
2 7/8	7/8	88-27-7	66
	1 1/8	88-27-13	75
	1 3/8	88-27-17	84
	2 1/8	88-27-23	93
	2 3/8	88-27-27	102
	3 1/8	88-27-33	110
	3 3/8	88-27-37	119
	4 1/8	88-27-47	137
	5 1/8	88-27-57	154

A	B	ITEM NUMBER	NET WT.
3 3/8	7/8	88-33-7	75
	1 1/8	88-33-13	84
	1 3/8	88-33-17	93
	2 1/8	88-33-23	102
	2 3/8	88-33-27	110
	3 1/8	88-33-33	119
	3 3/8	88-33-37	128
	4 1/8	88-33-47	145
	5 1/8	88-33-57	163
3 7/8	7/8	88-37-7	84
	1 1/8	88-37-13	93
	1 3/8	88-37-17	102
	2 1/8	88-37-23	110
	2 3/8	88-37-27	119
	3 1/8	88-37-33	128
	3 3/8	88-37-37	137
	4 1/8	88-37-47	154
	5 1/8	88-37-57	172
4 7/8	7/8	88-47-7	102
	1 1/8	88-47-13	110
	1 3/8	88-47-17	119
	2 1/8	88-47-23	128
	2 3/8	88-47-27	137
	3 1/8	88-47-33	145
	3 3/8	88-47-37	154
	4 1/8	88-47-47	172
	5 1/8	88-47-57	189
5 7/8	7/8	88-57-7	119
	1 1/8	88-57-13	128
	1 3/8	88-57-17	137
	2 1/8	88-57-23	145
	2 3/8	88-57-27	154
	3 1/8	88-57-33	163
	3 3/8	88-57-37	172
	4 1/8	88-57-47	189
	5 1/8	88-57-57	207

A	B	ITEM NUMBER	NET WT.
7/8	7/8	812-7-7	48
	1 1/8	812-7-13	61
	1 3/8	812-7-17	74
	2 1/8	812-7-23	87
	2 3/8	812-7-27	100
	3 1/8	812-7-33	113
	3 3/8	812-7-37	126
	4 1/8	812-7-47	153
	5 1/8	812-7-57	179
1 3/8	7/8	812-13-7	61
	1 1/8	812-13-13	74
	1 3/8	812-13-17	87
	2 1/8	812-13-23	100
	2 3/8	812-13-27	113
	3 1/8	812-13-33	126
	3 3/8	812-13-37	139
	4 1/8	812-13-47	166
	5 1/8	812-13-57	192
1 7/8	7/8	812-17-7	74
	1 1/8	812-17-13	87
	1 3/8	812-17-17	100
	2 1/8	812-17-23	113
	2 3/8	812-17-27	126
	3 1/8	812-17-33	139
	3 3/8	812-17-37	152
	4 1/8	812-17-47	179
	5 1/8	812-17-57	205
2 3/8	7/8	812-23-7	87
	1 1/8	812-23-13	100
	1 3/8	812-23-17	113
	2 1/8	812-23-23	126
	2 3/8	812-23-27	139
	3 1/8	812-23-33	152
	3 3/8	812-23-37	165
	4 1/8	812-23-47	192
	5 1/8	812-23-57	218

A	B	ITEM NUMBER	NET WT.
2 7/8	7/8	812-27-7	100
	1 1/8	812-27-13	113
	1 3/8	812-27-17	126
	2 1/8	812-27-23	139
	2 3/8	812-27-27	152
	3 1/8	812-27-33	165
	3 3/8	812-27-37	178
	4 1/8	812-27-47	205
	5 1/8	812-27-57	231
3 3/8	7/8	812-33-7	113
	1 1/8	812-33-13	126
	1 3/8	812-33-17	139
	2 1/8	812-33-23	152
	2 3/8	812-33-27	165
	3 1/8	812-33-33	178
	3 3/8	812-33-37	191
	4 1/8	812-33-47	218
	5 1/8	812-33-57	244
3 7/8	7/8	812-37-7	126
	1 1/8	812-37-13	139
	1 3/8	812-37-17	152
	2 1/8	812-37-23	165
	2 3/8	812-37-27	178
	3 1/8	812-37-33	191
	3 3/8	812-37-37	204
	4 1/8	812-37-47	231
	5 1/8	812-37-57	257
4 7/8	7/8	812-47-7	153
	1 1/8	812-47-13	166
	1 3/8	812-47-17	179
	2 1/8	812-47-23	192
	2 3/8	812-47-27	205
	3 1/8	812-47-33	218
	3 3/8	812-47-37	231
	4 1/8	812-47-47	258
	5 1/8	812-47-57	284
5 7/8	7/8	812-57-7	179
	1 1/8	812-57-13	192
	1 3/8	812-57-17	205
	2 1/8	812-57-23	218
	2 3/8	812-57-27	231
	3 1/8	812-57-33	244
	3 3/8	812-57-37	257
	4 1/8	812-57-47	284
	5 1/8	812-57-57	310

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2% thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

[CONTACT US](#)

**Cavity Retainer Sets $9\frac{7}{8} \times 8"$
 $\times 8"$ and $9\frac{7}{8} \times 11\frac{7}{8}$**

Cavity Retainer Sets

Cavity Retainer Sets | Cavity Retainer Sets $9\frac{7}{8} \times 8"$ and $9\frac{7}{8} \times 11\frac{7}{8}$



A	B	ITEM NUMBER	NET WT.
7/8	7/8	108-7-7	40
	1 3/8	108-7-13	51
	1 7/8	108-7-17	62
	2 3/8	108-7-23	73
	2 7/8	108-7-27	84
	3 3/8	108-7-33	96
	3 7/8	108-7-37	107
	4 3/8	108-7-47	129
	5 3/8	108-7-57	152
	7 3/8	108-13-7	51
1 3/8	108-13-13	62	
1 7/8	108-13-17	73	
2 3/8	108-13-23	84	
1 3/8	2 7/8	108-13-27	96
	3 3/8	108-13-33	107
	3 7/8	108-13-37	118
	4 3/8	108-13-47	140
	5 3/8	108-13-57	163
	7 3/8	108-17-7	62
	1 3/8	108-17-13	73
	1 7/8	108-17-17	84
1 7/8	2 3/8	108-17-23	96
	2 7/8	108-17-27	107
	3 3/8	108-17-33	118
	3 7/8	108-17-37	129
	4 3/8	108-17-47	152
	5 3/8	108-17-57	174
	7 3/8	108-23-7	73
	1 3/8	108-23-13	84
2 3/8	1 7/8	108-23-17	96
	2 3/8	108-23-23	107
	2 7/8	108-23-27	118
	3 3/8	108-23-33	129
	3 7/8	108-23-37	140
	4 3/8	108-23-47	163
	5 3/8	108-23-57	185
	7 3/8	108-27-7	84
2 7/8	1 3/8	108-27-13	96
	1 7/8	108-27-17	107
	2 3/8	108-27-23	118
	2 7/8	108-27-27	129
	3 3/8	108-27-33	140
	3 7/8	108-27-37	152
	4 3/8	108-27-47	174
	5 3/8	108-27-57	196

A	B	ITEM NUMBER	NET WT.
3 3/8	7/8	108-33-7	96
	1 3/8	108-33-13	107
	1 7/8	108-33-17	118
	2 3/8	108-33-23	129
	2 7/8	108-33-27	140
	3 3/8	108-33-33	152
	3 7/8	108-33-37	163
	4 3/8	108-33-47	185
	5 3/8	108-33-57	208
	7 3/8	108-37-7	107
3 7/8	1 3/8	108-37-13	118
	1 7/8	108-37-17	129
	2 3/8	108-37-23	140
	2 7/8	108-37-27	152
	3 3/8	108-37-33	163
	3 7/8	108-37-37	174
	4 3/8	108-37-47	196
	5 3/8	108-37-57	219
4 7/8	7/8	108-47-7	129
	1 3/8	108-47-13	140
	1 7/8	108-47-17	152
	2 3/8	108-47-23	163
	2 7/8	108-47-27	174
	3 3/8	108-47-33	185
	3 7/8	108-47-37	196
	4 3/8	108-47-47	219
5 7/8	7/8	108-57-7	152
	1 3/8	108-57-13	163
	1 7/8	108-57-17	174
	2 3/8	108-57-23	185
	2 7/8	108-57-27	196
	3 3/8	108-57-33	208
	3 7/8	108-57-37	219
	4 3/8	108-57-47	241
5 3/8	108-57-57	263	

A	B	ITEM NUMBER	NET WT.
7/8	7/8	1012-7-7	59
	1 3/8	1012-7-13	75
	1 7/8	1012-7-17	92
	2 3/8	1012-7-23	108
	2 7/8	1012-7-27	125
	3 3/8	1012-7-33	142
	3 7/8	1012-7-37	158
	4 3/8	1012-7-47	192
	5 3/8	1012-7-57	225
	7 3/8	1012-13-7	75
1 3/8	1 3/8	1012-13-13	92
	1 7/8	1012-13-17	108
	2 3/8	1012-13-23	125
	2 7/8	1012-13-27	142
	3 3/8	1012-13-33	158
	3 7/8	1012-13-37	175
	4 3/8	1012-13-47	208
	5 3/8	1012-13-57	241
1 7/8	7/8	1012-17-7	92
	1 3/8	1012-17-13	108
	1 7/8	1012-17-17	125
	2 3/8	1012-17-23	142
	2 7/8	1012-17-27	158
	3 3/8	1012-17-33	175
	3 7/8	1012-17-37	192
	4 3/8	1012-17-47	225
2 3/8	7/8	1012-23-7	108
	1 3/8	1012-23-13	125
	1 7/8	1012-23-17	142
	2 3/8	1012-23-23	158
	2 7/8	1012-23-27	175
	3 3/8	1012-23-33	192
	3 7/8	1012-23-37	208
	4 3/8	1012-23-47	241
5 3/8	1012-23-57	275	

A	B	ITEM NUMBER	NET WT.
2 7/8	7/8	1012-27-7	125
	1 3/8	1012-27-13	142
	1 7/8	1012-27-17	158
	2 3/8	1012-27-23	175
	2 7/8	1012-27-27	192
	3 3/8	1012-27-33	208
	3 7/8	1012-27-37	225
	4 3/8	1012-27-47	258
	5 3/8	1012-27-57	291
	7 3/8	1012-33-7	142
3 3/8	1 3/8	1012-33-13	158
	1 7/8	1012-33-17	175
	2 3/8	1012-33-23	192
	2 7/8	1012-33-27	208
	3 3/8	1012-33-33	225
	3 7/8	1012-33-37	241
	4 3/8	1012-33-47	275
	5 3/8	1012-33-57	308
3 7/8	7/8	1012-37-7	158
	1 3/8	1012-37-13	175
	1 7/8	1012-37-17	192
	2 3/8	1012-37-23	208
	2 7/8	1012-37-27	225
	3 3/8	1012-37-33	241
	3 7/8	1012-37-37	258
	4 3/8	1012-37-47	291
4 7/8	7/8	1012-47-7	192
	1 3/8	1012-47-13	208
	1 7/8	1012-47-17	225
	2 3/8	1012-47-23	241
	2 7/8	1012-47-27	258
	3 3/8	1012-47-33	275
	3 7/8	1012-47-37	291
	4 3/8	1012-47-47	324
5 7/8	7/8	1012-57-7	225
	1 3/8	1012-57-13	241
	1 7/8	1012-57-17	258
	2 3/8	1012-57-23	275
	2 7/8	1012-57-27	291
	3 3/8	1012-57-33	308
	3 7/8	1012-57-37	324
	4 3/8	1012-57-47	358
5 3/8	1012-57-57	391	

Thickness of each plate is finish ground $\pm .001"$. Width and length finished square and parallel.



WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2 3/8 inch thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

CONTACT US

Cavity Retainer Sets 9 7/8" × 16" and 9 7/8" × 20"

Cavity Retainer Sets



A	B	ITEM NUMBER	NET WT.
7/8	7/8	1016-7-7	79
	1 1/8	1016-7-13	101
	1 1/4	1016-7-17	124
	1 1/2	1016-7-23	146
	1 3/4	1016-7-27	168
	1 7/8	1016-7-33	191
	2 1/8	1016-7-37	213
	2 1/4	1016-7-47	258
1 1/8	2 1/2	1016-7-57	303
	2 3/4	1016-13-7	101
	3 1/8	1016-13-13	124
	3 1/4	1016-13-17	146
	3 1/2	1016-13-23	168
	3 3/4	1016-13-27	191
	4 1/8	1016-13-33	213
	4 1/4	1016-13-37	235
1 3/8	4 1/2	1016-13-47	280
	4 3/4	1016-13-57	325
	5 1/8	1016-17-7	124
	5 1/4	1016-17-13	146
	5 1/2	1016-17-17	168
	5 3/4	1016-17-23	191
	6 1/8	1016-17-27	213
	6 1/4	1016-17-33	235
1 5/8	6 1/2	1016-17-37	258
	6 3/4	1016-17-47	303
	7 1/8	1016-17-57	347
	7 1/4	1016-23-7	146
	7 1/2	1016-23-13	168
	7 3/4	1016-23-17	191
	8 1/8	1016-23-23	213
	8 1/4	1016-23-27	235
1 7/8	8 1/2	1016-23-33	258
	8 3/4	1016-23-37	280
	9 1/8	1016-23-47	325
	9 1/4	1016-23-57	370
	9 3/8	1016-27-7	168
	9 1/2	1016-27-13	191
	9 3/4	1016-27-17	213
	10 1/8	1016-27-23	235
1 9/8	10 1/4	1016-27-27	258
	10 1/2	1016-27-33	280
	10 3/4	1016-27-37	303
	10 7/8	1016-27-47	347
	11 1/8	1016-27-57	392
	11 1/4	1016-27-7	168
	11 1/2	1016-27-13	191
	11 3/4	1016-27-17	213
2 1/8	11 1/2	1016-27-23	235
	11 3/4	1016-27-27	258
	12 1/8	1016-27-33	280
	12 1/4	1016-27-37	303
	12 1/2	1016-27-47	347
	12 3/4	1016-27-57	392
	13 1/8	1016-27-7	168
	13 1/4	1016-27-13	191
2 3/8	13 1/2	1016-27-17	213
	13 3/4	1016-27-23	235
	14 1/8	1016-27-27	258
	14 1/4	1016-27-33	280
	14 1/2	1016-27-37	303
	14 3/4	1016-27-47	347
	15 1/8	1016-27-57	392
	15 1/4	1016-27-7	168
2 5/8	15 1/2	1016-27-13	191
	15 3/4	1016-27-17	213
	16 1/8	1016-27-23	235
	16 1/4	1016-27-27	258
	16 1/2	1016-27-33	280
	16 3/4	1016-27-37	303
	17 1/8	1016-27-47	347
	17 1/4	1016-27-57	392

A	B	ITEM NUMBER	NET WT.
3 3/8	7/8	1016-33-7	191
	1 1/8	1016-33-13	213
	1 1/4	1016-33-17	235
	1 1/2	1016-33-23	258
	1 3/4	1016-33-27	280
	1 7/8	1016-33-33	303
	2 1/8	1016-33-37	325
	2 1/4	1016-33-47	370
3 7/8	2 1/2	1016-33-57	415
	2 3/4	1016-37-7	213
	3 1/8	1016-37-13	235
	3 1/4	1016-37-17	258
	3 1/2	1016-37-23	280
	3 3/4	1016-37-27	303
	4 1/8	1016-37-33	325
	4 1/4	1016-37-37	347
4 1/8	4 1/2	1016-37-47	392
	4 3/4	1016-37-57	437
	5 1/8	1016-47-7	258
	5 1/4	1016-47-13	280
	5 1/2	1016-47-17	303
	5 3/4	1016-47-23	325
	6 1/8	1016-47-27	347
	6 1/4	1016-47-33	370
4 5/8	6 1/2	1016-47-37	392
	6 3/4	1016-47-47	437
	7 1/8	1016-47-57	482
	7 1/4	1016-57-7	303
	7 1/2	1016-57-13	325
	7 3/4	1016-57-17	347
	8 1/8	1016-57-23	370
	8 1/4	1016-57-27	392
5 1/8	8 1/2	1016-57-33	415
	8 3/4	1016-57-37	437
	9 1/8	1016-57-47	482
	9 1/4	1016-57-57	526

A	B	ITEM NUMBER	NET WT.
7/8	7/8	1020-7-7	98
	1 1/8	1020-7-13	126
	1 1/4	1020-7-17	154
	1 1/2	1020-7-23	182
	1 3/4	1020-7-27	210
	1 7/8	1020-7-33	238
	2 1/8	1020-7-37	266
	2 1/4	1020-7-47	322
1 1/8	2 1/2	1020-7-57	378
	2 3/4	1020-13-7	126
	3 1/8	1020-13-13	154
	3 1/4	1020-13-17	182
	3 1/2	1020-13-23	210
	3 3/4	1020-13-27	238
	4 1/8	1020-13-33	266
	4 1/4	1020-13-37	294
1 3/8	4 1/2	1020-13-47	350
	4 3/4	1020-13-57	406
	5 1/8	1020-17-7	154
	5 1/4	1020-17-13	182
	5 1/2	1020-17-17	210
	5 3/4	1020-17-23	238
	6 1/8	1020-17-27	266
	6 1/4	1020-17-33	294
1 5/8	6 1/2	1020-17-37	322
	6 3/4	1020-17-47	378
	7 1/8	1020-17-57	434
	7 1/4	1020-23-7	182
	7 1/2	1020-23-13	210
	7 3/4	1020-23-17	238
	8 1/8	1020-23-23	266
	8 1/4	1020-23-27	294
1 7/8	8 1/2	1020-23-33	322
	8 3/4	1020-23-37	350
	9 1/8	1020-23-47	406
	9 1/4	1020-23-57	462

A	B	ITEM NUMBER	NET WT.
2 1/8	7/8	1020-27-7	210
	1 1/8	1020-27-13	238
	1 1/4	1020-27-17	266
	1 1/2	1020-27-23	294
	1 3/4	1020-27-27	322
	1 7/8	1020-27-33	350
	2 1/8	1020-27-37	378
	2 1/4	1020-27-47	434
2 3/8	2 1/2	1020-27-57	490
	2 3/4	1020-33-7	238
	3 1/8	1020-33-13	266
	3 1/4	1020-33-17	294
	3 1/2	1020-33-23	322
	3 3/4	1020-33-27	350
	4 1/8	1020-33-33	378
	4 1/4	1020-33-37	406
2 5/8	4 1/2	1020-33-47	462
	4 3/4	1020-33-57	518
	5 1/8	1020-37-7	266
	5 1/4	1020-37-13	294
	5 1/2	1020-37-17	322
	5 3/4	1020-37-23	350
	6 1/8	1020-37-27	378
	6 1/4	1020-37-33	406
2 7/8	6 1/2	1020-37-37	434
	6 3/4	1020-37-47	490
	7 1/8	1020-37-57	546
	7 1/4	1020-47-7	322
	7 1/2	1020-47-13	350
	7 3/4	1020-47-17	378
	8 1/8	1020-47-23	406
	8 1/4	1020-47-27	434
3 1/8	8 1/2	1020-47-33	490
	8 3/4	1020-47-37	518
	9 1/8	1020-47-47	574
	9 1/4	1020-47-57	630
	9 1/2	1020-57-7	378
	9 3/4	1020-57-13	406
	10 1/8	1020-57-17	434
	10 1/4	1020-57-23	462
3 3/8	10 1/2	1020-57-27	490
	10 3/4	1020-57-33	518
	11 1/8	1020-57-37	546
	11 1/4	1020-57-47	602
	11 1/2	1020-57-57	658

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



1. Quantity & Item Number
2. No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2 1/2" thick)
3. L Dimension (Guide Pin Length)
4. Method of Shipment

[CONTACT US](#)

Cavity Retainer Sets | Cavity Retainer Sets 9 7/8" × 16" and 9 7/8" × 20"

Cavity Retainer Sets 9⁷/₈ × 23³/₄ and 10⁷/₈ × 12"

Cavity Retainer Sets



Cavity Retainer Sets | Cavity Retainer Sets 9⁷/₈ × 23³/₄ and 10⁷/₈ × 12"

9 ⁷ / ₈ × 23 ³ / ₄				10 ⁷ / ₈ × 12"			
A	B	ITEM NUMBER	NET WT.	A	B	ITEM NUMBER	NET WT.
1 ³ / ₈	1 ³ / ₈	1024-13-13	183	3 ³ / ₈	1 ³ / ₈	1024-33-13	316
	1 ⁷ / ₈	1024-13-17	216		1 ⁷ / ₈	1024-33-17	349
	2 ¹ / ₈	1024-13-23	250		2 ¹ / ₈	1024-33-23	383
	2 ⁵ / ₈	1024-13-27	283		2 ⁵ / ₈	1024-33-27	416
	3 ¹ / ₈	1024-13-33	316		3 ¹ / ₈	1024-33-33	449
	3 ⁵ / ₈	1024-13-37	349		3 ⁵ / ₈	1024-33-37	482
	4 ¹ / ₈	1024-13-47	416		4 ¹ / ₈	1024-33-47	549
	5 ¹ / ₈	1024-13-57	482		5 ¹ / ₈	1024-33-57	615
1 ⁷ / ₈	1 ³ / ₈	1024-17-13	216	3 ⁷ / ₈	1 ³ / ₈	1024-37-13	349
	1 ⁷ / ₈	1024-17-17	250		1 ⁷ / ₈	1024-37-17	383
	2 ¹ / ₈	1024-17-23	283		2 ¹ / ₈	1024-37-23	416
	2 ⁵ / ₈	1024-17-27	316		2 ⁵ / ₈	1024-37-27	449
	3 ¹ / ₈	1024-17-33	349		3 ¹ / ₈	1024-37-33	482
	3 ⁵ / ₈	1024-17-37	383		3 ⁵ / ₈	1024-37-37	515
	4 ¹ / ₈	1024-17-47	449		4 ¹ / ₈	1024-37-47	582
2 ³ / ₈	5 ¹ / ₈	1024-17-57	515	5 ¹ / ₈	1024-37-57	648	
	1 ³ / ₈	1024-23-13	250	4 ⁷ / ₈	1 ³ / ₈	1024-47-13	416
	1 ⁷ / ₈	1024-23-17	283		1 ⁷ / ₈	1024-47-17	449
	2 ¹ / ₈	1024-23-23	316		2 ¹ / ₈	1024-47-23	482
	2 ⁵ / ₈	1024-23-27	349		2 ⁵ / ₈	1024-47-27	515
	3 ¹ / ₈	1024-23-33	383		3 ¹ / ₈	1024-47-33	549
	3 ⁵ / ₈	1024-23-37	416		3 ⁵ / ₈	1024-47-37	582
4 ¹ / ₈	1024-23-47	482	4 ¹ / ₈		1024-47-47	648	
2 ⁷ / ₈	5 ⁵ / ₈	1024-23-57	549	5 ⁵ / ₈	1024-47-57	715	
	1 ³ / ₈	1024-27-13	283	5 ⁷ / ₈	1 ³ / ₈	1024-57-13	482
	1 ⁷ / ₈	1024-27-17	316		1 ⁷ / ₈	1024-57-17	515
	2 ¹ / ₈	1024-27-23	349		2 ¹ / ₈	1024-57-23	549
	2 ⁵ / ₈	1024-27-27	383		2 ⁵ / ₈	1024-57-27	582
	3 ¹ / ₈	1024-27-33	416		3 ¹ / ₈	1024-57-33	615
	3 ⁵ / ₈	1024-27-37	449		3 ⁵ / ₈	1024-57-37	648
4 ¹ / ₈	1024-27-47	515	4 ¹ / ₈		1024-57-47	715	
5 ¹ / ₈	1024-27-57	582	5 ¹ / ₈	1024-57-57	781		

7 ⁷ / ₈	7 ⁷ / ₈	1112-7-7	65	2 ⁷ / ₈	7 ⁷ / ₈	1112-27-7	139
	1 ³ / ₈	1112-7-13	84		1 ³ / ₈	1112-27-13	158
	1 ⁷ / ₈	1112-7-17	102		1 ⁷ / ₈	1112-27-17	176
	2 ¹ / ₈	1112-7-23	121		2 ¹ / ₈	1112-27-23	195
	2 ⁵ / ₈	1112-7-27	139		2 ⁵ / ₈	1112-27-27	213
	3 ¹ / ₈	1112-7-33	158		3 ¹ / ₈	1112-27-33	232
	3 ⁵ / ₈	1112-7-37	176		3 ⁵ / ₈	1112-27-37	250
1 ³ / ₈	4 ¹ / ₈	1112-7-47	213	4 ¹ / ₈	1112-27-47	287	
	5 ¹ / ₈	1112-7-57	250	5 ¹ / ₈	1112-27-57	324	
	7 ⁷ / ₈	1112-13-7	84	3 ³ / ₈	7 ⁷ / ₈	1112-33-7	158
	1 ³ / ₈	1112-13-13	102		1 ³ / ₈	1112-33-13	176
	1 ⁷ / ₈	1112-13-17	121		1 ⁷ / ₈	1112-33-17	195
	2 ¹ / ₈	1112-13-23	139		2 ¹ / ₈	1112-33-23	213
	2 ⁵ / ₈	1112-13-27	158		2 ⁵ / ₈	1112-33-27	232
3 ¹ / ₈	1112-13-33	176	3 ¹ / ₈		1112-33-33	250	
3 ⁵ / ₈	1112-13-37	195	3 ⁵ / ₈		1112-33-37	269	
1 ⁷ / ₈	4 ¹ / ₈	1112-13-47	232	4 ¹ / ₈	1112-33-47	306	
	5 ¹ / ₈	1112-13-57	269	5 ¹ / ₈	1112-33-57	343	
	7 ⁷ / ₈	1112-17-7	102	3 ⁷ / ₈	7 ⁷ / ₈	1112-37-7	176
	1 ³ / ₈	1112-17-13	121		1 ³ / ₈	1112-37-13	195
	1 ⁷ / ₈	1112-17-17	139		1 ⁷ / ₈	1112-37-17	213
	2 ¹ / ₈	1112-17-23	158		2 ¹ / ₈	1112-37-23	232
	2 ⁵ / ₈	1112-17-27	176		2 ⁵ / ₈	1112-37-27	250
3 ¹ / ₈	1112-17-33	195	3 ¹ / ₈		1112-37-33	269	
3 ⁵ / ₈	1112-17-37	213	3 ⁵ / ₈		1112-37-37	287	
2 ³ / ₈	4 ¹ / ₈	1112-17-47	250	4 ¹ / ₈	1112-37-47	324	
	5 ¹ / ₈	1112-17-57	287	5 ¹ / ₈	1112-37-57	361	
	7 ⁷ / ₈	1112-23-7	121	4 ⁷ / ₈	7 ⁷ / ₈	1112-47-7	213
	1 ³ / ₈	1112-23-13	139		1 ³ / ₈	1112-47-13	232
	1 ⁷ / ₈	1112-23-17	158		1 ⁷ / ₈	1112-47-17	250
	2 ¹ / ₈	1112-23-23	176		2 ¹ / ₈	1112-47-23	269
	2 ⁵ / ₈	1112-23-27	195		2 ⁵ / ₈	1112-47-27	287
3 ¹ / ₈	1112-23-33	213	3 ¹ / ₈		1112-47-33	306	
3 ⁵ / ₈	1112-23-37	232	3 ⁵ / ₈		1112-47-37	324	
2 ⁷ / ₈	4 ¹ / ₈	1112-23-47	269	4 ¹ / ₈	1112-47-47	361	
	5 ¹ / ₈	1112-23-57	306	4 ⁵ / ₈	1112-47-57	398	
	7 ⁷ / ₈	1112-57-7	121	5 ⁷ / ₈	7 ⁷ / ₈	1112-57-7	250
	1 ³ / ₈	1112-23-13	139		1 ³ / ₈	1112-57-13	269
	1 ⁷ / ₈	1112-23-17	158		1 ⁷ / ₈	1112-57-17	287
	2 ¹ / ₈	1112-23-23	176		2 ¹ / ₈	1112-57-23	306
	2 ⁵ / ₈	1112-23-27	195		2 ⁵ / ₈	1112-57-27	324
3 ¹ / ₈	1112-23-33	213	3 ¹ / ₈		1112-57-33	343	
3 ⁵ / ₈	1112-23-37	232	3 ⁵ / ₈		1112-57-37	361	
4 ¹ / ₈	1112-23-47	269	4 ¹ / ₈	1112-57-47	398		
5 ¹ / ₈	1112-23-57	306	5 ¹ / ₈	1112-57-57	435		

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- 1. Quantity & Item Number
 - 2. No. 1, No. 2, No. 3 or No. 7 Steel
 - 3. L Dimension (Guide Pin Length)
 - 4. Method of Shipment
- (No. 7 Steel available standard only for plates up to and including 2⁷/₈ thick)

SPECIAL ORDER SIZES: Please contact DME.

CONTACT US

Cavity Retainer Sets 10⁷/₈ × 14" and 10⁷/₈ × 18"

Cavity Retainer Sets



	A	B	ITEM NUMBER	NET WT.
7/8		7/8	1114-7-7	76
		1 1/8	1114-7-13	98
		1 1/4	1114-7-17	119
		2 1/8	1114-7-23	141
		2 1/2	1114-7-27	162
		3 1/8	1114-7-33	184
		3 1/2	1114-7-37	205
		4 1/8	1114-7-47	249
		5 1/8	1114-7-57	292
1 1/8		7/8	1114-13-7	98
		1 1/8	1114-13-13	119
		1 1/4	1114-13-17	141
		2 1/8	1114-13-23	162
		2 1/2	1114-13-27	184
		3 1/8	1114-13-33	205
		3 1/2	1114-13-37	227
		4 1/8	1114-13-47	270
		5 1/8	1114-13-57	313
1 1/4		7/8	1114-17-7	119
		1 1/8	1114-17-13	141
		1 1/4	1114-17-17	162
		2 1/8	1114-17-23	184
		2 1/2	1114-17-27	205
		3 1/8	1114-17-33	227
		3 1/2	1114-17-37	249
		4 1/8	1114-17-47	292
		5 1/8	1114-17-57	335
2 3/8		7/8	1114-23-7	141
		1 1/8	1114-23-13	162
		1 1/4	1114-23-17	184
		2 1/8	1114-23-23	205
		2 1/2	1114-23-27	227
		3 1/8	1114-23-33	249
		3 1/2	1114-23-37	270
		4 1/8	1114-23-47	313
		5 1/8	1114-23-57	356
2 7/8		7/8	1114-27-7	162
		1 1/8	1114-27-13	184
		1 1/4	1114-27-17	205
		2 1/8	1114-27-23	227
		2 1/2	1114-27-27	249
		3 1/8	1114-27-33	270
		3 1/2	1114-27-37	292
		4 1/8	1114-27-47	335
		5 1/8	1114-27-57	378

	A	B	ITEM NUMBER	NET WT.
3 3/8		7/8	1114-33-7	184
		1 1/8	1114-33-13	205
		1 1/4	1114-33-17	227
		2 1/8	1114-33-23	249
		2 1/2	1114-33-27	270
		3 1/8	1114-33-33	292
		3 1/2	1114-33-37	313
		4 1/8	1114-33-47	356
		5 1/8	1114-33-57	400
3 7/8		7/8	1114-37-7	205
		1 1/8	1114-37-13	227
		1 1/4	1114-37-17	249
		2 1/8	1114-37-23	270
		2 1/2	1114-37-27	292
		3 1/8	1114-37-33	313
		3 1/2	1114-37-37	335
		4 1/8	1114-37-47	378
		5 1/8	1114-37-57	421
4 7/8		7/8	1114-47-7	249
		1 1/8	1114-47-13	270
		1 1/4	1114-47-17	292
		2 1/8	1114-47-23	313
		2 1/2	1114-47-27	335
		3 1/8	1114-47-33	356
		3 1/2	1114-47-37	378
		4 1/8	1114-47-47	421
		5 1/8	1114-47-57	464
5 7/8		7/8	1114-57-7	292
		1 1/8	1114-57-13	313
		1 1/4	1114-57-17	335
		2 1/8	1114-57-23	356
		2 1/2	1114-57-27	378
		3 1/8	1114-57-33	400
		3 1/2	1114-57-37	421
		4 1/8	1114-57-47	464
		5 1/8	1114-57-57	507

	A	B	ITEM NUMBER	NET WT.
7/8		7/8	1118-7-7	98
		1 1/8	1118-7-13	125
		1 1/4	1118-7-17	153
		2 1/8	1118-7-23	181
		2 1/2	1118-7-27	208
		3 1/8	1118-7-33	236
		3 1/2	1118-7-37	264
		4 1/8	1118-7-47	319
		5 1/8	1118-7-57	375
1 1/8		7/8	1118-13-7	125
		1 1/8	1118-13-13	153
		1 1/4	1118-13-17	181
		2 1/8	1118-13-23	208
		2 1/2	1118-13-27	236
		3 1/8	1118-13-33	264
		3 1/2	1118-13-37	292
		4 1/8	1118-13-47	347
		5 1/8	1118-13-57	403
1 1/4		7/8	1118-17-7	153
		1 1/8	1118-17-13	181
		1 1/4	1118-17-17	208
		2 1/8	1118-17-23	236
		2 1/2	1118-17-27	264
		3 1/8	1118-17-33	292
		3 1/2	1118-17-37	319
		4 1/8	1118-17-47	375
		5 1/8	1118-17-57	430
2 3/8		7/8	1118-23-7	181
		1 1/8	1118-23-13	208
		1 1/4	1118-23-17	236
		2 1/8	1118-23-23	264
		2 1/2	1118-23-27	292
		3 1/8	1118-23-33	319
		3 1/2	1118-23-37	347
		4 1/8	1118-23-47	403
		5 1/8	1118-23-57	458

	A	B	ITEM NUMBER	NET WT.
2 7/8		7/8	1118-27-7	208
		1 1/8	1118-27-13	236
		1 1/4	1118-27-17	264
		2 1/8	1118-27-23	292
		2 1/2	1118-27-27	319
		3 1/8	1118-27-33	347
		3 1/2	1118-27-37	375
		4 1/8	1118-27-47	430
		5 1/8	1118-27-57	486
3 3/8		7/8	1118-33-7	236
		1 1/8	1118-33-13	264
		1 1/4	1118-33-17	292
		2 1/8	1118-33-23	319
		2 1/2	1118-33-27	347
		3 1/8	1118-33-33	375
		3 1/2	1118-33-37	403
		4 1/8	1118-33-47	458
		5 1/8	1118-33-57	513
3 7/8		7/8	1118-37-7	264
		1 1/8	1118-37-13	292
		1 1/4	1118-37-17	319
		2 1/8	1118-37-23	347
		2 1/2	1118-37-27	375
		3 1/8	1118-37-33	403
		3 1/2	1118-37-37	430
		4 1/8	1118-37-47	486
		5 1/8	1118-37-57	541
4 7/8		7/8	1118-47-7	319
		1 1/8	1118-47-13	347
		1 1/4	1118-47-17	375
		2 1/8	1118-47-23	403
		2 1/2	1118-47-27	430
		3 1/8	1118-47-33	458
		3 1/2	1118-47-37	486
		4 1/8	1118-47-47	541
		5 1/8	1118-47-57	597
5 7/8		7/8	1118-57-7	375
		1 1/8	1118-57-13	403
		1 1/4	1118-57-17	430
		2 1/8	1118-57-23	458
		2 1/2	1118-57-27	486
		3 1/8	1118-57-33	513
		3 1/2	1118-57-37	541
		4 1/8	1118-57-47	597
		5 1/8	1118-57-57	652

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2 7/8" thick)
- L Dimension (Guide Pin Length)
- Method of Shipment



[CONTACT US](#)

Cavity Retainer Sets | Cavity Retainer Sets 10⁷/₈ × 14" and 10⁷/₈ × 18"

Cavity Retainer Sets

10⁷/₈ × 23¹/₂ and 11⁷/₈ × 12"

Cavity Retainer Sets



A	B	ITEM NUMBER	NET WT.
1³/₈	1 ³ / ₈	1123-13-13	200
	1 ⁷ / ₈	1123-13-17	236
	2 ¹ / ₈	1123-13-23	272
	2 ⁷ / ₈	1123-13-27	308
	3 ¹ / ₈	1123-13-33	344
	3 ⁷ / ₈	1123-13-37	381
	4 ¹ / ₈	1123-13-47	453
	5 ¹ / ₈	1123-13-57	525
1⁷/₈	1 ³ / ₈	1123-17-13	236
	1 ⁷ / ₈	1123-17-17	272
	2 ¹ / ₈	1123-17-23	308
	2 ⁷ / ₈	1123-17-27	344
	3 ¹ / ₈	1123-17-33	381
	3 ⁷ / ₈	1123-17-37	417
	4 ¹ / ₈	1123-17-47	489
	5 ¹ / ₈	1123-17-57	562
2³/₈	1 ³ / ₈	1123-23-13	272
	1 ⁷ / ₈	1123-23-17	308
	2 ¹ / ₈	1123-23-23	344
	2 ⁷ / ₈	1123-23-27	381
	3 ¹ / ₈	1123-23-33	417
	3 ⁷ / ₈	1123-23-37	453
	4 ¹ / ₈	1123-23-47	525
	5 ¹ / ₈	1123-23-57	598
2⁷/₈	1 ³ / ₈	1123-27-13	308
	1 ⁷ / ₈	1123-27-17	344
	2 ¹ / ₈	1123-27-23	381
	2 ⁷ / ₈	1123-27-27	417
	3 ¹ / ₈	1123-27-33	453
	3 ⁷ / ₈	1123-27-37	489
	4 ¹ / ₈	1123-27-47	562
	5 ¹ / ₈	1123-27-57	634

A	B	ITEM NUMBER	NET WT.
3³/₈	1 ³ / ₈	1123-33-13	344
	1 ⁷ / ₈	1123-33-17	381
	2 ¹ / ₈	1123-33-23	417
	2 ⁷ / ₈	1123-33-27	453
	3 ¹ / ₈	1123-33-33	489
	3 ⁷ / ₈	1123-33-37	525
	4 ¹ / ₈	1123-33-47	598
	5 ¹ / ₈	1123-33-57	670
3⁷/₈	1 ³ / ₈	1123-37-13	381
	1 ⁷ / ₈	1123-37-17	417
	2 ¹ / ₈	1123-37-23	453
	2 ⁷ / ₈	1123-37-27	489
	3 ¹ / ₈	1123-37-33	525
	3 ⁷ / ₈	1123-37-37	562
	4 ¹ / ₈	1123-37-47	634
	5 ¹ / ₈	1123-37-57	706
4⁷/₈	1 ³ / ₈	1123-47-13	453
	1 ⁷ / ₈	1123-47-17	489
	2 ¹ / ₈	1123-47-23	525
	2 ⁷ / ₈	1123-47-27	562
	3 ¹ / ₈	1123-47-33	598
	3 ⁷ / ₈	1123-47-37	634
	4 ¹ / ₈	1123-47-47	706
	5 ¹ / ₈	1123-47-57	779
5⁷/₈	1 ³ / ₈	1123-57-13	525
	1 ⁷ / ₈	1123-57-17	562
	2 ¹ / ₈	1123-57-23	598
	2 ⁷ / ₈	1123-57-27	634
	3 ¹ / ₈	1123-57-33	670
	3 ⁷ / ₈	1123-57-37	706
	4 ¹ / ₈	1123-57-47	779
	5 ¹ / ₈	1123-57-57	851

A	B	ITEM NUMBER	NET WT.
7⁷/₈	7 ⁷ / ₈	1212-7-7	71
	1 ¹ / ₈	1212-7-13	91
	1 ³ / ₈	1212-7-17	112
	1 ⁵ / ₈	1212-7-23	132
	1 ⁷ / ₈	1212-7-27	152
	2 ¹ / ₈	1212-7-33	172
	2 ³ / ₈	1212-7-37	192
	2 ⁵ / ₈	1212-7-47	233
1³/₈	5 ¹ / ₈	1212-7-57	273
	7 ⁷ / ₈	1212-13-7	91
	1 ¹ / ₈	1212-13-13	112
	1 ³ / ₈	1212-13-17	132
	1 ⁵ / ₈	1212-13-23	152
	1 ⁷ / ₈	1212-13-27	172
	2 ¹ / ₈	1212-13-33	192
	2 ³ / ₈	1212-13-37	212
1⁷/₈	4 ⁷ / ₈	1212-13-47	253
	5 ¹ / ₈	1212-13-57	293
	7 ⁷ / ₈	1212-17-7	112
	1 ¹ / ₈	1212-17-13	132
	1 ³ / ₈	1212-17-17	152
	1 ⁵ / ₈	1212-17-23	172
	1 ⁷ / ₈	1212-17-27	192
	2 ¹ / ₈	1212-17-33	212
2³/₈	3 ¹ / ₈	1212-17-37	233
	3 ³ / ₈	1212-17-47	273
	3 ⁵ / ₈	1212-17-57	313
	4 ¹ / ₈	1212-23-7	132
	1 ¹ / ₈	1212-23-13	152
	1 ³ / ₈	1212-23-17	172
	1 ⁵ / ₈	1212-23-23	192
	1 ⁷ / ₈	1212-23-27	212
2⁷/₈	3 ⁷ / ₈	1212-23-33	233
	3 ⁹ / ₈	1212-23-37	253
	4 ¹ / ₈	1212-23-47	293
	4 ³ / ₈	1212-23-57	334
	5 ¹ / ₈	1212-23-7	132
	1 ¹ / ₈	1212-23-13	152
	1 ³ / ₈	1212-23-17	172
	1 ⁵ / ₈	1212-23-23	192

A	B	ITEM NUMBER	NET WT.
2⁷/₈	7 ⁷ / ₈	1212-27-7	152
	1 ¹ / ₈	1212-27-13	172
	1 ³ / ₈	1212-27-17	192
	1 ⁵ / ₈	1212-27-23	212
	1 ⁷ / ₈	1212-27-27	233
	2 ¹ / ₈	1212-27-33	253
	2 ³ / ₈	1212-27-37	273
	2 ⁵ / ₈	1212-27-47	313
3³/₈	5 ¹ / ₈	1212-27-57	354
	7 ⁷ / ₈	1212-33-7	172
	1 ¹ / ₈	1212-33-13	192
	1 ³ / ₈	1212-33-17	212
	1 ⁵ / ₈	1212-33-23	233
	1 ⁷ / ₈	1212-33-27	253
	2 ¹ / ₈	1212-33-33	273
	2 ³ / ₈	1212-33-37	293
3⁷/₈	4 ⁷ / ₈	1212-33-47	334
	5 ¹ / ₈	1212-33-57	374
	7 ⁷ / ₈	1212-37-7	192
	1 ¹ / ₈	1212-37-13	212
	1 ³ / ₈	1212-37-17	233
	1 ⁵ / ₈	1212-37-23	253
	1 ⁷ / ₈	1212-37-27	273
	2 ¹ / ₈	1212-37-33	293
3⁹/₈	3 ⁷ / ₈	1212-37-37	313
	3 ⁹ / ₈	1212-37-47	354
	4 ¹ / ₈	1212-37-57	394
	4 ³ / ₈	1212-47-7	233
	1 ¹ / ₈	1212-47-13	253
	1 ³ / ₈	1212-47-17	273
	1 ⁵ / ₈	1212-47-23	293
	1 ⁷ / ₈	1212-47-27	313
4⁷/₈	2 ⁷ / ₈	1212-47-33	334
	2 ⁹ / ₈	1212-47-37	354
	3 ¹ / ₈	1212-47-47	394
	3 ³ / ₈	1212-47-57	435
	3 ⁵ / ₈	1212-57-7	273
	1 ¹ / ₈	1212-57-13	293
	1 ³ / ₈	1212-57-17	313
	1 ⁵ / ₈	1212-57-23	334
5⁷/₈	2 ⁵ / ₈	1212-57-27	354
	2 ⁷ / ₈	1212-57-33	374
	2 ⁹ / ₈	1212-57-37	394
	3 ¹ / ₈	1212-57-47	435
	3 ³ / ₈	1212-57-57	475

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- 1. Quantity & Item Number
- 2. No. 1, No. 2, No. 3 or No. 7 Steel
- (No. 7 Steel available standard only for plates up to and including 2⁷/₈ thick)
- 3. L Dimension (Guide Pin Length)
- 4. Method of Shipment

CONTACT US

Cavity Retainer Sets

1 11/8 x 15" and 1 11/8 x 17 1/2

Cavity Retainer Sets



	A	B	ITEM NUMBER	NET WT.
7/8	7/8	7/8	1215-7-7	89
		1 1/8	1215-7-13	114
		1 1/4	1215-7-17	139
		1 3/8	1215-7-23	164
		1 1/2	1215-7-27	190
		1 5/8	1215-7-33	215
		1 3/4	1215-7-37	240
		1 7/8	1215-7-47	291
1 3/8	1 3/8	1 7/8	1215-13-7	114
		1 5/4	1215-13-13	139
		1 1/2	1215-13-17	164
		1 3/4	1215-13-23	190
		1 1/2	1215-13-27	215
		1 5/8	1215-13-33	240
		1 3/4	1215-13-37	265
		1 7/8	1215-13-47	316
1 7/8	1 7/8	1 5/8	1215-17-7	139
		1 5/4	1215-17-13	164
		1 1/2	1215-17-17	190
		1 3/4	1215-17-23	215
		1 1/2	1215-17-27	240
		1 5/8	1215-17-33	265
		1 3/4	1215-17-37	291
		1 7/8	1215-17-47	341
2 3/8	2 3/8	1 5/8	1215-23-7	164
		1 5/4	1215-23-13	190
		1 1/2	1215-23-17	215
		1 3/4	1215-23-23	240
		1 1/2	1215-23-27	265
		1 5/8	1215-23-33	291
		1 3/4	1215-23-37	316
		1 7/8	1215-23-47	366
2 7/8	2 7/8	1 5/8	1215-27-7	190
		1 5/4	1215-27-13	215
		1 1/2	1215-27-17	240
		1 3/4	1215-27-23	265
		1 1/2	1215-27-27	291
		1 5/8	1215-27-33	316
		1 3/4	1215-27-37	341
		1 7/8	1215-27-47	392
5/8	5/8	1 5/8	1215-57-7	417
		1 5/4	1215-57-13	442
		1 1/2	1215-57-17	467
		1 3/4	1215-57-23	492
		1 1/2	1215-57-27	517
		1 5/8	1215-57-33	542
		1 3/4	1215-57-37	567
		1 7/8	1215-57-47	617

	A	B	ITEM NUMBER	NET WT.
3 3/8	3 3/8	7/8	1215-33-7	215
		1 1/8	1215-33-13	240
		1 1/4	1215-33-17	265
		1 3/8	1215-33-23	291
		1 1/2	1215-33-27	316
		1 5/8	1215-33-33	341
		1 3/4	1215-33-37	366
		1 7/8	1215-33-47	417
3 7/8	3 7/8	7/8	1215-37-7	240
		1 1/8	1215-37-13	265
		1 1/4	1215-37-17	291
		1 3/8	1215-37-23	316
		1 1/2	1215-37-27	341
		1 5/8	1215-37-33	366
		1 3/4	1215-37-37	392
		1 7/8	1215-37-47	442
4 7/8	4 7/8	1 5/8	1215-47-7	291
		1 5/4	1215-47-13	316
		1 1/2	1215-47-17	341
		1 3/4	1215-47-23	366
		1 1/2	1215-47-27	392
		1 5/8	1215-47-33	417
		1 3/4	1215-47-37	442
		1 7/8	1215-47-47	492
5 7/8	5 7/8	1 5/8	1215-57-7	341
		1 5/4	1215-57-13	366
		1 1/2	1215-57-17	392
		1 3/4	1215-57-23	417
		1 1/2	1215-57-27	442
		1 5/8	1215-57-33	467
		1 3/4	1215-57-37	492
		1 7/8	1215-57-47	543

	A	B	ITEM NUMBER	NET WT.
7/8	7/8	7/8	1217-7-7	104
		1 1/8	1217-7-13	133
		1 1/4	1217-7-17	162
		1 3/8	1217-7-23	192
		1 1/2	1217-7-27	221
		1 5/8	1217-7-33	251
		1 3/4	1217-7-37	280
		1 7/8	1217-7-47	339
1 3/8	1 3/8	1 7/8	1217-13-7	133
		1 5/4	1217-13-13	162
		1 1/2	1217-13-17	192
		1 3/4	1217-13-23	221
		1 1/2	1217-13-27	251
		1 5/8	1217-13-33	280
		1 3/4	1217-13-37	310
		1 7/8	1217-13-47	368
1 7/8	1 7/8	1 5/8	1217-17-7	162
		1 5/4	1217-17-13	192
		1 1/2	1217-17-17	221
		1 3/4	1217-17-23	251
		1 1/2	1217-17-27	280
		1 5/8	1217-17-33	310
		1 3/4	1217-17-37	339
		1 7/8	1217-17-47	398
2 3/8	2 3/8	1 5/8	1217-23-7	192
		1 5/4	1217-23-13	221
		1 1/2	1217-23-17	251
		1 3/4	1217-23-23	280
		1 1/2	1217-23-27	310
		1 5/8	1217-23-33	339
		1 3/4	1217-23-37	368
		1 7/8	1217-23-47	427

	A	B	ITEM NUMBER	NET WT.
2 7/8	2 7/8	7/8	1217-27-7	221
		1 1/8	1217-27-13	251
		1 1/4	1217-27-17	280
		1 3/8	1217-27-23	310
		1 1/2	1217-27-27	339
		1 5/8	1217-27-33	368
		1 3/4	1217-27-37	398
		1 7/8	1217-27-47	457
3 3/8	3 3/8	1 7/8	1217-33-7	251
		1 5/4	1217-33-13	280
		1 1/2	1217-33-17	310
		1 3/4	1217-33-23	339
		1 1/2	1217-33-27	368
		1 5/8	1217-33-33	398
		1 3/4	1217-33-37	427
		1 7/8	1217-33-47	486
3 7/8	3 7/8	1 5/8	1217-37-7	280
		1 5/4	1217-37-13	310
		1 1/2	1217-37-17	339
		1 3/4	1217-37-23	368
		1 1/2	1217-37-27	398
		1 5/8	1217-37-33	427
		1 3/4	1217-37-37	457
		1 7/8	1217-37-47	516
4 7/8	4 7/8	1 5/8	1217-47-7	339
		1 5/4	1217-47-13	368
		1 1/2	1217-47-17	398
		1 3/4	1217-47-23	427
		1 1/2	1217-47-27	457
		1 5/8	1217-47-33	486
		1 3/4	1217-47-37	516
		1 7/8	1217-47-47	575
5 7/8	5 7/8	1 5/8	1217-57-7	398
		1 5/4	1217-57-13	427
		1 1/2	1217-57-17	457
		1 3/4	1217-57-23	486
		1 1/2	1217-57-27	516
		1 5/8	1217-57-33	545
		1 3/4	1217-57-37	575
		1 7/8	1217-57-47	633

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel
(No. 7 Steel available standard only for plates up to and including 2 7/8" thick)
- L Dimension (Guide Pin Length)
- Method of Shipment



SPECIAL ORDER SIZES: Please contact DME.

CONTACT US

Cavity Retainer Sets | Cavity Retainer Sets 1 11/8 x 15" and 1 11/8 x 17 1/2

Cavity Retainer Sets 11 7/8 × 20" and 11 7/8 × 23 1/2"

Cavity Retainer Sets



	A	B	ITEM NUMBER	NET WT.
7/8		7/8	1220-7-7	118
		1 1/8	1220-7-13	152
		1 1/4	1220-7-17	186
		2 1/8	1220-7-23	219
		2 1/2	1220-7-27	253
		3 1/8	1220-7-33	286
		3 3/8	1220-7-37	320
		4 1/8	1220-7-47	387
		5 1/8	1220-7-57	455
1 3/8		7/8	1220-13-7	152
		1 1/8	1220-13-13	186
		1 1/4	1220-13-17	219
		2 1/8	1220-13-23	253
		2 1/2	1220-13-27	286
		3 1/8	1220-13-33	320
		3 3/8	1220-13-37	354
		4 1/8	1220-13-47	421
		5 1/8	1220-13-57	488
1 7/8		7/8	1220-17-7	186
		1 1/8	1220-17-13	219
		1 1/4	1220-17-17	253
		2 1/8	1220-17-23	286
		2 1/2	1220-17-27	320
		3 1/8	1220-17-33	354
		3 3/8	1220-17-37	387
		4 1/8	1220-17-47	455
		5 1/8	1220-17-57	522
2 3/8		7/8	1220-23-7	219
		1 1/8	1220-23-13	253
		1 1/4	1220-23-17	286
		2 1/8	1220-23-23	320
		2 1/2	1220-23-27	354
		3 1/8	1220-23-33	387
		3 3/8	1220-23-37	421
		4 1/8	1220-23-47	488
		5 1/8	1220-23-57	556
2 7/8		7/8	1220-27-7	253
		1 1/8	1220-27-13	286
		1 1/4	1220-27-17	320
		2 1/8	1220-27-23	354
		2 1/2	1220-27-27	387
		3 1/8	1220-27-33	421
		3 3/8	1220-27-37	455
		4 1/8	1220-27-47	522
		5 1/8	1220-27-57	589

	A	B	ITEM NUMBER	NET WT.
3 3/8		7/8	1220-33-7	286
		1 1/8	1220-33-13	320
		1 1/4	1220-33-17	354
		2 1/8	1220-33-23	387
		2 1/2	1220-33-27	421
		3 1/8	1220-33-33	455
		3 3/8	1220-33-37	488
		4 1/8	1220-33-47	556
		5 1/8	1220-33-57	623
3 7/8		7/8	1220-37-7	320
		1 1/8	1220-37-13	354
		1 1/4	1220-37-17	387
		2 1/8	1220-37-23	421
		2 1/2	1220-37-27	455
		3 1/8	1220-37-33	488
		3 3/8	1220-37-37	522
		4 1/8	1220-37-47	589
		5 1/8	1220-37-57	656
4 7/8		7/8	1220-47-7	387
		1 1/8	1220-47-13	421
		1 1/4	1220-47-17	455
		2 1/8	1220-47-23	488
		2 1/2	1220-47-27	522
		3 1/8	1220-47-33	556
		3 3/8	1220-47-37	589
		4 1/8	1220-47-47	656
		5 1/8	1220-47-57	724
5 7/8		7/8	1220-57-7	455
		1 1/8	1220-57-13	488
		1 1/4	1220-57-17	522
		2 1/8	1220-57-23	556
		2 1/2	1220-57-27	589
		3 1/8	1220-57-33	623
		3 3/8	1220-57-37	656
		4 1/8	1220-57-47	724
		5 1/8	1220-57-57	791

	A	B	ITEM NUMBER	NET WT.
1 3/8		1 1/8	1223-13-13	218
		1 1/4	1223-13-17	257
		2 1/8	1223-13-23	297
		2 1/2	1223-13-27	336
		3 1/8	1223-13-33	376
		3 3/8	1223-13-37	416
		4 1/8	1223-13-47	495
		5 1/8	1223-13-57	574
	1 7/8		1 1/8	1223-17-13
		1 1/4	1223-17-17	297
		2 1/8	1223-17-23	336
		2 1/2	1223-17-27	376
		3 1/8	1223-17-33	416
		3 3/8	1223-17-37	455
		4 1/8	1223-17-47	534
		5 1/8	1223-17-57	613
2 3/8			1 1/8	1223-23-13
		1 1/4	1223-23-17	336
		2 1/8	1223-23-23	376
		2 1/2	1223-23-27	416
		3 1/8	1223-23-33	455
		3 3/8	1223-23-37	495
		4 1/8	1223-23-47	574
		5 1/8	1223-23-57	653
	2 7/8		1 1/8	1223-27-13
		1 1/4	1223-27-17	376
		2 1/8	1223-27-23	416
		2 1/2	1223-27-27	455
		3 1/8	1223-27-33	495
		3 3/8	1223-27-37	534
		4 1/8	1223-27-47	613
		5 1/8	1223-27-57	692

	A	B	ITEM NUMBER	NET WT.
3 3/8		1 1/8	1223-33-13	376
		1 1/4	1223-33-17	416
		2 1/8	1223-33-23	455
		2 1/2	1223-33-27	495
		3 1/8	1223-33-33	534
		3 3/8	1223-33-37	574
		4 1/8	1223-33-47	653
		5 1/8	1223-33-57	732
	3 7/8		1 1/8	1223-37-13
		1 1/4	1223-37-17	455
		2 1/8	1223-37-23	495
		2 1/2	1223-37-27	534
		3 1/8	1223-37-33	574
		3 3/8	1223-37-37	613
		4 1/8	1223-37-47	692
		5 1/8	1223-37-57	771
4 7/8			1 1/8	1223-47-13
		1 1/4	1223-47-17	534
		2 1/8	1223-47-23	574
		2 1/2	1223-47-27	613
		3 1/8	1223-47-33	653
		3 3/8	1223-47-37	692
		4 1/8	1223-47-47	771
		5 1/8	1223-47-57	850
	5 7/8		1 1/8	1223-57-13
		1 1/4	1223-57-17	613
		2 1/8	1223-57-23	653
		2 1/2	1223-57-27	692
		3 1/8	1223-57-33	732
		3 3/8	1223-57-37	771
		4 1/8	1223-57-47	850
		5 1/8	1223-57-57	929

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.



WHEN ORDERING, PLEASE SPECIFY:

- 1. Quantity & Item Number
- 2. No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2 7/8" thick)
- 3. L Dimension (Guide Pin Length)
- 4. Method of Shipment

[CONTACT US](#)

Cavity Retainer Sets 11 $\frac{7}{8}$ x 29 $\frac{1}{2}$ and 13 $\frac{3}{8}$ x 15"

Cavity Retainer Sets



A	B	ITEM NUMBER	NET WT.
1 $\frac{3}{8}$	1 $\frac{1}{8}$	1229-13-13	273
	1 $\frac{7}{8}$	1229-13-17	323
	2 $\frac{3}{8}$	1229-13-23	373
	2 $\frac{7}{8}$	1229-13-27	422
	3 $\frac{3}{8}$	1229-13-33	472
	3 $\frac{7}{8}$	1229-13-37	522
	4 $\frac{7}{8}$	1229-13-47	621
	5 $\frac{7}{8}$	1229-13-57	720
	1 $\frac{1}{8}$	1229-17-13	323
1 $\frac{7}{8}$	1 $\frac{7}{8}$	1229-17-17	373
	2 $\frac{3}{8}$	1229-17-23	422
	2 $\frac{7}{8}$	1229-17-27	472
	3 $\frac{3}{8}$	1229-17-33	522
	3 $\frac{7}{8}$	1229-17-37	571
	4 $\frac{7}{8}$	1229-17-47	670
	5 $\frac{7}{8}$	1229-17-57	770
	1 $\frac{1}{8}$	1229-23-13	373
	2 $\frac{3}{8}$	1 $\frac{1}{8}$	1229-23-17
2 $\frac{3}{8}$		1229-23-23	472
2 $\frac{7}{8}$		1229-23-27	522
3 $\frac{3}{8}$		1229-23-33	571
3 $\frac{7}{8}$		1229-23-37	621
4 $\frac{7}{8}$		1229-23-47	720
5 $\frac{7}{8}$		1229-23-57	819
1 $\frac{1}{8}$		1229-27-13	422
2 $\frac{7}{8}$		1 $\frac{1}{8}$	1229-27-17
	2 $\frac{3}{8}$	1229-27-23	522
	2 $\frac{7}{8}$	1229-27-27	571
	3 $\frac{3}{8}$	1229-27-33	621
	3 $\frac{7}{8}$	1229-27-37	670
	4 $\frac{7}{8}$	1229-27-47	770
	5 $\frac{7}{8}$	1229-27-57	869

A	B	ITEM NUMBER	NET WT.
3 $\frac{3}{8}$	1 $\frac{1}{8}$	1229-33-13	472
	1 $\frac{7}{8}$	1229-33-17	522
	2 $\frac{3}{8}$	1229-33-23	571
	2 $\frac{7}{8}$	1229-33-27	621
	3 $\frac{3}{8}$	1229-33-33	670
	3 $\frac{7}{8}$	1229-33-37	720
	4 $\frac{7}{8}$	1229-33-47	819
	5 $\frac{7}{8}$	1229-33-57	918
	1 $\frac{1}{8}$	1229-37-13	522
3 $\frac{7}{8}$	1 $\frac{7}{8}$	1229-37-17	571
	2 $\frac{3}{8}$	1229-37-23	621
	2 $\frac{7}{8}$	1229-37-27	670
	3 $\frac{3}{8}$	1229-37-33	720
	3 $\frac{7}{8}$	1229-37-37	770
	4 $\frac{7}{8}$	1229-37-47	869
	5 $\frac{7}{8}$	1229-37-57	968
	1 $\frac{1}{8}$	1229-47-13	621
	4 $\frac{7}{8}$	1 $\frac{7}{8}$	1229-47-17
2 $\frac{3}{8}$		1229-47-23	720
2 $\frac{7}{8}$		1229-47-27	770
3 $\frac{3}{8}$		1229-47-33	819
3 $\frac{7}{8}$		1229-47-37	869
4 $\frac{7}{8}$		1229-47-47	968
5 $\frac{7}{8}$		1229-47-57	1067
1 $\frac{1}{8}$		1229-57-13	720
5 $\frac{7}{8}$		1 $\frac{7}{8}$	1229-57-17
	2 $\frac{3}{8}$	1229-57-23	819
	2 $\frac{7}{8}$	1229-57-27	869
	3 $\frac{3}{8}$	1229-57-33	918
	3 $\frac{7}{8}$	1229-57-37	968
	4 $\frac{7}{8}$	1229-57-47	1067
	5 $\frac{7}{8}$	1229-57-57	1167

AVAILABLE WITH CHOICE OF LEADER PIN LOCATION:

TYPE A

For injection molds or die cast dies

DIM	TYPE	
	A	C
Q	6 $\frac{1}{16}$	6 $\frac{1}{2}$
R	5 $\frac{1}{16}$	4 $\frac{1}{4}$
S	6 $\frac{1}{8}$	6 $\frac{1}{2}$
T	5 $\frac{1}{16}$	4 $\frac{1}{16}$

TYPE C

For compression molds

A	B	ITEM NUMBER	NET WT.
7 $\frac{7}{8}$	7 $\frac{1}{8}$	1315-7-7	100
	1 $\frac{1}{8}$	1315-7-13	128
	1 $\frac{7}{8}$	1315-7-17	157
	2 $\frac{3}{8}$	1315-7-23	185
	2 $\frac{7}{8}$	1315-7-27	214
	3 $\frac{3}{8}$	1315-7-33	242
	3 $\frac{7}{8}$	1315-7-37	270
	4 $\frac{7}{8}$	1315-7-47	327
	5 $\frac{7}{8}$	1315-7-57	384
1 $\frac{3}{8}$	7 $\frac{1}{8}$	1315-13-7	128
	1 $\frac{1}{8}$	1315-13-13	157
	1 $\frac{7}{8}$	1315-13-17	185
	2 $\frac{3}{8}$	1315-13-23	214
	2 $\frac{7}{8}$	1315-13-27	242
	3 $\frac{3}{8}$	1315-13-33	270
	3 $\frac{7}{8}$	1315-13-37	299
	4 $\frac{7}{8}$	1315-13-47	356
	5 $\frac{7}{8}$	1315-13-57	413
1 $\frac{7}{8}$	7 $\frac{1}{8}$	1315-17-7	157
	1 $\frac{1}{8}$	1315-17-13	185
	1 $\frac{7}{8}$	1315-17-17	214
	2 $\frac{3}{8}$	1315-17-23	242
	2 $\frac{7}{8}$	1315-17-27	270
	3 $\frac{3}{8}$	1315-17-33	299
	3 $\frac{7}{8}$	1315-17-37	327
	4 $\frac{7}{8}$	1315-17-47	384
	5 $\frac{7}{8}$	1315-17-57	441
2 $\frac{3}{8}$	7 $\frac{1}{8}$	1315-23-7	185
	1 $\frac{1}{8}$	1315-23-13	214
	1 $\frac{7}{8}$	1315-23-17	242
	2 $\frac{3}{8}$	1315-23-23	270
	2 $\frac{7}{8}$	1315-23-27	299
	3 $\frac{3}{8}$	1315-23-33	327
	3 $\frac{7}{8}$	1315-23-37	356
	4 $\frac{7}{8}$	1315-23-47	413
	5 $\frac{7}{8}$	1315-23-57	469

A	B	ITEM NUMBER	NET WT.
2 $\frac{7}{8}$	7 $\frac{1}{8}$	1315-27-7	214
	1 $\frac{1}{8}$	1315-27-13	242
	1 $\frac{7}{8}$	1315-27-17	270
	2 $\frac{3}{8}$	1315-27-23	299
	2 $\frac{7}{8}$	1315-27-27	327
	3 $\frac{3}{8}$	1315-27-33	356
	3 $\frac{7}{8}$	1315-27-37	384
	4 $\frac{7}{8}$	1315-27-47	441
	5 $\frac{7}{8}$	1315-27-57	498
3 $\frac{3}{8}$	7 $\frac{1}{8}$	1315-33-7	242
	1 $\frac{1}{8}$	1315-33-13	270
	1 $\frac{7}{8}$	1315-33-17	299
	2 $\frac{3}{8}$	1315-33-23	327
	2 $\frac{7}{8}$	1315-33-27	356
	3 $\frac{3}{8}$	1315-33-33	384
	3 $\frac{7}{8}$	1315-33-37	413
	4 $\frac{7}{8}$	1315-33-47	469
	5 $\frac{7}{8}$	1315-33-57	526
3 $\frac{7}{8}$	7 $\frac{1}{8}$	1315-37-7	270
	1 $\frac{1}{8}$	1315-37-13	299
	1 $\frac{7}{8}$	1315-37-17	327
	2 $\frac{3}{8}$	1315-37-23	356
	2 $\frac{7}{8}$	1315-37-27	384
	3 $\frac{3}{8}$	1315-37-33	413
	3 $\frac{7}{8}$	1315-37-37	441
	4 $\frac{7}{8}$	1315-37-47	498
	5 $\frac{7}{8}$	1315-37-57	555
4 $\frac{7}{8}$	7 $\frac{1}{8}$	1315-47-7	327
	1 $\frac{1}{8}$	1315-47-13	356
	1 $\frac{7}{8}$	1315-47-17	384
	2 $\frac{3}{8}$	1315-47-23	413
	2 $\frac{7}{8}$	1315-47-27	441
	3 $\frac{3}{8}$	1315-47-33	469
	3 $\frac{7}{8}$	1315-47-37	498
	4 $\frac{7}{8}$	1315-47-47	555
	5 $\frac{7}{8}$	1315-47-57	612
5 $\frac{7}{8}$	7 $\frac{1}{8}$	1315-57-7	384
	1 $\frac{1}{8}$	1315-57-13	413
	1 $\frac{7}{8}$	1315-57-17	441
	2 $\frac{3}{8}$	1315-57-23	469
	2 $\frac{7}{8}$	1315-57-27	498
	3 $\frac{3}{8}$	1315-57-33	526
	3 $\frac{7}{8}$	1315-57-37	555
	4 $\frac{7}{8}$	1315-57-47	612
	5 $\frac{7}{8}$	1315-57-57	668

Thickness of each plate is finish ground ± .001".
Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2 $\frac{7}{8}$ thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

SPECIAL ORDER SIZES: Please contact DME.

CONTACT US

Cavity Retainer Sets 13 3/8" x 18" and 13 3/8" x 20 3/4"

Cavity Retainer Sets



A	B	ITEM NUMBER	NET WT.
7/8	7/8	1318-7-7	120
	1 1/8	1318-7-13	154
	1 1/4	1318-7-17	188
	2 1/8	1318-7-23	222
	2 1/2	1318-7-27	256
	3 1/8	1318-7-33	290
	3 1/4	1318-7-37	324
	4 1/8	1318-7-47	393
1 3/8	5 1/8	1318-7-57	461
	7/8	1318-13-7	154
	1 1/8	1318-13-13	188
	1 1/4	1318-13-17	222
	2 1/8	1318-13-23	256
	2 1/2	1318-13-27	290
	3 1/8	1318-13-33	324
	3 1/4	1318-13-37	359
1 7/8	4 1/8	1318-13-47	427
	5 1/8	1318-13-57	495
	7/8	1318-17-7	188
	1 1/8	1318-17-13	222
	1 1/4	1318-17-17	256
	2 1/8	1318-17-23	290
	2 1/2	1318-17-27	324
	3 1/8	1318-17-33	359
2 3/8	3 1/4	1318-17-37	393
	4 1/8	1318-17-47	461
	5 1/8	1318-17-57	529
	7/8	1318-23-7	222
	1 1/8	1318-23-13	256
	1 1/4	1318-23-17	290
	2 1/8	1318-23-23	324
	2 1/2	1318-23-27	359
2 7/8	3 1/8	1318-23-33	393
	3 1/4	1318-23-37	427
	4 1/8	1318-23-47	495
	5 1/8	1318-23-57	563
	7/8	1318-27-7	256
	1 1/8	1318-27-13	290
	1 1/4	1318-27-17	324
	2 1/8	1318-27-23	359
3 3/8	2 1/2	1318-27-27	393
	3 1/8	1318-27-33	427
	3 1/4	1318-27-37	461
	4 1/8	1318-27-47	529
	5 1/8	1318-27-57	597
	7/8	1318-33-7	290
	1 1/8	1318-33-13	324
	1 1/4	1318-33-17	359
3 7/8	2 1/8	1318-33-23	393
	2 1/2	1318-33-27	427
	3 1/8	1318-33-33	461
	3 1/4	1318-33-37	495
	4 1/8	1318-33-47	563
	5 1/8	1318-33-57	631
	7/8	1318-37-7	324
	1 1/8	1318-37-13	359
4 1/8	1 1/4	1318-37-17	393
	2 1/8	1318-37-23	427
	2 1/2	1318-37-27	461
	3 1/8	1318-37-33	495
	3 1/4	1318-37-37	529
	4 1/8	1318-37-47	597
	5 1/8	1318-37-57	665
	7/8	1318-47-7	393
4 7/8	1 1/8	1318-47-13	427
	1 1/4	1318-47-17	461
	2 1/8	1318-47-23	495
	2 1/2	1318-47-27	529
	3 1/8	1318-47-33	563
	3 1/4	1318-47-37	597
	4 1/8	1318-47-47	665
	5 1/8	1318-47-57	734
5 1/8	7/8	1318-57-7	461
	1 1/8	1318-57-13	495
	1 1/4	1318-57-17	529
	2 1/8	1318-57-23	563
	2 1/2	1318-57-27	597
	3 1/8	1318-57-33	631
	3 1/4	1318-57-37	665
	4 1/8	1318-57-47	734
5 1/8	1318-57-57	802	

A	B	ITEM NUMBER	NET WT.
3 3/8	7/8	1318-33-7	290
	1 1/8	1318-33-13	324
	1 1/4	1318-33-17	359
	2 1/8	1318-33-23	393
	2 1/2	1318-33-27	427
	3 1/8	1318-33-33	461
	3 1/4	1318-33-37	495
	4 1/8	1318-33-47	563
3 7/8	5 1/8	1318-33-57	631
	7/8	1318-37-7	324
	1 1/8	1318-37-13	359
	1 1/4	1318-37-17	393
	2 1/8	1318-37-23	427
	2 1/2	1318-37-27	461
	3 1/8	1318-37-33	495
	3 1/4	1318-37-37	529
4 1/8	4 1/8	1318-37-47	597
	5 1/8	1318-37-57	665
	7/8	1318-47-7	393
	1 1/8	1318-47-13	427
	1 1/4	1318-47-17	461
	2 1/8	1318-47-23	495
	2 1/2	1318-47-27	529
	3 1/8	1318-47-33	563
4 7/8	3 1/4	1318-47-37	597
	4 1/8	1318-47-47	665
	5 1/8	1318-47-57	734
	7/8	1318-57-7	461
	1 1/8	1318-57-13	495
	1 1/4	1318-57-17	529
	2 1/8	1318-57-23	563
	2 1/2	1318-57-27	597
5 1/8	3 1/8	1318-57-33	631
	3 1/4	1318-57-37	665
	4 1/8	1318-57-47	734
	5 1/8	1318-57-57	802

A	B	ITEM NUMBER	NET WT.
7/8	7/8	1321-7-7	138
	1 1/8	1321-7-13	177
	1 1/4	1321-7-17	217
	2 1/8	1321-7-23	256
	2 1/2	1321-7-27	295
	3 1/8	1321-7-33	335
	3 1/4	1321-7-37	374
	4 1/8	1321-7-47	453
1 3/8	5 1/8	1321-7-57	531
	7/8	1321-13-7	177
	1 1/8	1321-13-13	217
	1 1/4	1321-13-17	256
	2 1/8	1321-13-23	295
	2 1/2	1321-13-27	335
	3 1/8	1321-13-33	374
	3 1/4	1321-13-37	413
1 7/8	4 1/8	1321-13-47	492
	5 1/8	1321-13-57	570
	7/8	1321-17-7	217
	1 1/8	1321-17-13	256
	1 1/4	1321-17-17	295
	2 1/8	1321-17-23	335
	2 1/2	1321-17-27	374
	3 1/8	1321-17-33	413
2 3/8	3 1/4	1321-17-37	453
	4 1/8	1321-17-47	531
	5 1/8	1321-17-57	610
	7/8	1321-23-7	256
	1 1/8	1321-23-13	295
	1 1/4	1321-23-17	335
	2 1/8	1321-23-23	374
	2 1/2	1321-23-27	413
3 3/8	3 1/8	1321-23-33	453
	3 1/4	1321-23-37	492
	4 1/8	1321-23-47	570
	5 1/8	1321-23-57	649
	7/8	1321-27-7	295
	1 1/8	1321-27-13	335
	1 1/4	1321-27-17	374
	2 1/8	1321-27-23	413
3 7/8	2 1/2	1321-27-27	453
	3 1/8	1321-27-33	492
	3 1/4	1321-27-37	531
	4 1/8	1321-27-47	610
	5 1/8	1321-27-57	688
	7/8	1321-33-7	335
	1 1/8	1321-33-13	374
	1 1/4	1321-33-17	413
4 1/8	2 1/8	1321-33-23	453
	2 1/2	1321-33-27	492
	3 1/8	1321-33-33	531
	3 1/4	1321-33-37	570
	4 1/8	1321-33-47	649
	5 1/8	1321-33-57	728
	7/8	1321-37-7	374
	1 1/8	1321-37-13	413
4 7/8	1 1/4	1321-37-17	453
	2 1/8	1321-37-23	492
	2 1/2	1321-37-27	531
	3 1/8	1321-37-33	570
	3 1/4	1321-37-37	610
	4 1/8	1321-37-47	688
	5 1/8	1321-37-57	767
	7/8	1321-47-7	453
5 1/8	1 1/8	1321-47-13	492
	1 1/4	1321-47-17	531
	2 1/8	1321-47-23	570
	2 1/2	1321-47-27	610
	3 1/8	1321-47-33	649
	3 1/4	1321-47-37	688
	4 1/8	1321-47-47	767
	5 1/8	1321-47-57	846

A	B	ITEM NUMBER	NET WT.
2 7/8	7/8	1321-27-7	295
	1 1/8	1321-27-13	335
	1 1/4	1321-27-17	374
	2 1/8	1321-27-23	413
	2 1/2	1321-27-27	453
	3 1/8	1321-27-33	492
	3 1/4	1321-27-37	531
	4 1/8	1321-27-47	610
3 3/8	5 1/8	1321-27-57	688
	7/8	1321-33-7	335
	1 1/8	1321-33-13	374
	1 1/4	1321-33-17	413
	2 1/8	1321-33-23	453
	2 1/2	1321-33-27	492
	3 1/8	1321-33-33	531
	3 1/4	1321-33-37	570
3 7/8	4 1/8	1321-33-47	649
	5 1/8	1321-33-57	728
	7/8	1321-37-7	374
	1 1/8	1321-37-13	413
	1 1/4	1321-37-17	453
	2 1/8	1321-37-23	492
	2 1/2	1321-37-27	531
	3 1/8	1321-37-33	570
4 1/8	3 1/4	1321-37-37	610
	4 1/8	1321-37-47	688
	5 1/8	1321-37-57	767
	7/8	1321-47-7	453
	1 1/8	1321-47-13	492
	1 1/4	1321-47-17	531
	2 1/8	1321-47-23	570
	2 1/2	1321-47-27	610
4 7/8	3 1/8	1321-47-33	649
	3 1/4	1321-47-37	688
	4 1/8	1321-47-47	767
	5 1/8	1321-47-57	846
	7/8	1321-57-7	531
	1 1/8	1321-57-13	570
	1 1/4	1321-57-17	610
	2 1/8	1321-57-23	649
5 1/8	2 1/2	1321-57-27	688
	3 1/8	1321-57-33	728
	3 1/4	1321-57-37	767
	4 1/8	1321-57-47	846
	5 1/8	1321-57-57	924

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2 7/8" thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

CONTACT US

Cavity Retainer Sets

13³/₈ × 23¹/₂ and 13³/₈ × 26"

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1 ³ / ₈	1 ¹ / ₈	1323-13-13	245
	1 ¹ / ₈	1323-13-17	290
	2 ¹ / ₈	1323-13-23	334
	2 ¹ / ₈	1323-13-27	379
	3 ¹ / ₈	1323-13-33	423
	3 ¹ / ₈	1323-13-37	468
	4 ¹ / ₈	1323-13-47	557
	5 ¹ / ₈	1323-13-57	646
1 ⁷ / ₈	1 ¹ / ₈	1323-17-13	290
	1 ¹ / ₈	1323-17-17	334
	2 ¹ / ₈	1323-17-23	379
	2 ¹ / ₈	1323-17-27	423
	3 ¹ / ₈	1323-17-33	468
	3 ¹ / ₈	1323-17-37	512
	4 ¹ / ₈	1323-17-47	602
	5 ¹ / ₈	1323-17-57	691
2 ³ / ₈	1 ¹ / ₈	1323-23-13	334
	1 ¹ / ₈	1323-23-17	379
	2 ¹ / ₈	1323-23-23	423
	2 ¹ / ₈	1323-23-27	468
	3 ¹ / ₈	1323-23-33	512
	3 ¹ / ₈	1323-23-37	557
	4 ¹ / ₈	1323-23-47	646
	5 ¹ / ₈	1323-23-57	735
2 ⁷ / ₈	1 ¹ / ₈	1323-27-13	379
	1 ¹ / ₈	1323-27-17	423
	2 ¹ / ₈	1323-27-23	468
	2 ¹ / ₈	1323-27-27	512
	3 ¹ / ₈	1323-27-33	557
	3 ¹ / ₈	1323-27-37	602
	4 ¹ / ₈	1323-27-47	691
	5 ¹ / ₈	1323-27-57	780

A	B	ITEM NUMBER	NET WT.
3 ³ / ₈	1 ¹ / ₈	1323-33-13	423
	1 ¹ / ₈	1323-33-17	468
	2 ¹ / ₈	1323-33-23	512
	2 ¹ / ₈	1323-33-27	557
	3 ¹ / ₈	1323-33-33	602
	3 ¹ / ₈	1323-33-37	646
	4 ¹ / ₈	1323-33-47	735
	5 ¹ / ₈	1323-33-57	824
3 ⁷ / ₈	1 ¹ / ₈	1323-37-13	468
	1 ¹ / ₈	1323-37-17	512
	2 ¹ / ₈	1323-37-23	557
	2 ¹ / ₈	1323-37-27	602
	3 ¹ / ₈	1323-37-33	646
	3 ¹ / ₈	1323-37-37	691
	4 ¹ / ₈	1323-37-47	780
	5 ¹ / ₈	1323-37-57	869
4 ⁷ / ₈	1 ¹ / ₈	1323-47-13	557
	1 ¹ / ₈	1323-47-17	602
	2 ¹ / ₈	1323-47-23	646
	2 ¹ / ₈	1323-47-27	691
	3 ¹ / ₈	1323-47-33	735
	3 ¹ / ₈	1323-47-37	780
	4 ¹ / ₈	1323-47-47	869
	5 ¹ / ₈	1323-47-57	958
5 ⁷ / ₈	1 ¹ / ₈	1323-57-13	646
	1 ¹ / ₈	1323-57-17	691
	2 ¹ / ₈	1323-57-23	735
	2 ¹ / ₈	1323-57-27	780
	3 ¹ / ₈	1323-57-33	824
	3 ¹ / ₈	1323-57-37	869
	4 ¹ / ₈	1323-57-47	958
	5 ¹ / ₈	1323-57-57	1047

A	B	ITEM NUMBER	NET WT.
1 ³ / ₈	1 ¹ / ₈	1326-13-13	271
	1 ¹ / ₈	1326-13-17	321
	2 ¹ / ₈	1326-13-23	370
	2 ¹ / ₈	1326-13-27	419
	3 ¹ / ₈	1326-13-33	468
	3 ¹ / ₈	1326-13-37	518
	4 ¹ / ₈	1326-13-47	616
	5 ¹ / ₈	1326-13-57	715
1 ⁷ / ₈	1 ¹ / ₈	1326-17-13	321
	1 ¹ / ₈	1326-17-17	370
	2 ¹ / ₈	1326-17-23	419
	2 ¹ / ₈	1326-17-27	468
	3 ¹ / ₈	1326-17-33	518
	3 ¹ / ₈	1326-17-37	567
	4 ¹ / ₈	1326-17-47	666
	5 ¹ / ₈	1326-17-57	764
2 ³ / ₈	1 ¹ / ₈	1326-23-13	370
	1 ¹ / ₈	1326-23-17	419
	2 ¹ / ₈	1326-23-23	468
	2 ¹ / ₈	1326-23-27	518
	3 ¹ / ₈	1326-23-33	567
	3 ¹ / ₈	1326-23-37	616
	4 ¹ / ₈	1326-23-47	715
	5 ¹ / ₈	1326-23-57	813
2 ⁷ / ₈	1 ¹ / ₈	1326-27-13	419
	1 ¹ / ₈	1326-27-17	468
	2 ¹ / ₈	1326-27-23	518
	2 ¹ / ₈	1326-27-27	567
	3 ¹ / ₈	1326-27-33	616
	3 ¹ / ₈	1326-27-37	666
	4 ¹ / ₈	1326-27-47	764
	5 ¹ / ₈	1326-27-57	863

A	B	ITEM NUMBER	NET WT.
3 ³ / ₈	1 ¹ / ₈	1326-33-13	468
	1 ¹ / ₈	1326-33-17	518
	2 ¹ / ₈	1326-33-23	567
	2 ¹ / ₈	1326-33-27	616
	3 ¹ / ₈	1326-33-33	666
	3 ¹ / ₈	1326-33-37	715
	4 ¹ / ₈	1326-33-47	813
	5 ¹ / ₈	1326-33-57	912
3 ⁷ / ₈	1 ¹ / ₈	1326-37-13	518
	1 ¹ / ₈	1326-37-17	567
	2 ¹ / ₈	1326-37-23	616
	2 ¹ / ₈	1326-37-27	666
	3 ¹ / ₈	1326-37-33	715
	3 ¹ / ₈	1326-37-37	764
	4 ¹ / ₈	1326-37-47	863
	5 ¹ / ₈	1326-37-57	961
4 ⁷ / ₈	1 ¹ / ₈	1326-47-13	616
	1 ¹ / ₈	1326-47-17	666
	2 ¹ / ₈	1326-47-23	715
	2 ¹ / ₈	1326-47-27	764
	3 ¹ / ₈	1326-47-33	813
	3 ¹ / ₈	1326-47-37	863
	4 ¹ / ₈	1326-47-47	961
	5 ¹ / ₈	1326-47-57	1060
5 ⁷ / ₈	1 ¹ / ₈	1326-57-13	715
	1 ¹ / ₈	1326-57-17	764
	2 ¹ / ₈	1326-57-23	813
	2 ¹ / ₈	1326-57-27	863
	3 ¹ / ₈	1326-57-33	912
	3 ¹ / ₈	1326-57-37	961
	4 ¹ / ₈	1326-57-47	1060
	5 ¹ / ₈	1326-57-57	1158

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



1. Quantity & Item Number
2. No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2% thick)
3. L Dimension (Guide Pin Length)
4. Method of Shipment

CONTACT US

Cavity Retainer Sets

13³/₈ × 29¹/₂ and 14⁷/₈ × 17⁷/₈

CAVITY RETAINER SETS



	A	B	ITEM NUMBER	NET WT.
1³/₈		1 ³ / ₈	1329-13-13	308
		1 ⁷ / ₈	1329-13-17	364
		2 ¹ / ₈	1329-13-23	420
		2 ³ / ₈	1329-13-27	476
		3 ¹ / ₈	1329-13-33	531
		3 ³ / ₈	1329-13-37	587
		4 ¹ / ₈	1329-13-47	699
		5 ¹ / ₈	1329-13-57	811
1⁷/₈		1 ³ / ₈	1329-17-13	364
		1 ⁷ / ₈	1329-17-17	420
		2 ¹ / ₈	1329-17-23	476
		2 ³ / ₈	1329-17-27	531
		3 ¹ / ₈	1329-17-33	587
		3 ³ / ₈	1329-17-37	643
		4 ¹ / ₈	1329-17-47	755
		5 ¹ / ₈	1329-17-57	867
2³/₈		1 ³ / ₈	1329-23-13	420
		1 ⁷ / ₈	1329-23-17	476
		2 ¹ / ₈	1329-23-23	531
		2 ³ / ₈	1329-23-27	587
		3 ¹ / ₈	1329-23-33	643
		3 ³ / ₈	1329-23-37	699
		4 ¹ / ₈	1329-23-47	811
		5 ¹ / ₈	1329-23-57	923
2⁷/₈		1 ³ / ₈	1329-27-13	476
		1 ⁷ / ₈	1329-27-17	531
		2 ¹ / ₈	1329-27-23	587
		2 ³ / ₈	1329-27-27	643
		3 ¹ / ₈	1329-27-33	699
		3 ³ / ₈	1329-27-37	755
		4 ¹ / ₈	1329-27-47	867
		5 ¹ / ₈	1329-27-57	979

	A	B	ITEM NUMBER	NET WT.
3³/₈		1 ³ / ₈	1329-33-13	531
		1 ⁷ / ₈	1329-33-17	587
		2 ¹ / ₈	1329-33-23	643
		2 ³ / ₈	1329-33-27	699
		3 ¹ / ₈	1329-33-33	755
		3 ³ / ₈	1329-33-37	811
		4 ¹ / ₈	1329-33-47	923
		5 ¹ / ₈	1329-33-57	1034
3⁷/₈		1 ³ / ₈	1329-37-13	587
		1 ⁷ / ₈	1329-37-17	643
		2 ¹ / ₈	1329-37-23	699
		2 ³ / ₈	1329-37-27	755
		3 ¹ / ₈	1329-37-33	811
		3 ³ / ₈	1329-37-37	867
		4 ¹ / ₈	1329-37-47	979
		5 ¹ / ₈	1329-37-57	1090
4⁷/₈		1 ³ / ₈	1329-47-13	699
		1 ⁷ / ₈	1329-47-17	755
		2 ¹ / ₈	1329-47-23	811
		2 ³ / ₈	1329-47-27	867
		3 ¹ / ₈	1329-47-33	923
		3 ³ / ₈	1329-47-37	979
		4 ¹ / ₈	1329-47-47	1090
		5 ¹ / ₈	1329-47-57	1202
5⁷/₈		1 ³ / ₈	1329-57-13	811
		1 ⁷ / ₈	1329-57-17	867
		2 ¹ / ₈	1329-57-23	923
		2 ³ / ₈	1329-57-27	979
		3 ¹ / ₈	1329-57-33	1034
		3 ³ / ₈	1329-57-37	1090
		4 ¹ / ₈	1329-57-47	1202
		5 ¹ / ₈	1329-57-57	1314

	A	B	ITEM NUMBER	NET WT.
7⁷/₈		7 ⁷ / ₈	1518-7-7	132
		1 ³ / ₈	1518-7-13	170
		1 ⁷ / ₈	1518-7-17	208
		2 ¹ / ₈	1518-7-23	245
		2 ³ / ₈	1518-7-27	283
		3 ¹ / ₈	1518-7-33	321
		3 ³ / ₈	1518-7-37	358
		4 ¹ / ₈	1518-7-47	434
1³/₈		5 ¹ / ₈	1518-7-57	509
		7 ⁷ / ₈	1518-13-7	170
		1 ³ / ₈	1518-13-13	208
		1 ⁷ / ₈	1518-13-17	245
		2 ¹ / ₈	1518-13-23	283
		2 ³ / ₈	1518-13-27	321
		3 ¹ / ₈	1518-13-33	358
		3 ³ / ₈	1518-13-37	396
1⁷/₈		4 ¹ / ₈	1518-13-47	471
		5 ¹ / ₈	1518-13-57	547
		7 ⁷ / ₈	1518-17-7	208
		1 ³ / ₈	1518-17-13	245
		1 ⁷ / ₈	1518-17-17	283
		2 ¹ / ₈	1518-17-23	321
		2 ³ / ₈	1518-17-27	358
		3 ¹ / ₈	1518-17-33	396
2³/₈		3 ³ / ₈	1518-17-37	434
		4 ¹ / ₈	1518-17-47	509
		5 ¹ / ₈	1518-17-57	584
		7 ⁷ / ₈	1518-23-7	245
		1 ³ / ₈	1518-23-13	283
		1 ⁷ / ₈	1518-23-17	321
		2 ¹ / ₈	1518-23-23	358
		2 ³ / ₈	1518-23-27	396
3⁷/₈		3 ¹ / ₈	1518-23-33	434
		3 ³ / ₈	1518-23-37	471
		4 ¹ / ₈	1518-23-47	547
		5 ¹ / ₈	1518-23-57	622
		7 ⁷ / ₈	1518-27-7	283
		1 ³ / ₈	1518-27-13	321
		1 ⁷ / ₈	1518-27-17	358
		2 ¹ / ₈	1518-27-23	396

	A	B	ITEM NUMBER	NET WT.
2⁷/₈		7 ⁷ / ₈	1518-27-7	283
		1 ³ / ₈	1518-27-13	321
		1 ⁷ / ₈	1518-27-17	358
		2 ¹ / ₈	1518-27-23	396
		2 ³ / ₈	1518-27-27	434
		3 ¹ / ₈	1518-27-33	471
		3 ³ / ₈	1518-27-37	509
		4 ¹ / ₈	1518-27-47	584
3³/₈		5 ¹ / ₈	1518-27-57	660
		7 ⁷ / ₈	1518-33-7	321
		1 ³ / ₈	1518-33-13	358
		1 ⁷ / ₈	1518-33-17	396
		2 ¹ / ₈	1518-33-23	434
		2 ³ / ₈	1518-33-27	471
		3 ¹ / ₈	1518-33-33	509
		3 ³ / ₈	1518-33-37	547
3⁷/₈		4 ¹ / ₈	1518-33-47	622
		5 ¹ / ₈	1518-33-57	697
		7 ⁷ / ₈	1518-37-7	358
		1 ³ / ₈	1518-37-13	396
		1 ⁷ / ₈	1518-37-17	434
		2 ¹ / ₈	1518-37-23	471
		2 ³ / ₈	1518-37-27	509
		3 ¹ / ₈	1518-37-33	547
4⁷/₈		3 ³ / ₈	1518-37-37	584
		4 ¹ / ₈	1518-37-47	660
		5 ¹ / ₈	1518-37-57	735
		7 ⁷ / ₈	1518-47-7	434
		1 ³ / ₈	1518-47-13	471
		1 ⁷ / ₈	1518-47-17	509
		2 ¹ / ₈	1518-47-23	547
		2 ³ / ₈	1518-47-27	584
5⁷/₈		3 ¹ / ₈	1518-47-33	622
		3 ³ / ₈	1518-47-37	660
		4 ¹ / ₈	1518-47-47	735
		5 ¹ / ₈	1518-47-57	810
		7 ⁷ / ₈	1518-57-7	509
		1 ³ / ₈	1518-57-13	547
		1 ⁷ / ₈	1518-57-17	584
		2 ¹ / ₈	1518-57-23	622

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2% thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

CONTACT US

Cavity Retainer Sets

14⁷/₈ × 23³/₄ and 14⁷/₈ × 29¹/₂

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1³/₈	1 ³ / ₈	1524-13-13	276
	1 ⁷ / ₈	1524-13-17	326
	2 ³ / ₈	1524-13-23	376
	2 ⁷ / ₈	1524-13-27	426
	3 ³ / ₈	1524-13-33	476
	3 ⁷ / ₈	1524-13-37	526
	4 ³ / ₈	1524-13-47	626
	5 ³ / ₈	1524-13-57	726
1⁷/₈	1 ³ / ₈	1524-17-13	326
	1 ⁷ / ₈	1524-17-17	376
	2 ³ / ₈	1524-17-23	426
	2 ⁷ / ₈	1524-17-27	476
	3 ³ / ₈	1524-17-33	526
	3 ⁷ / ₈	1524-17-37	576
	4 ³ / ₈	1524-17-47	676
	5 ³ / ₈	1524-17-57	776
2³/₈	1 ³ / ₈	1524-23-13	376
	1 ⁷ / ₈	1524-23-17	426
	2 ³ / ₈	1524-23-23	476
	2 ⁷ / ₈	1524-23-27	526
	3 ³ / ₈	1524-23-33	576
	3 ⁷ / ₈	1524-23-37	626
	4 ³ / ₈	1524-23-47	726
	5 ³ / ₈	1524-23-57	826
2⁷/₈	1 ³ / ₈	1524-27-13	426
	1 ⁷ / ₈	1524-27-17	476
	2 ³ / ₈	1524-27-23	526
	2 ⁷ / ₈	1524-27-27	576
	3 ³ / ₈	1524-27-33	626
	3 ⁷ / ₈	1524-27-37	676
	4 ³ / ₈	1524-27-47	776
	5 ³ / ₈	1524-27-57	876

A	B	ITEM NUMBER	NET WT.
3³/₈	1 ³ / ₈	1524-33-13	476
	1 ⁷ / ₈	1524-33-17	526
	2 ³ / ₈	1524-33-23	576
	2 ⁷ / ₈	1524-33-27	626
	3 ³ / ₈	1524-33-33	676
	3 ⁷ / ₈	1524-33-37	726
	4 ³ / ₈	1524-33-47	826
	5 ³ / ₈	1524-33-57	926
3⁷/₈	1 ³ / ₈	1524-37-13	526
	1 ⁷ / ₈	1524-37-17	576
	2 ³ / ₈	1524-37-23	626
	2 ⁷ / ₈	1524-37-27	676
	3 ³ / ₈	1524-37-33	726
	3 ⁷ / ₈	1524-37-37	776
	4 ³ / ₈	1524-37-47	876
	5 ³ / ₈	1524-37-57	976
4⁷/₈	1 ³ / ₈	1524-47-13	626
	1 ⁷ / ₈	1524-47-17	676
	2 ³ / ₈	1524-47-23	726
	2 ⁷ / ₈	1524-47-27	776
	3 ³ / ₈	1524-47-33	826
	3 ⁷ / ₈	1524-47-37	876
	4 ³ / ₈	1524-47-47	976
	5 ³ / ₈	1524-47-57	1076
5⁷/₈	1 ³ / ₈	1524-57-13	726
	1 ⁷ / ₈	1524-57-17	776
	2 ³ / ₈	1524-57-23	826
	2 ⁷ / ₈	1524-57-27	876
	3 ³ / ₈	1524-57-33	926
	3 ⁷ / ₈	1524-57-37	976
	4 ³ / ₈	1524-57-47	1076
	5 ³ / ₈	1524-57-57	1176

A	B	ITEM NUMBER	NET WT.
1³/₈	1 ³ / ₈	1529-13-13	342
	1 ⁷ / ₈	1529-13-17	405
	2 ³ / ₈	1529-13-23	467
	2 ⁷ / ₈	1529-13-27	529
	3 ³ / ₈	1529-13-33	591
	3 ⁷ / ₈	1529-13-37	653
	4 ³ / ₈	1529-13-47	777
	5 ³ / ₈	1529-13-57	902
1⁷/₈	1 ³ / ₈	1529-17-13	405
	1 ⁷ / ₈	1529-17-17	467
	2 ³ / ₈	1529-17-23	529
	2 ⁷ / ₈	1529-17-27	591
	3 ³ / ₈	1529-17-33	653
	3 ⁷ / ₈	1529-17-37	715
	4 ³ / ₈	1529-17-47	840
	5 ³ / ₈	1529-17-57	964
2³/₈	1 ³ / ₈	1529-23-13	467
	1 ⁷ / ₈	1529-23-17	529
	2 ³ / ₈	1529-23-23	591
	2 ⁷ / ₈	1529-23-27	653
	3 ³ / ₈	1529-23-33	715
	3 ⁷ / ₈	1529-23-37	777
	4 ³ / ₈	1529-23-47	902
	5 ³ / ₈	1529-23-57	1026
2⁷/₈	1 ³ / ₈	1529-27-13	529
	1 ⁷ / ₈	1529-27-17	591
	2 ³ / ₈	1529-27-23	653
	2 ⁷ / ₈	1529-27-27	715
	3 ³ / ₈	1529-27-33	777
	3 ⁷ / ₈	1529-27-37	840
	4 ³ / ₈	1529-27-47	964
	5 ³ / ₈	1529-27-57	1088

A	B	ITEM NUMBER	NET WT.
3³/₈	1 ³ / ₈	1529-33-13	591
	1 ⁷ / ₈	1529-33-17	653
	2 ³ / ₈	1529-33-23	715
	2 ⁷ / ₈	1529-33-27	777
	3 ³ / ₈	1529-33-33	840
	3 ⁷ / ₈	1529-33-37	902
	4 ³ / ₈	1529-33-47	1026
	5 ³ / ₈	1529-33-57	1150
3⁷/₈	1 ³ / ₈	1529-37-13	653
	1 ⁷ / ₈	1529-37-17	715
	2 ³ / ₈	1529-37-23	777
	2 ⁷ / ₈	1529-37-27	840
	3 ³ / ₈	1529-37-33	902
	3 ⁷ / ₈	1529-37-37	964
	4 ³ / ₈	1529-37-47	1088
	5 ³ / ₈	1529-37-57	1213
4⁷/₈	1 ³ / ₈	1529-47-13	777
	1 ⁷ / ₈	1529-47-17	840
	2 ³ / ₈	1529-47-23	902
	2 ⁷ / ₈	1529-47-27	964
	3 ³ / ₈	1529-47-33	1026
	3 ⁷ / ₈	1529-47-37	1088
	4 ³ / ₈	1529-47-47	1213
	5 ³ / ₈	1529-47-57	1337
5⁷/₈	1 ³ / ₈	1529-57-13	902
	1 ⁷ / ₈	1529-57-17	964
	2 ³ / ₈	1529-57-23	1026
	2 ⁷ / ₈	1529-57-27	1088
	3 ³ / ₈	1529-57-33	1150
	3 ⁷ / ₈	1529-57-37	1213
	4 ³ / ₈	1529-57-47	1337
	5 ³ / ₈	1529-57-57	1461

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- 1. Quantity & Item Number
- 2. No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2⁷/₈ thick)
- 3. L Dimension (Guide Pin Length)
- 4. Method of Shipment

CONTACT US

Cavity Retainer Sets

15 7/8 x 16" and 15 7/8 x 20"

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
7/8	7/8	1616-7-7	126
	1 1/8	1616-7-13	162
	1 1/8	1616-7-17	198
	2 1/8	1616-7-23	234
	2 1/8	1616-7-27	270
	3 1/8	1616-7-33	306
	3 1/8	1616-7-37	342
	4 1/8	1616-7-47	414
	5 1/8	1616-7-57	486
1 3/8	7/8	1616-13-7	162
	1 1/8	1616-13-13	198
	1 1/8	1616-13-17	234
	2 1/8	1616-13-23	270
	2 1/8	1616-13-27	306
	3 1/8	1616-13-33	342
	3 1/8	1616-13-37	378
	4 1/8	1616-13-47	450
	5 1/8	1616-13-57	522
1 7/8	7/8	1616-17-7	198
	1 1/8	1616-17-13	234
	1 1/8	1616-17-17	270
	2 1/8	1616-17-23	306
	2 1/8	1616-17-27	342
	3 1/8	1616-17-33	378
	3 1/8	1616-17-37	414
	4 1/8	1616-17-47	486
	5 1/8	1616-17-57	558
2 3/8	7/8	1616-23-7	234
	1 1/8	1616-23-13	270
	1 1/8	1616-23-17	306
	2 1/8	1616-23-23	342
	2 1/8	1616-23-27	378
	3 1/8	1616-23-33	414
	3 1/8	1616-23-37	450
	4 1/8	1616-23-47	522
	5 1/8	1616-23-57	594
2 7/8	7/8	1616-27-7	270
	1 1/8	1616-27-13	306
	1 1/8	1616-27-17	342
	2 1/8	1616-27-23	378
	2 1/8	1616-27-27	414
	3 1/8	1616-27-33	450
	3 1/8	1616-27-37	486
	4 1/8	1616-27-47	558
	5 1/8	1616-27-57	630

A	B	ITEM NUMBER	NET WT.
3 3/8	7/8	1616-33-7	306
	1 1/8	1616-33-13	342
	1 1/8	1616-33-17	378
	2 1/8	1616-33-23	414
	2 1/8	1616-33-27	450
	3 1/8	1616-33-33	486
	3 1/8	1616-33-37	522
	4 1/8	1616-33-47	594
	5 1/8	1616-33-57	666
3 7/8	7/8	1616-37-7	342
	1 1/8	1616-37-13	378
	1 1/8	1616-37-17	414
	2 1/8	1616-37-23	450
	2 1/8	1616-37-27	486
	3 1/8	1616-37-33	522
	3 1/8	1616-37-37	558
	4 1/8	1616-37-47	630
	5 1/8	1616-37-57	702
4 7/8	7/8	1616-47-7	414
	1 1/8	1616-47-13	450
	1 1/8	1616-47-17	486
	2 1/8	1616-47-23	522
	2 1/8	1616-47-27	558
	3 1/8	1616-47-33	594
	3 1/8	1616-47-37	630
	4 1/8	1616-47-47	702
	5 1/8	1616-47-57	774
5 7/8	7/8	1616-57-7	486
	1 1/8	1616-57-13	522
	1 1/8	1616-57-17	558
	2 1/8	1616-57-23	594
	2 1/8	1616-57-27	630
	3 1/8	1616-57-33	666
	3 1/8	1616-57-37	702
	4 1/8	1616-57-47	774
	5 1/8	1616-57-57	846

A	B	ITEM NUMBER	NET WT.
7/8	7/8	1620-7-7	158
	1 1/8	1620-7-13	203
	1 1/8	1620-7-17	248
	2 1/8	1620-7-23	293
	2 1/8	1620-7-27	338
	3 1/8	1620-7-33	383
	3 1/8	1620-7-37	428
	4 1/8	1620-7-47	518
	5 1/8	1620-7-57	608
1 3/8	7/8	1620-13-7	203
	1 1/8	1620-13-13	248
	1 1/8	1620-13-17	293
	2 1/8	1620-13-23	338
	2 1/8	1620-13-27	383
	3 1/8	1620-13-33	428
	3 1/8	1620-13-37	473
	4 1/8	1620-13-47	563
	5 1/8	1620-13-57	653
1 7/8	7/8	1620-17-7	248
	1 1/8	1620-17-13	293
	1 1/8	1620-17-17	338
	2 1/8	1620-17-23	383
	2 1/8	1620-17-27	428
	3 1/8	1620-17-33	473
	3 1/8	1620-17-37	518
	4 1/8	1620-17-47	608
	5 1/8	1620-17-57	698
2 3/8	7/8	1620-23-7	293
	1 1/8	1620-23-13	338
	1 1/8	1620-23-17	383
	2 1/8	1620-23-23	428
	2 1/8	1620-23-27	473
	3 1/8	1620-23-33	518
	3 1/8	1620-23-37	563
	4 1/8	1620-23-47	653
	5 1/8	1620-23-57	743

A	B	ITEM NUMBER	NET WT.
2 7/8	7/8	1620-27-7	338
	1 1/8	1620-27-13	383
	1 1/8	1620-27-17	428
	2 1/8	1620-27-23	473
	2 1/8	1620-27-27	518
	3 1/8	1620-27-33	563
	3 1/8	1620-27-37	608
	4 1/8	1620-27-47	698
	5 1/8	1620-27-57	787
3 3/8	7/8	1620-33-7	383
	1 1/8	1620-33-13	428
	1 1/8	1620-33-17	473
	2 1/8	1620-33-23	518
	2 1/8	1620-33-27	563
	3 1/8	1620-33-33	608
	3 1/8	1620-33-37	653
	4 1/8	1620-33-47	743
	5 1/8	1620-33-57	832
3 7/8	7/8	1620-37-7	428
	1 1/8	1620-37-13	473
	1 1/8	1620-37-17	518
	2 1/8	1620-37-23	563
	2 1/8	1620-37-27	608
	3 1/8	1620-37-33	653
	3 1/8	1620-37-37	698
	4 1/8	1620-37-47	787
	5 1/8	1620-37-57	877
4 7/8	7/8	1620-47-7	518
	1 1/8	1620-47-13	563
	1 1/8	1620-47-17	608
	2 1/8	1620-47-23	653
	2 1/8	1620-47-27	698
	3 1/8	1620-47-33	743
	3 1/8	1620-47-37	787
	4 1/8	1620-47-47	877
	5 1/8	1620-47-57	967
5 7/8	7/8	1620-57-7	608
	1 1/8	1620-57-13	653
	1 1/8	1620-57-17	698
	2 1/8	1620-57-23	743
	2 1/8	1620-57-27	787
	3 1/8	1620-57-33	832
	3 1/8	1620-57-37	877
	4 1/8	1620-57-47	967
	5 1/8	1620-57-57	1057

Thickness of each plate is finish ground $\pm .001"$. Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- 1. Quantity & Item Number
- 2. No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2% thick)
- 3. L Dimension (Guide Pin Length)
- 4. Method of Shipment

CONTACT US

Cavity Retainer Sets

15 $\frac{7}{8}$ x 23 $\frac{1}{2}$ and 15 $\frac{7}{8}$ x 26"

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1 $\frac{3}{8}$	1 $\frac{1}{8}$	1623-13-13	291
	1 $\frac{1}{8}$	1623-13-17	344
	2 $\frac{3}{8}$	1623-13-23	397
	2 $\frac{7}{8}$	1623-13-27	450
	3 $\frac{3}{8}$	1623-13-33	503
	3 $\frac{7}{8}$	1623-13-37	555
	4 $\frac{3}{8}$	1623-13-47	661
	5 $\frac{3}{8}$	1623-13-57	767
1 $\frac{7}{8}$	1 $\frac{1}{8}$	1623-17-13	344
	1 $\frac{1}{8}$	1623-17-17	397
	2 $\frac{3}{8}$	1623-17-23	450
	2 $\frac{7}{8}$	1623-17-27	502
	3 $\frac{3}{8}$	1623-17-33	555
	3 $\frac{7}{8}$	1623-17-37	608
	4 $\frac{3}{8}$	1623-17-47	714
	5 $\frac{3}{8}$	1623-17-57	820
2 $\frac{3}{8}$	1 $\frac{1}{8}$	1623-23-13	397
	1 $\frac{1}{8}$	1623-23-17	450
	2 $\frac{3}{8}$	1623-23-23	502
	2 $\frac{7}{8}$	1623-23-27	555
	3 $\frac{3}{8}$	1623-23-33	608
	3 $\frac{7}{8}$	1623-23-37	661
	4 $\frac{3}{8}$	1623-23-47	767
	5 $\frac{3}{8}$	1623-23-57	872
2 $\frac{7}{8}$	1 $\frac{1}{8}$	1623-27-13	450
	1 $\frac{1}{8}$	1623-27-17	502
	2 $\frac{3}{8}$	1623-27-23	555
	2 $\frac{7}{8}$	1623-27-27	608
	3 $\frac{3}{8}$	1623-27-33	661
	3 $\frac{7}{8}$	1623-27-37	714
	4 $\frac{3}{8}$	1623-27-47	820
	5 $\frac{3}{8}$	1623-27-57	925

A	B	ITEM NUMBER	NET WT.
3 $\frac{3}{8}$	1 $\frac{1}{8}$	1623-33-13	502
	1 $\frac{1}{8}$	1623-33-17	555
	2 $\frac{3}{8}$	1623-33-23	608
	2 $\frac{7}{8}$	1623-33-27	661
	3 $\frac{3}{8}$	1623-33-33	714
	3 $\frac{7}{8}$	1623-33-37	767
	4 $\frac{3}{8}$	1623-33-47	872
	5 $\frac{3}{8}$	1623-33-57	978
3 $\frac{7}{8}$	1 $\frac{1}{8}$	1623-37-13	555
	1 $\frac{1}{8}$	1623-37-17	608
	2 $\frac{3}{8}$	1623-37-23	661
	2 $\frac{7}{8}$	1623-37-27	714
	3 $\frac{3}{8}$	1623-37-33	767
	3 $\frac{7}{8}$	1623-37-37	820
	4 $\frac{3}{8}$	1623-37-47	925
	5 $\frac{3}{8}$	1623-37-57	1031
4 $\frac{7}{8}$	1 $\frac{1}{8}$	1623-47-13	661
	1 $\frac{1}{8}$	1623-47-17	714
	2 $\frac{3}{8}$	1623-47-23	767
	2 $\frac{7}{8}$	1623-47-27	820
	3 $\frac{3}{8}$	1623-47-33	872
	3 $\frac{7}{8}$	1623-47-37	925
	4 $\frac{3}{8}$	1623-47-47	1031
	5 $\frac{3}{8}$	1623-47-57	1137
5 $\frac{7}{8}$	1 $\frac{1}{8}$	1623-57-13	767
	1 $\frac{1}{8}$	1623-57-17	820
	2 $\frac{3}{8}$	1623-57-23	872
	2 $\frac{7}{8}$	1623-57-27	925
	3 $\frac{3}{8}$	1623-57-33	978
	3 $\frac{7}{8}$	1623-57-37	1031
	4 $\frac{3}{8}$	1623-57-47	1137
	5 $\frac{3}{8}$	1623-57-57	1242

A	B	ITEM NUMBER	NET WT.
1 $\frac{3}{8}$	1 $\frac{1}{8}$	1626-13-13	322
	1 $\frac{1}{8}$	1626-13-17	381
	2 $\frac{3}{8}$	1626-13-23	439
	2 $\frac{7}{8}$	1626-13-27	497
	3 $\frac{3}{8}$	1626-13-33	556
	3 $\frac{7}{8}$	1626-13-37	614
	4 $\frac{3}{8}$	1626-13-47	731
	5 $\frac{3}{8}$	1626-13-57	848
1 $\frac{7}{8}$	1 $\frac{1}{8}$	1626-17-13	381
	1 $\frac{1}{8}$	1626-17-17	439
	2 $\frac{3}{8}$	1626-17-23	497
	2 $\frac{7}{8}$	1626-17-27	556
	3 $\frac{3}{8}$	1626-17-33	614
	3 $\frac{7}{8}$	1626-17-37	673
	4 $\frac{3}{8}$	1626-17-47	790
	5 $\frac{3}{8}$	1626-17-57	907
2 $\frac{3}{8}$	1 $\frac{1}{8}$	1626-23-13	439
	1 $\frac{1}{8}$	1626-23-17	497
	2 $\frac{3}{8}$	1626-23-23	556
	2 $\frac{7}{8}$	1626-23-27	614
	3 $\frac{3}{8}$	1626-23-33	673
	3 $\frac{7}{8}$	1626-23-37	731
	4 $\frac{3}{8}$	1626-23-47	848
	5 $\frac{3}{8}$	1626-23-57	965
2 $\frac{7}{8}$	1 $\frac{1}{8}$	1626-27-13	497
	1 $\frac{1}{8}$	1626-27-17	556
	2 $\frac{3}{8}$	1626-27-23	614
	2 $\frac{7}{8}$	1626-27-27	673
	3 $\frac{3}{8}$	1626-27-33	731
	3 $\frac{7}{8}$	1626-27-37	790
	4 $\frac{3}{8}$	1626-27-47	907
	5 $\frac{3}{8}$	1626-27-57	1024

A	B	ITEM NUMBER	NET WT.
3 $\frac{3}{8}$	1 $\frac{1}{8}$	1626-33-13	556
	1 $\frac{1}{8}$	1626-33-17	614
	2 $\frac{3}{8}$	1626-33-23	673
	2 $\frac{7}{8}$	1626-33-27	731
	3 $\frac{3}{8}$	1626-33-33	790
	3 $\frac{7}{8}$	1626-33-37	848
	4 $\frac{3}{8}$	1626-33-47	965
	5 $\frac{3}{8}$	1626-33-57	1082
3 $\frac{7}{8}$	1 $\frac{1}{8}$	1626-37-13	614
	1 $\frac{1}{8}$	1626-37-17	673
	2 $\frac{3}{8}$	1626-37-23	731
	2 $\frac{7}{8}$	1626-37-27	790
	3 $\frac{3}{8}$	1626-37-33	848
	3 $\frac{7}{8}$	1626-37-37	907
	4 $\frac{3}{8}$	1626-37-47	1024
	5 $\frac{3}{8}$	1626-37-57	1141
4 $\frac{7}{8}$	1 $\frac{1}{8}$	1626-47-13	731
	1 $\frac{1}{8}$	1626-47-17	790
	2 $\frac{3}{8}$	1626-47-23	848
	2 $\frac{7}{8}$	1626-47-27	907
	3 $\frac{3}{8}$	1626-47-33	965
	3 $\frac{7}{8}$	1626-47-37	1024
	4 $\frac{3}{8}$	1626-47-47	1141
	5 $\frac{3}{8}$	1626-47-57	1258
5 $\frac{7}{8}$	1 $\frac{1}{8}$	1626-57-13	848
	1 $\frac{1}{8}$	1626-57-17	907
	2 $\frac{3}{8}$	1626-57-23	965
	2 $\frac{7}{8}$	1626-57-27	1024
	3 $\frac{3}{8}$	1626-57-33	1082
	3 $\frac{7}{8}$	1626-57-37	1141
	4 $\frac{3}{8}$	1626-57-47	1258
	5 $\frac{3}{8}$	1626-57-57	1375

Thickness of each plate is finish ground $\pm .001$ ". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:

- 1. Quantity & Item Number
- 2. No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2 $\frac{7}{8}$ thick)
- 3. L Dimension (Guide Pin Length)
- 4. Method of Shipment



[CONTACT US](#)

Cavity Retainer Sets | Cavity Retainer Sets 15 $\frac{7}{8}$ x 23 $\frac{1}{2}$ and 15 $\frac{7}{8}$ x 26"

Cavity Retainer Sets

15 7/8 x 29 1/2 and 15 7/8 x 35 1/2

CAVITY RETAINER SETS



Cavity Retainer Sets | Cavity Retainer Sets 15 7/8 x 29 1/2 and 15 7/8 x 35 1/2

A	B	ITEM NUMBER	NET WT.
1 3/8	1 1/8	1629-13-13	365
	1 1/8	1629-13-17	432
	2 3/8	1629-13-23	498
	2 7/8	1629-13-27	564
	3 3/8	1629-13-33	631
	3 7/8	1629-13-37	697
	4 7/8	1629-13-47	830
	5 7/8	1629-13-57	962
1 7/8	1 1/8	1629-17-13	432
	1 1/8	1629-17-17	498
	2 3/8	1629-17-23	564
	2 7/8	1629-17-27	631
	3 3/8	1629-17-33	697
	3 7/8	1629-17-37	763
	4 7/8	1629-17-47	896
	5 7/8	1629-17-57	1029
2 3/8	1 1/8	1629-23-13	498
	1 1/8	1629-23-17	564
	2 3/8	1629-23-23	631
	2 7/8	1629-23-27	697
	3 3/8	1629-23-33	763
	3 7/8	1629-23-37	830
	4 7/8	1629-23-47	962
	5 7/8	1629-23-57	1095
2 7/8	1 1/8	1629-27-13	564
	1 1/8	1629-27-17	631
	2 3/8	1629-27-23	697
	2 7/8	1629-27-27	763
	3 3/8	1629-27-33	830
	3 7/8	1629-27-37	896
	4 7/8	1629-27-47	1029
	5 7/8	1629-27-57	1161

A	B	ITEM NUMBER	NET WT.
3 3/8	1 1/8	1629-33-13	631
	1 1/8	1629-33-17	697
	2 3/8	1629-33-23	763
	2 7/8	1629-33-27	830
	3 3/8	1629-33-33	896
	3 7/8	1629-33-37	962
	4 7/8	1629-33-47	1095
	5 7/8	1629-33-57	1228
3 7/8	1 1/8	1629-37-13	697
	1 1/8	1629-37-17	763
	2 3/8	1629-37-23	830
	2 7/8	1629-37-27	896
	3 3/8	1629-37-33	962
	3 7/8	1629-37-37	1029
	4 7/8	1629-37-47	1161
	5 7/8	1629-37-57	1294
4 7/8	1 1/8	1629-47-13	830
	1 1/8	1629-47-17	896
	2 3/8	1629-47-23	962
	2 7/8	1629-47-27	1029
	3 3/8	1629-47-33	1095
	3 7/8	1629-47-37	1161
	4 7/8	1629-47-47	1294
	5 7/8	1629-47-57	1427
5 7/8	1 1/8	1629-57-13	962
	1 1/8	1629-57-17	1029
	2 3/8	1629-57-23	1095
	2 7/8	1629-57-27	1161
	3 3/8	1629-57-33	1228
	3 7/8	1629-57-37	1294
	4 7/8	1629-57-47	1427
	5 7/8	1629-57-57	1559

A	B	ITEM NUMBER	NET WT.
1 3/8	1 1/8	1635-13-13	440
	1 1/8	1635-13-17	519
	2 3/8	1635-13-23	599
	2 7/8	1635-13-27	679
	3 3/8	1635-13-33	759
	3 7/8	1635-13-37	839
	4 7/8	1635-13-47	998
	5 7/8	1635-13-57	1158
1 7/8	1 1/8	1635-17-13	519
	1 1/8	1635-17-17	599
	2 3/8	1635-17-23	679
	2 7/8	1635-17-27	759
	3 3/8	1635-17-33	839
	3 7/8	1635-17-37	919
	4 7/8	1635-17-47	1078
	5 7/8	1635-17-57	1238
2 3/8	1 1/8	1635-23-13	599
	1 1/8	1635-23-17	679
	2 3/8	1635-23-23	759
	2 7/8	1635-23-27	839
	3 3/8	1635-23-33	919
	3 7/8	1635-23-37	998
	4 7/8	1635-23-47	1158
	5 7/8	1635-23-57	1318
2 7/8	1 1/8	1635-27-13	679
	1 1/8	1635-27-17	759
	2 3/8	1635-27-23	839
	2 7/8	1635-27-27	919
	3 3/8	1635-27-33	998
	3 7/8	1635-27-37	1078
	4 7/8	1635-27-47	1238
	5 7/8	1635-27-57	1398

A	B	ITEM NUMBER	NET WT.
3 3/8	1 1/8	1635-33-13	759
	1 1/8	1635-33-17	839
	2 3/8	1635-33-23	919
	2 7/8	1635-33-27	998
	3 3/8	1635-33-33	1078
	3 7/8	1635-33-37	1158
	4 7/8	1635-33-47	1318
	5 7/8	1635-33-57	1477
3 7/8	1 1/8	1635-37-13	839
	1 1/8	1635-37-17	919
	2 3/8	1635-37-23	998
	2 7/8	1635-37-27	1078
	3 3/8	1635-37-33	1158
	3 7/8	1635-37-37	1238
	4 7/8	1635-37-47	1398
	5 7/8	1635-37-57	1557
4 7/8	1 1/8	1635-47-13	998
	1 1/8	1635-47-17	1078
	2 3/8	1635-47-23	1158
	2 7/8	1635-47-27	1238
	3 3/8	1635-47-33	1318
	3 7/8	1635-47-37	1398
	4 7/8	1635-47-47	1557
	5 7/8	1635-47-57	1717
5 7/8	1 1/8	1635-57-13	1158
	1 1/8	1635-57-17	1238
	2 3/8	1635-57-23	1318
	2 7/8	1635-57-27	1398
	3 3/8	1635-57-33	1477
	3 7/8	1635-57-37	1557
	4 7/8	1635-57-47	1717
	5 7/8	1635-57-57	1877

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- 1. Quantity & Item Number
- 2. No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2 7/8" thick)
- 3. L Dimension (Guide Pin Length)
- 4. Method of Shipment

CONTACT US

Cavity Retainer Sets

16½ × 23¾ and 16½ × 29½

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1¾	1⅞	1724-13-13	306
	1⅞	1724-13-17	361
	2⅞	1724-13-23	417
	2⅞	1724-13-27	472
	3⅞	1724-13-33	528
	3⅞	1724-13-37	583
	4⅞	1724-13-47	694
	5⅞	1724-13-57	805
1⅞	1⅞	1724-17-13	361
	1⅞	1724-17-17	417
	2⅞	1724-17-23	472
	2⅞	1724-17-27	528
	3⅞	1724-17-33	583
	3⅞	1724-17-37	639
	4⅞	1724-17-47	750
	5⅞	1724-17-57	861
2¾	1⅞	1724-23-13	417
	1⅞	1724-23-17	472
	2⅞	1724-23-23	528
	2⅞	1724-23-27	583
	3⅞	1724-23-33	639
	3⅞	1724-23-37	694
	4⅞	1724-23-47	805
	5⅞	1724-23-57	916
2⅞	1⅞	1724-27-13	472
	1⅞	1724-27-17	528
	2⅞	1724-27-23	583
	2⅞	1724-27-27	639
	3⅞	1724-27-33	694
	3⅞	1724-27-37	750
	4⅞	1724-27-47	861
	5⅞	1724-27-57	972

A	B	ITEM NUMBER	NET WT.
3¾	1⅞	1724-33-13	528
	1⅞	1724-33-17	583
	2⅞	1724-33-23	639
	2⅞	1724-33-27	694
	3⅞	1724-33-33	750
	3⅞	1724-33-37	805
	4⅞	1724-33-47	916
	5⅞	1724-33-57	1027
3⅞	1⅞	1724-37-13	583
	1⅞	1724-37-17	639
	2⅞	1724-37-23	694
	2⅞	1724-37-27	750
	3⅞	1724-37-33	805
	3⅞	1724-37-37	861
	4⅞	1724-37-47	972
	5⅞	1724-37-57	1083
4⅞	1⅞	1724-47-13	694
	1⅞	1724-47-17	750
	2⅞	1724-47-23	805
	2⅞	1724-47-27	861
	3⅞	1724-47-33	916
	3⅞	1724-47-37	972
	4⅞	1724-47-47	1083
	5⅞	1724-47-57	1194
5⅞	1⅞	1724-57-13	805
	1⅞	1724-57-17	861
	2⅞	1724-57-23	916
	2⅞	1724-57-27	972
	3⅞	1724-57-33	1027
	3⅞	1724-57-37	1083
	4⅞	1724-57-47	1194
	5⅞	1724-57-57	1305

A	B	ITEM NUMBER	NET WT.
1¾	1⅞	1729-13-13	380
	1⅞	1729-13-17	449
	2⅞	1729-13-23	518
	2⅞	1729-13-27	587
	3⅞	1729-13-33	656
	3⅞	1729-13-37	724
	4⅞	1729-13-47	862
	5⅞	1729-13-57	1000
1⅞	1⅞	1729-17-13	449
	1⅞	1729-17-17	518
	2⅞	1729-17-23	587
	2⅞	1729-17-27	656
	3⅞	1729-17-33	724
	3⅞	1729-17-37	793
	4⅞	1729-17-47	931
	5⅞	1729-17-57	1069
2¾	1⅞	1729-23-13	518
	1⅞	1729-23-17	587
	2⅞	1729-23-23	656
	2⅞	1729-23-27	724
	3⅞	1729-23-33	793
	3⅞	1729-23-37	862
	4⅞	1729-23-47	1000
	5⅞	1729-23-57	1138
2⅞	1⅞	1729-27-13	587
	1⅞	1729-27-17	656
	2⅞	1729-27-23	724
	2⅞	1729-27-27	793
	3⅞	1729-27-33	862
	3⅞	1729-27-37	931
	4⅞	1729-27-47	1069
	5⅞	1729-27-57	1207

A	B	ITEM NUMBER	NET WT.
3¾	1⅞	1729-33-13	656
	1⅞	1729-33-17	724
	2⅞	1729-33-23	793
	2⅞	1729-33-27	862
	3⅞	1729-33-33	931
	3⅞	1729-33-37	1000
	4⅞	1729-33-47	1138
	5⅞	1729-33-57	1276
3⅞	1⅞	1729-37-13	724
	1⅞	1729-37-17	793
	2⅞	1729-37-23	862
	2⅞	1729-37-27	931
	3⅞	1729-37-33	1000
	3⅞	1729-37-37	1069
	4⅞	1729-37-47	1207
	5⅞	1729-37-57	1345
4⅞	1⅞	1729-47-13	862
	1⅞	1729-47-17	931
	2⅞	1729-47-23	1000
	2⅞	1729-47-27	1069
	3⅞	1729-47-33	1138
	3⅞	1729-47-37	1207
	4⅞	1729-47-47	1345
	5⅞	1729-47-57	1483
5⅞	1⅞	1729-57-13	1000
	1⅞	1729-57-17	1069
	2⅞	1729-57-23	1138
	2⅞	1729-57-27	1207
	3⅞	1729-57-33	1276
	3⅞	1729-57-37	1345
	4⅞	1729-57-47	1483
	5⅞	1729-57-57	1621

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2% thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

[CONTACT US](#)

Cavity Retainer Sets

17 $\frac{7}{8}$ x 18" and 17 $\frac{7}{8}$ x 20"

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1$\frac{3}{8}$	1 $\frac{3}{8}$	1818-13-13	251
	1 $\frac{7}{8}$	1818-13-17	297
	2 $\frac{3}{8}$	1818-13-23	342
	2 $\frac{7}{8}$	1818-13-27	388
	3 $\frac{3}{8}$	1818-13-33	434
	3 $\frac{7}{8}$	1818-13-37	479
	4 $\frac{3}{8}$	1818-13-47	570
	5 $\frac{3}{8}$	1818-13-57	661
1$\frac{7}{8}$	1 $\frac{3}{8}$	1818-17-13	297
	1 $\frac{7}{8}$	1818-17-17	342
	2 $\frac{3}{8}$	1818-17-23	388
	2 $\frac{7}{8}$	1818-17-27	434
	3 $\frac{3}{8}$	1818-17-33	479
	3 $\frac{7}{8}$	1818-17-37	525
	4 $\frac{3}{8}$	1818-17-47	616
	5 $\frac{3}{8}$	1818-17-57	707
2$\frac{3}{8}$	1 $\frac{3}{8}$	1818-23-13	342
	1 $\frac{7}{8}$	1818-23-17	388
	2 $\frac{3}{8}$	1818-23-23	434
	2 $\frac{7}{8}$	1818-23-27	479
	3 $\frac{3}{8}$	1818-23-33	525
	3 $\frac{7}{8}$	1818-23-37	570
	4 $\frac{3}{8}$	1818-23-47	661
	5 $\frac{3}{8}$	1818-23-57	753
2$\frac{7}{8}$	1 $\frac{3}{8}$	1818-27-13	388
	1 $\frac{7}{8}$	1818-27-17	434
	2 $\frac{3}{8}$	1818-27-23	479
	2 $\frac{7}{8}$	1818-27-27	525
	3 $\frac{3}{8}$	1818-27-33	570
	3 $\frac{7}{8}$	1818-27-37	616
	4 $\frac{3}{8}$	1818-27-47	707
	5 $\frac{3}{8}$	1818-27-57	798

A	B	ITEM NUMBER	NET WT.
3$\frac{3}{8}$	1 $\frac{3}{8}$	1818-33-13	434
	1 $\frac{7}{8}$	1818-33-17	479
	2 $\frac{3}{8}$	1818-33-23	525
	2 $\frac{7}{8}$	1818-33-27	570
	3 $\frac{3}{8}$	1818-33-33	616
	3 $\frac{7}{8}$	1818-33-37	661
	4 $\frac{3}{8}$	1818-33-47	753
	5 $\frac{3}{8}$	1818-33-57	844
3$\frac{7}{8}$	1 $\frac{3}{8}$	1818-37-13	479
	1 $\frac{7}{8}$	1818-37-17	525
	2 $\frac{3}{8}$	1818-37-23	570
	2 $\frac{7}{8}$	1818-37-27	616
	3 $\frac{3}{8}$	1818-37-33	661
	3 $\frac{7}{8}$	1818-37-37	707
	4 $\frac{3}{8}$	1818-37-47	798
	5 $\frac{3}{8}$	1818-37-57	889
4$\frac{7}{8}$	1 $\frac{3}{8}$	1818-47-13	570
	1 $\frac{7}{8}$	1818-47-17	616
	2 $\frac{3}{8}$	1818-47-23	661
	2 $\frac{7}{8}$	1818-47-27	707
	3 $\frac{3}{8}$	1818-47-33	753
	3 $\frac{7}{8}$	1818-47-37	798
	4 $\frac{3}{8}$	1818-47-47	889
	5 $\frac{3}{8}$	1818-47-57	980
5$\frac{7}{8}$	1 $\frac{3}{8}$	1818-57-13	661
	1 $\frac{7}{8}$	1818-57-17	707
	2 $\frac{3}{8}$	1818-57-23	753
	2 $\frac{7}{8}$	1818-57-27	798
	3 $\frac{3}{8}$	1818-57-33	844
	3 $\frac{7}{8}$	1818-57-37	889
	4 $\frac{3}{8}$	1818-57-47	980
	5 $\frac{3}{8}$	1818-57-57	1072

A	B	ITEM NUMBER	NET WT.
1$\frac{3}{8}$	1 $\frac{3}{8}$	1820-13-13	279
	1 $\frac{7}{8}$	1820-13-17	330
	2 $\frac{3}{8}$	1820-13-23	380
	2 $\frac{7}{8}$	1820-13-27	431
	3 $\frac{3}{8}$	1820-13-33	482
	3 $\frac{7}{8}$	1820-13-37	532
	4 $\frac{3}{8}$	1820-13-47	633
	5 $\frac{3}{8}$	1820-13-57	735
1$\frac{7}{8}$	1 $\frac{3}{8}$	1820-17-13	330
	1 $\frac{7}{8}$	1820-17-17	380
	2 $\frac{3}{8}$	1820-17-23	431
	2 $\frac{7}{8}$	1820-17-27	482
	3 $\frac{3}{8}$	1820-17-33	532
	3 $\frac{7}{8}$	1820-17-37	583
	4 $\frac{3}{8}$	1820-17-47	684
	5 $\frac{3}{8}$	1820-17-57	785
2$\frac{3}{8}$	1 $\frac{3}{8}$	1820-23-13	380
	1 $\frac{7}{8}$	1820-23-17	431
	2 $\frac{3}{8}$	1820-23-23	482
	2 $\frac{7}{8}$	1820-23-27	532
	3 $\frac{3}{8}$	1820-23-33	583
	3 $\frac{7}{8}$	1820-23-37	633
	4 $\frac{3}{8}$	1820-23-47	735
	5 $\frac{3}{8}$	1820-23-57	836
2$\frac{7}{8}$	1 $\frac{3}{8}$	1820-27-13	431
	1 $\frac{7}{8}$	1820-27-17	482
	2 $\frac{3}{8}$	1820-27-23	532
	2 $\frac{7}{8}$	1820-27-27	583
	3 $\frac{3}{8}$	1820-27-33	633
	3 $\frac{7}{8}$	1820-27-37	684
	4 $\frac{3}{8}$	1820-27-47	785
	5 $\frac{3}{8}$	1820-27-57	887

A	B	ITEM NUMBER	NET WT.
3$\frac{3}{8}$	1 $\frac{3}{8}$	1820-33-13	482
	1 $\frac{7}{8}$	1820-33-17	532
	2 $\frac{3}{8}$	1820-33-23	583
	2 $\frac{7}{8}$	1820-33-27	633
	3 $\frac{3}{8}$	1820-33-33	684
	3 $\frac{7}{8}$	1820-33-37	735
	4 $\frac{3}{8}$	1820-33-47	836
	5 $\frac{3}{8}$	1820-33-57	937
3$\frac{7}{8}$	1 $\frac{3}{8}$	1820-37-13	532
	1 $\frac{7}{8}$	1820-37-17	583
	2 $\frac{3}{8}$	1820-37-23	633
	2 $\frac{7}{8}$	1820-37-27	684
	3 $\frac{3}{8}$	1820-37-33	735
	3 $\frac{7}{8}$	1820-37-37	785
	4 $\frac{3}{8}$	1820-37-47	887
	5 $\frac{3}{8}$	1820-37-57	988
4$\frac{7}{8}$	1 $\frac{3}{8}$	1820-47-13	633
	1 $\frac{7}{8}$	1820-47-17	684
	2 $\frac{3}{8}$	1820-47-23	735
	2 $\frac{7}{8}$	1820-47-27	785
	3 $\frac{3}{8}$	1820-47-33	836
	3 $\frac{7}{8}$	1820-47-37	887
	4 $\frac{3}{8}$	1820-47-47	988
	5 $\frac{3}{8}$	1820-47-57	1089
5$\frac{7}{8}$	1 $\frac{3}{8}$	1820-57-13	735
	1 $\frac{7}{8}$	1820-57-17	785
	2 $\frac{3}{8}$	1820-57-23	836
	2 $\frac{7}{8}$	1820-57-27	887
	3 $\frac{3}{8}$	1820-57-33	937
	3 $\frac{7}{8}$	1820-57-37	988
	4 $\frac{3}{8}$	1820-57-47	1089
	5 $\frac{3}{8}$	1820-57-57	1191

Thickness of each plate is finish ground $\pm .001$ ". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel
(No. 7 Steel available standard only for plates up to and including 2 $\frac{7}{8}$ thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

[CONTACT US](#)

Cavity Retainer Sets

17⁷/₈ × 23¹/₂ and 17⁷/₈ × 26"

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1 ³ / ₈	1 ³ / ₈	1823-13-13	328
	1 ⁷ / ₈	1823-13-17	387
	2 ³ / ₈	1823-13-23	447
	2 ⁷ / ₈	1823-13-27	506
	3 ³ / ₈	1823-13-33	566
	3 ⁷ / ₈	1823-13-37	625
	4 ³ / ₈	1823-13-47	744
	5 ³ / ₈	1823-13-57	863
1 ⁷ / ₈	1 ³ / ₈	1823-17-13	387
	1 ⁷ / ₈	1823-17-17	447
	2 ³ / ₈	1823-17-23	506
	2 ⁷ / ₈	1823-17-27	566
	3 ³ / ₈	1823-17-33	625
	3 ⁷ / ₈	1823-17-37	685
	4 ³ / ₈	1823-17-47	804
	5 ³ / ₈	1823-17-57	923
2 ³ / ₈	1 ³ / ₈	1823-23-13	447
	1 ⁷ / ₈	1823-23-17	506
	2 ³ / ₈	1823-23-23	566
	2 ⁷ / ₈	1823-23-27	625
	3 ³ / ₈	1823-23-33	685
	3 ⁷ / ₈	1823-23-37	744
	4 ³ / ₈	1823-23-47	863
	5 ³ / ₈	1823-23-57	982
2 ⁷ / ₈	1 ³ / ₈	1823-27-13	506
	1 ⁷ / ₈	1823-27-17	566
	2 ³ / ₈	1823-27-23	625
	2 ⁷ / ₈	1823-27-27	685
	3 ³ / ₈	1823-27-33	744
	3 ⁷ / ₈	1823-27-37	804
	4 ³ / ₈	1823-27-47	923
	5 ³ / ₈	1823-27-57	1042

A	B	ITEM NUMBER	NET WT.
3 ³ / ₈	1 ³ / ₈	1823-33-13	566
	1 ⁷ / ₈	1823-33-17	625
	2 ³ / ₈	1823-33-23	685
	2 ⁷ / ₈	1823-33-27	744
	3 ³ / ₈	1823-33-33	804
	3 ⁷ / ₈	1823-33-37	863
	4 ³ / ₈	1823-33-47	982
	5 ³ / ₈	1823-33-57	1101
3 ⁷ / ₈	1 ³ / ₈	1823-37-13	625
	1 ⁷ / ₈	1823-37-17	685
	2 ³ / ₈	1823-37-23	744
	2 ⁷ / ₈	1823-37-27	804
	3 ³ / ₈	1823-37-33	863
	3 ⁷ / ₈	1823-37-37	923
	4 ³ / ₈	1823-37-47	1042
	5 ³ / ₈	1823-37-57	1161
4 ⁷ / ₈	1 ³ / ₈	1823-47-13	744
	1 ⁷ / ₈	1823-47-17	804
	2 ³ / ₈	1823-47-23	863
	2 ⁷ / ₈	1823-47-27	923
	3 ³ / ₈	1823-47-33	982
	3 ⁷ / ₈	1823-47-37	1042
	4 ³ / ₈	1823-47-47	1161
	5 ³ / ₈	1823-47-57	1280
5 ⁷ / ₈	1 ³ / ₈	1823-57-13	863
	1 ⁷ / ₈	1823-57-17	923
	2 ³ / ₈	1823-57-23	982
	2 ⁷ / ₈	1823-57-27	1042
	3 ³ / ₈	1823-57-33	1101
	3 ⁷ / ₈	1823-57-37	1161
	4 ³ / ₈	1823-57-47	1280
	5 ³ / ₈	1823-57-57	1399

A	B	ITEM NUMBER	NET WT.
1 ³ / ₈	1 ³ / ₈	1826-13-13	363
	1 ⁷ / ₈	1826-13-17	428
	2 ³ / ₈	1826-13-23	494
	2 ⁷ / ₈	1826-13-27	560
	3 ³ / ₈	1826-13-33	626
	3 ⁷ / ₈	1826-13-37	692
	4 ³ / ₈	1826-13-47	823
	5 ³ / ₈	1826-13-57	955
1 ⁷ / ₈	1 ³ / ₈	1826-17-13	428
	1 ⁷ / ₈	1826-17-17	494
	2 ³ / ₈	1826-17-23	560
	2 ⁷ / ₈	1826-17-27	626
	3 ³ / ₈	1826-17-33	692
	3 ⁷ / ₈	1826-17-37	758
	4 ³ / ₈	1826-17-47	889
	5 ³ / ₈	1826-17-57	1021
2 ³ / ₈	1 ³ / ₈	1826-23-13	494
	1 ⁷ / ₈	1826-23-17	560
	2 ³ / ₈	1826-23-23	626
	2 ⁷ / ₈	1826-23-27	692
	3 ³ / ₈	1826-23-33	758
	3 ⁷ / ₈	1826-23-37	823
	4 ³ / ₈	1826-23-47	955
	5 ³ / ₈	1826-23-57	1087
2 ⁷ / ₈	1 ³ / ₈	1826-27-13	560
	1 ⁷ / ₈	1826-27-17	626
	2 ³ / ₈	1826-27-23	692
	2 ⁷ / ₈	1826-27-27	758
	3 ³ / ₈	1826-27-33	823
	3 ⁷ / ₈	1826-27-37	889
	4 ³ / ₈	1826-27-47	1021
	5 ³ / ₈	1826-27-57	1153

A	B	ITEM NUMBER	NET WT.
3 ³ / ₈	1 ³ / ₈	1826-33-13	626
	1 ⁷ / ₈	1826-33-17	692
	2 ³ / ₈	1826-33-23	758
	2 ⁷ / ₈	1826-33-27	823
	3 ³ / ₈	1826-33-33	889
	3 ⁷ / ₈	1826-33-37	955
	4 ³ / ₈	1826-33-47	1087
	5 ³ / ₈	1826-33-57	1218
3 ⁷ / ₈	1 ³ / ₈	1826-37-13	692
	1 ⁷ / ₈	1826-37-17	758
	2 ³ / ₈	1826-37-23	823
	2 ⁷ / ₈	1826-37-27	889
	3 ³ / ₈	1826-37-33	955
	3 ⁷ / ₈	1826-37-37	1021
	4 ³ / ₈	1826-37-47	1153
	5 ³ / ₈	1826-37-57	1284
4 ⁷ / ₈	1 ³ / ₈	1826-47-13	823
	1 ⁷ / ₈	1826-47-17	889
	2 ³ / ₈	1826-47-23	955
	2 ⁷ / ₈	1826-47-27	1021
	3 ³ / ₈	1826-47-33	1087
	3 ⁷ / ₈	1826-47-37	1153
	4 ³ / ₈	1826-47-47	1284
	5 ³ / ₈	1826-47-57	1416
5 ⁷ / ₈	1 ³ / ₈	1826-57-13	955
	1 ⁷ / ₈	1826-57-17	1021
	2 ³ / ₈	1826-57-23	1087
	2 ⁷ / ₈	1826-57-27	1153
	3 ³ / ₈	1826-57-33	1218
	3 ⁷ / ₈	1826-57-37	1284
	4 ³ / ₈	1826-57-47	1416
	5 ³ / ₈	1826-57-57	1548

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2% thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

CONTACT US

Cavity Retainer Sets

17⁷/₈ × 29¹/₂ and 17⁷/₈ × 35¹/₂

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1 ³ / ₈	1 ³ / ₈	1829-13-13	411
	1 ⁷ / ₈	1829-13-17	486
	2 ³ / ₈	1829-13-23	561
	2 ⁷ / ₈	1829-13-27	635
	3 ³ / ₈	1829-13-33	710
	3 ⁷ / ₈	1829-13-37	785
	4 ³ / ₈	1829-13-47	934
	5 ³ / ₈	1829-13-57	1084
1 ⁷ / ₈	1 ³ / ₈	1829-17-13	486
	1 ⁷ / ₈	1829-17-17	561
	2 ³ / ₈	1829-17-23	635
	2 ⁷ / ₈	1829-17-27	710
	3 ³ / ₈	1829-17-33	785
	3 ⁷ / ₈	1829-17-37	859
	4 ³ / ₈	1829-17-47	1009
	5 ³ / ₈	1829-17-57	1158
2 ³ / ₈	1 ³ / ₈	1829-23-13	561
	1 ⁷ / ₈	1829-23-17	635
	2 ³ / ₈	1829-23-23	710
	2 ⁷ / ₈	1829-23-27	785
	3 ³ / ₈	1829-23-33	859
	3 ⁷ / ₈	1829-23-37	934
	4 ³ / ₈	1829-23-47	1084
	5 ³ / ₈	1829-23-57	1233
2 ⁷ / ₈	1 ³ / ₈	1829-27-13	635
	1 ⁷ / ₈	1829-27-17	710
	2 ³ / ₈	1829-27-23	785
	2 ⁷ / ₈	1829-27-27	859
	3 ³ / ₈	1829-27-33	934
	3 ⁷ / ₈	1829-27-37	1009
	4 ³ / ₈	1829-27-47	1158
	5 ³ / ₈	1829-27-57	1308

A	B	ITEM NUMBER	NET WT.
3 ³ / ₈	1 ³ / ₈	1829-33-13	710
	1 ⁷ / ₈	1829-33-17	785
	2 ³ / ₈	1829-33-23	859
	2 ⁷ / ₈	1829-33-27	934
	3 ³ / ₈	1829-33-33	1009
	3 ⁷ / ₈	1829-33-37	1084
	4 ³ / ₈	1829-33-47	1233
	5 ³ / ₈	1829-33-57	1382
3 ⁷ / ₈	1 ³ / ₈	1829-37-13	785
	1 ⁷ / ₈	1829-37-17	859
	2 ³ / ₈	1829-37-23	934
	2 ⁷ / ₈	1829-37-27	1009
	3 ³ / ₈	1829-37-33	1084
	3 ⁷ / ₈	1829-37-37	1158
	4 ³ / ₈	1829-37-47	1308
	5 ³ / ₈	1829-37-57	1457
4 ⁷ / ₈	1 ³ / ₈	1829-47-13	934
	1 ⁷ / ₈	1829-47-17	1009
	2 ³ / ₈	1829-47-23	1084
	2 ⁷ / ₈	1829-47-27	1158
	3 ³ / ₈	1829-47-33	1233
	3 ⁷ / ₈	1829-47-37	1308
	4 ³ / ₈	1829-47-47	1457
	5 ³ / ₈	1829-47-57	1606
5 ⁷ / ₈	1 ³ / ₈	1829-57-13	1084
	1 ⁷ / ₈	1829-57-17	1158
	2 ³ / ₈	1829-57-23	1233
	2 ⁷ / ₈	1829-57-27	1308
	3 ³ / ₈	1829-57-33	1382
	3 ⁷ / ₈	1829-57-37	1457
	4 ³ / ₈	1829-57-47	1606
	5 ³ / ₈	1829-57-57	1756

A	B	ITEM NUMBER	NET WT.
1 ³ / ₈	1 ³ / ₈	1835-13-13	495
	1 ⁷ / ₈	1835-13-17	585
	2 ³ / ₈	1835-13-23	675
	2 ⁷ / ₈	1835-13-27	765
	3 ³ / ₈	1835-13-33	854
	3 ⁷ / ₈	1835-13-37	944
	4 ³ / ₈	1835-13-47	1124
	5 ³ / ₈	1835-13-57	1304
1 ⁷ / ₈	1 ³ / ₈	1835-17-13	585
	1 ⁷ / ₈	1835-17-17	675
	2 ³ / ₈	1835-17-23	765
	2 ⁷ / ₈	1835-17-27	854
	3 ³ / ₈	1835-17-33	944
	3 ⁷ / ₈	1835-17-37	1034
	4 ³ / ₈	1835-17-47	1214
	5 ³ / ₈	1835-17-57	1394
2 ³ / ₈	1 ³ / ₈	1835-23-13	675
	1 ⁷ / ₈	1835-23-17	765
	2 ³ / ₈	1835-23-23	854
	2 ⁷ / ₈	1835-23-27	944
	3 ³ / ₈	1835-23-33	1034
	3 ⁷ / ₈	1835-23-37	1124
	4 ³ / ₈	1835-23-47	1304
	5 ³ / ₈	1835-23-57	1484
2 ⁷ / ₈	1 ³ / ₈	1835-27-13	765
	1 ⁷ / ₈	1835-27-17	854
	2 ³ / ₈	1835-27-23	944
	2 ⁷ / ₈	1835-27-27	1034
	3 ³ / ₈	1835-27-33	1124
	3 ⁷ / ₈	1835-27-37	1214
	4 ³ / ₈	1835-27-47	1394
	5 ³ / ₈	1835-27-57	1574

A	B	ITEM NUMBER	NET WT.
3 ³ / ₈	1 ³ / ₈	1835-33-13	854
	1 ⁷ / ₈	1835-33-17	944
	2 ³ / ₈	1835-33-23	1034
	2 ⁷ / ₈	1835-33-27	1124
	3 ³ / ₈	1835-33-33	1214
	3 ⁷ / ₈	1835-33-37	1304
	4 ³ / ₈	1835-33-47	1484
	5 ³ / ₈	1835-33-57	1663
3 ⁷ / ₈	1 ³ / ₈	1835-37-13	944
	1 ⁷ / ₈	1835-37-17	1034
	2 ³ / ₈	1835-37-23	1124
	2 ⁷ / ₈	1835-37-27	1214
	3 ³ / ₈	1835-37-33	1304
	3 ⁷ / ₈	1835-37-37	1394
	4 ³ / ₈	1835-37-47	1574
	5 ³ / ₈	1835-37-57	1753
4 ⁷ / ₈	1 ³ / ₈	1835-47-13	1124
	1 ⁷ / ₈	1835-47-17	1214
	2 ³ / ₈	1835-47-23	1304
	2 ⁷ / ₈	1835-47-27	1394
	3 ³ / ₈	1835-47-33	1484
	3 ⁷ / ₈	1835-47-37	1574
	4 ³ / ₈	1835-47-47	1753
	5 ³ / ₈	1835-47-57	1933
5 ⁷ / ₈	1 ³ / ₈	1835-57-13	1304
	1 ⁷ / ₈	1835-57-17	1394
	2 ³ / ₈	1835-57-23	1484
	2 ⁷ / ₈	1835-57-27	1574
	3 ³ / ₈	1835-57-33	1663
	3 ⁷ / ₈	1835-57-37	1753
	4 ³ / ₈	1835-57-47	1933
	5 ³ / ₈	1835-57-57	2113

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- 1. Quantity & Item Number
- 2. No 1, No 2, No 3 or No 7 Steel (No. 7 Steel available standard only for plates up to and including 2% thick)
- 3. L Dimension (Guide Pin Length)
- 4. Method of Shipment

CONTACT US

Cavity Retainer Sets

19½ × 23¾ and 19½ × 29½

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1 3/8	1 1/8	1924-13-13	361
	1 1/8	1924-13-17	427
	2 1/8	1924-13-23	493
	2 1/8	1924-13-27	558
	3 1/8	1924-13-33	624
	3 1/8	1924-13-37	689
	4 1/8	1924-13-47	821
5 1/8	1924-13-57	952	
1 7/8	1 1/8	1924-17-13	427
	1 1/8	1924-17-17	493
	2 1/8	1924-17-23	558
	2 1/8	1924-17-27	624
	3 1/8	1924-17-33	689
	3 1/8	1924-17-37	755
	4 1/8	1924-17-47	886
5 1/8	1924-17-57	1017	
2 3/8	1 1/8	1924-23-13	493
	1 1/8	1924-23-17	558
	2 1/8	1924-23-23	624
	2 1/8	1924-23-27	689
	3 1/8	1924-23-33	755
	3 1/8	1924-23-37	821
	4 1/8	1924-23-47	952
5 1/8	1924-23-57	1083	
2 7/8	1 1/8	1924-27-13	558
	1 1/8	1924-27-17	624
	2 1/8	1924-27-23	689
	2 1/8	1924-27-27	755
	3 1/8	1924-27-33	821
	3 1/8	1924-27-37	886
	4 1/8	1924-27-47	1017
5 1/8	1924-27-57	1149	

A	B	ITEM NUMBER	NET WT.
3 3/8	1 1/8	1924-33-13	624
	1 1/8	1924-33-17	689
	2 1/8	1924-33-23	755
	2 1/8	1924-33-27	821
	3 1/8	1924-33-33	886
	3 1/8	1924-33-37	952
	4 1/8	1924-33-47	1083
5 1/8	1924-33-57	1214	
3 7/8	1 1/8	1924-37-13	689
	1 1/8	1924-37-17	755
	2 1/8	1924-37-23	821
	2 1/8	1924-37-27	886
	3 1/8	1924-37-33	952
	3 1/8	1924-37-37	1017
	4 1/8	1924-37-47	1149
5 1/8	1924-37-57	1280	
4 7/8	1 1/8	1924-47-13	821
	1 1/8	1924-47-17	886
	2 1/8	1924-47-23	952
	2 1/8	1924-47-27	1017
	3 1/8	1924-47-33	1083
	3 1/8	1924-47-37	1149
	4 1/8	1924-47-47	1280
5 1/8	1924-47-57	1411	
5 7/8	1 1/8	1924-57-13	952
	1 1/8	1924-57-17	1017
	2 1/8	1924-57-23	1083
	2 1/8	1924-57-27	1149
	3 1/8	1924-57-33	1214
	3 1/8	1924-57-37	1280
	4 1/8	1924-57-47	1411
5 1/8	1924-57-57	1542	

A	B	ITEM NUMBER	NET WT.
1 3/8	1 1/8	1929-13-13	449
	1 1/8	1929-13-17	530
	2 1/8	1929-13-23	612
	2 1/8	1929-13-27	693
	3 1/8	1929-13-33	775
	3 1/8	1929-13-37	856
	4 1/8	1929-13-47	1019
5 1/8	1929-13-57	1182	
1 7/8	1 1/8	1929-17-13	530
	1 1/8	1929-17-17	612
	2 1/8	1929-17-23	693
	2 1/8	1929-17-27	775
	3 1/8	1929-17-33	856
	3 1/8	1929-17-37	938
	4 1/8	1929-17-47	1100
5 1/8	1929-17-57	1263	
2 3/8	1 1/8	1929-23-13	612
	1 1/8	1929-23-17	693
	2 1/8	1929-23-23	775
	2 1/8	1929-23-27	856
	3 1/8	1929-23-33	938
	3 1/8	1929-23-37	1019
	4 1/8	1929-23-47	1182
5 1/8	1929-23-57	1345	
2 7/8	1 1/8	1929-27-13	693
	1 1/8	1929-27-17	775
	2 1/8	1929-27-23	856
	2 1/8	1929-27-27	938
	3 1/8	1929-27-33	1019
	3 1/8	1929-27-37	1100
	4 1/8	1929-27-47	1263
5 1/8	1929-27-57	1426	

A	B	ITEM NUMBER	NET WT.
3 3/8	1 1/8	1929-33-13	775
	1 1/8	1929-33-17	856
	2 1/8	1929-33-23	938
	2 1/8	1929-33-27	1019
	3 1/8	1929-33-33	1100
	3 1/8	1929-33-37	1182
	4 1/8	1929-33-47	1345
5 1/8	1929-33-57	1508	
3 7/8	1 1/8	1929-37-13	856
	1 1/8	1929-37-17	938
	2 1/8	1929-37-23	1019
	2 1/8	1929-37-27	1100
	3 1/8	1929-37-33	1182
	3 1/8	1929-37-37	1263
	4 1/8	1929-37-47	1426
5 1/8	1929-37-57	1589	
4 7/8	1 1/8	1929-47-13	1019
	1 1/8	1929-47-17	1100
	2 1/8	1929-47-23	1182
	2 1/8	1929-47-27	1263
	3 1/8	1929-47-33	1345
	3 1/8	1929-47-37	1426
	4 1/8	1929-47-47	1589
5 1/8	1929-47-57	1752	
5 7/8	1 1/8	1929-57-13	1182
	1 1/8	1929-57-17	1263
	2 1/8	1929-57-23	1345
	2 1/8	1929-57-27	1426
	3 1/8	1929-57-33	1508
	3 1/8	1929-57-37	1589
	4 1/8	1929-57-47	1752
5 1/8	1929-57-57	1915	

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2% thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

CONTACT US

Cavity Retainer Sets

19½ × 35½ and 23¾ × 23¾

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1⅜	1⅜	1935-13-13	540
	1⅞	1935-13-17	638
	2⅜	1935-13-23	736
	2⅞	1935-13-27	834
	3⅜	1935-13-33	932
	3⅞	1935-13-37	1030
	4⅜	1935-13-47	1226
	5⅜	1935-13-57	1422
1⅞	1⅜	1935-17-13	638
	1⅞	1935-17-17	736
	2⅜	1935-17-23	834
	2⅞	1935-17-27	932
	3⅜	1935-17-33	1030
	3⅞	1935-17-37	1128
	4⅜	1935-17-47	1324
	5⅜	1935-17-57	1520
2⅜	1⅜	1935-23-13	736
	1⅞	1935-23-17	834
	2⅜	1935-23-23	932
	2⅞	1935-23-27	1030
	3⅜	1935-23-33	1128
	3⅞	1935-23-37	1226
	4⅜	1935-23-47	1422
	5⅜	1935-23-57	1618
2⅞	1⅜	1935-27-13	834
	1⅞	1935-27-17	932
	2⅜	1935-27-23	1030
	2⅞	1935-27-27	1128
	3⅜	1935-27-33	1226
	3⅞	1935-27-37	1324
	4⅜	1935-27-47	1520
	5⅜	1935-27-57	1717

A	B	ITEM NUMBER	NET WT.
3⅜	1⅜	1935-33-13	932
	1⅞	1935-33-17	1030
	2⅜	1935-33-23	1128
	2⅞	1935-33-27	1226
	3⅜	1935-33-33	1324
	3⅞	1935-33-37	1422
	4⅜	1935-33-47	1618
	5⅜	1935-33-57	1815
3⅞	1⅜	1935-37-13	1030
	1⅞	1935-37-17	1128
	2⅜	1935-37-23	1226
	2⅞	1935-37-27	1324
	3⅜	1935-37-33	1422
	3⅞	1935-37-37	1520
	4⅜	1935-37-47	1717
	5⅜	1935-37-57	1913
4⅞	1⅜	1935-47-13	1226
	1⅞	1935-47-17	1324
	2⅜	1935-47-23	1422
	2⅞	1935-47-27	1520
	3⅜	1935-47-33	1618
	3⅞	1935-47-37	1717
	4⅜	1935-47-47	1913
	5⅜	1935-47-57	2109
5⅞	1⅜	1935-57-13	1422
	1⅞	1935-57-17	1520
	2⅜	1935-57-23	1618
	2⅞	1935-57-27	1717
	3⅜	1935-57-33	1815
	3⅞	1935-57-37	1913
	4⅜	1935-57-47	2109
	5⅜	1935-57-57	2305

A	B	ITEM NUMBER	NET WT.
1⅜	1⅜	2424-13-13	440
	1⅞	2424-13-17	520
	2⅜	2424-13-23	600
	2⅞	2424-13-27	680
	3⅜	2424-13-33	760
	3⅞	2424-13-37	839
	4⅜	2424-13-47	999
	5⅜	2424-13-57	1159
1⅞	1⅜	2424-17-13	520
	1⅞	2424-17-17	600
	2⅜	2424-17-23	680
	2⅞	2424-17-27	760
	3⅜	2424-17-33	839
	3⅞	2424-17-37	919
	4⅜	2424-17-47	1079
	5⅜	2424-17-57	1239
2⅜	1⅜	2424-23-13	600
	1⅞	2424-23-17	680
	2⅜	2424-23-23	760
	2⅞	2424-23-27	839
	3⅜	2424-23-33	919
	3⅞	2424-23-37	999
	4⅜	2424-23-47	1159
	5⅜	2424-23-57	1319
2⅞	1⅜	2424-27-13	680
	1⅞	2424-27-17	760
	2⅜	2424-27-23	839
	2⅞	2424-27-27	919
	3⅜	2424-27-33	999
	3⅞	2424-27-37	1079
	4⅜	2424-27-47	1239
	5⅜	2424-27-57	1399

A	B	ITEM NUMBER	NET WT.
3⅜	1⅜	2424-33-13	760
	1⅞	2424-33-17	839
	2⅜	2424-33-23	919
	2⅞	2424-33-27	999
	3⅜	2424-33-33	1079
	3⅞	2424-33-37	1159
	4⅜	2424-33-47	1319
	5⅜	2424-33-57	1479
3⅞	1⅜	2424-37-13	839
	1⅞	2424-37-17	919
	2⅜	2424-37-23	999
	2⅞	2424-37-27	1079
	3⅜	2424-37-33	1159
	3⅞	2424-37-37	1239
	4⅜	2424-37-47	1399
	5⅜	2424-37-57	1559
4⅞	1⅜	2424-47-13	999
	1⅞	2424-47-17	1079
	2⅜	2424-47-23	1159
	2⅞	2424-47-27	1239
	3⅜	2424-47-33	1319
	3⅞	2424-47-37	1399
	4⅜	2424-47-47	1559
	5⅜	2424-47-57	1718
5⅞	1⅜	2424-57-13	1159
	1⅞	2424-57-17	1239
	2⅜	2424-57-23	1319
	2⅞	2424-57-27	1399
	3⅜	2424-57-33	1479
	3⅞	2424-57-37	1559
	4⅜	2424-57-47	1718
	5⅜	2424-57-57	1878

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:



- 1. Quantity & Item Number
- 2. No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2⅞ thick)
- 3. L Dimension (Guide Pin Length)
- 4. Method of Shipment

CONTACT US

Cavity Retainer Sets

23³/₄ × 29¹/₂ and 23³/₄ × 35¹/₂

CAVITY RETAINER SETS



A	B	ITEM NUMBER	NET WT.
1 ³ / ₈	1 ³ / ₈	2429-13-13	546
	1 ⁷ / ₈	2429-13-17	646
	2 ⁵ / ₈	2429-13-23	745
	2 ⁷ / ₈	2429-13-27	844
	3 ¹ / ₈	2429-13-33	943
	3 ³ / ₈	2429-13-37	1043
	4 ¹ / ₈	2429-13-47	1241
	5 ¹ / ₈	2429-13-57	1439
1 ⁷ / ₈	1 ³ / ₈	2429-17-13	646
	1 ⁷ / ₈	2429-17-17	745
	2 ⁵ / ₈	2429-17-23	844
	2 ⁷ / ₈	2429-17-27	943
	3 ¹ / ₈	2429-17-33	1043
	3 ³ / ₈	2429-17-37	1142
	4 ¹ / ₈	2429-17-47	1340
	5 ¹ / ₈	2429-17-57	1539
2 ³ / ₈	1 ³ / ₈	2429-23-13	745
	1 ⁷ / ₈	2429-23-17	844
	2 ⁵ / ₈	2429-23-23	943
	2 ⁷ / ₈	2429-23-27	1043
	3 ¹ / ₈	2429-23-33	1142
	3 ³ / ₈	2429-23-37	1241
	4 ¹ / ₈	2429-23-47	1439
	5 ¹ / ₈	2429-23-57	1638
2 ⁷ / ₈	1 ³ / ₈	2429-27-13	844
	1 ⁷ / ₈	2429-27-17	943
	2 ⁵ / ₈	2429-27-23	1043
	2 ⁷ / ₈	2429-27-27	1142
	3 ¹ / ₈	2429-27-33	1241
	3 ³ / ₈	2429-27-37	1340
	4 ¹ / ₈	2429-27-47	1539
	5 ¹ / ₈	2429-27-57	1737

A	B	ITEM NUMBER	NET WT.
3 ³ / ₈	1 ³ / ₈	2429-33-13	943
	1 ⁷ / ₈	2429-33-17	1043
	2 ⁵ / ₈	2429-33-23	1142
	2 ⁷ / ₈	2429-33-27	1241
	3 ¹ / ₈	2429-33-33	1340
	3 ³ / ₈	2429-33-37	1439
	4 ¹ / ₈	2429-33-47	1638
	5 ¹ / ₈	2429-33-57	1836
3 ⁷ / ₈	1 ³ / ₈	2429-37-13	1043
	1 ⁷ / ₈	2429-37-17	1142
	2 ⁵ / ₈	2429-37-23	1241
	2 ⁷ / ₈	2429-37-27	1340
	3 ¹ / ₈	2429-37-33	1439
	3 ³ / ₈	2429-37-37	1539
	4 ¹ / ₈	2429-37-47	1737
	5 ¹ / ₈	2429-37-57	1936
4 ⁷ / ₈	1 ³ / ₈	2429-47-13	1241
	1 ⁷ / ₈	2429-47-17	1340
	2 ⁵ / ₈	2429-47-23	1439
	2 ⁷ / ₈	2429-47-27	1539
	3 ¹ / ₈	2429-47-33	1638
	3 ³ / ₈	2429-47-37	1737
	4 ¹ / ₈	2429-47-47	1936
	5 ¹ / ₈	2429-47-57	2134
5 ⁷ / ₈	1 ³ / ₈	2429-57-13	1439
	1 ⁷ / ₈	2429-57-17	1539
	2 ⁵ / ₈	2429-57-23	1638
	2 ⁷ / ₈	2429-57-27	1737
	3 ¹ / ₈	2429-57-33	1836
	3 ³ / ₈	2429-57-37	1936
	4 ¹ / ₈	2429-57-47	2134
	5 ¹ / ₈	2429-57-57	2333

A	B	ITEM NUMBER	NET WT.
1 ³ / ₈	1 ³ / ₈	2435-13-13	657
	1 ⁷ / ₈	2435-13-17	777
	2 ⁵ / ₈	2435-13-23	896
	2 ⁷ / ₈	2435-13-27	1016
	3 ¹ / ₈	2435-13-33	1135
	3 ³ / ₈	2435-13-37	1255
	4 ¹ / ₈	2435-13-47	1493
	5 ¹ / ₈	2435-13-57	1732
1 ⁷ / ₈	1 ³ / ₈	2435-17-13	777
	1 ⁷ / ₈	2435-17-17	896
	2 ⁵ / ₈	2435-17-23	1016
	2 ⁷ / ₈	2435-17-27	1135
	3 ¹ / ₈	2435-17-33	1255
	3 ³ / ₈	2435-17-37	1374
	4 ¹ / ₈	2435-17-47	1613
	5 ¹ / ₈	2435-17-57	1852
2 ³ / ₈	1 ³ / ₈	2435-23-13	896
	1 ⁷ / ₈	2435-23-17	1016
	2 ⁵ / ₈	2435-23-23	1135
	2 ⁷ / ₈	2435-23-27	1255
	3 ¹ / ₈	2435-23-33	1374
	3 ³ / ₈	2435-23-37	1493
	4 ¹ / ₈	2435-23-47	1732
	5 ¹ / ₈	2435-23-57	1971
2 ⁷ / ₈	1 ³ / ₈	2435-27-13	1016
	1 ⁷ / ₈	2435-27-17	1135
	2 ⁵ / ₈	2435-27-23	1255
	2 ⁷ / ₈	2435-27-27	1374
	3 ¹ / ₈	2435-27-33	1493
	3 ³ / ₈	2435-27-37	1613
	4 ¹ / ₈	2435-27-47	1852
	5 ¹ / ₈	2435-27-57	2091

A	B	ITEM NUMBER	NET WT.
3 ³ / ₈	1 ³ / ₈	2435-33-13	1135
	1 ⁷ / ₈	2435-33-17	1255
	2 ⁵ / ₈	2435-33-23	1374
	2 ⁷ / ₈	2435-33-27	1493
	3 ¹ / ₈	2435-33-33	1613
	3 ³ / ₈	2435-33-37	1732
	4 ¹ / ₈	2435-33-47	1971
	5 ¹ / ₈	2435-33-57	2210
3 ⁷ / ₈	1 ³ / ₈	2435-37-13	1255
	1 ⁷ / ₈	2435-37-17	1374
	2 ⁵ / ₈	2435-37-23	1493
	2 ⁷ / ₈	2435-37-27	1613
	3 ¹ / ₈	2435-37-33	1732
	3 ³ / ₈	2435-37-37	1852
	4 ¹ / ₈	2435-37-47	2091
	5 ¹ / ₈	2435-37-57	2329
4 ⁷ / ₈	1 ³ / ₈	2435-47-13	1493
	1 ⁷ / ₈	2435-47-17	1613
	2 ⁵ / ₈	2435-47-23	1732
	2 ⁷ / ₈	2435-47-27	1852
	3 ¹ / ₈	2435-47-33	1971
	3 ³ / ₈	2435-47-37	2091
	4 ¹ / ₈	2435-47-47	2329
	5 ¹ / ₈	2435-47-57	2568
5 ⁷ / ₈	1 ³ / ₈	2435-57-13	1732
	1 ⁷ / ₈	2435-57-17	1852
	2 ⁵ / ₈	2435-57-23	1971
	2 ⁷ / ₈	2435-57-27	2091
	3 ¹ / ₈	2435-57-33	2210
	3 ³ / ₈	2435-57-37	2329
	4 ¹ / ₈	2435-57-47	2568
	5 ¹ / ₈	2435-57-57	2807

Thickness of each plate is finish ground ± .001". Width and length finished square and parallel.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2, No. 3 or No. 7 Steel (No. 7 Steel available standard only for plates up to and including 2⁷/₈ thick)
- L Dimension (Guide Pin Length)
- Method of Shipment

CONTACT US

Mold and Die Steels

STEEL DESCRIPTIONS

Three Steels for Structural Sections

DME NO. 1 STEEL

No. 1 Steel is a medium carbon (SAE 1030) or equivalent, silicon-killed forging quality steel with approximately 25% greater tensile strength than typical low-carbon warehouse steels. It machines easily, but is not "sticky," permitting a faster and smoother cut.

DME NO. 2 STEEL

No. 2 Steel is an AISI 4130 or equivalent type steel. It is supplied pre-heat treated to 28-34 HRC (271-321 Bhn). A high strength steel, it is ideal for cavity and core retainer plates, clamping plates and support plates in molds and dies.



DME NO. 7 STEEL

No. 7 Steel is a modified AISI 400 or equivalent series stainless steel for holder block applications. It is supplied pre-heat treated to 32-36 HRC (302-340 Bhn). This stainless steel offers corrosion-resistance and exceptional machinability but cannot be further hardened (see DME No. 6). For humid environments, corrosive plastics, "clean room" or "100% stainless" applications, it is an ideal choice for all structural (non-cavity/core) mold plates.

Three Steels for Cavities and Cores

DME NO. 3 STEEL

No. 3 Steel is a P-20 AISI 4130 (modified) type cavity steel. Exceptionally clean, it is pre-heat treated to 28-34 HRC (271-321 Bhn). It provides high hardness, good machinability and exceptional polishability for both plastics molds and die cast dies.

DME NO. 5 STEEL

No. 5 Steel is a thermal shock resistant, hotwork die steel (AISI-SAE H-13 type) or equivalent. Supplied fully annealed 13-20 HRC (approx. 200 Bhn) for easy machinability, it can be subsequently heat treated to the desired hardness with a minimum of deformation.

Mainly used for die cast dies, it is also suitable for plastics molds with exceptional hardness or polishability requirements.

DME NO. 5 Steel meets or exceeds the acceptance criteria established by the NADCA as detailed in Technical Digest Number 01-80-01D

DME NO. 6 STEEL

No. 6 Steel is T-420 type or equivalent stainless steel. It is supplied fully annealed to 8-23 HRC (179-241 Bhn), making it readily machinable. It can be used for injection, compression or transfer molds where the properties of the plastics materials or excessive condensation require a highly corrosion resistant cavity steel.

OTHER TYPES OF STEEL AVAILABLE ON SPECIAL ORDER. CONTACT DME.

DME Mold Plates


Over 400 Standard
Sizes in Four Steel
Types




DME No. 7



DME No. 5



DME No. 3



DME No. 1

DME Standard


DIE BLOCKS & PLATES-NO. 5 STEEL

Available in over 300 special order sizes from $7\frac{7}{8} \times 7\frac{7}{8}$ to $23\frac{3}{4} \times 35\frac{1}{2}$; $1\frac{1}{8}$ to $11\frac{1}{8}$ thick (depending on length and width). They are supplied in milled condition, with approximately .060" stock allowance.

DME No. 5 Steel meets or exceeds the acceptance criteria established by the NADCA as detailed in Technical Digest Number 01-80-01D.

SPECIAL ORDER SIZES: Please contact DME.

[CONTACT US](#)



MOLD PLATES & PLATE ITEMS

Mold Plates are available in over 400 standard sizes, from $6" \times 7"$ to $23\frac{3}{4} \times 35\frac{1}{2}$ in DME No. 1, No. 2, or No. 3 Steel. Plates from $7\frac{7}{8} \times 7\frac{7}{8}$ to $23\frac{3}{4} \times 35\frac{1}{2}$ are also available in DME No. 7 Steel (up to $2\frac{7}{8}$ thick).


In addition, they are offered in the following two conditions:

FINISH GROUND PLATES

Thickness is finish ground top and bottom to a tolerance of $\pm .001"$ with all edges finished square and parallel.

ROTARY GROUND PLATES

Thickness is rotary ground to a tolerance of $+.015/+.020$ or $+.025/+.030$ depending on plate width. Length and width are milled ($+.000/+.005$).




Additional standard plate items include:

EJECTOR AND EJECTOR RETAINER PLATES
PLATE ITEMS FOR SMALL MOLD BASES


SPACER BLOCKS

Plain, Slotted and Angle Spacers are all made from DME No. 1 Steel. Riser height (C dimension) is finish ground to plus or minus .001".



EJECTOR HOUSINGS

Rigid one-piece construction is made from DME No. 1 Steel. Available in over 150 standard sizes, corresponding to DME Standard "A" Series Mold Bases. The riser height (C dimension) is finish ground to plus or minus .001".



Die Blocks and Plates

7⁷/₈ through 13³/₈ wide – No. 5 Steel


DIE BLOCKS & PLATES

DME No. 5 steel is a thermal shock resistant, hotwork die steel (AISI-SAE H-13 type). Supplied fully annealed (approx. 200 Bhn) for easy machinability, it can be subsequently heat treated to the desired hardness with a minimum of deformation.

Mainly used for die cast dies, it is also suitable for plastics molds with exceptional hardness or polishability requirements.

DME No. 5 Steel meets or exceeds the acceptance criteria established by the NADCA as detailed in Technical Digest Number 01-80-01D.

Thickness, width and length are milled to approximately .060" oversized (.030" per side).



A	7 ⁷ / ₈ × 7 ⁷ / ₈	
	ITEM NUMBER	NET WT.
1 ¹ / ₈	88-13	25
1 ¹ / ₈	88-17	33
2 ¹ / ₈	88-23	42
2 ¹ / ₈	88-27	51
3 ¹ / ₈	88-33	60
3 ¹ / ₈	88-37	69
4 ¹ / ₈	88-47	86

A	9 ⁷ / ₈ × 8"		9 ⁷ / ₈ × 11 ⁷ / ₈		9 ⁷ / ₈ × 16"		9 ⁷ / ₈ × 20"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
1 ¹ / ₈	108-13	31	1012-13	46	1016-13	62	1020-13	77	1 ¹ / ₈
1 ¹ / ₈	108-17	42	1012-17	63	1016-17	84	1020-17	105	1 ¹ / ₈
2 ¹ / ₈	108-23	54	1012-23	79	1016-23	107	1020-23	133	2 ¹ / ₈
2 ¹ / ₈	108-27	65	1012-27	96	1016-27	129	1020-27	161	2 ¹ / ₈
3 ¹ / ₈	108-33	76	1012-33	113	1016-33	152	1020-33	189	3 ¹ / ₈
3 ¹ / ₈	108-37	87	1012-37	129	1016-37	174	1020-37	217	3 ¹ / ₈
4 ¹ / ₈	108-47	110	1012-47	162	1016-47	219	1020-47	273	4 ¹ / ₈
5 ¹ / ₈	108-57	132	1012-57	196	1016-57	263	1020-57	329	5 ¹ / ₈

A	10 ⁷ / ₈ × 12"		10 ⁷ / ₈ × 14"		10 ⁷ / ₈ × 18"		10 ⁷ / ₈ × 23 ¹ / ₂ "	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
1 ¹ / ₈	1112-13	51	1114-13	60	1118-13	77	1123-13	100
1 ¹ / ₈	1112-17	70	1114-17	81	1118-17	104	1123-17	136
2 ¹ / ₈	1112-23	88	1114-23	103	1118-23	132	1123-23	172
2 ¹ / ₈	1112-27	107	1114-27	125	1118-27	160	1123-27	209
3 ¹ / ₈	1112-33	125	1114-33	146	1118-33	188	1123-33	245
3 ¹ / ₈	1112-37	144	1114-37	168	1118-37	215	1123-37	281
4 ¹ / ₈	1112-47	181	1114-47	211	1118-47	271	1123-47	353
5 ¹ / ₈	1112-57	218	1114-57	254	1118-57	326	1123-57	426

A	11 ⁷ / ₈ × 12"		11 ⁷ / ₈ × 15"	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
1 ¹ / ₈	1212-13	56	1215-13	70
1 ¹ / ₈	1212-17	76	1215-17	95
2 ¹ / ₈	1212-23	96	1215-23	120
2 ¹ / ₈	1212-27	117	1215-27	146
3 ¹ / ₈	1212-33	137	1215-33	171
3 ¹ / ₈	1212-37	157	1215-37	196
4 ¹ / ₈	1212-47	197	1215-47	247
5 ¹ / ₈	1212-57	238	1215-57	297
7 ¹ / ₈	1212-77	318	1215-77	398

A	11 ⁷ / ₈ × 20"		11 ⁷ / ₈ × 23 ¹ / ₂ "	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
1 ¹ / ₈	1220-13	93	1223-13	109
1 ¹ / ₈	1220-17	127	1223-17	149
2 ¹ / ₈	1220-23	160	1223-23	188
2 ¹ / ₈	1220-27	194	1223-27	228
3 ¹ / ₈	1220-33	228	1223-33	267
3 ¹ / ₈	1220-37	261	1223-37	307
4 ¹ / ₈	1220-47	329	1223-47	386
5 ¹ / ₈	1220-57	396	1223-57	465
7 ¹ / ₈	1220-77	530	1223-77	623

A	13 ³ / ₈ × 15"		13 ³ / ₈ × 18"		13 ³ / ₈ × 20 ³ / ₄ "		13 ³ / ₈ × 23 ¹ / ₂ "	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
1 ¹ / ₈	1315-13	79	1318-13	94	1321-13	109	1323-13	123
1 ¹ / ₈	1315-17	107	1318-17	128	1321-17	148	1323-17	167
2 ¹ / ₈	1315-23	135	1318-23	162	1321-23	187	1323-23	212
2 ¹ / ₈	1315-27	164	1318-27	197	1321-27	227	1323-27	257
3 ¹ / ₈	1315-33	192	1318-33	231	1321-33	266	1323-33	301
3 ¹ / ₈	1315-37	221	1318-37	265	1321-37	305	1323-37	346
4 ¹ / ₈	1315-47	278	1318-47	333	1321-47	384	1323-47	435
5 ¹ / ₈	1315-57	334	1318-57	401	1321-57	462	1323-57	524
7 ¹ / ₈	1315-77	448	1318-77	538	1321-77	620	1323-77	702

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 5 Steel
- Method of Shipment

ALSO AVAILABLE:

- Rotary ground thickness
- Finish ground thickness and/or edges
- Standard width and thickness up to 12 feet long. For prices, contact DME.

SPECIAL ORDER SIZES: Please contact DME.


CONTACT US

Die Blocks and Plates

15⁷/₈ through 23³/₄ wide – No. 5 Steel


DIE BLOCKS & PLATES

A	15 ⁷ / ₈ × 16"		15 ⁷ / ₈ × 20"		15 ⁷ / ₈ × 23 ¹ / ₂ "		15 ⁷ / ₈ × 26"	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
1%	1616-13	99	1620-13	124	1623-13	146	1626-13	161
1%	1616-17	135	1620-17	169	1623-17	199	1626-17	220
2%	1616-23	171	1620-23	214	1623-23	252	1626-23	278
2%	1616-27	207	1620-27	259	1623-27	304	1626-27	337
3%	1616-33	243	1620-33	304	1623-33	357	1626-33	395
3%	1616-37	279	1620-37	349	1623-37	410	1626-37	454
4%	1616-47	351	1620-47	439	1623-47	516	1626-47	571
5%	1616-57	423	1620-57	529	1623-57	621	1626-57	687
7%	1616-77	567	1620-77	709	1623-77	833	1626-77	921
8%	1616-87	639	1620-87	799	1623-87	938	1626-87	1038
9%	1616-97	711	1620-97	889	1623-97	1044	1626-97	1155
11%	1616-117	855	1620-117	1069	1623-117	1256	1626-117	1389



A	17 ⁷ / ₈ × 18"		17 ⁷ / ₈ × 20"		17 ⁷ / ₈ × 23 ¹ / ₂ "		17 ⁷ / ₈ × 26"		17 ⁷ / ₈ × 29 ¹ / ₂ "		17 ⁷ / ₈ × 35 ¹ / ₂ "		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
1%	1818-17	171	1820-17	190	1823-17	224	1826-17	247	1829-17	281	1835-17	338	1%
2%	1818-23	217	1820-23	241	1823-23	283	1826-23	313	1829-23	355	1835-23	427	2%
2%	1818-27	263	1820-27	292	1823-27	343	1826-27	379	1829-27	430	1835-27	517	2%
3%	1818-33	308	1820-33	342	1823-33	402	1826-33	445	1829-33	505	1835-33	607	3%
3%	1818-37	354	1820-37	393	1823-37	462	1826-37	511	1829-37	579	1835-37	697	3%
4%	1818-47	445	1820-47	494	1823-47	581	1826-47	642	1829-47	729	1835-47	877	4%
5%	1818-57	536	1820-57	596	1823-57	700	1826-57	774	1829-57	878	1835-57	1057	5%
7%	1818-77	718	1820-77	798	1823-77	938	1826-77	1037	1829-77	1177	1835-77	1416	7%
8%	1818-87	809	1820-87	899	1823-87	1057	1826-87	1169	1829-87	1326	1835-87	1596	8%
9%	1818-97	901	1820-97	1001	1823-97	1176	1826-97	1301	1829-97	1476	1835-97	1776	9%
11%	1818-117	1083	1820-117	1203	1823-117	1414	1826-117	1564	1829-117	1774	1835-117	2135	11%

A	19 ¹ / ₂ × 23 ³ / ₄ "		A	23 ³ / ₄ × 23 ³ / ₄ "		23 ³ / ₄ × 29 ¹ / ₂ "		23 ³ / ₄ × 35 ¹ / ₂ "	
	ITEM NUMBER	NET WT.		ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
2%	1924-23	312	2%	2424-23	380	2429-23	472	2435-23	568
2%	1924-27	378	2%	2424-27	460	2429-27	571	2435-27	687
3%	1924-33	443	3%	2424-33	540	2429-33	670	2435-33	807
3%	1924-37	509	3%	2424-37	620	2429-37	770	2435-37	926
4%	1924-47	640	4%	2424-47	780	2429-47	968	2435-47	1165
5%	1924-57	771	5%	2424-57	939	2429-57	1167	2435-57	1404
7%	1924-77	1034	7%	2424-77	1259	2429-77	1564	2435-77	1882
8%	1924-87	1165	8%	2424-87	1419	2429-87	1762	2435-87	2120
9%	1924-97	1296	9%	2424-97	1579	2429-97	1961	2435-97	2359
11%	1924-117	1559	11%	2424-117	1898	2429-117	2358	2435-117	2837



Thickness, width and length are milled to approximately .060" oversized (.030" per side).

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 5 Steel
- Method of Shipment

ALSO AVAILABLE:

- Rotary ground thickness
- Finish ground thickness and/or edges
- Standard width and thickness up to 12 feet long. For prices, contact DME.


SPECIAL ORDER SIZES: Please contact DME.

CONTACT US

DME Standard Cavity Insert Blocks – 3", 4", 5" and 6" Series

CAVITY INSERT BLOCKS

Thickness, width and length are finished square and parallel .015" to .020" oversized (.0075" to .010" per side) to permit either fitting at assembly (No. 3 Steel) or finish grinding after heat treatment (No. 5 Steel, No. 6 Steel and AISI S-7 Steel).



A	3" (W) × 3" (L)				3" (W) × 4" (L)				3" (W) × 5" (L)				3" (W) × 6" (L)				3" (W) × 8" (L)								
	ITEM NO.	MATERIAL			NET WT.	ITEM NO.	MATERIAL			NET WT.	ITEM NO.	MATERIAL			NET WT.	ITEM NO.	MATERIAL			NET WT.					
		NO. 3	NO. 5	S-7			NO. 3	NO. 5	S-7			NO. 3	NO. 5	S-7			NO. 3	NO. 6	NO. 5		S-7	NO. 3	NO. 5	S-7	
3/8"	33-7	•	•	•	2.2	34-7	••	•	•	2.0	35-7	•	•	•	3.7	36-7	•	•	•	4.5	38-7	•	•	•	5.9
1/2"	33-13	•	•	•	3.5	34-13	••	•	•	4.7	35-13	•	•	•	5.8	36-13	•	•	•	7.0	38-13	•	•	•	9.3
1/2"	33-17	•	•	•	4.4	34-17	•	•	•	6.4	35-17	•	•	•	8.0	36-17	•	—	—	9.6	38-17	•	•	•	12.7
3/4"	33-23	•	•	•	6.1	34-23	—	•	•	8.1	35-23	•	•	•	10.1	36-23	•	•	•	12.1	—	—	—	—	—
1"	—	—	—	—	—	—	—	—	—	—	35-27	—	•	•	12.2	—	—	—	—	—	—	—	—	—	—
1 1/4"	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	36-33	•	—	—	17.2	38-33	—	•	•	22.9



A	4" (W) × 4" (L)				4" (W) × 5" (L)				4" (W) × 6" (L)				4" (W) × 8" (L)							
	ITEM NO.	MATERIAL			NET WT.	ITEM NO.	MATERIAL			NET WT.	ITEM NO.	MATERIAL			NET WT.	ITEM NO.	MATERIAL			NET WT.
		NO. 3	NO. 6	NO. 5			S-7	NO. 3	NO. 5			S-7	NO. 3	NO. 5			S-7	NO. 3	NO. 6	
3/8"	44-7	•	•	•	4.0	45-7	••	•	•	5.0	46-7	•	•	•	5.9	48-7	•	•	•	7.9
1/2"	44-13	•	•	•	6.2	45-13	••	•	•	7.8	46-13	•	•	•	9.3	48-13	•	•	•	12.5
1/2"	44-17	•	•	•	8.5	45-17	••	•	•	10.6	46-17	•	•	•	12.7	48-17	•	•	•	17.0
3/4"	44-23	•	—	•	10.8	45-23	•	•	•	13.5	46-23	•	•	•	16.1	48-23	•	•	•	21.5

A	5" (W) × 5" (L)			5" (W) × 6" (L)			5" (W) × 8" (L)					
	ITEM NO.	MATERIAL		NET WT.	ITEM NO.	MATERIAL		NET WT.	ITEM NO.	MATERIAL		NET WT.
		NO. 3	NO. 5			S-7	NO. 3			NO. 5	S-7	
3/8"	55-7	•	•	6.2	56-7	••	•	7.4	58-7	••	•	9.9
1/2"	55-13	•	•	9.7	56-13	••	•	11.7	58-13	••	•	15.6
1/2"	55-17	•	•	13.3	56-17	••	•	15.9	58-17	••	•	21.2
3/4"	55-23	•	—	16.8	56-23	•	•	20.2	58-23	•	—	26.9
1"	—	—	—	—	56-27	—	•	24.4	58-27	•	—	32.6
1 1/4"	—	—	—	—	56-33	—	—	28.7	—	—	—	—

A	6" (W) × 6" (L)				6" (W) × 8" (L)					
	ITEM NO.	MATERIAL			NET WT.	ITEM NO.	MATERIAL			NET WT.
		NO. 3	NO. 6	NO. 5			S-7	NO. 3	NO. 5	
3/8"	66-7	•	•	•	8.9	68-7	•	•	•	11.4
1/2"	66-13	•	•	•	14.0	68-13	•	•	•	18.7
1/2"	66-17	•	•	•	19.1	68-17	•	•	•	25.5
3/4"	66-23	•	—	•	24.2	68-23	•	—	•	32.3
1"	66-27	•	—	•	29.3	68-27	•	—	•	39.1
1 1/4"	—	—	—	—	—	68-33	•	•	•	45.9
1 3/4"	—	—	—	—	—	68-37	•	—	•	52.7

AVAILABLE STANDARD

DME No. 3 Steel

DME No. 3 Steel is a P-20 AISI 4130 (modified) type cavity steel, pre-heat treated to 277-331 Bhn. Exceptionally clean, it provides high hardness, good machinability and exceptional polishability for both plastics molds and die cast dies.

NOTE: Sizes above marked with a double dot (••) are also available as finish ground mold plates (beginning on the next page). Please specify **insert block** when ordering these sizes from this page.

DME No. 6 Steel

DME No. 6 Steel is a T-420 type stainless steel. It is supplied fully annealed to 220 Bhn (200-240), making it readily machinable. It can be used for injection, compression or transfer molds where the properties of the plastics materials or excessive condensation require a highly corrosion-resistant cavity steel.

AVAILABLE BY SPECIAL ORDER

DME No. 5 Steel

DME No. 5 Steel is a thermal shock resistant, hotwork die steel (AISI-SAE H-13 type). Supplied fully annealed (approx. 200 Bhn) for easy machinability, it can be subsequently heat treated to the desired hardness with a minimum of deformation. Mainly used for die cast dies, it is also suitable for plastics molds with exceptional hardness or polishability requirements.

DME No. 5 Steel meets or exceeds the acceptance criteria established by the NADCA as detailed in Technical Digest Number 01-80-01D.

DME AISI S-7 Steel (NOTE: AISI S-7 Steel is not a stainless steel and is not related to DME No. 7 Steel.)

DME S-7 Steel is supplied fully annealed to 225 Bhn maximum. This shock resisting tool steel combines toughness and wear resistance along with ease of machining and heat treatment. S-7 can be used for both hot and cold work applications as a result of its combination of properties. Due to the unique mold quality composition, minimal distortion occurs during the heat treating process. DME Mold Quality S-7 is selectively melted for improved cleanliness and excellent polishability. Follow standard procedures for heat treating AISI S-7 Steel. Double tempering is recommended.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 3 Steel, No. 5 Steel, No. 6 Steel, or AISI S-7 Steel
- Method of Shipment

*NOTE:

Net weight is specified for DME No. 3 Steel, No. 5 Steel, No. 6 Steel, and AISI S-7.

AVAILABLE STANDARD IN: No. 3 and No. 6 Steel.

AVAILABLE AS A SPECIAL ORDER IN: No. 5 Steel and AISI S-7.


CONTACT US

Finish Ground Mold Plates | Rotary Ground Mold Plates 6", 8^{15/16}, 9" and 9^{7/8} wide

FINISH GROUND MOLD PLATES

AVAILABLE IN:

DME No. 1, No. 2 or No. 3 Steel



Thickness (A) of plate is finish ground ±.001 Width and length are finished square and parallel.

A	6" x 7"	
	ITEM NUMBER	NET WT.
7/8	67-7	11
1 1/8	67-13	17
1 1/4	67-17	23
2 1/8	67-23	29

A	6" x 9 ^{1/2} "	
	ITEM NUMBER	NET WT.
7/8	69-7	14
1 1/8	69-13	22
1 1/4	69-17	29

*No. 2 or No. 3 Steel only.

A	6" x 10 ^{3/8}		9" x 9 ^{1/2} "		A	8 ^{15/16} x 11 ^{3/8}		9" x 11 ^{3/8}		9 ^{7/8} x 7 ^{7/8}	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.		ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
7/8	611-7	17	99-7	21	7/8	912V-7	27	912M-7	27	108R-7	20
1 1/8	611-13	26	99-13	32	1 1/8	912V-13	42	912M-13	42	108R-13	31
1 1/4	611-17	35	99-17	44	1 1/4	912V-17	57	912M-17	57	108R-17	42
2 1/8	611-23	44	*No. 2 or No. 3 Steel only.		2 1/8	912V-23	72	912M-23	72	108R-23	53
2 1/4	611-27	54			2 1/4	912V-27	88	912M-27	88		
3 1/8	611-33	63			3 1/8	912V-33	103	912M-33	103		
3 1/4	611-37	72			3 1/4	912V-37	118	912M-37	118		
4 1/8	611-47	91			4 1/8	912V-47	148	912M-47	148		
5 1/8	611-57	109	5 1/8	912V-57	178	912M-57	178				

ROTARY GROUND MOLD PLATES

ALL "A" THICKNESSES AVAILABLE IN:

DME No. 1, No. 2 or No. 3 Steel

Thickness (A) of plate is rotary ground. Width and length are milled.

TOLERANCES	
Thickness (A)	+0.015 to +0.020
Width (W) Nominal	+0.0025 / +0.005
Length (L) Nominal	+0.0025 / +0.005

A	6" x 7"	
	ITEM NUMBER	NET WT.
7/8	67-7RGM	11
1 1/8	67-13RGM	17
1 1/4	67-17RGM	23
2 1/8	67-23RGM	29

A	6" x 9 ^{1/2} "	
	ITEM NUMBER	NET WT.
7/8	69-7RGM	14
1 1/8	69-13RGM	22
1 1/4	69-17RGM	29

*No. 2 or No. 3 Steel only.

A	6" x 10 ^{3/8}		9" x 9 ^{1/2} "		A	9" x 11 ^{3/8} **		9 ^{7/8} x 7 ^{7/8}	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.		ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
7/8	611-7RGM	17	99-7RGM	21	7/8	912-7RGM	27	108R-7RGM	20
1 1/8	611-13RGM	26	99-13RGM	32	1 1/8	912-13RGM	42	108R-13RGM	31
1 1/4	611-17RGM	35	99-17RGM	44	1 1/4	912-17RGM	57	108R-17RGM	42
2 1/8	611-23RGM	44	*No. 2 or No. 3 Steel only.		2 1/8	912-23RGM	72	108R-23RGM	53
2 1/4	611-27RGM	54			2 1/4	912-27RGM	88		
3 1/8	611-33RGM	63			3 1/8	912-33RGM	103		
3 1/4	611-37RGM	72			3 1/4	912-37RGM	118		
4 1/8	611-47RGM	91			4 1/8	912-47RGM	148		
5 1/8	611-57RGM	109	5 1/8	912-57RGM	178				


**Suitable for both Van Dorn or Moslo applications.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2 or No. 3 Steel
- Method of Shipment

[CONTACT US](#)

Finish Ground Mold Plates 7 7/8 through 11 7/8 wide



Thickness (A) of plate is finish ground $\pm .001$
Width and length are finished square and parallel.

ALL "A" THICKNESSES AVAILABLE IN:

- DME No. 1 Steel – SAE 1030 type
- DME No. 2 Steel – AISI 4130 type, pre-heat treated (271-321 Bhn; 28-34 HRC)
- DME No. 3 Steel – P-20 type, pre-heat treated (271-321 Bhn; 28-34 HRC)

PLATES WITH "A" THICKNESSES FROM 7/8 TO 2 7/8 ALSO AVAILABLE IN:

- DME No. 7 Steel – Modified AISI 400 series stainless steel pre-heat treated (302-340 Bhn; 32-36 HRC)

THICKER PLATES IN DME NO. 7 STEEL ARE AVAILABLE ON SPECIAL ORDER

FINISH GROUND MOLD PLATES

A	7 7/8 x 7 7/8		7 7/8 x 11 7/8		A	9 7/8 x 8"		9 7/8 x 11 7/8	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.		ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
7/8	88-7	16	812-7	24	7/8	108-7	20	1012-7	30
1 1/8	88-13	25	812-13	37	1 1/8	108-13	31	1012-13	46
1 1/4	88-17	33	812-17	50	1 1/4	108-17	42	1012-17	63
1 3/8	88-23	42	812-23	63	1 3/8	108-23	54	1012-23	79
1 1/2	88-27	51	812-27	76	1 1/2	108-27	65	1012-27	96
1 5/8	88-33	60	812-33	89	1 5/8	108-33	76	1012-33	113
1 3/4	88-37	69	812-37	102	1 3/4	108-37	87	1012-37	129
1 7/8	88-47	86	812-47	129	1 7/8	108-47	110	1012-47	162
2	88-57	104	812-57	155	2	108-57	132	1012-57	196

A	9 7/8 16"		9 7/8 20"		9 7/8 23 3/4"		10 7/8 12"		10 7/8 14"		10 7/8 18"		10 7/8 23 1/2"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1016-7	40	1020-7	49	1024-7	59	1112-7	33	1114-7	38	1118-7	49	1123-7	64	7/8
1 1/8	1016-13	62	1020-13	77	1024-13	92	1112-13	51	1114-13	60	1118-13	77	1123-13	100	1 1/8
1 1/4	1016-17	84	1020-17	105	1024-17	125	1112-17	70	1114-17	81	1118-17	104	1123-17	136	1 1/4
1 3/8	1016-23	107	1020-23	133	1024-23	158	1112-23	88	1114-23	103	1118-23	132	1123-23	172	1 3/8
1 1/2	1016-27	129	1020-27	161	1024-27	192	1112-27	107	1114-27	125	1118-27	160	1123-27	209	1 1/2
1 5/8	1016-33	152	1020-33	189	1024-33	225	1112-33	125	1114-33	146	1118-33	188	1123-33	245	1 5/8
1 3/4	1016-37	174	1020-37	217	1024-37	258	1112-37	144	1114-37	168	1118-37	215	1123-37	281	1 3/4
1 7/8	1016-47	219	1020-47	273	1024-47	324	1112-47	181	1114-47	211	1118-47	271	1123-47	353	1 7/8
2	1016-57	263	1020-57	329	1024-57	391	1112-57	218	1114-57	254	1118-57	326	1123-57	426	2

A	11 7/8 12"		11 7/8 15"		11 7/8 17 1/2"		11 7/8 20"		11 7/8 23 1/2"		11 7/8 29 1/2"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1212-7	36	1215-7	45	1217-7	52	1220-7	59	1223-7	70	1229-7	87	7/8
1 1/8	1212-13	56	1215-13	70	1217-13	81	1220-13	93	1223-13	109	1229-13	137	1 1/8
1 1/4	1212-17	76	1215-17	95	1217-17	111	1220-17	127	1223-17	149	1229-17	187	1 1/4
1 3/8	1212-23	96	1215-23	120	1217-23	140	1220-23	160	1223-23	188	1229-23	236	1 3/8
1 1/2	1212-27	117	1215-27	146	1217-27	170	1220-27	194	1223-27	228	1229-27	286	1 1/2
1 5/8	1212-33	137	1215-33	171	1217-33	199	1220-33	228	1223-33	267	1229-33	335	1 5/8
1 3/4	1212-37	157	1215-37	196	1217-37	229	1220-37	261	1223-37	307	1229-37	385	1 3/4
1 7/8	1212-47	197	1215-47	247	1217-47	287	1220-47	329	1223-47	386	1229-47	484	1 7/8
2	1212-57	238	1215-57	297	1217-57	346	1220-57	396	1223-57	465	1229-57	584	2

WHEN ORDERING, PLEASE SPECIFY:

1. Quantity & Item Number
2. No. 1, No. 2, No. 3 or No. 7 Steel
3. Method of Shipment

CONTACT US

Rotary Ground Mold Plates 7/8 through 1 1/8 wide

ROTARY GROUND MOLD PLATES

TOLERANCES	88, 812, 108, 1012, 1016, 1112, 1114, 1118, 1212, 1215	1020, 1024, 1123, 1217, 1220, 1223, 1229
Thickness (A)	+0.015 to +0.020	+0.025 to +0.030
Width (W) Nominal +.0025	+.000/+.005	
Length (L) Nominal +.0025	+.000/+.005	

Thickness (A) of plate is rotary ground. Width and length are milled.

ALL "A" THICKNESSES AVAILABLE IN:

- DME No. 1 Steel – SAE 1030 type
- DME No. 2 Steel – AISI 4130 type, pre-heat treated (271-321 Bhn; 28-34 HRC)
- DME No. 3 Steel – P-20 type, pre-heat treated (271-321 Bhn; 28-34 HRC)

PLATES WITH "A" THICKNESSES FROM 7/8 TO 2 7/8 ALSO AVAILABLE IN:

- DME No. 7 Steel – Modified AISI 400 series stainless steel pre-heat treated (302-340 Bhn; 32-36 HRC)

THICKER PLATES IN DME NO. 7 STEEL ARE AVAILABLE ON SPECIAL ORDER

A	7/8 x 7/8		7/8 x 1 1/8		9/8 x 8"		9/8 x 11 7/8	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
7/8	88-7RGM	16	812-7RGM	24	108-7RGM	20	1012-7RGM	30
1 1/8	88-13RGM	25	812-13RGM	37	108-13RGM	31	1012-13RGM	46
1 1/8	88-17RGM	33	812-17RGM	50	108-17RGM	42	1012-17RGM	63
2 1/8	88-23RGM	42	812-23RGM	63	108-23RGM	54	1012-23RGM	79
2 1/8	88-27RGM	51	812-27RGM	76	108-27RGM	65	1012-27RGM	96
3 1/8	88-33RGM	60	812-33RGM	89	108-33RGM	76	1012-33RGM	113
3 1/8	88-37RGM	69	812-37RGM	102	108-37RGM	87	1012-37RGM	129
4 1/8	88-47RGM	86	812-47RGM	129	108-47RGM	110	1012-47RGM	162
5 1/8	88-57RGM	104	812-57RGM	155	108-57RGM	132	1012-57RGM	196

A	9/8 x 16"		9/8 x 20"		9/8 x 23 3/4"		10 7/8 x 12"		10 7/8 x 14"		10 7/8 x 18"		10 7/8 x 23 1/2"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1016-7RGM	40	1020-7RGM	49	1024-7RGM	59	1112-7RGM	33	1114-7RGM	38	1118-7RGM	49	1123-7RGM	64	7/8
1 1/8	1016-13RGM	62	1020-13RGM	77	1024-13RGM	92	1112-13RGM	51	1114-13RGM	60	1118-13RGM	77	1123-13RGM	100	1 1/8
1 1/8	1016-17RGM	84	1020-17RGM	105	1024-17RGM	125	1112-17RGM	70	1114-17RGM	81	1118-17RGM	104	1123-17RGM	136	1 1/8
2 1/8	1016-23RGM	107	1020-23RGM	133	1024-23RGM	158	1112-23RGM	88	1114-23RGM	103	1118-23RGM	132	1123-23RGM	172	2 1/8
2 1/8	1016-27RGM	129	1020-27RGM	161	1024-27RGM	192	1112-27RGM	107	1114-27RGM	124	1118-27RGM	160	1123-27RGM	209	2 1/8
3 1/8	1016-33RGM	152	1020-33RGM	189	1024-33RGM	225	1112-33RGM	125	1114-33RGM	146	1118-33RGM	188	1123-33RGM	245	3 1/8
3 1/8	1016-37RGM	174	1020-37RGM	217	1024-37RGM	258	1112-37RGM	144	1114-37RGM	168	1118-37RGM	215	1123-37RGM	281	3 1/8
4 1/8	1016-47RGM	219	1020-47RGM	273	1024-47RGM	324	1112-47RGM	181	1114-47RGM	211	1118-47RGM	271	1123-47RGM	353	4 1/8
5 1/8	1016-57RGM	263	1020-57RGM	329	1024-57RGM	391	1112-57RGM	218	1114-57RGM	254	1118-57RGM	326	1123-57RGM	426	5 1/8


A	1 1/8 x 12"		1 1/8 x 15"		1 1/8 x 17 1/2"		1 1/8 x 20"		1 1/8 x 23 1/2"		1 1/8 x 29 1/2"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1212-7RGM	36	1215-7RGM	45	1217-7RGM	52	1220-7RGM	59	1223-7RGM	70	1229-7RGM	87	7/8
1 1/8	1212-13RGM	56	1215-13RGM	70	1217-13RGM	81	1220-13RGM	93	1223-13RGM	109	1229-13RGM	137	1 1/8
1 1/8	1212-17RGM	76	1215-17RGM	95	1217-17RGM	111	1220-17RGM	127	1223-17RGM	149	1229-17RGM	187	1 1/8
2 1/8	1212-23RGM	96	1215-23RGM	120	1217-23RGM	140	1220-23RGM	160	1223-23RGM	188	1229-23RGM	236	2 1/8
2 1/8	1212-27RGM	117	1215-27RGM	146	1217-27RGM	170	1220-27RGM	194	1223-27RGM	228	1229-27RGM	286	2 1/8
3 1/8	1212-33RGM	137	1215-33RGM	171	1217-33RGM	199	1220-33RGM	228	1223-33RGM	267	1229-33RGM	335	3 1/8
3 1/8	1212-37RGM	157	1215-37RGM	196	1217-37RGM	229	1220-37RGM	261	1223-37RGM	307	1229-37RGM	385	3 1/8
4 1/8	1212-47RGM	197	1215-47RGM	247	1217-47RGM	287	1220-47RGM	329	1223-47RGM	386	1229-47RGM	484	4 1/8
5 1/8	1212-57RGM	238	1215-57RGM	297	1217-57RGM	346	1220-57RGM	396	1223-57RGM	465	1229-57RGM	584	5 1/8

WHEN ORDERING, PLEASE SPECIFY:

1. Quantity & Item Number
2. No. 1, No. 2, No. 3 or No. 7 Steel
3. Method of Shipment

[CONTACT US](#)

Finish Ground Mold Plates 13³/₈ through 15⁷/₈ wide



FINISH GROUND MOLD PLATES

Thickness (A) of plate is finish ground ±.001. Width and length are finished square and parallel.

ALL "A" THICKNESSES AVAILABLE IN:

- DME No. 1 Steel – SAE 1030 type
- DME No. 2 Steel – AISI 4130 type, pre-heat treated (271-321 Bhn; 28-34 HRC)
- DME No. 3 Steel – P-20 type, pre-heat treated (271-321 Bhn; 28-34 HRC)

PLATES WITH "A" THICKNESSES FROM 7/8 TO 2 7/8 ALSO AVAILABLE IN:

- DME No. 7 Steel – Modified AISI 400 series stainless steel pre-heat treated (302-340 Bhn; 32-36 HRC)

THICKER PLATES IN DME NO. 7 STEEL ARE AVAILABLE ON SPECIAL ORDER

A	13 ³ / ₈ × 15"		13 ³ / ₈ × 18"		13 ³ / ₈ × 20 ³ / ₄ "	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
7/8	1315-7	50	1318-7	60	1321-7	69
1 1/8	1315-13	79	1318-13	94	1321-13	109
1 1/4	1315-17	107	1318-17	128	1321-17	148
2 1/8	1315-23	135	1318-23	162	1321-23	187
2 1/4	1315-27	164	1318-27	197	1321-27	227
3 1/8	1315-33	192	1318-33	231	1321-33	266
3 1/4	1315-37	221	1318-37	265	1321-37	305
4 1/8	1315-47	278	1318-47	333	1321-47	384
5 1/8	1315-57	334	1318-57	401	1321-57	462

A	13 ³ / ₈ × 23 ¹ / ₂ "		13 ³ / ₈ × 26"		13 ³ / ₈ × 29 ¹ / ₂ "		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1323-7	78	1326-7	87	1329-7	98	7/8
1 1/8	1323-13	123	1326-13	136	1329-13	154	1 1/8
1 1/4	1323-17	167	1326-17	185	1329-17	210	1 1/4
2 1/8	1323-23	212	1326-23	234	1329-23	266	2 1/8
2 1/4	1323-27	256	1326-27	284	1329-27	322	2 1/4
3 1/8	1323-33	301	1326-33	333	1329-33	378	3 1/8
3 1/4	1323-37	346	1326-37	382	1329-37	434	3 1/4
4 1/8	1323-47	435	1326-47	481	1329-47	545	4 1/8
5 1/8	1323-57	524	1326-57	579	1329-57	657	5 1/8

A	14 ⁷ / ₈ × 17 ⁷ / ₈ "		14 ⁷ / ₈ × 23 ³ / ₄ "		14 ⁷ / ₈ × 29 ¹ / ₂ "		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1518-7	66	1524-7	88	1529-7	109	7/8
1 1/8	1518-13	104	1524-13	138	1529-13	171	1 1/8
1 1/4	1518-17	142	1524-17	188	1529-17	233	1 1/4
2 1/8	1518-23	179	1524-23	238	1529-23	296	2 1/8
2 1/4	1518-27	217	1524-27	288	1529-27	358	2 1/4
3 1/8	1518-33	255	1524-33	338	1529-33	420	3 1/8
3 1/4	1518-37	292	1524-37	388	1529-37	482	3 1/4
4 1/8	1518-47	368	1524-47	488	1529-47	606	4 1/8
5 1/8	1518-57	443	1524-57	588	1529-57	731	5 1/8

A	15 ⁷ / ₈ × 16"		15 ⁷ / ₈ × 20"		15 ⁷ / ₈ × 23 ¹ / ₂ "		15 ⁷ / ₈ × 26"		15 ⁷ / ₈ × 29 ¹ / ₂ "		15 ⁷ / ₈ × 35 ¹ / ₂ "		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1616-7	63	1620-7	79	1623-7	93	1626-7	103	1629-7	116	1635-7	140	7/8
1 1/8	1616-13	99	1620-13	124	1623-13	146	1626-13	161	1629-13	183	1635-13	220	1 1/8
1 1/4	1616-17	135	1620-17	169	1623-17	199	1626-17	220	1629-17	249	1635-17	300	1 1/4
2 1/8	1616-23	171	1620-23	214	1623-23	252	1626-23	278	1629-23	315	1635-23	380	2 1/8
2 1/4	1616-27	207	1620-27	259	1623-27	304	1626-27	337	1629-27	382	1635-27	459	2 1/4
3 1/8	1616-33	243	1620-33	304	1623-33	357	1626-33	395	1629-33	448	1635-33	539	3 1/8
3 1/4	1616-37	279	1620-37	349	1623-37	410	1626-37	454	1629-37	515	1635-37	619	3 1/4
4 1/8	1616-47	351	1620-47	439	1623-47	516	1626-47	570	1629-47	647	1635-47	779	4 1/8
5 1/8	1616-57	423	1620-57	529	1623-57	621	1626-57	687	1629-57	780	1635-57	938	5 1/8

WHEN ORDERING, PLEASE SPECIFY:

1. Quantity & Item Number
2. No. 1, No. 2, No. 3 or No. 7 Steel
3. Method of Shipment

[CONTACT US](#)

Rotary Ground Mold Plates 1 3/8 through 1 5/8 wide

ROTARY GROUND MOLD PLATES

Thickness (A) of plate is rotary ground. Width and length are milled.

ALL "A" THICKNESSES AVAILABLE IN:

- DME No. 1 Steel – SAE 1030 type
- DME No. 2 Steel – AISI 4130 type, pre-heat treated (271-321 Bhn; 28-34 HRC)
- DME No. 3 Steel – P-20 type, pre-heat treated (271-321 Bhn; 28-34 HRC)

PLATES WITH "A" THICKNESSES FROM 7/8 TO 2 7/8 ALSO AVAILABLE IN:

- DME No. 7 Steel – Modified AISI 400 series stainless steel pre-heat treated (302-340 Bhn; 32-36 HRC)

THICKER PLATES IN DME NO. 7 STEEL ARE AVAILABLE ON SPECIAL ORDER

Mold Plate Size	TOLERANCES	
	1315, 1318, 1518	1321, 1323, 1326, 1329, 1524, 1529, 1616, 1620, 1623, 1626, 1629, 1635
Thickness (A)	+0.015 to +0.020	+0.025 to +0.030
Width (W) Nominal +.0025	+.000/+0.005	
Length (L) Nominal +.0025	+.000/+0.005	

A	1 3/8 x 15"		1 3/8 x 18"		1 3/8 x 20 3/4"	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
7/8	1315-7RGM	50	1318-7RGM	60	1321-7RGM	69
1 1/8	1315-13RGM	79	1318-13RGM	94	1321-13RGM	109
1 1/4	1315-17RGM	107	1318-17RGM	128	1321-17RGM	148
2 1/8	1315-23RGM	135	1318-23RGM	162	1321-23RGM	187
2 1/4	1315-27RGM	164	1318-27RGM	197	1321-27RGM	227
3 1/8	1315-33RGM	192	1318-33RGM	231	1321-33RGM	266
3 1/4	1315-37RGM	221	1318-37RGM	265	1321-37RGM	305
4 1/8	1315-47RGM	278	1318-47RGM	333	1321-47RGM	384
5 1/8	1315-57RGM	334	1318-57RGM	401	1321-57RGM	462

A	1 3/8 x 23 1/2"		1 3/8 x 26"		1 3/8 x 29 1/2"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1323-7RGM	78	1326-7RGM	87	1329-7RGM	98	7/8
1 1/8	1323-13RGM	123	1326-13RGM	136	1329-13RGM	154	1 1/8
1 1/4	1323-17RGM	167	1326-17RGM	185	1329-17RGM	210	1 1/4
2 1/8	1323-23RGM	212	1326-23RGM	234	1329-23RGM	266	2 1/8
2 1/4	1323-27RGM	256	1326-27RGM	284	1329-27RGM	322	2 1/4
3 1/8	1323-33RGM	301	1326-33RGM	333	1329-33RGM	378	3 1/8
3 1/4	1323-37RGM	346	1326-37RGM	382	1329-37RGM	434	3 1/4
4 1/8	1323-47RGM	435	1326-47RGM	481	1329-47RGM	545	4 1/8
5 1/8	1323-57RGM	524	1326-57RGM	579	1329-57RGM	657	5 1/8

A	1 7/8 x 17 1/8"		1 7/8 x 23 3/4"		1 7/8 x 29"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1518-7RGM	66	1524-7RGM	88	1529-7RGM	109	7/8
1 1/8	1518-13RGM	104	1524-13RGM	138	1529-13RGM	171	1 1/8
1 1/4	1518-17RGM	142	1524-17RGM	188	1529-17RGM	233	1 1/4
2 1/8	1518-23RGM	179	1524-23RGM	238	1529-23RGM	296	2 1/8
2 1/4	1518-27RGM	217	1524-27RGM	288	1529-27RGM	358	2 1/4
3 1/8	1518-33RGM	255	1524-33RGM	338	1529-33RGM	420	3 1/8
3 1/4	1518-37RGM	292	1524-37RGM	388	1529-37RGM	482	3 1/4
4 1/8	1518-47RGM	368	1524-47RGM	488	1529-47RGM	606	4 1/8
5 1/8	1518-57RGM	443	1524-57RGM	588	1529-57RGM	731	5 1/8


A	1 5/8 x 16"		1 5/8 x 20"		1 5/8 x 23 1/2"		1 5/8 x 26"		1 5/8 x 29 1/2"		1 5/8 x 35 1/2"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
7/8	1616-7RGM	63	1620-7RGM	79	1623-7RGM	93	1626-7RGM	103	1629-7RGM	116	1635-7RGM	140	7/8
1 1/8	1616-13RGM	99	1620-13RGM	124	1623-13RGM	146	1626-13RGM	161	1629-13RGM	183	1635-13RGM	220	1 1/8
1 1/4	1616-17RGM	135	1620-17RGM	169	1623-17RGM	199	1626-17RGM	220	1629-17RGM	249	1635-17RGM	300	1 1/4
2 1/8	1616-23RGM	171	1620-23RGM	214	1623-23RGM	252	1626-23RGM	278	1629-23RGM	315	1635-23RGM	380	2 1/8
2 1/4	1616-27RGM	207	1620-27RGM	259	1623-27RGM	304	1626-27RGM	337	1629-27RGM	382	1635-27RGM	459	2 1/4
3 1/8	1616-33RGM	243	1620-33RGM	304	1623-33RGM	357	1626-33RGM	395	1629-33RGM	448	1635-33RGM	539	3 1/8
3 1/4	1616-37RGM	279	1620-37RGM	349	1623-37RGM	410	1626-37RGM	454	1629-37RGM	515	1635-37RGM	619	3 1/4
4 1/8	1616-47RGM	351	1620-47RGM	439	1623-47RGM	516	1626-47RGM	570	1629-47RGM	647	1635-47RGM	779	4 1/8
5 1/8	1616-57RGM	423	1620-57RGM	529	1623-57RGM	621	1626-57RGM	687	1629-57RGM	780	1635-57RGM	938	5 1/8

WHEN ORDERING, PLEASE SPECIFY:

1. Quantity & Item Number
2. No. 1, No. 2, No. 3 or No. 7 Steel
3. Method of Shipment

[CONTACT US](#)

Finish Ground Mold Plates 16½ through 23¾ wide



FINISH GROUND MOLD PLATES

Thickness (A) of plate is finish ground ±.001. Width and length are finished square and parallel.

ALL "A" THICKNESSES AVAILABLE IN:

- DME No. 1 Steel – SAE 1030 type
- DME No. 2 Steel – AISI 4130 type, pre-heat treated (271-321 Bhn; 28-34 HRC)
- DME No. 3 Steel – P-20 type, pre-heat treated (271-321 Bhn; 28-34 HRC)

PLATES WITH "A" THICKNESSES FROM 7/8 TO 27/8 ALSO AVAILABLE IN:

- DME No. 7 Steel – Modified AISI 400 series stainless steel pre-heat treated (302-340 Bhn; 32-36 HRC)

THICKER PLATES IN DME NO. 7 STEEL ARE AVAILABLE ON SPECIAL ORDER

A	16½ × 23¾		16½ × 29½		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
¾	1724-7	98	1729-7	121	¾
1%	1724-13	153	1729-13	190	1%
1½	1724-17	209	1729-17	259	1½
2%	1724-23	264	1729-23	328	2%
2½	1724-27	320	1729-27	397	2½
3%	1724-33	375	1729-33	466	3%
3½	1724-37	431	1729-37	535	3½
4%	1724-47	542	1729-47	673	4%
5%	1724-57	653	1729-57	811	5%

A	17⅞ × 18"		17⅞ × 20"		17⅞ × 23½		17⅞ × 26"		17⅞ × 29½		17⅞ × 35½		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
¾	1818-7	80	1820-7	89	1823-7	105	1826-7	116	1829-7	131	1835-7	158	¾
1%	1818-13	126	1820-13	140	1823-13	164	1826-13	182	1829-13	206	1835-13	248	1%
1½	1818-17	171	1820-17	190	1823-17	224	1826-17	247	1829-17	281	1835-17	338	1½
2%	1818-23	217	1820-23	241	1823-23	283	1826-23	313	1829-23	355	1835-23	427	2%
2½	1818-27	263	1820-27	292	1823-27	343	1826-27	379	1829-27	430	1835-27	517	2½
3%	1818-33	308	1820-33	342	1823-33	402	1826-33	445	1829-33	505	1835-33	607	3%
3½	1818-37	354	1820-37	393	1823-37	462	1826-37	511	1829-37	579	1835-37	697	3½
4%	1818-47	445	1820-47	494	1823-47	581	1826-47	642	1829-47	729	1835-47	877	4%
5%	1818-57	536	1820-57	596	1823-57	700	1826-57	774	1829-57	878	1835-57	1057	5%

A	19½ × 23¾		19½ × 29½		19½ × 35½		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
¾	1924-7	115	1929-7	143	1935-7	172	¾
1%	1924-13	181	1929-13	224	1935-13	270	1%
1½	1924-17	246	1929-17	306	1935-17	368	1½
2%	1924-23	312	1929-23	387	1935-23	466	2%
2½	1924-27	378	1929-27	469	1935-27	564	2½
3%	1924-33	443	1929-33	550	1935-33	662	3%
3½	1924-37	509	1929-37	632	1935-37	760	3½
4%	1924-47	640	1929-47	795	1935-47	956	4%
5%	1924-57	771	1929-57	958	1935-57	1153	5%

A	23¾ × 23¾		23¾ × 29½		23¾ × 35½		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
¾	2424-7	140	2429-7	174	2435-7	209	¾
1%	2424-13	220	2429-13	273	2435-13	329	1%
1½	2424-17	300	2429-17	373	2435-17	448	1½
2%	2424-23	380	2429-23	472	2435-23	568	2%
2½	2424-27	460	2429-27	571	2435-27	687	2½
3%	2424-33	540	2429-33	670	2435-33	807	3%
3½	2424-37	620	2429-37	770	2435-37	926	3½
4%	2424-47	779	2429-47	968	2435-47	1165	4%
5%	2424-57	939	2429-57	1167	2435-57	1404	5%

WHEN ORDERING, PLEASE SPECIFY:

1. Quantity & Item Number
2. No. 1, No. 2, No. 3 or No. 7 Steel
3. Method of Shipment

[CONTACT US](#)

Rotary Ground Mold Plates 16½ through 23¾ wide

ROTARY GROUND MOLD PLATES

Mold Plate Size	TOLERANCES	
	1315, 1318, 1518	1321, 1323, 1326, 1329, 1524, 1529, 1616, 1620, 1623, 1626, 1629, 1635
Thickness (A)	+0.015 to +0.020	+0.025 to +0.030
Width (W) Nominal +0.0025	+0.000/+0.005	
Length (L) Nominal +0.0025	+0.000/+0.005	

Thickness (A) of plate is rotary ground. Width and length are milled.

ALL "A" THICKNESSES AVAILABLE IN:

- DME No. 1 Steel – SAE 1030 type
- DME No. 2 Steel – AISI 4130 type, pre-heat treated (271-321 Bhn; 28-34 HRC)
- DME No. 3 Steel – P-20 type, pre-heat treated (271-321 Bhn; 28-34 HRC)

PLATES WITH "A" THICKNESSES FROM ⅞ TO 2⅞ ALSO AVAILABLE IN:

- DME No. 7 Steel – Modified AISI 400 series stainless steel pre-heat treated (302-340 Bhn; 32-36 HRC)

THICKER PLATES IN DME NO. 7 STEEL ARE AVAILABLE ON SPECIAL ORDER

A	16½ × 23¾		16½ × 29½		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
⅞	1724-7RGM	98	1729-7RGM	121	⅞
1⅞	1724-13RGM	153	1729-13RGM	190	1⅞
1⅞	1724-17RGM	209	1729-17RGM	259	1⅞
2⅞	1724-23RGM	264	1729-23RGM	328	2⅞
2⅞	1724-27RGM	320	1729-27RGM	397	2⅞
3⅞	1724-33RGM	375	1729-33RGM	466	3⅞
3⅞	1724-37RGM	431	1729-37RGM	535	3⅞
4⅞	1724-47RGM	542	1729-47RGM	673	4⅞
5⅞	1724-57RGM	653	1729-57RGM	811	5⅞

A	17⅞ × 18"		17⅞ × 20"		17⅞ × 23½		17⅞ × 26"		17⅞ × 29½		17⅞ × 35½		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
⅞	1818-7RGM	80	1820-7RGM	89	1823-7RGM	105	1826-7RGM	116	1829-7RGM	131	1835-7RGM	158	⅞
1⅞	1818-13RGM	126	1820-13RGM	140	1823-13RGM	164	1826-13RGM	182	1829-13RGM	206	1835-13RGM	248	1⅞
1⅞	1818-17RGM	171	1820-17RGM	190	1823-17RGM	224	1826-17RGM	247	1829-17RGM	281	1835-17RGM	338	1⅞
2⅞	1818-23RGM	217	1820-23RGM	241	1823-23RGM	283	1826-23RGM	313	1829-23RGM	355	1835-23RGM	427	2⅞
2⅞	1818-27RGM	263	1820-27RGM	292	1823-27RGM	343	1826-27RGM	379	1829-27RGM	430	1835-27RGM	517	2⅞
3⅞	1818-33RGM	308	1820-33RGM	342	1823-33RGM	402	1826-33RGM	445	1829-33RGM	505	1835-33RGM	607	3⅞
3⅞	1818-37RGM	354	1820-37RGM	393	1823-37RGM	462	1826-37RGM	511	1829-37RGM	579	1835-37RGM	697	3⅞
4⅞	1818-47RGM	445	1820-47RGM	494	1823-47RGM	581	1826-47RGM	642	1829-47RGM	729	1835-47RGM	877	4⅞
5⅞	1818-57RGM	536	1820-57RGM	596	1823-57RGM	700	1826-57RGM	774	1829-57RGM	878	1835-57RGM	1057	5⅞

A	19½ × 23¾		19½ × 29½		19½ × 35½		A	A	23¾ × 23¾		23¾ × 29½		23¾ × 35½		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.			ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
⅞	1924-7RGM	115	1929-7RGM	143	1935-7RGM	172	⅞	⅞	2424-7RGM	140	2429-7RGM	174	2435-7RGM	209	⅞
1⅞	1924-13RGM	181	1929-13RGM	224	1935-13RGM	270	1⅞	1⅞	2424-13RGM	220	2429-13RGM	273	2435-13RGM	329	1⅞
1⅞	1924-17RGM	246	1929-17RGM	306	1935-17RGM	368	1⅞	1⅞	2424-17RGM	300	2429-17RGM	373	2435-17RGM	448	1⅞
2⅞	1924-23RGM	312	1929-23RGM	387	1935-23RGM	466	2⅞	2⅞	2424-23RGM	380	2429-23RGM	472	2435-23RGM	568	2⅞
2⅞	1924-27RGM	378	1929-27RGM	469	1935-27RGM	564	2⅞	2⅞	2424-27RGM	460	2429-27RGM	571	2435-27RGM	687	2⅞
3⅞	1924-33RGM	443	1929-33RGM	550	1935-33RGM	662	3⅞	3⅞	2424-33RGM	540	2429-33RGM	670	2435-33RGM	807	3⅞
3⅞	1924-37RGM	509	1929-37RGM	632	1935-37RGM	760	3⅞	3⅞	2424-37RGM	620	2429-37RGM	770	2435-37RGM	926	3⅞
4⅞	1924-47RGM	640	1929-47RGM	795	1935-47RGM	956	4⅞	4⅞	2424-47RGM	779	2429-47RGM	968	2435-47RGM	1165	4⅞
5⅞	1924-57RGM	771	1929-57RGM	958	1935-57RGM	1153	5⅞	5⅞	2424-57RGM	939	2429-57RGM	1167	2435-57RGM	1404	5⅞


WHEN ORDERING, PLEASE SPECIFY:

1. Quantity & Item Number
2. No. 1, No. 2, No. 3 or No. 7 Steel
3. Method of Shipment

[CONTACT US](#)

Ejector Plates DME No. 1 Steel

EJECTOR PLATES



Thickness of plate is finish ground to a tolerance of plus or minus .001".

WIDTH OF MOLD BASE	A THICK	M WIDTH	E LENGTH	ITEM NUMBER	NET WT.
6	1	4	14	6-614C	16
7	1/2	5	6	6-67R	5
7 7/8	1	5 1/4	7 7/8	6-88	8
			11 1/8	6-812	12
			16	6-816	15
			20	6-820	19
8 15/16	1/2	6*	11 1/8	6-912V	11
9	1	6	11 1/8	6-912M	21
			16	6-916M	28
			23 1/2	6-923M	40
9 7/8	1/2	6	8	6-108V	7
			7 7/8	6-108R	8
	1	6 7/8	8	6-108	16
			11 1/8	6-1012	24
			16	6-1016	32
			20	6-1020	39
			23 1/2	6-1023	46
			29 1/2	6-1029	58
10 7/8	1	7 7/8	12	6-1112	26
			14	6-1114	30
			18	6-1118	38
			23 1/2	6-1123	50
			29 1/2	6-1129	62
11 7/8	1 1/2	8 7/8	12	6-1212	33
			15	6-1215	41
			20	6-1220	54
			23 1/2	6-1223	63
			29 1/2	6-1229	79

WIDTH OF MOLD BASE	A THICK	M WIDTH	E LENGTH	ITEM NUMBER	NET WT.
13 3/8	1 1/2	9 1/2	15	6-1315	46
			18	6-1318	55
			18 1/2	6-1319	57
			20 3/4	6-1321	63
			23 1/2	6-1323	72
			26	6-1326	79
			29 1/2	6-1329	90
14 7/8	1 1/2	11	35 1/2	6-1335	108
			17 7/8	6-1518	63
			23 3/4	6-1524	84
			29 1/2	6-1529	104
			35 1/2	6-1535	125
15 7/8	1 1/2	12	16	6-1616	62
			20	6-1620	77
			23 1/2	6-1623	90
			26	6-1626	100
			29 1/2	6-1629	113
			35 1/2	6-1635	136
16 1/2	1 1/2	12 5/8	23 3/4	6-1724	96
			29 1/2	6-1729	119
			35 1/2	6-1735	143
17 7/8	1 1/2	14	18	6-1818	81
			20	6-1820	90
			23 1/2	6-1823	105
			26	6-1826	117
			29 1/2	6-1829	132
			35 1/2	6-1835	159
19 1/2	1 1/2	15 5/8	23 3/4	6-1924	119
			29 1/2	6-1929	147
			35 1/2	6-1935	177
23 3/4	1 1/2	19 7/8	23 3/4	6-2424	151
			29 1/2	6-2429	187
			35 1/2	6-2435	225


WHEN ORDERING, PLEASE SPECIFY:

1. Quantity
2. Item Number
3. Method of Shipment

[CONTACT US](#)

Ejector Retainer Plates DME No. 1 Steel

EJECTOR RETAINER PLATES



Thickness of plate tolerance of plus .015", minus .000".

A THICK	M WIDTH	L LENGTH	USED WITH MOLD BASES LISTED BELOW	ITEM NUMBER	NET WT.	
3/8	5	6	6 × 7R	7-67R	4	
	4	10 5/8	6 × 10 5/8	7-611C	7	
	5 1/4	7 7/8	7 7/8 × 7 7/8	7-88	6	
	5 1/4	11 1/8	7 7/8 × 11 1/8	7-812	9	
	6	8	9 5/8 × 8V	7-108V	7	
	6	11 1/8	8 5/16 × 11 1/8V or 9 × 11 1/8M	7-912VM	11	
	1/2	6 3/8	7 7/8	108R	7-108R	8
			8	9 5/8 × 8	7-108	8
		6 1/2	11 1/8	9 5/8 × 11 1/8	7-1012	12
			16	9 5/8 × 16	7-1016	16
20			9 5/8 × 20	7-1020	20	
12			10 1/8 × 12	7-1112	13	
7 1/8		14	10 1/8 × 14	7-1114	15	
		18	10 1/8 × 18	7-1118	19	
		23 1/2	10 1/8 × 23 1/2	7-1123	25	
8 1/8		12	11 1/8 × 12	7-1212	15	
	15	11 1/8 × 15	7-1215	18		
	20	11 1/8 × 20	7-1220	24		
	23 1/2	11 1/8 × 23 1/2	7-1223	28		
5/8	9 1/2	15	13 3/8 × 15	7-1315	26	
		18	13 3/8 × 18	7-1318	31	
		20 3/4	13 3/8 × 20 3/4	7-1321	35	
		23 1/2	13 3/8 × 23 1/2	7-1323	40	
	11	26	13 3/8 × 26	7-1326	44	
		29 1/2	13 3/8 × 29 1/2	7-1329	50	
		17 7/8	14 1/8 × 17 7/8	7-1518	35	
		23 3/4	14 1/8 × 23 3/4	7-1524	47	
		29 1/2	14 1/8 × 29 1/2	7-1529	58	

A THICK	M WIDTH	L LENGTH	USED WITH MOLD BASES LISTED BELOW	ITEM NUMBER	NET WT.
5/8 (cont.)	12	16	15 5/8 × 16	7-1616	34
		20	15 5/8 × 20	7-1620	43
		23 1/2	15 5/8 × 23 1/2	7-1623	50
		26	15 5/8 × 26	7-1626	58
		29 1/2	15 5/8 × 29 1/2	7-1629	63
	12 5/8	35 1/2	15 5/8 × 35 1/2	7-1635	76
		23 3/4	16 1/2 × 23 3/4	7-1724	54
	14	29 1/2	16 1/2 × 29 1/2	7-1729	66
		18	17 7/8 × 18	7-1818	45
		20	17 7/8 × 20	7-1820	50
		23 1/2	17 7/8 × 23 1/2	7-1823	59
		26	17 7/8 × 26	7-1826	65
		29 1/2	17 7/8 × 29 1/2	7-1829	74
		35 1/2	17 7/8 × 35 1/2	7-1835	89
	15 1/8	23 3/4	19 1/2 × 23 3/4	7-1924	66
		29 1/2	19 1/2 × 29 1/2	7-1929	82
		35 1/2	19 1/2 × 35 1/2	7-1935	99
	19 1/8	23 3/4	23 3/4 × 23 3/4	7-2424	84
		29 1/2	23 3/4 × 29 1/2	7-2429	104
		35 1/2	23 3/4 × 35 1/2	7-2435	125



WHEN ORDERING, PLEASE SPECIFY:

- Quantity
- Item Number
- Method of Shipment

[CONTACT US](#)

Spacer Blocks Plain and Slotted – DME No. 1 Steel

SPACER BLOCKS



Machined all over. Riser height ("C" dimension) is finish ground to a tolerance of plus or minus .001". Width ("P" dimension) is rough ground to a tolerance of - .000, + .015. Finish ground width available on special order.

P	L	C	PLAIN		SLOTTED		
			ITEM NUMBER	NET WT.	ITEM NUMBER		
1/16	11 1/2	2 1/2	25-912V	8	—		
			25-408	7	25-508		
1/4	7	2 1/2	30-408	9	30-508		
			3	30-408	9	30-508	
1/8	8	2 1/2	25-608	9	25-708		
			3	30-608	10	30-708	
			4	40-608	14	40-708	
		3	50-608	17	50-708		
			25-612	13	25-712		
			30-612	15	30-712		
	11 1/2	3 1/2	—		35-712M		
			40-612	20	40-712		
			50-612	25	50-712		
		2 1/2	25-616	17	25-716		
			30-616	20	30-716		
			40-616	27	40-716		
16	5	50-616	33	50-716			
		25-620	21	25-720			
		30-620	25	30-720			
	4	40-620	33	40-720			
		50-620	41	50-720			
		30-112	18	30-212			
12	4	40-112	23	40-212			
		50-112	29	50-212			
		60-112	35	60-212			
	3	30-115	22	30-215			
		40-115	29	40-215			
		50-115	36	50-215			
15	6	60-115	44	60-215			
		30-118	26	30-218			
		40-118	35	40-218			
	4	50-118	44	50-218			
		60-118	52	60-218			
		30-120	29	30-220			
18	4	40-120	39	40-220			
		50-120	48	50-220			
		60-120	58	60-220			
	3	30-123	34	30-223			
		40-123	45	40-223			
		50-123	57	50-223			
23 1/2	6	60-123	68	60-223			

P	L	C	PLAIN		SLOTTED		
			ITEM NUMBER	NET WT.	ITEM NUMBER		
1/16 (cont.)	26	3	30-126	38	30-226		
			40-126	50	40-226		
			50-126	63	50-226		
		6	60-126	75	60-226		
			30-129	43	30-229		
			40-129	57	40-229		
	29 1/2	5	50-129	71	50-229		
			60-129	85	60-229		
			30-135	51	30-235		
		4	40-135	68	40-235		
			5	50-135	85	50-235	
				60-135	102	60-235	
1/8	8	25-108V		11	—		
		30-418	29	30-518			
		40-418	39	40-518			
	18	5	50-418	48	50-518		
			60-418	58	60-518		
			30-420	32	30-520		
		4	40-420	43	40-520		
			5	50-420	54	50-520	
				60-420	64	60-520	
	20	3		30-424	38	30-524	
			40-424	51	40-524		
			50-424	64	50-524		
6		60-424	76	60-524			
		3	30-426	42	30-526		
			40-426	56	40-526		
26	5		50-426	70	50-526		
		60-426	83	60-526			
		30-429	48	30-529			
	4	40-429	63	40-529			
		5	50-429	79	50-529		
			60-429	95	60-529		
29 1/2	3		30-435	57	30-535		
		40-435	76	40-535			
		50-435	95	50-535			
	6	60-435	114	60-535			

WHEN ORDERING, PLEASE SPECIFY:

- Quantity
- Item Number
- Method of Shipment





[CONTACT US](#)

A-Slotted Rails – DME No. 1 Steel and No. 7 Steel

A-SLOTTED RAILS

AVAILABLE IN:

- DME No. 1 Steel – SAE 1030 type
- DME No. 7 Steel – Modified AISI 400 series stainless steel



STEEL DESCRIPTIONS

DME NO. 1 STEEL

No. 1 Steel is a medium carbon (SAE 1030) or equivalent, silicon-killed forging quality steel with approximately 25% greater tensile strength than typical low-carbon warehouse steels. It machines easily, but is not “sticky,” permitting a faster and smoother cut.

DME NO. 7 STEEL

No. 7 Steel is a modified AISI 400 or equivalent series stainless steel for holder block applications. It is supplied pre-heat treated to 32-36 HRC (302-340 Bhn). This stainless steel offers corrosion-resistance and exceptional machinability but cannot be further hardened (see DME No. 6). For humid environments, corrosive plastics, “clean room” or “100% stainless” applications, it is an ideal choice for all structural (non-cavity/core) mold plates.

For A-Slotted Rails in other steel types please contact DME Customer Service.

CONTACT US

HOW TO ORDER: Specify Item Number Prefix (SA), Steel Type (S), Rail Width (P), Rail Length (L), Rail Height (C) and Item Number Suffix (0030).

Item Key:

SA	(S)	(P)	(L)	(C)	0030
----	-----	-----	-----	-----	------

SA : Item Number Prefix

(S) : Enter **1** for #1 steel or **7** for #7 steel

(P) : Rail Width

12 – 1.25 [1 1/4] (mold base series 88 and 812)

14 – 1.4375 [1 7/16] (mold base series 10xx)

16 – 1.6875 [1 11/16] (mold base series 11xx and 12xx)

17 – 1.875 [1 7/8] (mold base series 13xx and larger)

(L) : Rail Length (same as mold base length – examples 7 7/8 = **08**, 11 7/8 = **12**)

(C) : Rail Height (C dimension – do not include decimals – examples 2.5 = **25**, 3.0 = **30**, 3.5 = **35**, 4.0 = **40**, 4.5 = **45**)

0030 : Item Number Suffix

Example:

SA**1140825**0030

Example:

SA**7141230**0030




Do not include dashes or decimals in your item number.

Pre-Drilled A-Slotted Rails – DME No. 1 Steel and No. 7 Steel

PRE-DRILLED A-SLOTTED RAILS FOR 3-PIECE HOUSINGS

AVAILABLE IN:

- DME No. 1 Steel – SAE 1030 type
- DME No. 7 Steel – Modified AISI 400 series stainless steel



STEEL DESCRIPTIONS

DME NO. 1 STEEL

No. 1 Steel is a medium carbon (SAE 1030) or equivalent, silicon-killed forging quality steel with approximately 25% greater tensile strength than typical low-carbon warehouse steels. It machines easily, but is not “sticky,” permitting a faster and smoother cut.

DME NO. 7 STEEL

No. 7 Steel is a modified AISI 400 or equivalent series stainless steel for holder block applications. It is supplied pre-heat treated to 32-36 HRC (302-340 Bhn). This stainless steel offers corrosion-resistance and exceptional machinability but cannot be further hardened (see DME No. 6). For humid environments, corrosive plastics, “clean room” or “100% stainless” applications, it is an ideal choice for all structural (non-cavity/core) mold plates.

For A-Slotted Rails in other steel types please contact DME Customer Service.

CONTACT US

HOW TO ORDER: Specify Item Number Prefix (SA), Steel Type (S), Rail Width (P), Rail Length (L), Rail Height (C), Mold Base Width (W) and Item Number Suffix (70).

Item Key:

SA	(S)	(P)	(L)	(C)	(W)	70
----	-----	-----	-----	-----	-----	----

SA : Item Number Prefix

(S) : Enter **1** for #1 steel or **7** for #7 steel

(P) : Rail Width

12 – 1.25 [1 1/4] (mold base series 88 and 812)

14 – 1.4375 [1 7/16] (mold base series 10xx)

16 – 1.6875 [1 11/16] (mold base series 11xx and 12xx)

17 – 1.875 [1 7/8] (mold base series 13xx and larger)

(L) : Rail Length (same as mold base length – examples 7 7/8 = **08**, 11 7/8 = **12**)

(C) : Rail Height (C dimension – do not include decimals – examples 2.5 = **25**, 3.0 = **30**, 3.5 = **35**, 4.0 = **40**, 4.5 = **45**)

(W) : Mold Base Width - examples 7 7/8 = **08**, 19 1/2 = **19**)

70 : Item Number Suffix

Example:

SA11208250870

Example:

SA71412301070



Do not include dashes or decimals in your item number.

Spacer Blocks Angle Spacers – DME No. 1 Steel

SPACER BLOCKS


Riser height ("C" dimension) is finish ground to a tolerance of plus or minus .001".

These Angle Spacers are useful for the buildup of Compression Mold Assemblies.




AUXILIARY SPACER PLATENS

When the use of Auxiliary Spacer Platens becomes necessary to reduce the minimum daylight of the press, the importance of proper rigidity cannot be over-emphasized. The drawing shown here illustrates a typical installation that meets good rigidity requirements. The distance between the parallel spacer blocks is dependent on the location of the knock-out rods on the press.



The drawing shown below illustrates a recommended design that is available from DME on special order. The use of standard DME mold plates and spacer blocks can help keep the cost at a minimum. A detailed drawing should accompany your request for a quotation.




L	C	ITEM NUMBER	NET WT.
12	3	30-312	22
	4	40-312	27
	5	50-312	32
	6	60-312	37
15	3	30-315	28
	4	40-315	34
	5	50-315	40
18	3	30-318	33
	4	40-318	41
	5	50-318	48
20	3	30-320	37
	4	40-320	45
	5	50-320	54
23 3/4	3	30-324	43
	4	40-324	53
	5	50-324	64
26	3	30-326	47
	4	40-326	59
	5	50-326	70
29 1/2	3	30-329	54
	4	40-329	66
	5	50-329	79
35 1/2	3	30-335	65
	4	40-335	80
	5	50-335	95
	6	60-335	110

WHEN ORDERING, PLEASE SPECIFY:

- Quantity
- Item Number
- Method of Shipment



[CONTACT US](#)

Ejector Housings 7 7/8 to 13 3/8 Wide – DME No. 1 Steel



EJECTOR HOUSINGS

3-PIECE HOUSING



Three piece construction provides modular capabilities. Easily swap rails with an existing bottom clamp plate to obtain a different riser height. Riser height ("C" dimension) is finish ground to a tolerance of plus or minus .001". Outer surfaces are finished square and parallel.

NOTES:

Thickness of the base plate (T) is 7/8" for all sizes from 7 7/8" to 19 1/2" wide. The base plate for the 23 3/4" wide series is 1 3/8" thick.
* 1/2" on 88A and 812A Series Mold Bases
Stripper bolt hole locations (4) on the horizontal or "X" axis are 1.0" out board from the standard assembly mounting screws

DETAIL DIMENSIONS

W	7 7/8"	9 1/8"	10 1/8"	11 1/8"	13 1/8"	14 1/8"	15 1/8"	16 1/2"	17 1/8"	19 1/2"	23 3/4"
P	1 1/4"	1 1/16"	1 1/16"	1 1/16"	1"	1"	1"	1"	1"	1"	1"
Q	5 5/8"	7"	7 1/2"	8 1/2"	9 5/8"	11 1/8"	12 1/4"	12 3/4"	14 1/8"	15 3/4"	20"

C	Height of Riser	2 1/2"	3"	3 1/2"	4"	4 1/2"
	7 7/8" to 19 1/2" Wide Housings	3%	3%	4%	4%	5%
N	7 7/8" to 19 1/2" Wide Housings	3%	4%	4%	5%	5%
	23 3/4" Wide Housings	3%	4%	4%	5%	5%

W	L	C	ITEM NUMBER	NET WT.
7 7/8"	7 7/8"	2 1/2"	25-88	28
		3"	30-88	30
		3 1/2"	35-88	33
		4"	40-88	36
		4 1/2"	45-88	39
		5"	50-88	42
	11 1/8"	2 1/2"	25-812	42
		3"	30-812	45
		3 1/2"	35-812	50
		4"	40-812	54
		4 1/2"	45-812	59
		5"	50-812	64
9 1/8"	7 7/8"	2 1/2"	25-108R	34
		2 1/2"	25-108	34
		3"	30-108	37
	8"	3 1/2"	35-108	41
		4"	40-108	44
		4 1/2"	45-108	47
	11 1/8"	2 1/2"	25-1012	50
		3"	30-1012	55
		3 1/2"	35-1012	60
		4"	40-1012	65
		4 1/2"	45-1012	70
		16"	2 1/2"	25-1016
3"			30-1016	74
3 1/2"			35-1016	81
20"		4"	40-1016	87
	4 1/2"	45-1016	94	
	2 1/2"	25-1020	84	
	3"	30-1020	93	
	3 1/2"	35-1020	101	
	4"	40-1020	109	

W	L	C	ITEM NUMBER	NET WT.
10 7/8"	12"	2 1/2"	25-1112	58
		3"	30-1112	64
		3 1/2"	35-1112	70
		4"	40-1112	75
		4 1/2"	45-1112	81
		5"	50-1112	87
	14"	2 1/2"	25-1114	68
		3"	30-1114	74
		3 1/2"	35-1114	81
		4"	40-1114	88
		4 1/2"	45-1114	94
		5"	50-1114	100
11 7/8"	18"	2 1/2"	25-1118	87
		3"	30-1118	95
		3 1/2"	35-1118	104
	23 1/2"	4"	40-1118	113
		4 1/2"	45-1118	121
		5"	50-1118	129
	12"	2 1/2"	25-1123	113
		3"	30-1123	124
		3 1/2"	35-1123	136
		4"	40-1123	147
		4 1/2"	45-1123	158
		5"	50-1123	169
15"	3"	30-1212	67	
	3 1/2"	35-1212	73	
	4"	40-1212	78	
	4 1/2"	45-1212	84	
	3"	30-1215	83	
	3 1/2"	35-1215	91	

W	L	C	ITEM NUMBER	NET WT.
11 7/8" (cont.)	20"	3"	30-1220	111
		3 1/2"	35-1220	121
		4"	40-1220	130
		4 1/2"	45-1220	140
		3"	30-1223	130
		3 1/2"	35-1223	142
	23 1/2"	4"	40-1223	153
		4 1/2"	45-1223	164
		3"	30-1315	94
		3 1/2"	35-1315	102
		4"	40-1315	110
		4 1/2"	45-1315	118
13 3/8"	15"	3"	30-1318	112
		3 1/2"	35-1318	122
		4"	40-1318	131
	18"	4 1/2"	45-1318	141
		3"	30-1321	129
		3 1/2"	35-1321	140
	20 3/4"	4"	40-1321	152
		4 1/2"	45-1321	163
		3"	30-1323	147
	23 1/2"	3 1/2"	35-1323	159
		4"	40-1323	172
		4 1/2"	45-1323	184
26"	3"	30-1326	162	
	3 1/2"	35-1326	176	
	4"	40-1326	190	

WHEN ORDERING, PLEASE SPECIFY:

- Quantity
- Item Number
- Method of Shipment


[CONTACT US](#)

Ejector Housings 13³/₈ to 23³/₄ wide – DME No. 1 Steel

EJECTOR HOUSINGS

Three piece construction provides more rigid support for plastics molds or die-cast dies.

Riser height ("C" dimension) is finish ground to a tolerance of plus or minus .001". Outer surfaces are finished square and parallel.



Mold Plates | Ejector Housings 13³/₈ to 23³/₄ wide – DME No. 1 Steel

W	L	C	ITEM NUMBER	NET WT.	
13 ³ / ₈ (cont.)	29 ¹ / ₂	3	30-1329	184	
		3 ¹ / ₂	35-1329	200	
		4	40-1329	215	
		4 ¹ / ₂	45-1329	231	
14 ⁷ / ₈	17 ⁷ / ₈	3	30-1518	118	
		3 ¹ / ₂	35-1518	128	
		4	40-1518	137	
		4 ¹ / ₂	45-1518	147	
14 ⁷ / ₈	23 ³ / ₄	3	30-1524	157	
		3 ¹ / ₂	35-1524	170	
		4	40-1524	182	
		4 ¹ / ₂	45-1524	195	
15 ⁷ / ₈	29 ¹ / ₂	3	30-1529	195	
		3 ¹ / ₂	35-1529	210	
		4	40-1529	226	
		4 ¹ / ₂	45-1529	242	
	16	16	3	30-1616	110
			3 ¹ / ₂	35-1616	118
			4	40-1616	127
			4 ¹ / ₂	45-1616	135
	20	20	3	30-1620	137
			3 ¹ / ₂	35-1620	148
			4	40-1620	158
			4 ¹ / ₂	45-1620	169
23 ¹ / ₂		23 ¹ / ₂	3	30-1623	161
			3 ¹ / ₂	35-1623	174
			4	40-1623	186
			4 ¹ / ₂	45-1623	199
26	26	3	30-1626	178	
		3 ¹ / ₂	35-1626	192	
		4	40-1626	206	
		4 ¹ / ₂	45-1626	220	

W	L	C	ITEM NUMBER	NET WT.	
15 ⁷ / ₈ (cont.)	29 ¹ / ₂	3	30-1629	202	
		3 ¹ / ₂	35-1629	218	
		4	40-1629	233	
		4 ¹ / ₂	45-1629	249	
16 ¹ / ₂	35 ¹ / ₂	3	30-1635	243	
		3 ¹ / ₂	35-1635	262	
		4	40-1635	281	
		4 ¹ / ₂	45-1635	300	
16 ¹ / ₂	23 ³ / ₄	3	30-1724	166	
		3 ¹ / ₂	35-1724	179	
		4	40-1724	192	
		4 ¹ / ₂	45-1724	204	
17 ⁷ / ₈	29 ¹ / ₂	3	30-1729	207	
		3 ¹ / ₂	35-1729	222	
		4	40-1729	238	
		4 ¹ / ₂	45-1729	254	
17 ⁷ / ₈	18	3	30-1818	132	
		3 ¹ / ₂	35-1818	142	
		4	40-1818	152	
		4 ¹ / ₂	45-1818	161	
	20	20	3	30-1820	147
			3 ¹ / ₂	35-1820	158
			4	40-1820	168
			4 ¹ / ₂	45-1820	179
17 ⁷ / ₈	23 ¹ / ₂	3	30-1823	173	
		3 ¹ / ₂	35-1823	185	
		4	40-1823	198	
		4 ¹ / ₂	45-1823	210	
	26	26	3	30-1826	191
			3 ¹ / ₂	35-1826	205
			4	40-1826	219
			4 ¹ / ₂	45-1826	233

W	L	C	ITEM NUMBER	NET WT.	
17 ⁷ / ₈ (cont.)	29 ¹ / ₂	3	30-1829	217	
		3 ¹ / ₂	35-1829	232	
		4	40-1829	248	
		4 ¹ / ₂	45-1829	264	
19 ¹ / ₂	35 ¹ / ₂	3	30-1835	261	
		3 ¹ / ₂	35-1835	280	
		4	40-1835	298	
		4 ¹ / ₂	45-1835	317	
19 ¹ / ₂	23 ³ / ₄	3	30-1924	184	
		3 ¹ / ₂	35-1924	197	
		4	40-1924	209	
		4 ¹ / ₂	45-1924	222	
	29 ¹ / ₂	29 ¹ / ₂	3	30-1929	229
			3 ¹ / ₂	35-1929	244
			4	40-1929	260
			4 ¹ / ₂	45-1929	276
23 ³ / ₄	35 ¹ / ₂	3	30-1935	275	
		3 ¹ / ₂	35-1935	294	
		4	40-1935	313	
		4 ¹ / ₂	45-1935	332	
	23 ³ / ₄	23 ³ / ₄	3	30-2424	289
			3 ¹ / ₂	35-2424	302
			4	40-2424	314
			4 ¹ / ₂	45-2424	327
23 ³ / ₄	29 ¹ / ₂	3	30-2429	359	
		3 ¹ / ₂	35-2429	375	
		4	40-2429	390	
		4 ¹ / ₂	45-2429	406	
	35 ¹ / ₂	35 ¹ / ₂	3	30-2435	432
			3 ¹ / ₂	35-2435	451
			4	40-2435	470
			4 ¹ / ₂	45-2435	488

WHEN ORDERING, PLEASE SPECIFY:

- 1. Quantity
- 2. Item Number
- 3. Method of Shipment


[CONTACT US](#)

Mold Plates, Ejector and Ejector Retainer Plates and Ejector Housings

MOLD PLATES

For 34 & 45R, 56 & 58N, 56 & 58U Mold Assemblies

(For cavity, support and top clamping plates).



Thickness of plate is finish ground to a tolerance of plus or minus .001". Width and length are finished square and parallel.


TYPE OF SEAL	A (THICKNESS)	3 1/2" x 3 3/4"		4" x 5"		5" x 6"		5" x 8"	
		ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
No. 2	3/8	34-3	1.4	—	—	—	—	—	—
	1/2	34-4	1.9	—	—	—	—	—	—
	5/8	—	—	45-5	3.5	—	—	—	—
No. 3	7/8	34-7 *	3.3	45-7 *	4.9	56-7 *	7.5	58-7 *	10.0
No. 2	1	—	—	—	—	56-8	8.5	58-8	11.4
No. 3	1 1/8	34-11	4.2	—	—	—	—	—	—
	1 3/8	34-13 *	5.2	45-13 *	7.8	56-13 *	11.7	58-13 *	15.6
	1 5/8	—	—	45-17 *	10.6	56-17 *	16.0	58-17 *	21.3

NOTE: Plates marked with a * are also available as cavity insert blocks with additional stock allowance. Please specify **mold plate** when ordering these sizes from this page.

EJECTOR & EJECTOR RETAINER PLATES

For 34 & 45R, 56 & 58N, 56 & 58U Mold Assemblies

A	2 1/2" x 3 1/2"		3 3/8" x 4"		3 3/8" x 8"	
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.
3/16	6-34	.5	—	—	—	—
3/8	—	—	7-45	1.3	7-58	2.7
1/2	—	—	6-45	1.8	6-58	3.6



DME NO. 1 STEEL (EXCEPT 6-34 = SAE 1020)

EJECTOR PLATES



Thickness of plate is finish ground to a tolerance of plus or minus .001".

EJECTOR RETAINER PLATES

Thickness of plate is rotary ground to a tolerance of plus .015", minus .000".

EJECTOR HOUSINGS

For 34 & 45R, 56 & 58N, 56 & 58U Mold Assemblies



DME NO. 1 STEEL

Ejector Housings for small-size Mold Bases are one-piece construction which provides more rigid support with fewer parts. All surfaces are machined square and parallel. The riser height is finish ground parallel to the surface of the base plate.

W	L	C	T OR SUPPORT PLATE	N	P	Q	ITEM NUMBER	No. 1 STEEL	No. 3 STEEL	NET WT.
3 3/4	3 1/2	1.080	1/2	1.580	3/16	2 3/4	10-34	•	—	3.1
	4	2	1/2	2 1/2	7/8	3 3/4	20-45	•	—	6.8
5	6	1 3/8	1 1/4	2 3/8	7/8	3 3/4	15-56	•	•	15.5
	8	1 3/8	1 1/4	2 3/8	7/8	3 3/4	15-58	•	•	20.7
7	6	2	1/2	2 1/2	1 5/16	5 3/8	20-67	•	—	12.4

Large Custom Mold Plates

Precision Machined Custom Mold Plates with Lengths to 90"

CONTACT US

SERVICES

Manufacturing Capabilities

- Plate lengths up to 90" (2300mm)
- Plate widths up to 60" (1500mm)
- Plate thicknesses up to 39" (1000mm)
- Plate weights up to 6,600 pounds (3000kg) after machining
– 8600 lbs. (3900kg) before machining
- Proven medical/package market specialization; also specialize in automotive, caps & closures, housewares and PET preform applications

Special Machining Plate Work

- Custom mold bases (especially for high cavitation)
- Mold plates, frames and other components
- Clamping plates, cavity plates, etc.
- Hot runner manifold plates
- Parting line plates
- Insulator plates, rails, etc.

Steel Material Options



- Precise machining of all alloy tool steels
 - DME #7 stainless steel (1.2085)
 - DME #3 P-20 modified steel (1.2312)
 - DME #1 steel (1.1730)
 - DME #5 H-13 hot work die steel (1.2343)
 - DME #2 steel (1.2312)
 - DME #6 stainless steel (1.4028)
 - EDRO RoyAlloy
 - Many other types
(including customer provided)



- Fully machined custom mold bases, plates and frames for high cavitation injection mold tools, die casting and press tools
- Custom manifolds for hot runner systems
- Mold base/plate assembly (bushings, pins, pillars, etc.)
- All finishing operations executed in climate-controlled areas
- Manufacturing capacity of 300 fully machined mold plates per month
- All plates 3D-measured and delivered with measurement report

Large Mold Plates 26¾ through 33¾ wide

LARGE MOLD PLATES



A	26¾ × 30"		26¾ × 36"		26¾ × 42"		26¾ × 48"		26¾ × 54"		29¾ × 30"		29¾ × 36"		29¾ × 42"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
1⅝	2730-13	313	2736-13	376	2742-13	438	2748-13	501	2754-13	563	3030-13	348	3036-13	418	3042-13	487	1⅝
1⅝	2730-17	427	2736-17	512	2742-17	597	2748-17	683	2754-17	768	3030-17	475	3036-17	569	3042-17	664	1⅝
2⅞	2730-27	654	2736-27	785	2742-27	916	2748-27	1046	2754-27	1177	3030-27	727	3036-27	873	3042-27	1018	2⅞
3⅞	2730-37	881	2736-37	1058	2742-37	1234	2748-37	1410	2754-37	1586	3030-37	980	3036-37	1176	3042-37	1372	3⅞
4⅞	2730-47	1109	2736-47	1330	2742-47	1552	2748-47	1774	2754-47	1995	3030-47	1233	3036-47	1480	3042-47	1726	4⅞
5⅞	2730-57	1336	2736-57	1603	2742-57	1870	2748-57	2138	2754-57	2405	3030-57	1486	3036-57	1783	3042-57	2080	5⅞

A	29¾ × 48"		29¾ × 54"		33¾ × 36"		33¾ × 42"		33¾ × 48"		33¾ × 54"		33¾ × 60"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
1⅝	3048-13	557	3054-13	626	3436-13	474	3442-13	553	3448-13	632	3454-13	710	3460-13	789	1⅝
1⅝	3048-17	759	3054-17	854	3436-17	646	3442-17	753	3448-17	861	3454-17	969	3460-17	1076	1⅝
2⅞	3048-27	1164	3054-27	1309	3436-27	990	3442-27	1155	3448-27	1320	3454-27	1485	3460-27	1650	2⅞
3⅞	3048-37	1568	3054-37	1764	3436-37	1334	3442-37	1557	3448-37	1779	3454-37	2001	3460-37	2224	3⅞
4⅞	3048-47	1973	3054-47	2219	3436-47	1679	3442-47	1958	3448-47	2238	3454-47	2518	3460-47	2797	4⅞
5⅞	3048-57	2377	3054-57	2674	3436-57	2023	3442-57	2360	3448-57	2697	3454-57	3034	3460-57	3371	5⅞

Thickness of plate is rotary ground to a tolerance of plus .010", minus .000". Width and length are machined square and parallel to a tolerance of +.015/+0.020.

DME No. 1 Steel

DME No. 1 steel is a medium carbon (SAE 1030), silicon-killed forging quality steel with approximately 25% greater tensile strength than typical low-carbon warehouse steels.

DME No. 2 Steel

DME No. 2 steel is an AISI 4130 type steel. It is supplied pre-heat treated to 28-34 HRC (271-321 Bhn). A high-strength steel, DME No. 2 is ideal for cavity and core retainer plates, clamping plates, and support plates in molds and dies.

DME No. 3 Steel

DME No. 3 steel is a P-20 AISI 4130 (modified) type cavity steel, pre-heat treated to 28-34 HRC (271-321 Bhn). It provides high hardness, good machinability and exceptional polishability for both plastics molds and die cast dies.

WHEN ORDERING, PLEASE SPECIFY:

- Quantity & Item Number
- No. 1, No. 2 or No. 3 Steel
- Method of Shipment


[CONTACT US](#)

NOTE:


Other sizes and materials are available by special order.

Large Mold Plates 37³/₄ through 45³/₄ wide

CONFIGURATOR



LARGE MOLD PLATES



A	37 ³ / ₄ × 42"		37 ³ / ₄ × 48"		37 ³ / ₄ × 54"		37 ³ / ₄ × 60"		37 ³ / ₄ × 66"		41 ³ / ₄ × 42"		41 ³ / ₄ × 48"		41 ³ / ₄ × 54"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
1 ³ / ₈	3842-13	618	3848-13	706	3854-13	795	3860-13	883	3866-13	971	4242-13	684	4248-13	781	4254-13	879	1 ³ / ₈
1 ⁷ / ₈	3842-17	843	3848-17	963	3854-17	1083	3860-17	1204	3866-17	1324	4242-17	932	4248-17	1065	4254-17	1198	1 ⁷ / ₈
2 ¹ / ₈	3842-27	1292	3848-27	1476	3854-27	1661	3860-27	1845	3866-27	2030	4242-27	1429	4248-27	1633	4254-27	1837	2 ¹ / ₈
3 ¹ / ₈	3842-37	1741	3848-37	1990	3854-37	2238	3860-37	2487	3866-37	2736	4242-37	1925	4248-37	2200	4254-37	2475	3 ¹ / ₈
4 ¹ / ₈	3842-47	2190	3848-47	2503	3854-47	2816	3860-47	3129	3866-47	3441	4242-47	2422	4248-47	2768	4254-47	3114	4 ¹ / ₈
5 ¹ / ₈	3842-57	2639	3848-57	3016	3854-57	3393	3860-57	3770	3866-57	4147	4242-57	2919	4248-57	3336	4254-57	3753	5 ¹ / ₈

A	41 ³ / ₄ × 60"		41 ³ / ₄ × 66"		45 ³ / ₄ × 48"		45 ³ / ₄ × 54"		45 ³ / ₄ × 60"		45 ³ / ₄ × 66"		A
	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	ITEM NUMBER	NET WT.	
1 ³ / ₈	4260-13	976	4266-13	1074	4648-13	856	4654-13	963	4660-13	1070	4666-13	1177	1 ³ / ₈
1 ⁷ / ₈	4260-17	1331	4266-17	1464	4648-17	1167	4654-17	1313	4660-17	1459	4666-17	1604	1 ⁷ / ₈
2 ¹ / ₈	4260-27	2041	4266-27	2245	4648-27	1789	4654-27	2013	4660-27	2236	4666-27	2460	2 ¹ / ₈
3 ¹ / ₈	4260-37	2750	4266-37	3025	4648-37	2411	4654-37	2713	4660-37	3014	4666-37	3315	3 ¹ / ₈
4 ¹ / ₈	4260-47	3806	4266-47	3460	4648-47	3033	4654-47	3412	4660-47	3792	4666-47	4171	4 ¹ / ₈
5 ¹ / ₈	4260-57	4170	4266-57	4587	4648-57	3655	4654-57	4112	4660-57	4569	4666-57	5026	5 ¹ / ₈

Thickness of plate is rotary ground to a tolerance of plus .010", minus .000". Width and length are machined square and parallel to a tolerance of plus +.015/+0.020.

DME No. 1 Steel

DME No. 1 steel is a medium carbon (SAE 1030), silicon-killed forging quality steel with approximately 25% greater tensile strength than typical low-carbon warehouse steels.

DME No. 2 Steel

DME No. 2 steel is an AISI 4130 type steel. It is supplied pre-heat treated to 28-34 HRC (271-321 Bhn). A high strength steel, DME No. 2 is ideal for cavity and core retainer plates, clamping plates, and support plates in molds and dies.

DME No. 3 Steel

DME No. 3 steel is a P-20 AISI 4130 (modified) type cavity steel, pre-heat treated to 28-34 HRC (271-321 Bhn). It provides high hardness, good machinability and exceptional polishability for both plastics molds and die cast dies.

WHEN ORDERING, PLEASE SPECIFY:


- Quantity & Item Number
- No. 1, No. 2 or No. 3 Steel
- Method of Shipment

[CONTACT US](#)

NOTE:

Other sizes and materials are available by special order.

Ejector Plates and Ejector Retainer Plates for Large Mold Assemblies – DME No. 1 Steel



EJECTOR RETAINER PLATES

Thickness of plate is rotary ground to a tolerance of plus .010", minus .000". Width and length are machined square and parallel to a tolerance of plus .020", minus .000".

T-1/T-2	M	L	ITEM NUMBER	NET WT.	T-1/T-2	M	L	ITEM NUMBER	NET WT.	T-1/T-2	M	L	ITEM NUMBER	NET WT.
7/8	20%	30	7-2130-7	155	1 3/8	20%	30	6-2130-13	243	1 7/8	20%	30	6-2130-17	331
		36	7-2136-7	186			36	6-2136-13	291			36	6-2136-17	397
		42	7-2142-7	217			42	6-2142-13	340			42	6-2142-17	463
		48	7-2148-7	247			48	6-2148-13	388			48	6-2148-17	530
		54	7-2154-7	278			54	6-2154-13	437			54	6-2154-17	596
	22%	30	7-2330-7	170		22%	30	6-2330-13	266		22%	30	6-2330-17	363
		36	7-2336-7	204			36	6-2336-13	320			36	6-2336-17	436
		42	7-2342-7	237			42	6-2342-13	373			42	6-2342-17	508
		48	7-2348-7	271			48	6-2348-13	426			48	6-2348-17	581
		54	7-2354-7	305			54	6-2354-13	479			54	6-2354-17	653
	23%	30	7-2430-7	177		23%	30	6-2430-13	278		23%	30	6-2430-17	379
		36	7-2436-7	212			36	6-2436-13	334			36	6-2436-17	455
		42	7-2442-7	248			42	6-2442-13	389			42	6-2442-17	530
		48	7-2448-7	283			48	6-2448-13	445			48	6-2448-17	606
		54	7-2454-7	318			54	6-2454-13	500			54	6-2454-17	682
	25%	60	7-2460-7	354		25%	60	6-2460-13	556		25%	60	6-2460-17	757
		30	7-2630-7	192			30	6-2630-13	301			30	6-2630-17	411
		36	7-2636-7	230			36	6-2636-13	362			36	6-2636-17	493
		42	7-2642-7	269			42	6-2642-13	422			42	6-2642-17	575
		48	7-2648-7	307			48	6-2648-13	482			48	6-2648-17	657
	27%	54	7-2654-7	345		27%	54	6-2654-13	542		27%	54	6-2654-17	739
		60	7-2660-7	383			60	6-2660-13	602			60	6-2660-17	821
		36	7-2836-7	248			36	6-2836-13	390			36	6-2836-17	531
		42	7-2842-7	289			42	6-2842-13	454			42	6-2842-17	620
		48	7-2848-7	331			48	6-2848-13	519			48	6-2848-17	708
	29%	54	7-2854-7	372		29%	54	6-2854-13	584		29%	54	6-2854-17	796
		60	7-2860-7	413			60	6-2860-13	649			60	6-2860-17	885
		66	7-2866-7	454			66	6-2866-13	714			66	6-2866-17	973
		36	7-3036-7	266			36	6-3036-13	478			36	6-3036-17	569
		42	7-3042-7	310			42	6-3042-13	487			42	6-3042-17	664
	31%	48	7-3048-7	354		31%	48	6-3048-13	557		31%	48	6-3048-17	759
		54	7-3054-7	399			54	6-3054-13	626			54	6-3054-17	854
		60	7-3060-7	443			60	6-3060-13	696			60	6-3060-17	949
		66	7-3066-7	487			66	6-3066-13	765			66	6-3066-17	1043
		42	7-3242-7	331			42	6-3242-13	520			42	6-3242-17	709
	33%	48	7-3248-7	378		33%	48	6-3248-13	594		33%	48	6-3248-17	810
		54	7-3254-7	425			54	6-3254-13	668			54	6-3254-17	911
		60	7-3260-7	473			60	6-3260-13	743			60	6-3260-17	1012
		66	7-3266-7	520			66	6-3266-13	817			66	6-3266-17	1114
		42	7-3442-7	352			42	6-3442-13	553			42	6-3442-17	753
	35%	48	7-3448-7	402		35%	48	6-3448-13	632		35%	48	6-3448-17	861
		54	7-3454-7	452			54	6-3454-13	710			54	6-3454-17	969
		60	7-3460-7	502			60	6-3460-13	789			60	6-3460-17	1076
		66	7-3466-7	553			66	6-3466-13	868			66	6-3466-17	1184
		42	7-3642-7	373			42	6-3642-13	585			42	6-3642-17	798
	37%	48	7-3648-7	426		37%	48	6-3648-13	669		37%	48	6-3648-17	912
		54	7-3654-7	479			54	6-3654-13	752			54	6-3654-17	1026
		60	7-3660-7	532			60	6-3660-13	836			60	6-3660-17	1140
		66	7-3666-7	585			66	6-3666-13	920			66	6-3666-17	1254
		42	7-3842-7	394			42	6-3842-13	618			42	6-3842-17	843
	39%	48	7-3848-7	450		39%	48	6-3848-13	706		39%	48	6-3848-17	963
		54	7-3854-7	506			54	6-3854-13	795			54	6-3854-17	1083
		60	7-3860-7	562			60	6-3860-13	883			60	6-3860-17	1204
		66	7-3866-7	618			66	6-3866-13	971			66	6-3866-17	1324
		48	7-4048-7	473			48	6-4048-13	744			48	6-4048-17	1014
	39%	54	7-4054-7	533		39%	54	6-4054-13	837		39%	54	6-4054-17	1141
		66	7-4060-7	592			66	6-4060-13	930			66	6-4060-17	1267
		66	7-4066-7	651			66	6-4066-13	1022			66	6-4066-17	1394



WHEN ORDERING, PLEASE SPECIFY:

- Quantity
- Item Number
- Method of Shipment

CONTACT US

Spacer Blocks for Large Mold Assemblies DME No. 1 Steel

SPACER BLOCKS



Machined all over. Riser heights ("C" dimension) are finish ground to a tolerance of plus or minus .001".

P	C	L	ITEM NUMBER	NET WT.
1 7/8	5	30	50-1730	80
		36	50-1736	96
		42	50-1742	112
		48	50-1748	128
		54	50-1754	144
		60	50-1760	160
		66	50-1766	176
		66	50-1766	176
	6	30	60-1730	96
		36	60-1736	115
		42	60-1742	134
		48	60-1748	153
		54	60-1754	173
		60	60-1760	192
		66	60-1766	211
		66	60-1766	211
	8	30	80-1730	128
		36	80-1736	153
		42	80-1742	179
		48	80-1748	204
		54	80-1754	230
		60	80-1760	255
		66	80-1766	281
		66	80-1766	281

P	C	L	ITEM NUMBER	NET WT.
2 7/8	5	30	50-2730	123
		36	50-2736	147
		42	50-2742	172
		48	50-2748	196
		54	50-2754	220
		60	50-2760	245
		66	50-2766	269
		66	50-2766	269
	6	30	60-2730	147
		36	60-2736	176
		42	60-2742	206
		48	60-2748	235
		54	60-2754	264
		60	60-2760	294
		66	60-2766	323
		66	60-2766	323
	8	30	80-2730	196
		36	80-2736	235
		42	80-2742	274
		48	80-2748	313
		54	80-2754	352
		60	80-2760	391
		66	80-2766	431
		66	80-2766	431

P	C	L	ITEM NUMBER	NET WT.
3 7/8	5	-	-	-
		36	50-3736	198
		42	50-3742	231
		48	50-3748	264
		54	50-3754	297
		60	50-3760	330
		66	50-3766	363
		66	50-3766	363
	6	-	-	-
		36	60-3736	238
		42	60-3742	277
		48	60-3748	317
		54	60-3754	356
		60	60-3760	396
		66	60-3766	435
		66	60-3766	435
	8	-	-	-
		36	80-3736	317
		42	80-3742	369
		48	80-3748	422
		54	80-3754	475
		60	80-3760	527
		66	80-3766	580
		66	80-3766	580

WHEN ORDERING, PLEASE SPECIFY:

1. Quantity
2. Item Number
3. Method of Shipment

[CONTACT US](#)

Steel Processing Services to meet your Special Requirements



DME Company has been buying, cutting, machining and finishing high-quality steel for seven decades. We understand that our customers face unprecedented demands for speed, cost reduction and performance. To assist you in meeting your challenges, we've developed an industry-leading steel processing infrastructure, including the specialized equipment and technical expertise to handle the most demanding steel requirements. It's a unique capability that's just one way DME strives to be an essential resource to the customers we serve.

DME's North American manufacturing locations have some of the largest, most modern sawing, straightening, milling and grinding equipment in the industry. As one of the world's largest users of alloy steel plate, DME has a close working relationship with the leading steel mills. This provides you with the ability to meet whatever special steel requirements you may have by working with us. Steel plates and blocks of any size and grade of steel are available from DME.

Any specified steel condition – rough, semi-finished or finished (milled or ground) is available to order. Even specially machined large blocks and plates are available.

Steel Plate

Let DME quote your machining requirements for steel plate. As a convenient, one-stop solution, DME can reduce your overall costs whether your needs only require plate machining, or drilling, tapping, boring, and milling, as well. DME prides itself on providing highly competent technical support and highly responsive customer service. We specialize in supplying the steel product that meets your exact specification.

Steel Processing Services

DME's steel processing services for moldmakers and die casters provide a full array of steel machining capabilities

to customers worldwide. DME can supply plates, strips and blocks from our inventory or accept your material for the machining services we offer.

AVAILABLE SERVICES

DME can execute CNC machining to your exact specifications whether we're provided hand drawings or CAD files. ([See Guidelines](#)) The list below includes just some of the services that we handle every day:

- Steel plates, strips and blocks up to 6 $\frac{1}{8}$ " thick available in 1030, 4130, P-20 and 420F
- Plate sawing up to 150" long and 20" thick
- Flame cut strips up to 6 $\frac{1}{8}$ " thick
- Horizontal and vertical band sawing
- Flattening with 2,000-ton press or roller leveling
- Milling up to 150" long, 46" wide and 20" thick
- Edge milling up to 70" square; beveled edge machining
- Rotary grinding on 84" or 42" Blanchard or double-disc grinding
- Finish grinding up to 40" wide

Quality You Can Count On!

Quality has been and continues to be a part of our fabric at DME, and our undying commitment to quality extends throughout all facets of our business. To maintain customer focus, all DME Quality Management Systems are ISO 9001:2000 certified. We undergo continuous testing for quality including consistently measuring tooling, calibrating our machinery, and inspecting finished work to ensure our customers receive quality they can count on. The DME high standard for quality has been a hallmark of DME since its inception and is just another aspect of how we partner with you every step of the way.

DME Molding Supplies

**CLEAN AND PROTECT YOUR
MOLDS WITH DME MOLD
CLEANER AND MOLD SAVER**



Molding Supplies

Please Name of Contents in Above Box

Mold Cleaner and Mold Saver

DME MOLD CLEANER

DME Mold Cleaner is used to remove corrosion forming substances such as lactic acid, urea and sodium chloride, which are common in perspiration residues left by ordinary handling of polished cavities. In addition to cleaning the polished cavity it also provides up to 20 days rust protection at temperatures to 120°F at 100% humidity.

Use DME Mold Cleaner to clean polished mold surfaces and protect them for up to 20 days. Use DME Mold Saver for long lasting protection from corrosion.



ITEM NUMBER	MOLD CLEANER DESCRIPTION
CLE 0001	(1) 12 oz. aerosol can
CLE 0012	Case of (12) 12 oz. aerosol cans
CLE 0004	(1) one gallon can
CLE 0016	Case of (4) one gallon cans

Download Mold Components or Equipment & Supplies Catalogs at <https://www.dme.net/digital-catalogs/>

Available in 12 oz. aerosol or 1 gallon non-aerosol... individually or by the case.

DME MOLD SAVER

DME Mold Saver is an ideal protective coating for molds to be stored over a long period of time. It protects polished cavities and all metal parts from costly corrosion damage. Its thin, transparent film averages about .0003" thick. It is soft, dry and waxy and can be easily wiped off without solvents. One can of Mold Saver covers about 80 square feet.



ITEM NUMBER	MOLD SAVER DESCRIPTION
SAV 0001	(1) 12 oz. aerosol can
SAV 0012	Case of (12) 12 oz. aerosol cans
SAV 0004	(1) one gallon can
SAV 0016	Case of (4) one gallon cans


QUANTITY DISCOUNT:

- 2 to 5 cases Less 3%
- 6 to 19 cases Less 5%
- 20 to 50 cases Less 8%
- 51 or more cases Less 12%

BLANKET ORDER DISCOUNT:

Money-saving blanket orders reduce your inventory costs and permit maximum savings over a twelve month period. They are accepted provided the combined annual order totals 20 cases or more. Split shipments against blanket orders must be in quantities of 10 cases or more.

ACCESSORIES FOR MOLD CLEANER AND MOLD SAVER



TRIGGER PUMPS
for 15 oz. cans

ITEM NUMBER	DESCRIPTION
SAV 0003	Package of (6) trigger pumps



"SURE SHOT" COMPRESSED-AIR SPRAY CANISTER


Holds one quart of Mold Cleaner or Mold Saver. Metal can is refillable and reusable. Includes stemmed air valve.

ITEM NUMBER
SAV 0002


Technical Reference

Table of Contents

<u><i>Metric Equivalents and Conversions</i></u>	278
<u><i>Steel Hardness Chart</i></u>	279
<u><i>Tensile Strength</i></u>	280
<u><i>Draft Angles</i></u>	281
<u><i>Steel Designations</i></u>	282
<u><i>Determining Metric Tolerances</i></u>	283-294
<u><i>American Standard Mold Base Features</i></u>	295-296



Technical Reference



Metric Equivalents and Conversions

Equivalents: Inch, fraction, decimal, millimeter

Inches	Milli Meters	Inches	Milli Meters
1	25.4	34	863.6
2	50.8	35	889.0
3	76.2	36	914.4
4	101.6	37	939.8
5	127.0	38	965.2
6	152.4	39	990.6
7	177.8	40	1016.0
8	203.2	41	1041.4
9	228.6	42	1066.8
10	254.0	43	1092.2
11	279.4	44	1117.6
12	304.8	45	1143.0
13	330.2	46	1168.4
14	355.6	47	1193.8
15	381.0	48	1219.2
16	406.4	49	1244.6
17	431.8	50	1270.0
18	457.2	51	1295.4
19	482.6	52	1320.8
20	508.0	53	1346.2
21	533.4	54	1371.6
22	558.8	55	1397.0
23	584.2	56	1422.4
24	609.6	57	1447.8
25	635.0	58	1473.2
26	660.4	59	1498.6
27	685.8	60	1524.0
28	711.2	61	1549.4
29	736.6	62	1574.8
30	762.0	63	1600.2
31	787.4	64	1625.6
32	812.8	65	1651.0
33	838.2	66	1676.4

Inches		Milli Meters	Inches		Milli Meters
1/64	0.015625	0.396875	33/64	0.515625	13.096875
1/32	0.031250	0.793750	17/32	0.531250	13.493750
3/64	0.046875	1.190625	35/64	0.546875	13.890625
1/16	0.062500	1.587500	9/16	0.562500	14.287500
5/64	0.078125	1.984375	37/64	0.578125	14.684375
3/32	0.093750	2.381250	19/32	0.593750	15.081250
7/64	0.109375	2.778125	39/64	0.609375	15.478125
1/8	0.125000	3.175000	5/8	0.625000	15.875000
9/64	0.140625	3.571875	41/64	0.640625	16.271875
5/32	0.156250	3.968750	21/32	0.656250	16.668750
11/64	0.171875	4.365625	43/64	0.671875	17.065625
3/16	0.187500	4.762500	11/16	0.687500	17.462500
13/64	0.203125	5.159375	45/64	0.703125	17.859375
7/32	0.218750	5.556250	23/32	0.718750	18.256250
15/64	0.234375	5.953125	47/64	0.734375	18.653125
1/4	0.250000	6.350000	3/4	0.750000	19.050000
17/64	0.265625	6.746875	49/64	0.765625	19.446875
9/32	0.281250	7.143750	25/32	0.781250	19.843750
19/64	0.296875	7.540625	51/64	0.796875	20.240625
5/16	0.312500	7.937500	13/16	0.812500	20.637500
21/64	0.328125	8.334375	53/64	0.828125	21.034375
11/32	0.343750	8.731250	27/32	0.843750	21.431250
23/64	0.359375	9.128125	55/64	0.859375	21.828125
3/8	0.375000	9.525000	7/8	0.875000	22.225000
25/64	0.390625	9.921875	57/64	0.890625	22.621875
13/32	0.406250	10.318750	29/32	0.906250	23.018750
27/64	0.421875	10.715625	59/64	0.921875	23.415625
7/16	0.437500	11.112500	15/16	0.937500	23.812500
29/64	0.453125	11.509375	61/64	0.953125	24.209375
15/32	0.468750	11.906250	31/32	0.968750	24.606250
31/64	0.484375	12.303125	63/64	0.984375	25.003125
1/2	0.500000	12.700000	1	1.000000	25.400000

Equivalents: Decimal, millimeter

Inches	Milli Meters	Inches	Milli Meters	Inches	Milli Meters
0.001	0.0254	0.01	0.254	0.1	2.54
0.002	0.0508	0.02	0.508	0.2	5.08
0.003	0.0762	0.03	0.762	0.3	7.62
0.004	0.1016	0.04	1.016	0.4	10.16
0.005	0.1270	0.05	1.270	0.5	12.70
0.006	0.1524	0.06	1.524	0.6	15.24
0.007	0.1778	0.07	1.778	0.7	17.78
0.008	0.2032	0.08	2.032	0.8	20.32
0.009	0.2286	0.09	2.286	0.9	22.86

Measurement conversions

MULTIPLY by	FROM	TO	MULTIPLY by
0.03937	inch	millimeter	25.4
0.0016	inch ²	millimeter ²	645.16
0.061	inch ³	centimeter ³	16.3871
0.2642	gallon (U.S.)	liter	3.7854
0.03527	oz. (avdp.)	gram	28.3495
2.2044	pound	kilogram	0.4536
62.43	lbs/ft ³	g/cm ³	0.0160
0.145	psi	kPa	6.8948
14.2247	psi	kg/cm ²	0.0703
1.8°C + 32	°F	°C	(°F-32)/1.8

Steel Hardness Chart

Cross-reference between different hardness measurements						
Brinell hardness bhn *	Vickers hardness HV	Rockwell C hardness HRC	Rockwell B hardness HRB	Rockwell A hardness HRA	Shore hardness HS	
10mm ball, 3000kgf load	136° diamond pyramid, 10kgf load	Brale pene Tra Tor, 60kgf load	1/16 in Ch ball, 100kgf load	Brale pene Tra Tor, 150kgf load		
86	90		48			
95	100		56.2			
105	110		62.3			
114	120		66.7			
124	130		71.2			20
133	140		75			21
143	150		78.7			22
152	160		81.7	(0)		24
162	170		85	(3)		25
171	180		87.1	(6)		26
181	190		89.5	(8.5)		28
190	200		91.5	(11)		29
200	210		93.4	(13.4)		30
209	220		95	(15.7)		32
219	230		96.7	(18)		33
228	240	60.7	98.1	20.3		34
238	250	61.6	99.5	22.2		36
247	260	62.4	(101)	24		37
256	270	63.1	(102)	25.6		38
265	280	63.8	(103.5)	27.1		40
275	290	64.5	(104.5)	28.5		41
284	300	65.2	(105.5)	29.8		42
303	320	66.4	(107)	32.2		45
322	340	67.6	(108)	34.4		47
341	360	68.7	(109)	36.6		50
360	380	69.8	(110)	38.8		52
379	400	70.8		40.8		55
397	420	71.8		42.7		57
415	440	72.8		44.5		59
433	460	73.6		46.1		62
452	480	74.5		47.7		64
471	500	75.3		49.1		66
488	520	76.1		50.5		67
507	540	76.7		51.7		69
525	560	77.4		53		71
545	580	78		54.1		72
564	600	78.6		55.2		74
582	620	79.2		56.3		75
601	640	79.8		57.3		77
620	660	80.3		58.3		79
638	680	80.8		59.2		80
656	700	81.3		60.1		81
670	720	81.8		61		83
684	740	82.2		61.8		84
698	760	82.6		62.5		86
710	780	83		63.3		87
722	800	83.4		64		88
745	840	84.1		65.3		91
767	880	84.7		66.4		93

*A 10mm steel ball is used for 450 bhn and below. A 10mm carbide ball is used above 450 bhn.

Also known as Firth Diamond hardness number.

Values in parentheses are not contained in the normal definition range for hardness checking, but are often used in a comparable measure.

All values shown in this chart are approximate and intended only as a reference guide.

Tensile Strength

general sTeel group Through hardness versus approxima Te Tensile sTrenG Th									
hardness		Tensile sTrenG Th							
brinell hardness bhn *	ro Ckwell hardness hr C	plain Carbon sTeel and low alloy sTeel		sTainless sTeel aus Teni TiC Type			sTainless sTeel Chromium Type		
10mm ball, 3000kgf load	brale pene Tra Tor, 150kgf load	n/mm ² (approx.)	psi (approx.)	kgf/mm ² (approx.)	n/mm ² (approx.)	psi (approx.)	kgf/mm ² (approx.)	n/mm ² (approx.)	psi (approx.)
86		285	41,334						
95		320	46,410						
105		350	50,761						
114		385	55,837						
124		415	60,188						
133		450	65,264						
143		480	69,615	50	490	71,115	50	490	71,115
152	(0)	510	73,966	56	549	79,649	53	520	75,382
162	(3)	545	79,042	62	608	88,183	59	579	83,916
171	(6)	575	83,393	62	608	88,183	59	579	83,916
181	(8.5)	610	88,470	68	667	96,716	65	637	92,450
190	(11)	640	92,820	68	667	96,716	65	637	92,450
200	(13.4)	675	97,897	75	736	106,673	71	696	100,983
209	(15.7)	705	102,248	75	736	106,673	71	696	100,983
219	(18)	740	107,324	80	785	113,784	78	765	110,939
228	20.3	770	111,675	80	785	113,784	78	765	110,939
238	22.2	800	116,026	85	834	120,896	81	794	115,206
247	24	835	121,102	88	863	125,162			
256	25.6	865	125,453	91	892	129,429	88	863	125,162
265	27.1	900	130,529	94	922	133,696			
275	28.5	930	134,880	97	951	137,963	96	941	136,541
284	29.8	965	139,956	100	981	142,230			
303	32.2	1,030	149,383	109	1,069	155,031	106	1,040	150,764
322	34.4	1,095	158,810	118	1,157	167,831	113	1,108	160,720
341	36.6	1,155	167,512	127	1,245	180,632	120	1,177	170,676
360	38.8	1,220	176,939	136	1,334	193,433	127	1,245	180,632
379	40.8	1,290	187,091	145	1,422	206,234	134	1,314	190,588
397	42.7	1,350	195,793	156	1,530	221,879			
415	44.5	1,420	205,945	167	1,638	237,524			
433	46.1	1,485	215,372	178	1,746	253,169			
452	47.7	1,555	225,525	189	1,853	268,815			
471	49.1	1,630	236,402	200	1,961	284,460			
488	50.5	1,700	246,554	209	2,050	297,261			
507	51.7	1,775	257,432	218	2,138	310,061			
525	53	1,845	267,584	227	2,226	322,862			
545	54.1	1,920	278,461	236	2,314	335,663			
564	55.2	1,995	289,339	245	2,403	348,464			

*A 10mm steel ball is used for 450 bhn and below. A 10mm carbide ball is used above 450 bhn .

Values in parentheses are not contained in the normal definition range for hardness checking, but are often used in a comparable measure.

t he tensile strength relationship to hardness is inexact, even for the steel, unless it is determined for a specific material. t herefore, this chart provides only very general approximate tensile strength values.


All values shown in this chart are approximate and intended only as a reference guide.

Draft Angles

DEPTH	1/2°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	15°	20°	25°	30°	DEPTH
1/32	.0003	.0005	.001	.0016	.002	.0027	.003	.0038	.004	.005	.0055	.006	.0066	.008	.011	.014	.018	1/32
1/16	.0005	.0011	.002	.0033	.004	.0055	.007	.0077	.009	.010	.011	.012	.013	.017	.023	.029	.036	1/16
3/32	.0008	.0017	.003	.0049	.006	.008	.010	.0115	.013	.015	.0165	.018	.020	.025	.034	.044	.054	3/32
1/8	.0011	.0022	.004	.0066	.009	.0109	.013	.015	.018	.020	.022	.024	.027	.033	.045	.058	.072	1/8
5/32	.0014	.0028	.005	.008	.011	.014	.016	.019	.022	.025	.027	.030	.033	.042	.057	.073	.089	5/32
3/16	.0016	.0033	.006	.0098	.013	.016	.019	.023	.027	.030	.033	.036	.040	.050	.068	.087	.108	3/16
7/32	.0019	.0039	.008	.011	.015	.019	.023	.027	.031	.035	.039	.042	.047	.059	.080	.102	.126	7/32
1/4	.0022	.0043	.009	.013	.018	.022	.026	.031	.035	.040	.044	.049	.053	.067	.091	.117	.144	1/4
9/32	.0025	.005	.010	.014	.020	.024	.030	.034	.040	.045	.049	.055	.060	.075	.102	.131	.162	9/32
5/16	.0027	.0055	.011	.016	.022	.027	.033	.038	.044	.050	.055	.061	.066	.084	.114	.146	.180	5/16
11/32	.003	.006	.012	.018	.024	.030	.036	.042	.049	.055	.061	.067	.073	.092	.125	.160	.197	11/32
3/8	.0032	.0066	.013	.020	.026	.033	.039	.046	.053	.060	.066	.073	.080	.100	.136	.175	.217	3/8
13/32	.0035	.007	.014	.021	.028	.035	.043	.050	.057	.064	.071	.079	.086	.108	.148	.189	.234	13/32
7/16	.0038	.0077	.015	.023	.031	.038	.046	.054	.062	.069	.077	.085	.093	.117	.159	.204	.253	7/16
15/32	.0041	.008	.016	.024	.033	.041	.049	.058	.066	.074	.083	.091	.100	.126	.171	.219	.270	15/32
1/2	.0044	.0088	.018	.026	.035	.044	.053	.061	.071	.079	.088	.097	.106	.134	.182	.233	.289	1/2
17/32	.0046	.009	.019	.028	.037	.046	.056	.065	.075	.084	.093	.103	.113	.142	.193	.247	.306	17/32
9/16	.0049	.0099	.020	.030	.039	.049	.059	.069	.079	.088	.099	.109	.120	.151	.205	.262	.325	9/16
19/32	.0052	.010	.021	.031	.042	.052	.062	.073	.084	.094	.105	.115	.127	.159	.216	.277	.343	19/32
5/8	.0055	.011	.022	.033	.044	.055	.066	.077	.088	.100	.110	.120	.133	.167	.227	.291	.361	5/8
21/32	.0057	.011	.023	.035	.046	.057	.069	.082	.092	.104	.115	.127	.140	.176	.239	.306	.379	21/32
11/16	.006	.012	.024	.036	.048	.060	.072	.085	.096	.109	.121	.133	.147	.183	.250	.321	.397	11/16
23/32	.0063	.013	.025	.038	.050	.063	.075	.088	.101	.114	.126	.139	.153	.193	.261	.335	.415	23/32
3/4	.0065	.013	.027	.039	.053	.066	.079	.092	.106	.119	.132	.146	.159	.201	.273	.350	.433	3/4
25/32	.0068	.014	.028	.040	.055	.068	.081	.096	.110	.124	.137	.152	.166	.209	.284	.364	.451	25/32
13/16	.0071	.014	.029	.043	.057	.071	.085	.100	.115	.129	.143	.158	.173	.218	.296	.379	.469	13/16
27/32	.0074	.015	.030	.045	.059	.074	.089	.104	.119	.134	.149	.163	.180	.226	.307	.393	.487	27/32
7/8	.0076	.015	.031	.046	.061	.077	.092	.107	.123	.139	.154	.171	.186	.234	.318	.408	.505	7/8
29/32	.0079	.016	.032	.048	.063	.079	.095	.111	.128	.144	.159	.176	.193	.243	.329	.422	.523	29/32
15/16	.0082	.017	.033	.050	.066	.082	.098	.115	.132	.149	.165	.182	.200	.251	.341	.437	.541	15/16
31/32	.0085	.017	.034	.051	.068	.084	.101	.119	.137	.153	.170	.188	.206	.260	.353	.452	.559	31/32
1	.0087	.0175	.035	.052	.070	.087	.105	.123	.141	.158	.176	.194	.213	.268	.364	.466	.577	1
DEPTH	1/2°	1°	2°	3°	4°	5°	6°	7°	8°	9°	10°	11°	12°	15°	20°	25°	30°	DEPTH

The depth columns represent cavities from 1/32" to 1" in increments of 1/32". The most commonly used draft angles are noted in degrees at the top and bottom of the table. The measurement listed in any block represents the amount of draft obtained with the corresponding angle and cavity depth.

EXAMPLE: The difference between the diameter of the top and the diameter of the bottom of a 1/2" inch cavity with a draft angle of 8° is found by noting the figure in the table opposite the 1/2" depth and corresponding to the 8° draft angle (.071") and multiplying by two (1.420").



The length and necessary angle for cam pins used in actuating core pulls can also be calculated with this table.

EXAMPLE: The length of a pin set at a 15° angle required to pull a core 1". Since 20° and 1" of length allow .364" travel, a 4" pin permits four times the travel (1.456").

Steel Designations

general sTeel group designa Tions					
Plain Carbon Steel	Low Alloy Carbon Steel	Cold Work Tool Steel	Hot Work Tool Steel	Stainless Steel Austenitic Type	Stainless Steel Chromium Type (Martensitic & Ferritic)
AISI	AISI	AISI	AISI	AISI	AISI
1000 SERIES	4000 SERIES	A2	H10	201	410
	5000 SERIES	A3A	H11	203	416
	6000 SERIES	4	H12	205	420
	8000 SERIES	A5	H13	301	429
	9000 SERIES	A6	H14	302	430
		A7	H19	303	431
		A8	H21	304	434
		A9	H22	305	436
		A10	H23	307	439
		D2	H24	308	440
		D3	H25	309	442
		D4	H26	310	444
		D5	H40	314	446
		D7	H41	316	
			H42	317	
			H43	318	
				321	
				329	
				330	
				332	
				334	
				347	
				348	
				384	
				385	

General Steel Cross Reference Information*

German Werkstoff Standard Number for Steel	U.S. Steel Number AISI
1.0716	No Cross Reference
1.0718	12 L 13 Type*
1.1191	1045 Type*
1.1730	No Cross Reference
1.2210	1L-2 Type*
1.2344	H-13 type*
1.2826	No Cross Reference
1.4305	303 Type Stainless
1.5710 (AFn Or 35 nc 6)	3135 Type*
1.7131	5115 Type (Similar to 1018 & 8620*)
1.8159 (DIn 50 crV 4)	6150 Type*

*exchangeability should only be considered after thorough examination of individual case.

Tables for Determining Metric Tolerances

Table 1: Description of Preferred Fits

Table 1 is pulled from the ANSI metric tolerances section of the machinists' handbook, which conforms to the ISO and DIN tolerances for hole basis and shaft basis fits. Table 1 provides an overview of the hole basis and shaft basis fits that make up clearance fit, transition fit and interference fit combinations.

	ISO SYMBOL			
	Hole Basis	Shaft Basis		
CLEARANCE FITS	H11/c11	H11/h11	Loose Running Fit	For wide commercial tolerance or allowances on external members
	H9/d9	D9/h9	Free Running Fit	Not for use where accuracy is essential. Good for large temperature variations, high running speeds or heavy journal pressures
	H8/f7	F8/h7	Close running Fit	For running on accurate machines and for accurate location at moderate speeds and journal pressures
	H7/g6	G7/h6	Sliding Fit	Not intended to run freely, but to move and turn freely and locate accurately
	H7/h6	H7/h6	Locational Clearance Fit	Provides snug fit for locating stationary parts, can be freely assembled and disassembled
TRANSITION FITS	H7/k6	K7/h6	Locational Transition Fit	For accurate location, a compromise between clearance and interference
	H7/n6	N7/h6	Locational Transition Fit	For more accurate location where greater interference is permissible
INTERFERENCE FITS	H7/p6*	P7/h6	Locational Interference Fit	For parts requiring rigidity and alignment with prime accuracy of location but without special bore pressure requirements
	H7/s6	S7/h6	Medium Drive Fit	For ordinary steel parts or shrink-fits on light sections, the tightest fit usable with cast iron
	H7/u6	U7/h6	Force Fit	Suitable for parts which can be highly stressed or for shrink-fits where the heavy pressing forces required are impractical

excerpt from *Machinists' Handbook*, pg. 661, 25 ed., Industrial press.
 *The h7/p6 hole basis fit is a transition fit for basic sizes in ranges from 0 through 3mm.

Tables for Determining Metric Tolerances

Table 2: Commonly Used Hole-Basis System of Fits

Table 2 shows closer detail on the hole-basis system of fits than Table 1. When using the hole-basis system of fits, the smallest diameter in the hole tolerance range is fixed to the zero line (basic nominal hole size or diameter), and the clearance between the shaft and hole extends below the zero line, or negative relative to the basic nominal hole size.

BASIC HOLES	LETTER SYMBOLS AND GRADE NUMBERS OF SHAFTS																
	CLEARANCE FITS						TRANSITION FITS				INTERFERENCE FITS						
	b	c	d	e	f	g	h	js	k	m	n	p	r	s	t	u	x
H5						4	4	4	4	4							
H6					6	6	6	6	6	6	6*	6*					
				6	6	6	6	6	6	6	6	6*	6*	6	6	6	6
H7				7	7	7	7	7	7	7	7	7*	7*	7	7	7	7
					7		7										
H8				8	8		8										
			9	9													
H9			8	8			8										
		9	9	9			9										
H10	9	9	9														

*Exceptions occur in some steps of dimensions.

Table 3: Commonly Used Shaft-Basis System of Fits

Table 3 shows closer detail on the shaft-basis system of fits than Table 1. When using the shaft-basis system of fits, the largest diameter in the shaft tolerance range is fixed to the zero line (basic nominal shaft size or diameter), and the clearance between the shaft and hole extends above the zero line, or positive relative to the basic shaft size.

BASIC SHAFTS	LETTER SYMBOLS AND GRADE NUMBERS OF HOLES																
	CLEARANCE FITS							TRANSITION FITS				INTERFERENCE FITS					
	B	C	D	E	F	G	H	Js	K	M	N	P	R	S	T	U	X
h4							5	5	5	5							
h5							6	6	6	6	6*	6					
h6					6	6	6	6	6	6	6	6*					
				7	7	7	7	7	7	7	7	7*	7	7	7	7	7
h7				7	7	7	7	7	7	7	7	7	7*	7			
					8		8										
h8			8	8	8		8										
			9	9			9										
h9			8	8			8										
		9	9	9			9										
	10	10	10														

*Exceptions occur in some steps of dimensions.

Tables for Determining Metric Tolerances

Table 4: IT Standard Tolerances

Table 4 details the ISO-basic tolerances (International Tolerance Grades, or, "IT") which apply to all linear sizes (external and internal sizes, diameters, lengths, widths and thicknesses). An IT-grade number establishes the magnitude of the tolerance zone, while the tolerance position letter determines where the tolerance zone is in relation to the zero line. The combination of tolerance position letter (A-X, a-x) and IT-grade number (01-8) creates the overall tolerance symbol (i.e., F8/h7 when using the shaft-basis system of fits).

For nominal size range up to 500mm according to DIN 7151/ISO 286, and for nominal size range over 500mm, according to DIN 7172/ISO 286.

Items in mm		IT STANDARD TOLERANCES (UNITS IN 0.001MM)																				
Over	TO	IT01	IT0	IT1	IT2	IT3	IT4	IT5	IT6	IT7	IT8	IT9	IT10	IT11	IT12	IT13	IT14	IT15	IT16	IT17	IT18	
NOMINAL SIZE RANGE	0	3	0.3	0.5	0.8	1.2	2	3	4	6	10	14	25	40	60	100	140	250	400	600	—	—
	3	6	0.4	0.6	1	1.5	2.5	4	5	8	12	18	30	48	75	120	180	300	480	750	—	—
	6	10	0.4	0.6	1	1.5	2.5	4	6	9	15	22	36	58	90	150	220	360	580	900	1500	—
	10	18	0.5	0.8	1.2	2	3	5	8	11	18	27	43	70	110	180	270	430	700	1100	1800	2700
	18	30	0.6	1	1.5	2.5	4	6	9	13	21	33	52	84	130	210	330	520	840	1300	2100	3300
	30	50	0.6	1	1.5	2.5	4	7	11	16	25	39	62	100	160	250	390	620	1000	1600	2500	3900
	50	80	0.8	1.2	2	3	5	8	13	19	30	46	74	120	190	300	460	740	1200	1900	3000	4600
	80	120	1	1.5	2.5	4	6	10	15	22	35	54	87	140	220	350	540	870	1400	2200	3500	5400
	120	180	1.2	2	3.5	5	8	12	18	25	40	63	100	160	250	400	630	1000	1600	2500	4000	6300
	180	250	2	3	4.5	7	10	14	20	29	46	72	115	185	290	460	720	1150	1850	2900	4600	7200
	250	315	2.5	4	6	8	12	16	23	32	52	81	130	210	320	520	810	1300	2100	3200	5200	8100
	315	400	3	5	7	9	13	18	25	36	57	89	140	230	360	570	890	1400	2300	3600	5700	8900
	400	500	4	6	8	10	15	20	27	40	63	97	155	250	400	630	970	1550	2500	4000	6300	9700
	500	630	4.5	6	9	11	16	22	30	44	70	110	175	280	440	700	1100	1750	2800	4400	—	—
	630	800	5	7	10	13	18	25	35	50	80	125	200	320	500	800	1250	2000	3200	5000	—	—
	800	1000	5.5	8	11	15	21	29	40	56	90	140	230	360	560	900	1400	2300	3600	5600	—	—

Tables for Determining Metric Tolerances

Table 5: Fundamental Deviations of Holes and Shafts

Table 5 details fundamental deviations between holes and shafts, and is provided for reference.

HOLES	Grade		IT6 To IT16													
	Divisions		Fundamental Deviations (Lower Deviations)					Js	Fundamental Deviations (Upper Deviations)							
	Letter Symbols		D	E	F	G	H		K	M	N	P	R	S	T	U
	Signs		+	+	+	+			-	-	-	-	-	-	-	
Above	UP To															
500	560	260	145	76	22	0	Deviations (+/-) It/2	0	26	44	78	150	280	400	600	
560	630											155	310	450	660	
630	710	290	160	80	24	0		0	30	50	88	175	340	500	740	
710	800											185	380	560	840	
800	900	320	170	86	26	0		0	34	56	100	210	430	620	940	
900	1000											220	470	680	1050	
1000	1120	350	195	98	28	0		0	40	66	120	250	520	780	1150	
1120	1250											260	580	840	1300	
1250	1400	390	220	110	30	0		0	48	78	140	300	640	960	1450	
1400	1600											330	720	1050	1600	
1600	1800	430	240	120	32	0		0	58	92	170	370	820	1200	1850	
1800	2000											400	920	1350	2000	
2000	2240	480	260	130	34	0		0	68	110	195	440	1000	1500	2300	
2240	2500											460	1100	1650	2500	
2500	2800	520	290	145	38	0		0	76	135	240	550	1250	1900	2900	
2800	3150											580	1400	2100	3200	
Above	UP To															
Signs		-	-	-	-			+	+	+	+	+	+	+		
Letter Symbols		d	e	f	g	h	js	k	m	n	p	r	s	t	u	
Divisions		Fundamental Deviations (Upper Deviations)					Fundamental Deviations (Lower Deviations)									
Grade		IT6 To IT16														

Tables for Determining Metric Tolerances

Table 6: Tolerances for Inside Dimensions (Holes)

Table 6 details tolerances for inside dimensions (holes) based relative to the tolerance symbol. Upper and lower values are provided as either positive or negative (or zero) values relative to the nominal size chosen. Pick the range in which the desired nominal value falls, and then either add or subtract the tolerances to find the upper and lower tolerance range for the desired nominal size.

Units IN mm		TOLERANCES FOR INSIDE DIMENSIONS (HOLES) UNITS in 0.001 MM																				
Over	TO	A11	B8	B11	C11	D9	D10	D11	E8	E9	F6	F7	F8	G6	G7	H5	H6	H7	H8	H9	H10	
NOMINAL SIZE RANGE	0	1	—	—	—	+120	+45	+60	+80	+28	+39	+12	+16	+20	+8	+12	+4	+6	+10	+14	+25	+40
	1	3	+330 +270	+154 +140	+200 +140	+60	+20	+20	+20	+14	+14	+6	+6	+6	+2	+2	0	0	0	0	0	0
	3	6	+345 +270	+158 +140	+215 +140	+145 +70	+60 +30	+78 +30	+105 +30	+38 +20	+50 +20	+18 +10	+22 +10	+28 +10	+12 +4	+16 +4	+5 0	+8 0	+12 0	+18 0	+30 0	+48 0
	6	10	+370 +280	+172 +150	+240 +150	+170 +80	+76 +40	+98 +40	+130 +40	+47 +25	+61 +25	+22 +13	+28 +13	+35 +13	+14 +5	+20 +5	+6 0	+9 0	+15 0	+22 0	+36 0	+58 0
	10	14	+400 +290	+177 +150	+260 +150	+205 +95	+93 +50	+120 +50	+160 +50	+59 +32	+75 +32	+27 +16	+34 +16	+43 +16	+17 +6	+24 +6	+8 0	+11 0	+18 0	+27 0	+43 0	+70 0
	14	18																				
	18	24	+430 +300	+193 +160	+290 +160	+240 +110	+117 +65	+149 +65	+195 +65	+73 +40	+92 +40	+33 +20	+41 +20	+53 +20	+20 +7	+28 +7	+9 0	+13 0	+21 0	+33 0	+52 0	+84 0
	24	30																				
	30	40	+470 +310	+209 +170	+330 +170	+280 +120	+142 +80	+180 +80	+240 +80	+89 +50	+112 +50	+41 +25	+50 +25	+64 +25	+25 +9	+34 +9	+11 0	+16 0	+25 0	+39 0	+62 0	+100 0
	40	50	+480 +320	+219 +180	+340 +180	+290 +130																
	50	65	+530 +340	+236 +190	+380 +190	+330 +140	+174 +100	+220 +100	+290 +100	+106 +60	+134 +60	+49 +30	+60 +30	+76 +30	+29 +10	+40 +10	+13 0	+19 0	+30 0	+46 0	+74 0	+120 0
	65	80	+550 +360	+246 +200	+390 +200	+340 +150																
	80	100	+600 +380	+274 +220	+440 +220	+390 +170	+207 +120	+260 +120	+340 +120	+126 +72	+159 +72	+58 +36	+71 +36	+90 +36	+34 +12	+47 +12	+15 0	+22 0	+35 0	+54 0	+87 0	+140 0
	100	120	+630 +410	+294 +240	+460 +240	+400 +180																
	120	140	+710 +460	+323 +260	+510 +260	+450 +200																
	140	160	+770 +520	+343 +280	+530 +280	+460 +210	+245 +145	+305 +145	+395 +145	+148 +85	+185 +85	+68 +43	+83 +43	+106 +43	+39 +14	+54 +14	+18 0	+25 0	+40 0	+63 0	+100 0	+160 0
	160	180	+830 +580	+373 +310	+560 +310	+480 +230																
	180	200	+950 +660	+412 +340	+630 +340	+530 +240																
	200	225	+1030 +740	+452 +380	+670 +380	+550 +260	+285 +170	+355 +170	+460 +170	+172 +100	+215 +100	+79 +50	+96 +50	+122 +50	+44 +15	+61 +15	+20 0	+29 0	+46 0	+72 0	+115 0	+185 0
	225	250	+1110 +820	+492 +420	+710 +420	+570 +280																
250	280	+1240 +920	+561 +480	+800 +480	+620 +300	+320 +190	+400 +190	+510 +190	+191 +110	+240 +110	+88 +56	+108 +56	+137 +56	+49 +17	+69 +17	+23 0	+32 0	+52 0	+81 0	+130 0	+210 0	
280	315	+1370 +1050	+621 +540	+860 +540	+650 +330																	
315	355	+1560 +1200	+689 +600	+960 +600	+720 +360	+350 +210	+440 +210	+570 +210	+214 +125	+265 +125	+98 +62	+119 +62	+151 +62	+54 +18	+75 +18	+25 0	+36 0	+57 0	+89 0	+140 0	+230 0	
355	400	+1710 +1350	+769 +680	+1040 +680	+760 +400																	
400	450	+1900 +1500	+857 +760	+1160 +760	+840 +440	+385 +230	+480 +230	+630 +230	+232 +135	+290 +135	+108 +68	+131 +68	+165 +68	+60 +20	+83 +20	+27 0	+40 0	+63 0	+97 0	+155 0	+250 0	
450	500	+2050 +1650	+937 +840	+1240 +840	+880 +480																	

Technical Reference | Tables for Determining Metric Tolerances

Tables for Determining Metric Tolerances

Table 6: Tolerances for Inside Dimension (Holes) - continued

Units IN mm		TOLERANCES FOR INSIDE DIMENSIONS (HOLES) UNITS IN 0.001 MM																			
Over	TO	H11	H12	H13	J6	J7	J8	K6	K7	K8	M6	M7	M8	N6	N7	N8	R7	JS6	JS7	JS8	JS9
0	1	+60	+100	+140	+2	+4	+6	0	0	0	-2	-2	-2	-4	-4	-4	-10	+3	+5	+7	+12.5
1	3	0	0	0	-4	-6	-8	-6	-10	-14	-8	-12	-16	-10	-14	-18	-20	-3	-5	-7	-12.5
3	6	+75	+120	+180	+5	+6	+10	+2	+3	+5	-1	0	+2	-5	-4	-2	-11	+4	+6	+9	+15
		0	0	0	-3	-6	-8	-6	-9	-13	-9	-12	-16	-13	-16	-20	-23	-4	-6	-9	-15
6	10	+90	+150	+220	+5	+8	+12	+2	+5	+6	-3	0	+1	-7	-4	-3	-13	+4.5	+7.5	+11	+18
		0	0	0	-4	-7	-10	-7	-10	-16	-12	-15	-21	-16	-19	-25	-28	-4.5	-7.5	-11	-18
10	14	+110	+180	+270	+6	+10	+15	+2	+6	+8	-4	0	+2	-9	-5	-3	-16	+5.5	+9	+13.5	+21.5
14	18	0	0	0	-5	-8	-12	-9	-12	-19	-15	-18	-25	-20	-23	-30	-34	-5.5	-9	-13.5	-21.5
18	24	+130	+210	+330	+8	+12	+20	+2	+6	+10	-4	0	+4	-11	-7	-3	-20	+6.5	+10.5	+16.5	+26
24	30	0	0	0	-5	-9	-13	-11	-15	-23	-17	-21	-29	-24	-28	-36	-41	-6.5	-10.5	-16.5	-26
30	40	+160	+250	+390	+10	+14	+24	+3	+7	+12	-4	0	+5	-12	-8	-3	-25	+8	+12.5	+19.5	+31
40	50	0	0	0	-6	-11	-15	-13	-18	-27	-20	-25	-34	-28	-33	-42	-50	-8	-12.5	-19.5	-31
50	65	+190	+300	+460	+13	+18	+28	+4	+9	+14	-5	0	+5	-14	-9	-4	-30	+9.5	+15	+23	+37
		0	0	0	-6	-12	-18	-15	-21	-32	-24	-30	-41	-33	-39	-50	-60	-9.5	-15	-23	-37
65	80																				
80	100	+220	+350	+540	+16	+22	+34	+4	+10	+16	-6	0	+6	-16	-10	-4	-38	+11	+17.5	+27	+43.5
		0	0	0	-6	-13	-20	-18	-25	-38	-28	-35	-48	-38	-45	-58	-73	-11	-17.5	-27	-43.5
100	120																				
120	140																				
140	160	+250	+400	+630	+18	+26	+41	+4	+12	+20	-8	0	+8	-20	-12	-4	-48	+12.5	+20	+31.5	+50
		0	0	0	-7	-14	-22	-21	-28	-43	-33	-40	-55	-45	-52	-67	-90	-12.5	-20	-31.5	-50
160	180																				
180	200																				
200	225	+290	+460	+720	+22	+30	+47	+5	+13	+22	-8	0	+9	-22	-14	-5	-60	+14.5	+23	+36	+57.5
		0	0	0	-7	-16	-25	-24	-33	-50	-37	-46	-63	-51	-60	-77	-109	-14.5	-23	-36	-57.5
225	250																				
250	280	+320	+520	+810	+25	+36	+55	+5	+16	+25	-9	0	+9	-25	-14	-5	-74	+16	+26	+40.5	+65
		0	0	0	-7	-16	-26	-27	-36	-56	-41	-52	-72	-57	-66	-86	-126	-16	-26	-40.5	-65
280	315																				
315	355	+360	+570	+890	+29	+39	+60	+7	+17	+28	-10	0	+11	-26	-16	-5	-87	+18	+28.5	+44.5	+70
		0	0	0	-7	-18	-29	-29	-40	-61	-46	-57	-78	-62	-73	-94	-144	-18	-28.5	-44.5	-70
355	400																				
400	450	+400	+630	+970	+33	+43	+66	+8	+18	+29	-10	0	+11	-27	-17	-6	-103	+20	+31.5	+48.5	+77.5
		0	0	0	-7	-20	-31	-32	-45	-68	-50	-63	-86	-67	-80	-103	-166	-20	-31.5	-48.5	-77.5
450	500																				

Tables for Determining Metric Tolerances

Table 6: Tolerances for Inside Dimensions (Holes) - continued

Units IN mm		TOLERANCES FOR INSIDE DIMENSIONS (HOLES) UNITS IN 0.001 MM									
Over	TO	JS10	JS11	JS12	JS13	JS14	JS15	JS16	JS17	JS18	
NOMINAL SIZE RANGE	0	1	+20	+30	+50	+70	+125	+200	+300	—	—
	1	3	-20	-30	-50	-70	-125	-200	-300	—	—
	3	6	+24	+37.5	+60	+90	+150	+240	+375	—	—
			-24	-37.5	-60	-90	-150	-240	-375	—	—
	6	10	+29	+45	+75	+110	+180	+290	+450	+750	—
			-29	-45	-75	-110	-180	-290	-450	-750	—
	10	14	+35	+55	+90	+135	+215	+350	+550	+900	+1350
			-35	-55	-90	-135	-215	-350	-550	-900	-1350
	18	24	+42	+65	+105	+165	+260	+420	+650	+1050	+1650
			-42	-65	-105	-165	-260	-420	-650	-1050	-1650
	30	40	+50	+80	+125	+195	+310	+500	+800	+1250	+1950
			-50	-80	-125	-195	-310	-500	-800	-1250	-1950
	50	65	+60	+95	+150	+230	+370	+600	+950	+1500	+2300
			-60	-95	-150	-230	-370	-600	-950	-1500	-2300
	80	100	+70	+110	+175	+270	+435	+700	+1100	+1750	+2700
			-70	-110	-175	-270	-435	-700	-1100	-1750	-2700
	120	140	+80	+125	+200	+315	+500	+800	+1250	+2000	+3150
			-80	-125	-200	-315	-500	-800	-1250	-2000	-3150
	180	200	+92.5	+145	+230	+360	+575	+925	+1450	+2300	+3600
			-92.5	-145	-230	-360	-575	-925	-1450	-2300	-3600
250	280	+105	+160	+260	+405	+650	+1050	+1600	+2600	+4050	
		-105	-160	-260	-405	-650	-1050	-1600	-2600	-4050	
315	355	+115	+180	+285	+445	+700	+1150	+1800	+2850	+4450	
		-115	-180	-285	-445	-700	-1150	-1800	-2850	-4450	
400	450	+125	+200	+315	+485	+775	+1250	+2000	+3150	+4850	
		-125	-200	-315	-485	-775	-1250	-2000	-3150	-4850	

Tables for Determining Metric Tolerances

Table 7: Tolerances for Outside Dimensions (Shafts)

Table 7 details tolerances for outside dimensions (shafts) based relative to the tolerance symbol. Upper and lower values are provided as either positive or negative (or zero) values relative to the nominal size chosen. Pick the range in which the desired nominal value falls, and then either add or subtract the tolerances to find the upper and lower tolerance range for the desired nominal size.

Units IN mm		TOLERANCES FOR OUTSIDE DIMENSIONS (SHAFTS) UNITS IN 0.001 MM																				
Over	TO	a11	b8	b11	c11	d9	d10	d11	e7	e8	e9	f6	f7	f8	f9	g5	g6	g7	h4	h5	h6	h7
0	1	—	—	—	-60	-20	-20	-20	-14	-14	-14	-6	-6	-6	-6	-2	-2	-2	0	0	0	0
1	3	-270 -330	-140 -154	-140 -200	-120	-45	-60	-80	-24	-28	-39	-12	-16	-20	-31	-6	-8	-12	-3	-4	-6	-10
3	6	-270 -345	-140 -158	-140 -215	-70 -145	-30 -60	-30 -78	-30 -105	-20 -32	-20 -38	-20 -50	-10 -18	-10 -22	-10 -28	-10 -40	-4 -9	-4 -12	-4 -16	0 -4	0 -5	0 -8	0 -12
6	10	-280 -370	-150 -172	-150 -240	-80 -170	-40 -76	-40 -98	-40 -130	-25 -40	-25 -47	-25 -61	-13 -22	-13 -28	-13 -35	-13 -49	-5 -11	-5 -14	-5 -20	0 -4	0 -6	0 -9	0 -15
10	14	-290 -400	-150 -177	-150 -260	-95 -205	-50 -93	-50 -120	-50 -160	-32 -50	-32 -59	-32 -75	-16 -27	-16 -34	-16 -43	-16 -59	-6 -14	-6 -17	-6 -24	0 -5	0 -8	0 -11	0 -18
14	18	-300 -430	-160 -193	-160 -290	-110 -240	-65 -117	-65 -149	-65 -195	-40 -61	-40 -73	-40 -92	-20 -33	-20 -41	-20 -53	-20 -72	-7 -16	-7 -20	-7 -28	0 -6	0 -9	0 -13	0 -21
18	24	-310 -470	-170 -209	-170 -330	-120 -280	-80	-80	-80	-50	-50	-50	-25	-25	-25	-25	-9	-9	-9	0	0	0	0
24	30	-320 -480	-180 -219	-180 -340	-130 -290	-142	-180	-240	-75	-89	-112	-41	-50	-64	-87	-20	-25	-34	-7	-11	-16	-25
30	40	-340 -530	-190 -236	-190 -380	-140 -330	-100	-100	-100	-60	-60	-60	-30	-30	-30	-30	-10	-10	-10	0	0	0	0
40	50	-360 -550	-200 -246	-200 -390	-150 -340	-174	-220	-290	-90	-106	-134	-49	-60	-76	-104	-23	-29	-40	-8	-13	-19	-30
50	65	-380 -600	-220 -274	-220 -440	-170 -390	-120	-120	-120	-72	-72	-72	-36	-36	-36	-36	-12	-12	-12	0	0	0	0
65	80	-410 -630	-240 -294	-240 -460	-180 -400	-207	-260	-340	-107	-126	-159	-58	-71	-90	-123	-27	-34	-47	-10	-15	-22	-35
80	100	-460 -710	-260 -323	-260 -510	-200 -450	-145	-145	-145	-85	-85	-85	-43	-43	-43	-43	-14	-14	-14	0	0	0	0
100	120	-520 -770	-280 -343	-280 -530	-210 -460	-245	-305	-395	-125	-148	-185	-68	-83	-106	-143	-32	-39	-54	-12	-18	-25	-40
120	140	-580 -830	-310 -373	-310 -560	-230 -480	-170	-170	-170	-100	-100	-100	-50	-50	-50	-50	-15	-15	-15	0	0	0	0
140	160	-660 -950	-340 -412	-340 -630	-240 -530	-190	-170	-170	-100	-100	-100	-50	-50	-50	-50	-15	-15	-15	0	0	0	0
160	180	-740 -1030	-380 -452	-380 -670	-260 -550	-285	-355	-460	-146	-172	-215	-79	-96	-122	-165	-35	-44	-61	-14	-20	-29	-46
180	200	-820 -1110	-420 -492	-420 -710	-280 -570	-190	-190	-190	-110	-110	-110	-56	-56	-56	-56	-17	-17	-17	0	0	0	0
200	225	-920 -1240	-480 -561	-480 -800	-300 -620	-320	-400	-510	-162	-191	-240	-88	-108	-137	-186	-40	-49	-69	-16	-23	-32	-52
225	250	-1050 -1370	-540 -621	-540 -860	-330 -650	-210	-210	-210	-125	-125	-125	-62	-62	-62	-62	-18	-18	-18	0	0	0	0
250	280	-1200 -1560	-600 -689	-600 -960	-360 -720	-350	-440	-570	-182	-214	-265	-98	-119	-151	-202	-43	-54	-75	-18	-25	-36	-57
280	315	-1350 -1710	-680 -769	-680 -1040	-400 -760	-230	-230	-230	-135	-135	-135	-68	-68	-68	-68	-20	-20	-20	0	0	0	0
315	355	-1650 -2050	-840 -937	-840 -1240	-480 -880	-385	-480	-630	-198	-232	-290	-108	-131	-165	-223	-47	-60	-83	-20	-27	-40	-63
355	400	-1500 -1900	-760 -857	-760 -1160	-440 -840	-230	-230	-230	-135	-135	-135	-68	-68	-68	-68	-20	-20	-20	0	0	0	0
400	450	-1650 -2050	-840 -937	-840 -1240	-480 -880	-385	-480	-630	-198	-232	-290	-108	-131	-165	-223	-47	-60	-83	-20	-27	-40	-63

Technical Reference | Tables for Determining Metric Tolerances

NOMINAL SIZE RANGE

Tables for Determining Metric Tolerances

Table 7: Tolerances for Outside Dimensions (Shafts)- continued

Units IN mm		TOLERANCES FOR OUTSIDE DIMENSIONS (SHAFTS) UNITS IN 0.001 MM																				
Over	TO	h8	h9	h10	h11	j5	j6	j7	k5	k6	k7	k8	m5	m6	m7	n5	n6	n7	r6	js6	js7	
NOMINAL SIZE RANGE	0	1	0	0	0	0	+2	+4	+6	+4	+6	+10	+14	+6	+8	+12	+8	+10	+14	+16	+3	+5
	1	3	-14	-25	-40	-60	-2	-2	-4	0	0	0	0	+2	+2	+2	+4	+4	+4	+10	-3	-5
	3	6	0	0	0	0	+3	+6	+8	+6	+9	+13	+18	+9	+12	+16	+13	+16	+20	+23	+4	+6
			-18	-30	-48	-75	-2	-2	-4	+1	+1	+1	0	+4	+4	+4	+8	+8	+8	+15	-4	-6
	6	10	0	0	0	0	+4	+7	+10	+7	+10	+16	+22	+12	+15	+21	+16	+19	+25	+28	+4.5	+7.5
			-22	-36	-58	-90	-2	-2	-5	+1	+1	+1	0	+6	+6	+6	+10	+10	+10	+19	-4.5	-7.5
	10	14	0	0	0	0	+5	+8	+12	+9	+12	+19	+27	+15	+18	+25	+20	+23	+30	+34	+5.5	+9
			-27	-43	-70	-110	-3	-3	-6	+1	+1	+1	0	+7	+7	+7	+12	+12	+12	+23	-5.5	-9
	18	24	0	0	0	0	+5	+9	+13	+11	+15	+23	+33	+17	+21	+29	+24	+28	+36	+41	+6.5	+10.5
			-33	-52	-84	-130	-4	-4	-8	+2	+2	+2	0	+8	+8	+8	+15	+15	+15	+28	-6.5	-10.5
	30	40	0	0	0	0	+6	+11	+15	+13	+18	+27	+39	+20	+25	+34	+28	+33	+42	+50	+8	+12.5
			-39	-62	-100	-160	-5	-5	-10	+2	+2	+2	0	+9	+9	+9	+17	+17	+17	+34	-8	-12.5
	50	65	0	0	0	0	+6	+12	+18	+15	+21	+32	+46	+24	+30	+41	+33	+39	+50	+60	+9.5	+15
			-46	-74	-120	-190	-7	-7	-12	+2	+2	+2	0	+11	+11	+11	+20	+20	+20	+41	-9.5	-15
	65	80																		+62		
																				+43		
	80	100	0	0	0	0	+6	+13	+20	+18	+25	+38	+54	+28	+35	+48	+38	+45	+58	+73	+11	+17.5
			-54	-87	-140	-220	-9	-9	-15	+3	+3	+3	0	+13	+13	+13	+23	+23	+23	+51	-11	-17.5
	100	120																		+76		
																				+54		
120	140																		+88			
																			+63			
140	160	0	0	0	0	+7	+14	+22	+21	+28	+43	+63	+33	+40	+55	+45	+52	+67	+90	+12.5	+20	
		-63	-100	-160	-250	-11	-11	-18	+3	+3	+3	0	+15	+15	+15	+27	+27	+27	+65	-12.5	-20	
160	180																		+93			
																			+68			
180	200																		+106			
																			+77			
200	225	0	0	0	0	+7	+16	+25	+24	+33	+50	+72	+37	+46	+63	+51	+60	+77	+109	+14.5	+23	
		-72	-115	-185	-290	-13	-13	-21	+4	+4	+4	0	+17	+17	+17	+31	+31	+31	+80	-14.5	-23	
225	250																		+113			
																			+84			
250	280	0	0	0	0	+7	+16	+26	+27	+36	+56	+81	+43	+52	+72	+57	+66	+86	+126	+16	+26	
		-81	-130	-210	-320	-16	-16	-26	+4	+4	+4	0	+20	+20	+20	+34	+34	+34	+94	-16	-26	
280	315																		+130			
																			+98			
315	355	0	0	0	0	+7	+18	+29	+29	+40	+61	+89	+46	+57	+78	+62	+73	+94	+144	+18	+28.5	
		-89	-140	-230	-360	-18	-18	-28	+4	+4	+4	0	+21	+21	+21	+37	+37	+37	+108	-18	-28.5	
355	400																		+150			
																			+114			
400	450	0	0	0	0	+7	+20	+31	+32	+45	+68	+97	+50	+63	+86	+67	+80	+103	+166	+20	+31.5	
		-97	-155	-250	-400	-20	-20	-32	+5	+5	+5	0	+23	+23	+23	+40	+40	+40	+126	-20	-31.5	
450	500																		+172			
																			+132			

Technical Reference | Tables for Determining Metric Tolerances

Tables for Determining Metric Tolerances

Table 7: Tolerances for Outside Dimensions (Shafts) - continued

Units IN mm		TOLERANCE FOR OUTSIDE DIMENSIONS (SHAFTS) UNITS IN 0.001 MM											
Over	TO	js8	js9	js10	js11	js12	js13	js14	js15	js16	js17	js18	
NOMINAL SIZE RANGE	0	1	+7	+12.5	+20	+30	+50	+70	+125	+200	+300	—	—
	1	3	-7	-12.5	-20	-30	-50	-70	-125	-200	-300	—	—
	3	6	+9	+15	+24	+37.5	+60	+90	+150	+240	+375	—	—
			-9	-15	-24	-37.5	-60	-90	-150	-240	-375	—	—
	6	10	+11	+18	+29	+45	+75	+110	+180	+290	+450	+750	—
			-11	-18	-29	-45	-75	-110	-180	-290	-450	-750	—
	10	14	+13.5	+21.5	+35	+55	+90	+135	+215	+350	+550	+900	+1350
			-13.5	-21.5	-35	-55	-90	-135	-215	-350	-550	-900	-1350
	18	24	+16.5	+26	+42	+65	+105	+165	+260	+420	+650	+1050	+1650
			-16.5	-26	-42	-65	-105	-165	-260	-420	-650	-1050	-1650
	30	40	+19.5	+31	+50	+80	+125	+195	+310	+500	+800	+1250	+1950
			-19.5	-31	-50	-80	-125	-195	-310	-500	-800	-1250	-1950
	50	65	+23	+37	+60	+95	+150	+230	+370	+600	+950	+1500	+2300
			-23	-37	-60	-95	-150	-230	-370	-600	-950	-1500	-2300
	80	100	+27	+43.5	+70	+110	+175	+270	+435	+700	+1100	+1750	+2700
			-27	-43.5	-70	-110	-175	-270	-435	-700	-1100	-1750	-2700
	120	140	+31.5	+50	+80	+125	+200	+315	+500	+800	+1250	+2000	+3150
			-31.5	-50	-80	-125	-200	-315	-500	-800	-1250	-2000	-3150
	180	200	+36	+57.5	+92.5	+145	+230	+360	+575	+925	+1450	+2300	+3600
-36			-57.5	-92.5	-145	-230	-360	-575	-925	-1450	-2300	-3600	
250	280	+40.5	+65	+105	+160	+260	+405	+650	+1050	+1600	+2600	+4050	
		-40.5	-65	-105	-160	-260	-405	-650	-1050	-1600	-2600	-4050	
315	355	+44.5	+70	+115	+180	+285	+445	+700	+1150	+1800	+2850	+4450	
		-44.5	-70	-115	-180	-285	-445	-700	-1150	-1800	-2850	-4450	
400	450	+48.5	+77.5	+125	+200	+315	+485	+775	+1250	+2000	+3150	+4850	
		-48.5	-77.5	-125	-200	-315	-485	-775	-1250	-2000	-3150	-4850	

Tables for Determining Metric Tolerances

Table 8: Tolerances for Inside Dimensions (Holes)

Table 8 details tolerances for inside dimensions (holes) based relative to the tolerance symbol. This table works the same way as Table 6, but is pulled from a different source (ANSI standards) and details S7 and U7 fits. Pick the nominal size value that is **closest** to the desired nominal size to determine the required tolerance range relative to the chosen tolerance symbol.

Hole Basis Fit	Example:	Nominal size:	[mm]	60	Hole [mm]	60	H7	+0.030	(0.030mm range)
		Size range to be used:		50 to 65		60		-0	
This Gives:		ISO Grade No.:		IT7 (hole), It 6 (shaft)	Shaft: [mm]	60	k6	+0.021	(0.019mm range)
		Tolerance Symbol:		H7/k6		60		+0.002	
		Desired Fit:		Locational Transition Fit					
		Allowance for Hole:		0.030mm					
		Allowance for Shaft:		0.019mm					

TOLERANCES FOR OUTSIDE DIMENSIONS (SHAFTS) UNITS IN 0.001 MM						
NOMINAL SIZE RANGE	Pick Closest Value to Desired Dimension (Units IN mm)	S7	U7	Pick Closest Value to Desired Dimension (Units IN mm)	S7	U7
		1	-14 -24	-18 -28	25	-27 -48
	1.2	-14 -24	-18 -28	30	-27 -48	-40 -61
	1.6	-14 -24	-18 -28	40	-34 -59	-51 -76
	2	-14 -24	-18 -28	50	-34 -59	-61 -86
	2.5	-14 -24	-18 -28	60	-42 -72	-76 -106
	3	-14 -24	-18 -28	80	-48 -78	-91 -121
	4	-15 -27	-19 -31	100	-58 -93	-111 -146
	5	-15 -27	-19 -31	120	-66 -101	-131 -166
	6	-15 -27	-19 -31	160	-85 -125	-175 -215
	8	-17 -32	-22 -37	200	-105 -151	-219 -265
	10	-17 -32	-22 -37	250	-123 -169	-267 -313
	12	-21 -39	-26 -44	300	-150 -202	-330 -382
	16	-21 -39	-26 -44	400	-187 -244	-414 -471
	20	-27 -48	-33 -54	500	-229 -292	-517 -580

Tables for Determining Metric Tolerances

Table 9: Tolerances for Outside Dimensions (Shafts)

Table 9 details tolerances for outside dimensions (shafts) based relative to the tolerance symbol. This table works the same way as Table 7, but is pulled from a different source (ANSI standards) and details s6 and u6 fits. Pick the nominal size value that is **closest** to the desired nominal size to determine the required tolerance range relative to the chosen tolerance symbol.


HOLE BASIS FIT		[mm]	Hole:	
Example:	Nominal size:	24	[mm]	
	Size range to be used:	18 to 30		
	ISO Grade No.:	IT 6		
	Tolerance Symbol:	F6/h6		
This Gives:	Desired Fit:	Clearance Fit		
	Allowance for hole:	0.013mm		
	Allowance for shaft:	0.013mm		

24	F6	+0.033	(0.013mm range)
		+0.020	

24	h6	0	(0.013mm range)
		-0.013	

TOLERANCES FOR OUTSIDE DIMENSIONS (SHAFTS) UNITS IN 0.001 MM					
Pick Closest Value to desired dimension (Units IN mm)	s6	u6	Pick Closest Value to desired dimension (Units IN mm)	s6	u6
1	+20 +14	+24 +18	25	+48 +35	+61 +48
1.2	+20 +14	+24 +18	30	+48 +35	+61 +48
1.6	+20 +14	+24 +18	40	+59 +43	+76 +60
2	+20 +14	+24 +18	50	+59 +43	+86 +70
2.5	+20 +14	+24 +18	60	+72 +53	+106 +87
3	+20 +14	+24 +18	80	+78 +59	+121 +102
4	+27 +19	+31 +23	100	+93 +71	+146 +124
5	+27 +19	+31 +23	120	+101 +79	+166 +144
6	+27 +19	+31 +23	160	+125 +100	+215 +190
8	+32 +23	+37 +28	200	+151 +122	+265 +236
10	+32 +23	+37 +28	250	+169 +140	+313 +284
12	+39 +28	+44 +33	300	+202 +170	+382 +350
16	+39 +28	+44 +33	400	+244 +208	+471 +435
20	+48 +35	+54 +41	500	+292 +252	+580 +540

American Standard Mold Base Features





- 43 Nominal Sizes
- 9 Plate Thicknesses
- 4 Steel Types
- Guided Ejection
- Pry Slots
- Lifting Holes
- Leader Pin Vents
- Ejector Housing Cover
- Feature Positions
- Feature Omissions
- Three-Piece or Welded Housing Type
- Clamp Slot Type
- Mixed Steel
- Sprue Puller Pin Diameter
- Stop Pin Location


Pry Slots




Mold base features Pry Slots, installed in any plate specified, on the parting and/or non-parting line side. This provides handling ease when opening and/or disassembling a mold.



Base Size	Slot Length Z
88-1123	.56 X 45°
1212-1315	.88 X 45°
1318-2435	1.00 X 45°



Return Pins & Stop Pins






Base Size	RP Diameter (Recom'd)	RP -y SP -y	Position 1		Position 2		SP -x1 SP -x6	SP -x2 SP -x7	SP -x3 SP -x8	sp -x4 sp -x9	sp -x5 sp -x10
			RP -x0s	RP -x	RP -x0s	RP -x					
88	0.500	1.500	3.250	3.375	3.188	3.312	3.375				3.375
812	0.500	1.500	5.250	5.375	5.188	5.312	5.375		On center		5.375
108	0.625	2.250	3.250	3.375	3.125	3.250	3.375				3.375
1012	0.625	2.250	5.188	5.312	5.063	5.188	5.312		On center		5.312
1016	0.625	2.250	7.250	7.375	7.125	7.250	7.375	2.500		2.500	7.375
1020	0.625	2.250	9.250	9.375	9.125	9.250	9.375	3.125		3.125	9.375
1112	0.625	2.812	5.250	5.375	5.125	5.250	5.375		On center		5.375
1114	0.625	2.812	6.250	6.375	6.125	6.250	6.375		On center		6.375
1118	0.625	2.812	8.250	8.375	8.125	8.250	8.375		On center		8.375
1123	0.625	2.812	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
1212	0.750	3.188	5.250	5.375	5.000	5.125	5.375		On center		5.375
1215	0.750	3.188	6.750	6.875	6.500	6.625	6.875	2.250		2.250	6.875
1220	0.750	3.188	9.250	9.375	9.000	9.125	9.375	3.094		3.094	9.375
1223	0.750	3.188	11.000	11.125	10.750	10.875	11.125	3.750		3.750	11.125
1315	0.750	3.812	6.750	6.875	6.500	6.625	6.875	2.250		2.250	6.875
1318	0.750	3.812	8.250	8.375	8.000	8.125	8.375	2.750		2.750	8.375
1321	0.750	3.812	9.500	9.625	9.375	9.500	9.625	4.000		4.000	9.625
1323	0.750	3.812	10.875	11.000	10.750	10.875	11.000	4.000		4.000	11.000
1326	0.750	3.812	12.125	12.250	12.000	12.125	12.250	4.000		4.000	12.250
1329	0.750	3.812	13.875	14.000	13.750	13.875	14.000	5.000		5.000	14.000
1518	0.750	3.875	8.125	8.250	7.938	8.062	8.250	2.750		2.750	8.250
1524	0.750	3.875	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
1529	0.750	3.875	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1616	0.750	4.375	7.125	7.250	7.000	7.125	7.250	2.375		2.375	7.250
1620	0.750	4.375	9.125	9.250	9.000	9.125	9.250	3.062		3.062	9.250
1623	0.750	4.375	10.875	11.000	10.750	10.875	11.000	4.000		4.000	11.000
1626	0.750	4.375	12.125	12.250	12.000	12.125	12.250	4.000		4.000	12.250
1629	0.750	4.375	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1635	0.750	4.375	16.875	17.000	16.750	16.875	17.000	8.500	On center	8.500	17.000
1724	0.750	4.625	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
1729	0.750	4.625	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1818	0.750	5.375	8.125	8.250	8.000	8.125	8.250	2.750		2.750	8.250
1820	0.750	5.375	9.125	9.250	9.000	9.125	9.250	3.062		3.062	9.250
1823	0.750	5.375	10.875	11.000	10.750	10.875	11.000	4.000		4.000	11.000
1826	0.750	5.375	12.125	12.250	12.000	12.125	12.250	4.000		4.000	12.250
1829	0.750	5.375	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1835	0.750	5.375	16.875	17.000	16.750	16.875	17.000	8.500	On center	8.500	17.000
1924	0.750	6.125	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
1929	0.750	6.125	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
1935	0.750	6.125	16.875	17.000	16.750	16.875	17.000	8.500	On center	8.500	17.000
2424	0.750	7.750	11.000	11.125	10.875	11.000	11.125	3.750		3.750	11.125
2429	0.750	7.750	13.875	14.000	13.750	13.875	14.000	4.688		4.688	14.000
2435	0.750	7.750	16.875	17.000	16.750	16.875	17.000	8.500	On center	8.500	17.000

American Standard Mold Base Features

Leader Pins, Vents & Bushings

Leader Pins and Bushings align both halves of the mold at the parting line. Leader Pin Vents, which allow trapped air to escape from the mold, are designed into all 15-inch-and-wider series molds. When desired, they can be specified on smaller molds.



SIZE	DIA	LPxos	LPx	LPy
88	0.750	3.000	3.125	3.125
812	0.750	5.000	5.125	3.125
108	0.750	2.938	3.125	4.062
1012	0.875	4.875	5.062	4.062
1016	0.875	6.938	7.125	4.062
1020	0.875	8.938	9.125	4.062
1112	0.875	4.938	5.125	4.562
1114	0.875	5.938	6.125	4.562
1118	0.875	7.938	8.125	4.562
1123	0.875	10.688	10.875	4.562
1212	1.000	4.625	4.812	5.000
1215	1.000	6.125	6.312	5.000
1220	1.000	8.625	8.812	5.000
1223	1.000	10.375	10.562	5.000
1315	1.000	6.125	6.312	5.688
1318	1.000	7.375	7.562	5.688
1321	1.000	8.750	8.938	5.688
1323	1.000	10.125	10.312	5.688
1326	1.000	11.375	11.562	5.688
1329	1.000	13.125	13.312	5.688
1518	1.250	7.375	7.562	6.062
1524	1.250	10.250	10.438	6.062
1529	1.250	13.125	13.312	6.062
1616	1.250	6.375	6.562	6.562
1620	1.250	8.375	8.562	6.562
1623	1.250	10.125	10.312	6.562
1626	1.250	11.375	11.562	6.562
1629	1.250	13.125	13.312	6.562
1635	1.250	16.125	16.312	6.562
1724	1.250	10.250	10.438	6.812
1729	1.250	13.125	13.312	6.812
1818	1.250	7.375	7.562	7.562
1820	1.250	8.375	8.562	7.562
1823	1.250	10.125	10.312	7.562
1826	1.250	11.375	11.562	7.562
1829	1.250	13.125	13.312	7.562
1835	1.250	16.125	16.312	7.562
1924	1.250	10.250	10.438	8.312
1929	1.250	13.125	13.312	8.312
1935	1.250	16.125	16.312	8.312
2424	1.500	10.062	10.250	10.250
2429	1.500	12.938	13.125	10.250
2435	1.500	15.938	16.125	10.250


Ejector Housing & Cover

Ejector Housing Cover


For additional operator safety, SelectBase molds include an ejector housing cover, except when a longer length ejector bar is selected. The perforated DME logo helps the operator to visually determine if the ejector plate and ejector retainer plate are in the returned position. The cover is fastened on both sides with 5/16-18 button-head cap screws. Once again, DME is leading the industry into a safer work environment.

Ejector Housing

DME offers a selection of housing types to fit application demands. A one-piece welded housing is available for customers requiring maximum rigidity and robust durability. For maximum flexibility of configuration options, a three-piece housing is also available.




Recommended Dimensions for Drilling and Tapping




Clamp Slots

Type A




NOTE: When this plate is 0.875 thick, the slots will be machined through the thickness.


Type B



Type C



Type D





Lifting Holes

Lifting Hole Diameters


BASE SIZE	PLATE THICKNESS	
	0.875	1.375
88-1118	1/2-13 UNC	1/2-13 UNC
1123-1524	5/8-11 UNC	5/8-11 UNC
1529-1829	5/8-11 UNC	3/4-10 UNC
1835-2429	5/8-11 UNC	1"-8 UNC
2435	N/A	1"-8 UNC

Lifting Holes

THREAD SIZE	S	T MAX.
1/2-13	1.00	1.38
5/8-11	1.25	1.75
3/4-10	1.50	2.00
1"-8	2.00	2.62




Lifting Holes can be used to install hoist rings for ease of handling. Mold base can be configured only with Lifting Holes which are appropriate for the specific mold base size. Refer to the DME catalog for a comprehensive selection of Hoist Rings.



American Standard Mold Base Features

Guided Ejection Systems

Guided Ejection Systems hold the ejector assembly in alignment and support the weight of the ejector assembly throughout the molding cycle – greatly reducing wear on ejection components and preventing cocking of the ejector assembly.




“B” HALF OF MOLD FOR 88, 812 & 108 MOLD BASE SIZE ONLY

“B” HALF OF MOLD FOR 1012 – 2435 BASES


Guided Ejection Positions

PIN DIAMETER (RECOM'D)	BASE SIZE	GE X	GE Y
0.750	88	3.000	Center
	812	5.000	Center
	108	3.062	Center
	1012	5.000	1.000
	1016	7.062	1.000
	1020	9.062	1.000
	1112	5.062	1.625
	1114	6.062	1.625
	1118	8.062	1.625
	1123	10.812	1.625
0.875	212	5.000	1.750
	1215	6.500	1.750
	1220	9.000	1.750
	1223	10.750	1.750
	1315	6.500	2.375
	1318	8.000	2.375
	1321	9.375	2.375
	1323	10.750	2.375
	1326	12.000	2.375
	1329	13.750	2.375
1.000	1518	7.875	2.375
	1524	10.812	2.375
	1529	13.688	2.375
	1616	6.938	2.875
	1620	8.938	2.875
	1623	10.688	2.875
	1626	11.938	2.875
	1629	13.688	2.875
	1635	16.688	2.875
	1724	10.812	3.125
	1729	13.688	3.125
	1818	7.938	3.875
	1820	8.938	3.875
	1823	10.688	3.875
	1826	11.038	3.875
1829	13.688	3.875	
1835	16.688	3.875	
1924	10.812	4.625	
1929	13.688	4.625	
1935	16.688	4.625	
1.250	2424	10.688	6.125
	2429	13.562	6.125
	2435	16.562	6.125



System 1

When pins are installed in the support plate, the ejector housing can be removed from the mold without removing ejector plates. This permits easy access to service the ejector system.



System 2

Pins installed in the ejector housing permit fast installation. When the ejector housing is removed from the mold base, the complete ejector assembly is removed.

Sizes & Thicknesses

43 Nominal Sizes

- The American Standard Mold Base is available in 43 nominal sizes to match the mold space requirements for your application.
- As the creator of the American mold base standard, DME has the largest selection of mold base sizes and most are available in less than five business days.

CODE	THICKNESS
7	0.875
13	1.375
17	1.875
23	2.375
27	2.875
33	3.375
37	3.875
47	4.875
57	5.875

9 Plate Thicknesses

- DME offers mold plates for all nominal sizes up to 5-7/8".
- Our own steel processing facility manufactures our mold plate directly from raw steel slabs.

NOMINAL SIZE	WIDTH (IN)	LENGTH (IN)	WEIGHT RANGE (LBS)	
			MIN	MAX
88	7.875	7.875	116	305
812	7.875	11.875	175	460
108	9.875	8.000	156	393
1012	9.875	11.875	235	592
1016	9.875	16.000	316	798
1020	9.875	20.000	395	997
1112	10.875	12.000	261	659
1114	10.875	14.000	305	769
1118	10.875	18.000	392	988
1123	10.875	23.500	511	1290
1212	11.875	12.000	285	719
1215	11.875	15.000	379	899
1220	11.875	20.000	505	1199
1223	11.875	23.500	594	1409
1315	13.375	15.000	427	1038
1318	13.375	18.000	512	1246
1321	13.375	20.750	590	1436
1323	13.375	23.500	669	1627
1326	13.375	26.000	740	1800
1329	13.375	29.500	839	2042
1518	14.875	17.875	599	1410
1524	14.875	23.750	796	1873

NOMINAL SIZE	WIDTH (IN)	LENGTH (IN)	WEIGHT RANGE (LBS)	
			MIN	MAX
1529	14.875	29.500	989	2327
1616	15.875	16.000	573	1347
1620	15.875	20.000	716	1683
1623	15.875	23.500	841	1978
1626	15.875	26.000	930	2189
1629	15.875	29.500	1056	2483
1635	15.875	35.500	1270	2988
1724	16.500	23.750	883	2078
1729	16.500	29.500	1097	2581
1818	17.875	18.000	725	1706
1820	17.875	20.000	806	1896
1823	17.875	23.500	947	2227
1826	17.875	26.000	1048	2464
1829	17.875	29.500	1189	2796
1835	17.875	35.500	1430	3365
1924	19.500	23.750	1044	2456
1929	19.500	29.500	1297	3050
1935	19.500	35.500	1648	3758
2424	23.750	23.750	1343	3062
2429	23.750	29.500	1668	3804
2435	23.750	35.500	2008	4578

Steels for Structural and Holder Block Applications

DME #1 Steel is a medium carbon quality steel with greater tensile strength than typical plain carbon warehouse steels. It machines easily, but is not "sticky", permitting a faster and smoother cut. International comparisons: DIN 1.1178 (CK 30) and 1.1730 (C 45 W); JIS S 30 CM, S50C, S55C; ISO 683-1 C30E4.

DME #2 Steel is a medium alloy steel specified for durability in structural applications. It is supplied pre-heat treated to 28-34 HRC (271-321 Bhn). A high strength steel, it is ideal for cavity and core retainer plates, clamping plates and support plates in molds. International comparisons: DIN 1.2312 (40CrMnMoS 8 6), 1.7218 (25CrMo4) and 1.2331 (41CrMoS4); JIS SCM 430; ISO 683-2 Type 1.

DME #7 Steel is a modified AISI 400 series stainless steel for holder block applications. It is supplied pre-heat treated to 32-36 HRC (302-340 Bhn). This stainless steel offers corrosion-resistance and exceptional machinability but cannot be further hardened (see DME #6). For humid environments, corrosive plastics, "clean room" or "100% stainless" applications, it is an ideal choice for all structural mold plates. International comparisons: none.

Steels for Cavity & Core Applications


DME #3 Steel is a P-20 AISI 4130 type cavity steel. Exceptionally clean, it is pre-heat treated to 28-34 HRC (271-321 Bhn). It provides good machinability, the ability to heat treat to higher hardness, and exceptional polishability. International comparisons: DIN 1.2311 G40CrMnMo7; JIS none; ISO none.

DME #5 Steel is an AISI/SAE H-13 type thermal shock resistant, hotwork die steel. Supplied fully annealed (approximately 200 Bhn; 13-20 HRC) for easy machinability, it can be subsequently heat treated to the desired hardness with a minimum of deformation. Mainly used for die cast dies, it is also suitable for plastic molds with exceptional hardness or polishability requirements. DME #5 Steel meets or exceeds the acceptance criteria established by the NADCA as detailed in Technical Digest Number 01-80-01D. International comparisons: DIN 1.2344 (X40CrMoV5-1); JIS SKD 61; ISO 4955 H13.

DME #6 Steel is a modified AISI 420 type stainless steel. It is supplied fully annealed to 179-241 Bhn (8-23 HRC), making it readily machinable. Unlike DME #7 steel, DME #6 steel is a cavity-grade material that can be subsequently heat treated to the desired hardness and has excellent polishability. International comparisons: DIN 1.4028 (X30Cr13); JIS SUS 420 J2; ISO none.

American Standard Mold Base Features

Ejector Assembly Screws




"B" half of mold


Ejector Assembly Screw Positions

BASE SIZE	SCREW SIZE	EAS X	EAS Y
88	5/16-18	3.375	2.250
812	5/16-18	5.375	2.250
108	5/16-18	3.375	3.062
1012	5/16-18	5.312	3.062
1016	5/16-18	7.375	3.062
1020	5/16-18	9.375	3.062
1112	5/16-18	4.562	3.312
1114	5/16-18	5.562	3.312
1118	5/16-18	7.562	3.312
1123	5/16-18	10.312	3.312
1212	5/16-18	4.500	3.812
1215	5/16-18	6.000	3.812
1220	5/16-18	8.500	3.812
1223	5/16-18	10.250	3.812
*1315	3/8-16	5.812	4.250
*1318	3/8-16	7.312	4.250
1321	3/8-16	8.688	4.250
1323	3/8-16	10.062	4.250
1326	3/8-16	11.312	4.250
1329	3/8-16	13.062	4.250
1518	3/8-16	8.312	5.000
1524	3/8-16	11.250	5.000
1529	3/8-16	14.125	5.000
1616	3/8-16	7.375	5.438
1620	3/8-16	9.375	5.438
1623	3/8-16	11.125	5.438
1626	3/8-16	12.375	5.438
1629	3/8-16	14.125	5.438
1635	3/8-16	17.125	5.438
1724	3/8-16	11.250	5.750
1729	3/8-16	14.125	5.750
1818	3/8-16	8.375	6.438
1820	3/8-16	9.375	6.438
1823	3/8-16	11.125	6.438
1826	3/8-16	12.375	6.438
1829	3/8-16	14.125	6.438
1835	3/8-16	17.125	6.438
1924	1/2-13	11.250	7.250
1929	1/2-13	14.125	7.250
1935	1/2-13	17.125	7.250
2424	1/2-13	11.250	8.875
2429	1/2-13	14.125	8.875
2435	1/2-13	17.125	8.875

Upper & Lower Assembly Screws



"A" half of mold inverted





"B" half of mold


Upper and Lower Assembly Screw Positions

BASE SIZE	SCREW SIZE	UASy LASy	UASx1 LASx1	UASx2 LASx2	UASx3 LASx3	UASx4 LASx4	UASx5 LASx5	UASx6 LASx6	UASx7 LASx7	UASx8 LASx8	UASx9 LASx9	UASx10 LASx10	UASx11 LASx11	UASx12 LASx12
88	1/2-13	3.125	1.375	—	—	—	—	1.375	1.375	—	—	—	—	1.375
812	1/2-13	3.125	2.250	—	—	—	—	2.250	2.250	—	—	—	—	2.250
108	1/2-13	4.000	1.875	—	—	—	—	1.875	1.875	—	—	—	—	1.875
1012	1/2-13	4.000	3.250	—	—	—	—	3.250	3.250	—	—	—	—	3.250
1016	1/2-13	4.000	5.000	—	—	—	—	5.000	5.000	—	—	—	—	5.000
1020	1/2-13	4.000	6.500	—	—	1.000	—	6.500	6.500	—	1.000	—	—	6.500
1112	1/2-13	4.469	3.188	—	—	—	—	3.188	3.188	—	—	—	—	3.188
1114	1/2-13	4.469	3.188	—	—	—	—	3.188	3.188	—	—	—	—	3.188
1118	1/2-13	4.469	5.875	—	—	1.000	—	5.875	5.875	—	1.000	—	—	5.875
1123	1/2-13	4.469	8.625	—	3.188	3.188	—	8.625	8.625	—	3.188	3.188	—	8.625
1212	1/2-13	4.969	2.812	—	—	—	—	2.812	2.812	—	—	—	—	2.812
1215	1/2-13	4.969	4.500	—	—	1.000	—	4.500	4.500	—	1.000	—	—	4.500
1220	1/2-13	4.969	6.625	—	—	1.000	—	6.625	6.625	—	1.000	—	—	6.625
1223	1/2-13	4.969	8.625	—	2.812	2.812	—	8.625	8.625	—	2.812	2.812	—	8.625
1315	1/2-13	5.719	4.500	—	—	1.000	—	4.500	4.500	—	1.000	—	—	4.500
1318	1/2-13	5.719	5.438	—	—	1.000	—	5.438	5.438	—	1.000	—	—	5.438
1321	1/2-13	5.719	6.750	—	—	1.000	—	6.750	6.750	—	1.000	—	—	6.750
1323	1/2-13	5.719	8.125	—	2.750	2.750	—	8.125	8.125	—	2.750	2.750	—	8.125
1326	1/2-13	5.719	9.375	—	3.250	3.250	—	9.375	9.375	—	3.250	3.250	—	9.375
1329	1/2-13	5.719	11.125	—	3.250	3.250	—	11.125	11.125	—	3.250	3.250	—	11.125
1518	1/2-13	6.469	5.438	—	—	1.000	—	5.438	5.438	—	1.000	—	—	5.438
1524	1/2-13	6.469	7.750	—	2.750	2.750	—	7.750	7.750	—	2.750	2.750	—	7.750
1529	1/2-13	6.469	10.625	—	3.688	3.688	—	10.625	10.625	—	3.688	3.688	—	10.625
1616	1/2-13	6.969	4.250	—	—	1.000	—	4.250	4.250	—	1.000	—	—	4.250
1620	1/2-13	6.969	6.250	—	—	1.000	—	6.250	6.250	—	1.000	—	—	6.250
1623	1/2-13	6.969	8.000	—	2.750	2.750	—	8.000	8.000	—	2.750	2.750	—	8.000
1626	1/2-13	6.969	9.250	—	3.125	3.125	—	9.250	9.250	—	3.125	3.125	—	9.250
1629	1/2-13	6.969	11.000	—	3.688	3.688	—	11.000	11.000	—	3.688	3.688	—	11.000
1635	1/2-13	6.969	14.000	8.500	2.875	2.875	8.500	14.000	14.000	8.500	2.875	2.875	8.500	14.000
1724	1/2-13	7.281	7.750	—	2.750	2.750	—	7.750	7.750	—	2.750	2.750	—	7.750
1729	1/2-13	7.281	10.625	—	3.688	3.688	—	10.625	10.625	—	3.688	3.688	—	10.625
1818	1/2-13	7.969	5.438	—	—	1.000	—	5.438	5.438	—	1.000	—	—	5.438
1820	1/2-13	7.969	6.438	—	—	1.000	—	6.438	6.438	—	1.000	—	—	6.438
1823	1/2-13	7.969	8.125	—	2.750	2.750	—	8.125	8.125	—	2.750	2.750	—	8.125
1826	1/2-13	7.969	9.375	—	3.125	3.125	—	9.375	9.375	—	3.125	3.125	—	9.375
1829	1/2-13	7.969	11.125	—	3.688	3.688	—	11.125	11.125	—	3.688	3.688	—	11.125
1835	1/2-13	7.969	14.125	8.500	2.875	2.875	8.500	14.125	14.125	8.500	2.875	2.875	8.500	14.125
1924	1/2-13	8.781	7.750	—	2.750	2.750	—	7.750	7.750	—	2.750	2.750	—	7.750
1929	1/2-13	8.781	11.125	—	3.688	3.688	—	11.125	11.125	—	3.688	3.688	—	11.125
1935	1/2-13	8.781	14.125	8.500	2.875	2.875	8.500	14.125	14.125	8.500	2.875	2.875	8.500	14.125
2424	5/8-11	10.844	7.750	—	2.750	2.750	—	7.750	7.750	—	2.750	2.750	—	7.750
2429	5/8-11	10.844	10.625	—	3.688	3.688	—	10.625	10.625	—	3.688	3.688	—	10.625
2435	5/8-11	10.844	13.625	8.500	2.750	2.750	8.500	13.625	13.625	8.500	2.750	2.750	8.500	13.625

*New dimensions 10/02



2-PLATE
SERIES



4-PLATE
SERIES

MOLD BASES AND PLATES

DME Company USA

29111 Stephenson Highway
Madison Heights, MI 48071
800-626-6653 (toll-free)
248-398-6000
888-808-4363 (toll-free fax)
dme@milacron.com

DME Canada

6510 Northwest Drive
Mississauga, ONT
Canada L4V 1J6
800-387-6600 (toll-free)
905-677-6370
800-461-9985 (toll-free fax)
dme_canada@milacron.com

DME Mexico

Circuito el Marques Norte
No. 55
Parque Industrial El Marques
El Marques, Queretaro,
CP 76246
52.442.713.5666
dme_mexico@milacron.com

