



# AIR GRINDERS & TURBOLAP PROFILERS EXCELLENT PERFORMANCE - OUTSTANDING EFFICIENCY

# **AIR GRINDER SYSTEM** Air Micro Straight Grinder Series

Air Micro Grinder Series provide high-speed rotation, high durability and high precision. Applications in low-pressure environment, ranging from 58 PSI are supported.

The rotation speed, body strength, and the cooling function have further improved compared to the conventional products.

This product comes with all the necessary accessories, such as hoses, joints, and grindstones, you can start using it from the day of purchase.

### FEATURES:

- Comfortable weight and size with a multi angle body design for prolonged jobs
- Pneumatic and capable of continuous operation
- Air-driven yet designed to be kept from getting too cold
- 65,000 rpm for efficiency
- A high precision collet with a small run-out
- Durable structure with four evenly distributed bearings
- Analog on-off valve to adjust the rate of air flow
- Quick change air hose, exhaust overhose, and fitting for easy maintenance
- Repairable for long life
- Equipped with hoses and fittings to be ready for use out of the box
- Requires air pressure of only 58 PSI to save air consumption
- The spiral bevel gear in the angle grinders delivers high durability and high revolution with reduced noise level

### APPLICATIONS

- Polishing and fixing molds, reshaping ejector pins
- Deburring die cast parts
- Processing precision parts
- Removing paint
- Processing engines and more
- Dental crafting
- Shaping stones
- Hobbies and DIY











## DME<sup>®</sup> MOLDPolishing

# AIR GRINDER SYSTEM Air Micro Straight Grinders

**Air Micro Grinder HTSG3S** is the most powerful high torque Air Grinder among UHT Air Micro Grinder Series. Rotational speed is limited to 24,000 rpm and is designed to be effective in deburring and die polishing. The stable and powerful torque output allows the use of various tip tools such as rubber grinding stones, carbide rotary burs, and mounted felts.

## Ergonomic shape for comfortable grip applications.

The same design as the best-selling MSG3BSN is employed to achieve a slim yet powerful pneumatic hand tool.




## Highly efficient and air saving

A new high torque air motor is employed to minimize air consumption.


## Ideal for Rubber Grinding Stone "Daiwa Rabin"

Having the rotation speed of 24,000 rpm, this grinder is excellent for use with Rubber Grinding Stone. It also features high torque to offer a great performance with carbide rotary burs.






## **Carbide Rotary Burs**



Item No.	Reference
50104270	5QLB
50104280	5ULB
50104290	5SLB
50104300	5PLB
50104310	5NLB

3.0mm Shaft Diameter - 1 per case

## Tip tools for HTSG3S





Item No.	Stone Ø	Grit - Color
50103200		#80 - Red
50103210	10	#120 - Blue
50103220		#220 - Green
3.0mm Shaft Diameter - 5 per case		

Item No.	Stone Ø	Grit - Color
50103230		#80 - Red
50103240	6	#120 - Blue
50103250		#220 - Green

3.0mm Shaft Diameter - 5 per case



# AIR GRINDER SYSTEM Air Micro Straight Grinders

## **High Torque**



Item No.	HTSG3S
Collet Size	<b>Ø</b> 3.0 mm
RPM	24,000 rpm
Air Pressure	58 PSI
Air Consumption	75 NL/min
Weight	135 grams

\* HTSG32S (Collet size of 3.175mm) is also available

### FEATURES:

1.) High torque - It has double the torque of the existing model, providing powerful grinding operations at constant rotation speed under load.

2.) 24,000 rpm of rotation speed - Keeping the low speed to provide a stable torque and and gives you a wider choice of abrasives such as rubber abrasives, carbide rotary burs and mounted felt points.

3.) Air Saving - It uses 40% less air than the existing model, reducing the plant air consumption.

## **High Rotation Speed**

### **APPLICATIONS:**

- · Polishing and fixing molds, reshaping ejector pins
- Deburring die cast parts
- Processing precision parts
- Removing paint
- Shaping stones

Item No.	MSG3BSN
Collet Size	<b>Ø</b> 3.0 mm
RPM	65,000 rpm
Air Pressure	58-87 PSI
Air Consumption	120 NL/min
Weight	130 grams

	100.5 10101			
•	M00-855H	-	<b>N</b> lese	16.7 MM

Item No.	MSG24BSN		Item No.	MSG32BSN
Collet Size	Ø 2.34 mm (3/32in)	-	Collet Size	Ø 3.175 mm
RPM	65,000 rpm	-	RPM	65,000 rpm
Air Pressure	58-87 PSI	-	Air Pressure	58-87 PSI
Air Consumption	120 NL/min	-	Air Consumption	120 NL/min
Weight	130 grams	-	Weight	130 grams

### FEATURES:

- 1.) Comfortable weight and size with a multi-angle body for prolonged jobs.
- 2.) 65,000 rpm for efficiency.
- 3.) Pneumatic and capable of continuous operation.
- 4.) Quick change air hose, exhaust overhose, and fittting for easy maintenance.

# AIR GRINDER SYSTEM Air Micro Straight Grinders

## Modular Type



Item No.	FX3
Collet Size	Ø 3.0 mm
RPM	55,000 rpm
Air Pressure	58-87 PSI
Air Consumption	120 NL/min
Weight	78 grams

### FEATURES:

1.) It is possible to make on-site repair by customer himself because FX3.0 consists of 4 modules (4 main parts)


2.) Lightweight, only 78 grams, because the body is made of resin

3.) Special resin grip absorbs the vibration and improves the insulation effects from overcooled and overheated.

4.) Widened application from professional use to general use.

## **Precautions**

- 1.) Make sure to install a filter, regulator, and lubricator (FRL unit) in the air line.
- 2.) Before starting the grinder, apply a few drops of oil from the tip of the hose.
- 3.) The grinding stone may break due to excessive speed if the air supply exceeds 116 PSI



## **Cautions**

If you do not use FRL unit, it may result in extremely shortened service life, performance degradation, and heat.
Repair costs for malfunction of the grinder caused by failure to use the FRL unit will be charged even during the warranty period.


3) Be sure to disconnect the grinder from the air pressure source after use. reword sentence. Store in manner to prevent dust and debris from getting in at the quick joint.

# AIR GRINDER SYSTEM Air Micro Angle Grinder



Item No.	MAG091N
Collet Size	Ø 3.0 mm
RPM	48,000 rpm
Air Pressure	58-87 PSI
Air Consumption	120 NL/min
Weight	116 grams

- 1.) Compact head ideal for narrow work spaces
- 2.) 90-degree angle head, easy to keep parallel to the workpiece
- 3.) Reduced noise level
- 4.) Low air consumption at 58 PSI
- 5.) Includes hose with coupler to be ready for use on the spot



1.) 120-degree angle head grinder improving operating efficiency with the ergonomic grip

- 2.) Reduced noise level
- 3.) Low air consumption at 58 PSI
- 4.) Includes hose with coupler to be ready for use on the spot
- 5.) 3.175 mm (1/8") collet model is also available



Item No.	MAG122N
Collet Size	M6 - P0.75
RPM	35,000 rpm
Air Pressure	58-87 PSI
Air Consumption	120 NL/min
Weight	140 grams

### FEATURES:

- 1.) 120-degree angle head grinder improving operating efficiency with the ergonomic grip
- 2.) Reduced noise level
- 3.) Low air consumption at 58 PSI
- 4.) Higher in speed with smaller head than the MAG-123 and MAG-093, offering more efficient o
- 5.) Includes hose with coupler to be ready for use on the spot

# AIR GRINDER SYSTEM Air Micro Angle Grinder



Item No.	MAG093N
Collet Size	M6 - P0.75
RPM	23,500 rpm
Air Pressure	58-87 PSI
Air Consumption	120 NL/min
Weight	160 grams

### FEATURES:

- 1.) 90-degree angle head, easy to keep parallel to the workpiece
- 2.) Reduced noise level
- 3.) Low air consumption at 58 PSI
- 4.) Includes hose with coupler to be ready for use on the spot



Item No.	MAG132N
Collet Size	M6 - P0.75
RPM	23,500 rpm
Air Pressure	58-87 PSI
Air Consumption	120 NL/min
Weight	175 grams

### **FEATURES**:

- 1.) 120-degree angle head grinder improving operating efficiency with the ergonomic grip
- 2.) Reduced noise level
- 3.) Low air consumption at 58 PSI
- 4.) Includes hose with coupler to be ready for use on the spot





peration

# **AIR GRINDER SYSTEM Precision Grinding & Polishing Tools**



### **MOUNTED POINTS** - Metal Grinding

Item No.	Tip Ø	Size
5111MP	3mm	PA 3x10x3 #80
5112MP	6mm	PA 6x10x3 #80
5113MP	8mm	PA 8x10x3 #80
5114MP	10mm	PA 10x10x3 #80

3.0mm Shaft Diameter - 20/pk

## **DISK TYPE SOFT LAP Mirror Face Polishing & Finishing**

Item No.	Grit/Color
5150DSL	#120 Black
5151DSL	#240 Yellow
5152DSL	#320 Green
5153DSL	#400 Orange
5154DSL	#600 Pink
5155DSL	#800 Purple
5156DSL	#1000 Lt. Brown
5157DSL	#1500 Blue



### **ROTARY BURS** - Cutting

Туре
4UCW
4ASW
4TBW
40BW
4PBW
4NBW



3.0mm Shaft Diameter - 1/pk Material: Carbide Steel

# **MOUNTED TYPE SOFT LAP**

# **Mirror Face Polishing & Finishing**

Item No.	Grit/Color
5160MSL	#120 Black
5161MSL	#240 Yellow
5162MSL	#320 Green
5163MSL	#400 Orange
5164MSL	#600 Pink
5165MSL	#800 Purple
5166MSL	#1000 Lt. Brown
5167MSL	#1500 Blue



10mm

10mm

3.0mm Shaft Diameter - 25/pk

### 3.0mm Shaft Diameter - 25/pk

### **POL-PER SYSTEM & RUBBER DISC HOLDER Grinding & Polishing**

Item No.	Grit	ltem No.	Grit	Item No.	Description
5141PP	<b>Ø</b> 10mm #60	5144PP	<b>Ø</b> 10mm #240	5147RDH	Ø 10mm Rubber
5142PP	Ø 10mm #100	5145PP	<b>Ø</b> 10mm #400		Disc Holder
5143PP	<b>Ø</b> 10mm #150	5146PP	Ø 10mm #600	3.0mm Shaft	: Diameter - 10/pk

150/pk w 2 rubber disc holders

-0-
25mm
- 6041001 ·

5113MP

5111MP

5112MP

5114MP


# **AIR GRINDER SYSTEM Precision Grinding & Polishing Tools**



## **CUP WHEEL (FOR MAG122N)**

Grinding

ltem No.	Grit/Color	
MAG5231	#60 Yellow	
MAG5232	#100 Red	
MAG5233	#150 Blue	
<b>Ø</b> 20mm 24/µ	ok	



Item No.	Grit/Color
MAG5331	#60 Yellow
MAG5332	#100 Red
MAG5333	#150 Blue
<b>a</b> 20mm 24/m	L

M7 P=0.75 30 MM

### **NEW SOFT LAP (FOR MAG122N) Polishing**

Item No.	Grit/Color	
MAG5260	#120 Black	
MAG5261	#240 Yellow	1
MAG5262	#320 Green	M6 P=0
MAG5263	#400 Orange	
MAG5264	#600 Pink	
MAG5266	#1000 Lt Brown	20 MM
MAG5267	#1500 Blue	20 1010



Ø 20mm 40/pk w 1 rubber disc holder

### **POL-PER SYSTEM & RUBBER DISC HOLDER (FOR MAG122N) Grinding & Polishing**

~		мм
	00	2
	20 MN	1

M6 P=0.75

20 MM

Item No.	Grit	ltem No.	Grit
MAG5241	<b>Ø</b> 20mm #60	MAG5244	Ø 20mm #240
MAG5242	<b>Ø</b> 20mm #100	MAG5245	<b>Ø</b> 20mm #400
MAG5243	<b>Ø</b> 20mm #150	MAG5246	Ø 20mm #600

Ø 20mm w 2 rubber disc holders / 150/pk

Item No.	Description
MAG5291	Ø 20mm Rubber Disc Holder (10/pk)

## CUP WHEEL (FOR MAG132N/MGN093N)) Grinding

Item No.	Grit/Color	
MAG5331	#60 Yellow	
MAG5332	#100 Red	
MAG5333 #150 Blue		
Ø 30mm 24/pk		



### **NEW SOFT LAP** (FOR MAG122N) **Polishing**

Item No.	Grit/Color
MAG5360	#120 Black
MAG5361	#240 Yellow
MAG5362	#320 Green
MAG5363	#400 Orange
MAG5364	#600 Pink
MAG5366	#1000 Lt Brown
MAG5367	#1500 Blue



Ø 30mm 25/pk w 1 rubber disc holder

### **POL-PER SYSTEM & RUBBER DISC** HOLDER (FOR MAG132N/MAG093N) **Grinding & Polishing**

Item No.	Grit	ltem No.	Grit
MAG5341	#60 - 130/pk	MAG5344	#240 - 150/pk
MAG5342	#100 - 140/pk	MAG5345	#400 - 150/pk
MAG5343	#150 - 150/pk	MAG5346	#600 - 150/pk

Ø 30mm w 1 rubber disc holders



30 MM

Item No.	Description
MAG5391	Ø 30mm Rubber Disc Holder (10/pk)



# **TURBOLAP - AIR TYPE LAPPING TOOLS** Precision Grinding & Polishing Tools

### **APPLICATIONS:**

- Ideal as a precision machining tool for various industries, such as mold & die making, dental technology and jewelry industry
- Lapping, Polishing, Honing, Carving of mold precision parts.
- Shaving, Carving, Polishing of Precision metals and Jewelry



### TURBOLAP LINEAR (TLL-)

The linear reciprocating track is particularly powerful for polishing narrow areas and corners of precision parts and components.



# **TURBOLAP - AIR TYPE LAPPING TOOLS Air Type Lapping Tools**

## **TURBOLAP LINEAR SPECIFICATIONS**

Model	TLL03	TLL07	TLL12
Stroke (mm)	0.3		
Recommended R.P.M.	25,000	21,000	13,500
Noise Level		65 dB (A)	
Air Cpnsumption		30 NL/min	
Vibration Level	8.69 [m/s²]	9.79 [m/s²]	7.86 [m/s²]
Recommended Air Pressure		43.5 PSI	
Length / Weight		218mm / 180g	

### **DIAMOND FILES**

DME

Item No.	Grit
DF503200	#200
DF503400	#400
DF503600	#600
DF506200	#200
DF506400	#400
DF506600	#600
<b>5</b> /case	


Item No.	Grit
DF703200	#200
DF703400	#400
DF703600	#600
DF706200	#200
DF706400	#400
DF706600	#600
DFP03200	#200

15

### **CERAMIC STONES**

Item No.	Grit
CS404300	#300
CS404400	#400
CS404600	#600
CS404800	#800
CS4041000	#1000
CS4041200	#1200
CS406300	#300
CS406400	#400
CS406600	#600
CS406800	#800
CS4061000	#1000
CS4061200	#1200

ltem No.	Grit
CS704300	#300
CS704400	#400
CS704600	#600
CS704800	#800
CS7041000	#1000
CS7041200	#1200
CS706300	#300
CS706400	#400
CS706600	#600
CS706800	#800
CS7061000	#1000
CS7061200	#1200





DME<sup>®</sup> MOLDPolishing

5/case

**TLL12** 

# **TURBOLAP - AIR TYPE LAPPING TOOLS Precision Grinding & Polishing Tools**





1.) Lapping tools for polishing molds

- 2.) Easy-grip rubber cover designed to reduce fatigue
- 3.) Super Collet that holds the abrasive stone tight
- 4.) The 0.7 mm standard stroke works for all-around operations
- 5.) Includes hose with coupler to be ready for use on the spot



Item No.	TLL12
Stroke	1.2mm
No. of Sroke	19,000
Air Pressure	58-87 PSI
Air Consumption	120 NL/min
Weight	140 grams

### FEATURES:

- 1.) Lapping tools for polishing molds
- 2.) Easy-grip rubber cover designed to reduce fatigue
- 3.) Super Collet that holds the abrasive stone tight
- 4.) The 1.2 mm long stroke is a good choice for lapping wide areas
- 5.) Includes hose with coupler to be ready for use on the spot

# SONOCRAFT FINISHING MACHINE **Precision Grinding & Polishing Tools**

SonoCraft finishing machine provides application versatility; with a broad variety of accessories and tools it can be used for ultrasonic polishing, simple ultrasonic cutting, metal working, geological survey and fossil cleaning, removal of film on printed circuit boards and a host of other applications.



ST360 Oscillator Controller			
Max. Output Power	45W	Oscillation Mode	4 steps
Frequency	21 - 24 kH	Application Standard	CE certification
Power Consumption	150VA	External Dimension (mm)	130 x 250 x 240 (H)
Frequency Adjustment	Automatic feedback system	Weight	2.6kg
Amplitude Adjustment	Continuous variable		



HP9760 Ultrasonic Handpiece			
Tool Screw Diameter (Screw Thread)	M6 (with M6-M4 adaptor		
Transducre Cord	1.7M (curl type)		
External Dimension (mm)	Ø28 x 118(L)		
Weight	150g		
Cooling System	Air-cooling		



## ST360S Controller Set (includes) **Oscillator** (Controller) **Ultrasonic Handpiece**

Standard Tools & Accessories\*

**Power Cord** 

Toolbox



Standard accessories

- 1.) SE-8851
- 6.) TB-3000 Chisel 2.) SE-5845 Diamond file 7.) MX-4010 Tool clamp
- 3.) HR-2020 Chisel holder 8.) NSP106F Ceramic stone
- 4.) TF-1000 Chisel 9.) NSR106F Ceramic stone
- 5.) TR-1000 Chisel





Standard tools

Spanners: 3 pcs (2 pcs M10 / 1 pc M8)



Standard tools Torque wrench 1pc Heaxgonal wrench 1 pc

\*Note: Jewelry making, engraving, metal working and archaeological tool and accessories available upon request

# DME<sup>®</sup> MOLDPolishing

#### With tens of thousands of products to choose from, DME is your one-stop shop for everything molding.

From complex undercuts solutions and plate control to standard pins, bushings and interlocks, the DME line of mold components will help you build or rebuild your mold base inside out, top to bottom. Industrial Supplies, Mold Bases, MUD Quick-Change, Control Systems, and Hot Runner solutions round out our extensive offering to truly be your one-stop shop.





### World Headquarters DME Company LLC

29111 Stephenson Highway Madison Heights, MI 48071 800-626-6653 toll-free tel 248-398-6000 tel www.DME.net web DME@DME.net e-mail

### DME of Canada Ltd.

5345 Outer Drive - Unit 3 Oldcastle, Ontario Canada N9G 0C4 **800-387-6600** *toll-free tel* **905-677-6370** *tel* DME\_Canada@DME.net e-mail

### **DME Mexico / South America**

Circuito el Marques Notre, No.55 Parque Industrial El Marqués El Marqués, Querétaro, CP 76246 **52.442.713.5666** *tel* DME\_Mexico@DME.net

