

## 1. Identification

Product number 41515  
 Product identifier Slide Plastic Cleaner with FoamAction  
 Company information SLIDE PRODUCTS INC  
 430 S WHEELING ROAD  
 WHEELING, IL 60090 United States  
 Company phone General Assistance 800-323-6433  
 Emergency telephone US 1-800-535-5053 (North America)  
 Emergency telephone outside US 1-352-323-3500  
 Version # 02  
 Recommended use Industrial Mold and Part Cleaner  
 Recommended restrictions None known.

## 2. Hazard(s) identification

Physical hazards Gases under pressure Liquefied gas  
 Health hazards Not classified.  
 Environmental hazards Not classified.  
 OSHA defined hazards Not classified.

### Label elements



Signal word Warning  
 Hazard statement Contains gas under pressure; may explode if heated.  
 Precautionary statement  
 Prevention Observe good industrial hygiene practices.  
 Response Wash hands after handling.  
 Storage Protect from sunlight. Store in a well-ventilated place.  
 Disposal Dispose of waste and residues in accordance with local authority requirements.  
 Hazard(s) not otherwise classified (HNOC) None known.  
 Supplemental information None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	2.5 - 10
Ethyl Alcohol		64-17-5	2.5 - 10
Butane		106-97-8	1 - 2.5
Propane		74-98-6	1 - 2.5
Other components below reportable levels			90 - 100

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

Inhalation Move to fresh air. Get medical attention if symptoms persist.

Skin contact	Get medical attention if irritation develops and persists.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. See Section 8 of the SDS for Personal Protective Equipment. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol.  Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3
Ethyl Alcohol (CAS 64-17-5)	PEL	50 ppm 1900 mg/m3
Propane (CAS 74-98-6)	PEL	1000 ppm 1800 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3
Butane (CAS 106-97-8)	TWA	5 ppm 1900 mg/m3 800 ppm
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

### Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

\* - For sampling details, please see the source document.

### Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Skin protection

Other Wear suitable protective clothing.

Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

Appearance	Clear.
Physical state	Gas.
Form	Aerosol. Liquefied gas.
Color	Light yellow.
Odor	Characteristic.
Odor threshold	Not available.
pH	9.1 - 10.1 estimated
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	80 - 100 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Aerosol spray enclosed space	
Deflagration density	> 2.52 g/cm <sup>3</sup> Tested
Aerosol spray ignition distance	< 15 cm Tested estimated
Specific gravity	0.977 - 0.997

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard.  
Inhalation Prolonged inhalation may be harmful.  
Skin contact No adverse effects due to skin contact are expected.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

Acute toxicity May be harmful if swallowed. May be harmful in contact with skin. May be harmful if inhaled. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components	Species	Test Results	
2-Butoxyethanol (CAS 111-76-2)			
Acute Dermal LD50	Guinea pig	230 ml/kg, 24 Hours	
		7.3 ml/kg, 4 Days	
		450 ml/kg, 24 Hours	
		435 mg/kg, 24 Hours	
	Rabbit	0.63 ml/kg	
		> 2000 mg/kg, 24 Hours	
	Inhalation LC50	Rabbit	400 ppm, 7 Hours
		Rat	450 ppm, 4 Hours
	Oral LD100 LD50	Rabbit	695 mg/kg
Dog		> 695 mg/kg	
Guinea pig		1200 mg/kg	
Rat		530 - 2800 mg/kg	
Butane (CAS 106-97-8)			
Acute Inhalation LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
Ethyl Alcohol (CAS 64-17-5)			
Acute Inhalation LC50	Cat	85.41 mg/l, 4.5 Hours	
		43.68 mg/l, 6 Hours	
	Mouse	> 60000 ppm	
		79.43 mg/l, 134 Minutes	
	Rat	> 115.9 mg/l, 4 Hours	
		51.3 mg/l, 6 Hours	

Components	Species	Test Results
Oral LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Rat	1187 - 2769 mg/kg 7800 ml/kg
Propane (CAS 74-98-6) Acute Inhalation LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	May be irritating to the skin. Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation. May be irritating to eyes.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
2-Butoxyethanol (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard. Not likely, due to the form of the product.
Chronic effects	Prolonged inhalation may be harmful. May be harmful if absorbed through skin.  2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

## 12. Ecological information

Product	Species	Test Results
Slide Plastic Cleaner with FoamAction (CAS Mixture)		
Aquatic		
Crustacea	EC50	Daphnia
		13838.1602 mg/l, 48 hours estimated
Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-2)		
Aquatic		
Fish	LC50	Inland silverside (Menidia beryllina)
		1250 mg/l, 96 hours
Ethyl Alcohol (CAS 64-17-5)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna)
		7700 - 11200 mg/l, 48 hours

Components	Species	Test Results
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> ) > 100.1 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol	0.83
Butane	2.89
Ethyl Alcohol	-0.31
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

Disposal instructions Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport information

#### DOT

UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s) Packing	2.2
group Environmental	Not applicable.
hazards ERG Code	No.
	2L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s) Packing	2.2
group Environmental	Not applicable.
hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
DOT	



IATA; IMDG



## 15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	
Not regulated.	
CERCLA Hazardous Substance List (40 CFR 302.4)	
Not listed.	
SARA 304 Emergency release notification	
Not regulated.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Superfund Amendments and Reauthorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No



SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)  
Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)  
Butane (CAS 106-97-8)  
Ethyl Alcohol (CAS 64-17-5)  
Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)  
Butane (CAS 106-97-8)  
Ethyl Alcohol (CAS 64-17-5)  
Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2)  
Butane (CAS 106-97-8)  
Ethyl Alcohol (CAS 64-17-5)  
Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8)  
Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-13-2015

Version #	02
References	EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

