

1. IDENTIFICATION

Product identifier

Product Name Slide Quick RP Rust Preventive

Other means of identification

SDS # 42810RP

UN/ID No UN1950

Recommended use of the chemical and restrictions on use

Recommended Use Industrial Rust Preventive

Details of the supplier of the safety data sheet

Supplier Address

Slide Products Inc.
430 S. Wheeling Road
Wheeling, IL 60090

Emergency telephone number

Company Phone Number Phone: 1-847-541-7220
Fax: 1-847-541-7986
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Physical state Aerosol

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Aerosols	Category 1
Gases under pressure	Compressed gas

Signal Word

Danger

Hazard statements

Causes skin irritation
May cause respiratory irritation. May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated



Precautionary Statements - Prevention

Wear protective gloves, protective clothing, eye protection, and face protection
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust, fume, gas, mist, vapors, or spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat, sparks, open flames, and hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of water and soap
 Take off contaminated clothing and wash before reuse
 If skin irritation occurs; Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a poison center or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Heptane	142-82-5	60-75
Petroleum gases, liquified, sweetened	68476-86-8	25-35
Petroleum distillates (naphtha)	8002-05-9	1-5
Calcium salts	68783-96-0	1-5
Soy Lecithin	8002-43-5	1-3

**If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret. **

4. FIRST AID MEASURES

Description of first aid measures

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
Inhalation	Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Ingestion	Immediately call a poison center or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms	May be harmful if swallowed. May be harmful in contact with skin. Causes skin irritation. May cause drowsiness or dizziness. May cause respiratory irritation. May be fatal if swallowed and enters airways.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Extremely flammable aerosol. Pressurized container: May burst if heated.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions	Use personal protective equipment as required.
-----------------------------	--

Environmental precautions**Methods and material for containment and cleaning up**

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling	Wear protective gloves/protective clothing and eye/face protection. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust, fume, gas, mist, vapors, or spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames, and hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
--------------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions	Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Incompatible Materials	None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
Petroleum distillates (naphtha) 8002-05-9	-	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³	IDLH: 1100 ppm Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³

Appropriate engineering controls

Engineering Controls

Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection

Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection

Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Aerosol	Odor	Not determined
Appearance	Not determined	Odor Threshold	Not determined
Color	Not determined		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	Not determined		
Melting point / freezing point	Not determined		
Boiling point / boiling range	Not determined		
Flash point	Not determined		
Evaporation Rate	Not determined		
Flammability (Solid, Gas)	Not determined		
Flammability Limit in Air			
Upper flammability or explosive limits	Not determined		
Lower flammability or explosive limits	Not determined		
Vapor Pressure	Not determined		
Vapor Density	Not determined		
Relative Density	Not determined		
Water Solubility	Not determined		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Autoignition temperature	Not determined		
Decomposition temperature	Not determined		
Kinematic viscosity	Not determined		
Dynamic Viscosity	Not determined		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	May be harmful in contact with skin.
Inhalation	Do not inhale.
Ingestion	May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
Calcium salts 68783-96-0	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 1.9 mg/L (Rat) 4 h
Petroleum distillates (naphtha) 8002-05-9	> 5000 mg/kg (Rat) > 4300 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Carcinogenicity Group 3 IARC components are "not classifiable as human carcinogens".

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates (naphtha) 8002-05-9	A2	Group 3	Known	X

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.**Aspiration hazard** May be fatal if swallowed and enters airways.**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document.

Oral LD50 4,992.20 mg/kg**Dermal LD50** 2,838.50 mg/kg**ATEmix (inhalation-dust/mist)** 20.30 mg/L**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L EC50
Calcium salts 68783-96-0	1000: 96 h Pseudokirchneriella subcapitata mg/L EC50	40: 96 h Pimephales promelas mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Petroleum distillates (naphtha) 8002-05-9		258: 96 h Salmo gairdneri mg/L LC50 static	36: 24 h Daphnia magna mg/L EC50 0.26: 48 h Daphnia magna mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Heptane 142-82-5	4.66
Petroleum gases, liquified, sweetened 68476-86-8	<=2.8

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.**Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Heptane 142-82-5	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1950
 Proper Shipping Name Aerosols
 Hazard class 2.1

IATA

UN number UN1950
 Proper Shipping Name Aerosols, flammable
 Transport hazard class(es) 2.1

IMDG

UN number UN1950
 Proper Shipping Name Aerosols
 Transport hazard class(es) 2.1
 Marine Pollutant N-Heptane

15. REGULATORY INFORMATION**International Inventories**

Chemical name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Heptane	X	X	X	X	X	X	X	X
Petroleum gases, liquified, sweetened	X	X	X		X	X	X	X
Calcium salts	X	X	X	X	X	X	X	X
Petroleum distillates (naphtha)	X	X	X		X	X	X	X
Lecithin	X	X	X		X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Petroleum distillates (naphtha) - 8002-05-9	8002-05-9	1-5	0.1

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Heptane 142-82-5	X	X	X
Petroleum distillates (naphtha) 8002-05-9	X	X	X

16. OTHER INFORMATION**NFPA****Health Hazards**

Not determined

Flammability

Not determined

Instability

Not determined

Special Hazards

Not determined

HMIS**Health Hazards**

Not determined

Flammability

Not determined

Physical hazards

Not determined

Personal Protection

Not determined

Issue Date:

24-Aug-2018

Revision Date:

01-Feb-2019

Revision Note:

Updated classification

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet