

# TECHNICAL DATA SHEET



## 43900-01 Super Grease Non-Aerosol

### Product Description

Super Grease will not separate, run or fall out and has exceptional load-bearing properties. Thixotropic properties provide excellent mechanical stability when sudden temperature changes occur. A clear, clean, non-yellowing grease, Super Grease is ideal for injection molds, mold assemblies, and especially medical and food grade plastic parts. It also repels water and prevents corrosion.

### Applications

Ejector Pin Lubricant

### Unit Package Description

Multiple sizes

### Generic Description

Ejector Pin Grease

### Net Weight Fill

multiple sizes

### UPC Code

858799000752

### Units Per Case

multiple sizes

### Case Weight (lbs)

0

### Appearance

Colorless Grease

### Flash Point F

455 degrees

### Flash Point C

235 degrees

### Base Type

PTFE

### Evaporation Rate

N/A

### Working Temperature F

32 to 650 degrees

### Working Temperature C

0 to 343 degrees

### Propellant

N/A

### NFPA Aerosol Flammability Level

N/A

### DOT Proper Shipping Name

Not Regulated, Lubricating, NOI

### VOC % (Federal)

0

### VOC g/L (Federal)

0

### VOC lbs./Gal (Federal)

0

### Removal

Remove with organic or hydrocarbon solvents

### Independent Certifications

NSF category H1