

TECHNICAL DATA SHEET

44110L

Hi-Temp 1800 Release Aerosol



Product Description

Bring on the heat. Hi-Temp 1800 is the perfect partner to maximize productivity with high-temperature resins. Formulated with Boron Nitride, Hi-Temp maintains its lubrication integrity, helping maximize productivity. It is also an excellent release for die-casting of low melting point metals such as lead, zinc and aluminum.

Applications

Mold Release

Unit Package Description

16 ounce aerosol

Generic Description

Mold Release for Hi-Temp applications

Net Weight Fill

10 net ounces

UPC Code

858799000417

Units Per Case

12

Case Weight (lbs)

12

Appearance

White Powder

Flash Point F

Not Determined

Flash Point C

Not Determined

Base Type

Boron Nitride

Evaporation Rate

Fast

Working Temperature F

32 to 1800 degrees

Working Temperature C

0 to 982 degrees

Propellant

DME/152A

NFPA Aerosol

Flammability Level

1

DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

VOC % (Federal)

54.44

VOC g/L (Federal)

414.89

VOC lbs./Gal (Federal)

3.46

Removal

Remove with organic or hydrocarbon solvents